

Styling



Cory House

@housecor

reactjsconsulting.com





I Am Devloper

@iamdevloper

Following



CSS is easy. It's like riding a bike, which is on fire and the ground is on fire and everything is on fire because it is hell.

RETWEETS

2,497

LIKES

3,848



The Plan



React styling approaches

- Compiled CSS
- Inline Styles
- CSS Modules
- CSS in JS

Styling decisions

1. Pick a styling approach
2. Theming



Compiled CSS and Naming Schemes



Why Compile CSS?



Variables

Custom functions

Automatic vendor prefixes

Nested selectors



Sass Variables

```
$font-stack: Helvetica, sans-serif
```

```
$primary-color: #333 body
```

```
font: 100% $font-stack
```

```
color: $primary-color
```



Sass Nesting

```
nav
  ul
    margin: 0
    list-style: none
  li
    display: inline-block
```



```
nav ul {
  margin: 0;
  list-style: none;
}

nav li {
  display: inline-block;
}
```



PostCSS



Transpile your CSS

- Autoprefixer
- CSS4
- Polyfill Flexbox
- Style linting
- Accessibility
- Much more!

CSS Naming Schemes



“I’m too scared to delete any styles.”



One Solution to Global CSS:

Naming Scheme: BEM, OOCSS, SMACSS



46% have used a naming scheme

40% BEM

15% OOCSS


13% SMACSS

Source: sitepoint.com/front-end-tooling-trends-2017



BEM


Whole component



Block

The component


Label



Element

Part of the component

Input error state styling



Modifier

A variant/extension



BEM Example

// Block

```
.registrationform{ }
```

// Element

```
.registrationform__submitbutton { }
```

// Modifier

```
.registrationform--error { }
```



Demo



CSS with BEM



Inline Styles



style

The `style` attribute accepts a JavaScript object with camelCased properties rather than a CSS string. This is consistent with the DOM `style` JavaScript property, is more efficient, and prevents XSS security holes. For example:

Code

```
const divStyle = {
  color: 'blue',
  backgroundImage: 'url(' + imgUrl + ')',
};

function HelloWorldComponent() {
  return <div style={divStyle}>Hello World!</div>;
}
```

Note that styles are not autoprefixed. To support older browsers, you need to supply corresponding style properties:


Code

```
const divStyle = {
  WebkitTransition: 'all', // note the capital 'W' here
  msTransition: 'all' // 'ms' is the only lowercase vendor prefix
};

function ComponentWithTransition() {
  return <div style={divStyle}>This should work cross-browser</div>;
}
```

Style keys are camelCased in order to be consistent with accessing the properties on DOM nodes from JS (e.g. `node.style.backgroundImage`). Vendor prefixes **other than** `ms` should begin with a capital letter. This is why `WebkitTransition` has an uppercase "W".

React Inline Styles – Differences from CSS



Keys are camelCased

Values are strings

Commas instead of semicolons

Capitalized vendor prefixes

Why React Inline Styles?

Advantages

Easy

Encapsulated

Explicit

No mental mapping overhead

Deterministic

Dynamic styles

Disadvantages

Can't use:

- Pseudo classes
- Pseudo elements
- Media queries
- Style fallbacks
- Animations

Must use !important to override

Messier markup





How opinionated should my styling be?

- Inline styles = strong enforcement
- External styles = more flexibility

Consider mixing React's
inline styles with plain CSS



Demo



You've already seen the demo. 😊



CSS Modules




CSS Modules

Class names are scoped locally by default.



CSS Modules



Modular and reusable CSS

1. Write plain CSS
2. Import stylesheet
3. Reference style like an object




1. Declare stylesheet

```
/* TextInput.css */  
.error {  
  color: red;  
}
```

2. Configure webpack

3. Import stylesheet & apply styles

```
import React from 'react';  
import PropTypes from 'prop-types';  
import Label from '../Label';  
import styles from './textInput.css';  
  
/** TextInput using CSS Modules */  
function TextInputCssModules ({htmlId, name, label, type = "text",  
  return (  
    <div className={styles.fieldset}>  
      <Label htmlFor={htmlId} label={label} required={required} />  
      <input  
        id={htmlId}  
        type={type}  
        name={name}  
        className={error && styles.inputError}  
        placeholder={placeholder}  
        value={value}  
        onChange={onChange}  
        {...props}/>  
      {children}  
      {error && <div className={styles.error}>{error}</div>}  
    </div>  
  );  
};  
  
<div className="textInput__error__16c-r">{error}</div>
```



```
// Webpack 1
```

```
'css-loader?modules&importLoaders=1&localIdentName=[name]_[local]_[hash:base64:5]'
```

```
// Webpack 2
```

```
loader: 'css-loader',
```

```
options: {
```

```
  modules: true,
```

```
  localIdentName: '[name]_[local]_[hash:base64:5]'
```

```
},
```



css-loader

https://webpack.js.org/loaders/css-loader/#css-scope

webpack v2.2.1

Introduction

- babel-loader
- bundle-loader
- coffee-loader
- coffee-redux-loader
- coverjs-loader
- css-loader
 - Install
 - Usage
 - Via webpack config (recomm...
 - CLI
 - Inline
 - Options
 - Options
 - Root
 - CSS Scope
 - [CSS Modules](https://github...
 - CSS Composing
 - Importing CSS Locals
 - SourceMaps
 - toString
 - ImportLoaders

url() URLs in block scoped (:local .abc) rules behave like requests in modules:

- ./file.png instead of file.png
- module/file.png instead of ~module/file.png

You can use :local(#someId) , but this is not recommended. Use classes instead of ids.

You can configure the generated ident with the localIdentName query parameter (default [hash:base64]).

webpack.config.js

```
{  test: /\.css$/,  use: [    {      loader: 'css-loader',      options: {        modules: true,        localIdentName: '[path][name]__[local]--[hash:base64:5]'      }    }  ]}
```

You can also specify the absolute path to your custom getLocalIdent function to generate classname based on a different schema. Note that this requires webpack >= v2.x . since to be able to pass function in. For example:

```
{
```


1. Declare stylesheet

```
/* TextInput.css */  
.error {  
  color: red;  
}
```


2. Configure webpack

3. Import stylesheet & apply styles

```
import React from 'react';  
import PropTypes from 'prop-types';  
import Label from '../Label';  
import styles from './textInput.css';  
  
/** TextInput using CSS Modules */  
function TextInputCssModules ({htmlId, name, label, type = "text",  
  return (  
    <div className={styles.fieldset}>  
      <Label htmlFor={htmlId} label={label} required={required} />  
      <input  
        id={htmlId}  
        type={type}  
        name={name}  
        className={error && styles.inputError}  
        placeholder={placeholder}  
        value={value}  
        onChange={onChange}  
        {...props}/>  
      {children}  
      {error && <div className={styles.error}>{error}</div>}  
    </div>  
  );  
};  
  
<div className="textInput__error__16c-r">{error}</div>
```



Why CSS Modules?



Write plain CSS, or Sass/Less

Explicit

Composable

Automatic encapsulation

No risk of conflicts

Write short CSS selectors

Supports global CSS





Mark Dalgleish

@markdalgleish

Following

Compiled a React component into a standalone lib—CSS Modules really paid off. Need to keep bundle size down, so not shipping a runtime is 👉

RETWEETS

2

LIKES

22



Why Not CSS Modules

CSS
MODULES

No dynamic state-based styles

Theming is tricky



Demo



CSS Modules



CSS in JS



~50 CSS in JS options?!
O_o





Mark Dalgleish
@markdalgleish



Following

@kentcdodds

"Here's a made-up programming language that compiles to CSS"

Devs: 🙌🙌🙌🙌

"I'm just gonna use JS"

Devs: 🙅😱😡😭



Why JS Over Sass, Less, PostCSS?

A yellow square containing the letters 'JS' in a large, bold, black sans-serif font.

You already know JS

- Variables
- Functions
- Looping

JS is a better language

Leverage the same tooling

- Linter
- Minification
- Dead code elimination

CSS in JS Issues

A yellow square containing the letters 'sr' in a bold, dark grey, sans-serif font. The 's' is slightly larger than the 'r'.

No sourcemaps


Library lock-in

May lack full CSS support

Confusing when mixed with CSS

Forces consumers to accept your decision



A yellow square containing the letters 'JS' in a large, bold, dark grey sans-serif font.

JS

JS styles

- Aphrodite
- Radium
- JSS
- jsxstyle
- Styled-components
- Glamour
- Over 40 more!



Features

How to read the table

More crosses doesn't mean "better", it depends on your needs. For example, if a package supports the css file extraction you can run the autoprefixing at build time.

Package	Version	Automatic Vendor Prefixing	Pseudo Classes	Media Queries	Styles As Object Literals	Extract CSS File
aphrodite	0.1.2	x	x	x	x	x
babel-plugin-css-in-js	1.2.2	x	x	x	x	x
bloody-react-styled	3.0.0		x	x		
classy	0.3.0		x	x	x	
csjs	1.0.0		x	x		
css-constructor	0.1.1	x	x	x		
css-loader	0.15.6		x	x		x
css-ns	1.0.0		x	x		x
cssobj	0.2.21	x	x	x	x	
cssx-loader	3.8.0	x	x	x		x
es-css-modules	1.2.3		x	x		x
glamor	2.1.0	x	x	x	x	x
hyperstyles	3.3.0		x	x		x
j2c	0.10.0		x	x	x	x
jsxstyle	0.0.14	x			x	
radium	0.13.5	x	x	x	x	
react-css-builder	0.2.0				x	
react-css-components	0.6.9		x	x		x
react-css-modules	3.0.2		x	x		x
react-cxs	1.0.0-beta.4		x	x	x	x

	styled- components	Radium	Aphrodite	JSS	Glamor	jsx-style
GitHub Stars	5160	5036	2627	1940	1895	1557
Automatic Vendor prefixing	x	x	x	x	x	x
Pseudo classes	x	x	x	x	x	x
Media queries	x	x	x	x	x	No
Write plain CSS	Yes	Object literals	Object literals	Object literals	Object literals	Object literals
Extract CSS file	No	No	x	x	x	x



Demo



CSS in JS via styled-components



Decision: Styling approach




React Styling Approaches




Plain CSS




Compiled CSS



Inline Styles



CSS Modules



CSS in JS



	CSS	Sass/Less	CSS Modules	Inline styles	CSS in JS
Deterministic	No	No	Yes	Yes	Yes
Explicit application	No	No	Yes	Yes	Yes
Dead code elimination	No	No	Yes	Yes	Yes
Encapsulated	No, but BEM helps	No, but BEM helps	Yes	Yes	Yes
Collocated	No	No	No	Yes	Yes
Themeable	Yes	Yes, change variables	Yes, but no standard	Not easily	Varies
Full CSS Support	Yes	Yes	Yes	No	Not typically
Write standardized CSS	Yes	No	Yes, or Sass/Less/PostCSS	No	Varies
Generate plain CSS during build	Yes	Yes	Yes, but dynamic class names	No	Varies
Syntax highlighting	Yes	Yes	Yes	It's JS	Varies
Autocomplete when writing	Yes	Yes	Yes	No	No
Autocomplete when using	No	No	No	Yes	Yes
Library lock-in	No	Yes	CSS, no. In React, yes	Yes	Varies
Requires wrapper component	No	No	No	No	Varies
Server side rendering support	Yes	Yes	Must run webpack on server	Yes	Yes
Post-processing support	Yes	Yes	Yes	No	Varies
Lintable	Yes	Yes	Yes	No	Not typically
Build Setup	None	webpack loader	css-loader, or PostCSS	None	None
Style testing setup	Test via screenshots	Test via screenshots	Config tests to ignore	None	None





Oh great, they're all lousy.





Need theming?

- Prefer Sass/Less/cssnext, avoid inline

Can't trust people to follow conventions?

- Prefer inline or CSS in JS

Concerned about lock-in?

- Prefer plain CSS

Automated style testing important?

- Easier with inline or CSS in JS

July 2016



Max Stoiber

@mxstbr



How are you styling your [@reactjs](#) applications? (reply with specific libraries)



RT for reach, please!

54% Plain CSS, Sass, Less,...

31% CSS Modules

8% Inline (Plain, Radium,...)

7% CSS-in-JS (JSS, Aphro,...)

Feb 2017



Cory House

@housecor

How are you styling your [@reactjs](#) applications?
Reply with specific libraries.

#reactjs

58% Plain CSS, Sass, Less...

22% CSS Modules

5% Inline (Plain, Radium...)

15% CSS-in-JS (JSS, Aphro...)



Styling Approaches Used By Top Libraries

React Toolbox	CSS modules with cssNext via PostCSS
React Bootstrap	Less with bs prefix
Ant	Less with ant prefix
Blueprint	Sass
Grommet	Sass with BEM with grommetux prefix
Material-UI	Inline styles (also offer unstyled exports)



Decision:
Unstyled, enforced or themeable?





Styling Opinions

Font

Color

Size

Border

Positioning

Responsive Design



Unstyled

Themeable

Built-in styles

Opinion →

← Flexibility



Should a component be shipped *without* styles?



Public? Be themeable.



Private? Be opinionated.



Conway's Law

Organizations which design systems are constrained to produce designs which are copies of the communication structures of these organizations



Funnel designs through a
centralized team.



Un-themed UI Libraries

material-ui-core

belle-core

elemental-core

react-toolbox-core



Un-themed UI Components

react-select

react-autocomplete

react-modal



If you're using external CSS,
you can offer both themed
and unthemed.



“Depending on whether you want the styles...you can import components in two different ways.”

React Toolbox



```
// Styled
import { AppBar } from 'react-toolbox/lib/app_bar';

// Unstyled
import AppBar from 'react-toolbox/lib/app_bar/AppBar.js';
```



Theming Approaches



There is no theming standard.



Theming Approaches By Tech

CSS, Sass, Less

Use a different stylesheet

Inline styles

Accept theme as object via prop

CSS modules


Accept theme as object via prop

CSS in JS

Varies




Careful With CSS Classes for Themes



May conflict with other markup

Consider a unique prefix

Namespace Your Theme Styles



Ant

ant

React-Bootstrap

bs

Grommet

grommetux



Wrap Up



React styling approaches

- Compiled CSS
- Inline Styles
- CSS Modules
- CSS in JS

Styling decisions

1. Use naming schemes for compiled CSS
2. Theming – Consider shipping without styles.

Next up: Testing

