Layered Architecture and Network Protocols

EE450: Introduction to Computer Networks

Professor A. Zahid

Protocols

Human Protocols:

- what's the time?

- I have a question

- Introductions

… specific msgs sent

… specific actions taken when msgs received, or other events

Network Protocols:

- Machines rather than humans

- All communication activity in Internet governed by protocols

> Protocols define format, order of msgs sent and received among network entities, and actions taken on msg transmission, receipt

Human vs. Network Protocols

Hi

Hi

Got the time?

2:00

time

TCP connection request

TCP connection reply

Get http://www.usc.com/grades.html

Key Elements of a Protocol

- **Syntax**
  - Data formats, compression, encryption, etc..
  - Signal levels

- **Semantics**
  - Control information such as flow & congestion
  - Error detection and control mechanisms

- **Timing**
 - Speed matching
  - Sequencing

- **Fairness**

Standards

- Required to allow for interoperability between equipment

- Advantages
  - Ensures a large market for equipment and software
  - Allows products from different vendors to communicate

- Disadvantages
  - Freeze technology

OSI Reference Model

Data Transfer in OSI

Actual data transmission path

Layered Communications

- Peer layers communicate via protocols
- Adjacent layers communicate via service interfaces
- Protocol control information (PCI) is added to Service data unit (SDU) at each layer to form a Protocol data unit (PDU)
 - $(SDU)_N = (PDU)_{N+1}$
  - $(PDU)_N = (SDU)_N + (PCI)_N$

Why Layering?

Dealing with complex systems:

- explicit structure allows identification,

  relationship of complex system's pieces
  - layered reference model for discussion

- Modularization eases maintenance, updating

  of system
  - change of implementation of layer's service transparent to rest of system
 - change in one layer doesn't affect rest of system

Summary of Layers Functionality

To translate, encrypt, and compress data

Application

To allow access to network resources

Presentation

To provide end-to-end message delivery and error recovery

Session

To establish, manage, and terminate sessions

Transport

To organize bits into frames; to provide node-to-node delivery

Network

To move packets from source to destination; to provide internetworking

Data link

Physical

To transmit bits; to provide mechanical and electrical specifications

The Internet and TCP/IP

a. An actual internet

b. An internet seen by TCP/IP

Internet Protocol Stack

- Application: supporting network applications
  - FTP, SMTP, HTTP
- Transport: process-process data transfer
  - TCP, UDP
- Network: routing of datagrams from source to destination
  - IP, routing protocols
- Link: data transfer between neighboring network elements
 - PPP, Ethernet
- Physical: bits "on the wire"

application
transport
network
link
physical

Developed by the US Defence Advanced Research Project Agency (DARPA) for its packet switched network (ARPANET)

TCP/IP Model

Device A

Device B

Intermediate node

Intermediate node

5	Application	Peer-to-peer protocol (5th layer)	Application	5
4	Transport	Peer-to-peer protocol (4th layer)	Transport	4
3	Network	Network	Network	Network	3
2	Data link	Data link	Data link	Data link	2
1	Physical	Physical	Physical	Physical	1

5-4 interface
4-3 interface
3-2 interface
2-1 interface

3rd
2nd
1st

Physical communication

Message Transmission using TCP/IP

TCP/IP vs. OSI Models

Encapsulation

source

message	M
segment	H_t M
packet	H_n H_t M
frame	H_l H_n H_t M

application
transport
network
link
physical

Switch

link
physical

destination

application
transport
network
link
physical

| M |
| H_t M |
| H_n H_t M |
| H_l H_n H_t M |

| H_n H_t M |
| H_l H_n H_t M |

network
link
physical

Router

| H_n H_t M |

Communications between Networked Applications

Figure 2.1 ♦ Communication for a network application takes place between end systems at the application layer.

Communications between Transport Layers

Figure 3.1 ♦ The transport layer provides logical rather than physical communication between application processes.

Network Layer Communications

**Figure 4.1** ♦ The network layer

Link Layer Communications

Figure 5.1 ♦ The link layer

Addressing in TCP/IP

```
                    ┌──────────────────┐
                    │    Addresses     │
                    └──────────────────┘
                             │
         ┌───────────────────┼───────────────────┐
         │                   │                   │
┌────────────────┐  ┌────────────────┐  ┌────────────────┐
│   Physical     │  │      IP        │  │     Port       │
│   address      │  │   address      │  │   address      │
└────────────────┘  └────────────────┘  └────────────────┘
```

TCP/IP Layers and Addresses

Link Layer (MAC) Addresses

Most local area networks use a 48-bit (6 Bytes) physical address written as 12 hexadecimal digits, with every 2 Bytes separated by a hyphen for example

"07-01-02-01-2C-4B"

a node with MAC address 10 sends a frame to a node with MAC address 87. The two nodes are connected by a link. At the data link level this frame contains MAC addresses in the header. These are the <u>only</u> addresses needed. The header contains other information needed @ this level. The trailer contains extra bits needed for error detection

Internetwork Communications

An Internet address (in IPv4) is 32 bits in length written as four decimal numbers, with each number representing 1 Byte. The numbers are separated by a dot. For example 128.125.75.9

A node with an IP address A and MAC address 10, located on one LAN, to a node with an IP address P and MAC address 95, located on another LAN. Because the two devices are located on different networks, we cannot use MAC addresses only; the MAC addresses only have local significance. What we need here are universal addresses that can pass through the LAN boundaries. The IP address has this characteristic.

Port Addresses


A port address is a 16-bit address represented by one decimal number for example 750

Data coming from the upper layers have port addresses j and k (j is the address of the sending process, and k is the address of the receiving process). Data are split into two Packets, each retaining the port addresses (j and k). Then in the network layer, IP addresses (A and P) are added to each packet.

Layered Architecture and Networks

Service access point

Application

Transport

Network address

Network access

Communications network

Application

Transport

Network access

Application

Transport

Network access

- Each host needs a unique global address referred to as the IP address
- Each application on a multitasking computer needs a unique address, referred to as the Port number, within the computer

Overview of Network Programming: Sockets

## EE450: Introduction to Computer Networks

Professor A. Zahid

Application Programming Interface

- The services provided by the operating system that provide the interface between application and the TCP/IP Protocol Suite.

Application
Network API

Protocol A	Protocol B	Protocol C

API: Sockets

- TCP/IP does not include an API definition.

- There are a variety of APIs for use with TCP/IP:
  - UNIX Sockets
  - Winsock (Windows Sockets)

- A socket is an abstract representation of a communication endpoint.

- A socket allows the application to "plug in" to the network and communicate with other applications

- A socket is uniquely identified by the IP address, Port number and the underlying transport layer protocol

Socket Types

Socket Structure

Socket

Family	Type	Protocol

Local socket address

Remote socket address

Socket Descriptor Data Structure

Descriptor Table

0	●
1	●
2	●
3	●
4	●

Family: PF_INET
Service: SOCK_STREAM
Local IP: 111.22.3.4
Remote IP: 123.45.6.78
Local Port: 2249
Remote Port: 3726

Basic Sockets API

- Clients and Servers differ in some aspects of their use of API and they are the same in other aspects

- Both client and server programs begin by asking the NOS to "create" a socket. The function to accomplish that is Socket ( )
  - int socket (int protocol family, int type, int protocol)
  - Protocol family: PF_INET
  - Type: SOCK_STREAM, SOCK_DGRAM
  - Protocol: TCP, UDP

- Return value of Socket ( ) is a non-negative integer called Socket Descriptor (or –1 if errors)

TCP Server

- Create a TCP socket using Socket ( )

- Assign a port number to the socket using Bind ( )
  - int bind (int socket, local address, address length)
  - Local address is the IP address and the port number of the server. It is this address that the client and the server need to agree on to communicate. Neither one need to know the client address.
  - Address length is length of address structure
  - If successful, Bind ( ) returns a 0, otherwise it returns –1
  - If successful, the socket at server side is "associated " to the local IP address and the local port number

- Listen to connections from clients using Listen ( )
  - int listen (int socket, int queue limit)
  - Queue limit is an upper bound on # of clients that can be waiting
  - If successful, Listen ( ) returns a 0, otherwise it returns –1

TCP Server (Continued)

- The socket that has been bounded to a port and marked for listening is never actually used for sending and receiving. The socket (known as the welcoming socket or the "parent" socket.

- "Child" sockets are created for each client. It is this socket that is actually used for sending and receiving

- Server gets a socket for an incoming client connection by calling Accept ( )
  - int accept (int socket, client address, address length)
  - If successful, accept ( ) returns a descriptor for the new socket, otherwise it returns -1

TCP Server (Continued)

- Once the child socket is created, communications (send and receive) can take place
  - int send (int socket, message, message length)
  - int recv (int socket, recv buffer, buffer length)

- When the application is done with the socket, it needs to close it (The child socket, not the parent socket which is passively open to welcome new clients). This is done by calling Close ( )
  - int close (int socket)

TCP Client

- Create a TCP socket using Socket ( )

- Establish a connection to the server using Connect ( )
  - int connect (int socket, foreign address, address length)
  - Foreign address is the address of the server and the port number of the server (The well-known port number)

- Communications using Send and Recv
  - int send (int socket, message, message length)
  - int recv (int socket, recv buffer, buffer length)

- Close the socket using Close ( )
  - int close (int socket)

Connection-less Iterative Server

Flow Chart: Socket Interface for Connection-Less Iterative Server

Each server serves many clients but handles one request at a time.

Clients

Create a socket

Repeat as needed

Send the request

Receive response when it arrives

Destroy the socket

Server

Create a socket

Bind the socket

Repeat infinitely

Receive a request when it arrives

Process the request

Send the result

Requests

Responses

Connection-oriented Concurrent Server

Flow Chart: Socket Interface for Connection-Oriented Concurrent Server

A parent server creates many children; each child server serves only one client.

Server
- Create a socket
- Bind the socket
- Listen for a client

Connection setup

Repeat infinitely

Create a child to server client

Child server | Parent server

Client
- Create a socket
- Connect to server

Repeat as needed
- Write bytes
- Read bytes when they arrive

Destroy the socket

Child server
- Create a temporary socket

Repeat as needed
- Read bytes when they arrive
- Process
- Write bytes

Destroy the temporary socket