

DEMO DATA â Well Completion Report (Kopili Mud Loss Section)

=====

DEMO DATA - OIL INDIA LIMITED | EXPLORATION & PRODUCTION
WELL COMPLETION REPORT - GEOLOGICAL SECTION 8-1/2 INCH

=====

Well: Duliajan-NWIS-01 | Well ID: OIL-NWIS-ACT-001 | Field: Duliajan
Section: Kopili Formation (Fractured Limestone & Calcareous Siltstone)
Depth Interval: 2350m - 2650m | Section Depth: 2420m

DRILLING EVENT: MUD LOSS at 2420m (Severity: HIGH)
Description: Severe mud loss observed in Kopili Formation. Rate: 12 m3/hr into fractured zone.
Cause: Natural micro-fractures in upper Kopili carbonate stringer coupled with excessive ECD during surge.
Mitigation: Reduced flow rate from 2400 to 1800 L/min. Spotted coarse and medium nutshell LCM pill (50 bbl).
Outcome: Full returns established after 2.0 hours. Resumed drilling with managed equivalent circulating density.
NPT Hours: 2.0 | Mud Loss Rate: 12 m3/hr

DRILLING PARAMETERS AT EVENT:
WOB: 12 t | RPM: 75 | Torque: 16 kN.m | ROP: 6.8 m/hr
MW: 1.32 g/cc | SPP: 210 bar | Flow Rate: 1800 L/min

LESSONS LEARNED: Pre-treat drilling fluid with fine fiber LCM prior to penetrating Kopili limestone top.
BEST PRACTICE: Stage mud weight reduction and monitor pit levels at 5-minute intervals in fractured zones.

=====