Linked List Cycle - LeetCode | SPR102: Placement Ki Taiyari | Q.206 easy - Google Docs | sahilkha453/cap2012-CA3 | Ask Gemini

leetcode.com/problems/linked-list-cycle/

Problem List | Submit | Premium

Description | Editorial | Solutions | Submissions

141. Linked List Cycle

Solved


Easy | Topics | Companies

Given `head`, the head of a linked list, determine if the linked list has a cycle in it.

There is a cycle in a linked list if there is some node in the list that can be reached again by continuously following the `next` pointer. Internally, `pos` is used to denote the index of the node that tail's `next` pointer is connected to. **Note that `pos` is not passed as a parameter**.

Return `true` *if there is a cycle in the linked list*. Otherwise, return `false`.

Example 1:



Input: head = [3,2,0,-4], pos = 1
Output: true
Explanation: There is a cycle in the linked list, where the tail

18K | 588 | 43 Online

Code | Note

C++ | Auto

```cpp
class Solution {
public:
    bool hasCycle(ListNode *head) {
        if (head == nullptr || head->next == nullptr) {
            return false;
        }

        ListNode *slow = head;
        ListNode *fast = head;

        while (fast != nullptr && fast->next != nullptr) {
            slow = slow->next;
            fast = fast->next->next;

            if (slow
```

Saved | Ln 15, Col 21

Testcase | Test Result

Search | ENG IN | 6:56 PM 11/12/2026