

Sr No.	Error	Error Line Number	Error Type	Solution
1	for(int i=0;i<=10;i++) used to print numbers[] (array size is 10, valid indices 0-9)	17	Runtime Error (Array Out of Bounds)	Change loop condition to i<10 so it stays within valid indices.
2	sum = numbers[i]; overwrites sum instead of accumulating it	28	Logical Error	Use sum += numbers[i]; to accumulate the total instead of overwriting it.
3	average = sum / 10; performs integer division, losing decimal part	35	Logical Error	Use average = sum / 10.0f; (or cast sum to float) to get a correct decimal average.
4	printf("Average = %d\n", average); uses %d for a float variable	37	Format Specifier Error	Use %f instead of %d, e.g. printf("Average = %.2f\n", average);
5	if(marks[i] < highest) finds the lowest mark instead of the highest	49	Logical Error	Change the comparison to if(marks[i] > highest) to correctly find the highest mark.
6	attendance[5] = 1; writes outside the array (size 5, valid indices 0-4)	67	Runtime Error (Array Out of Bounds)	Increase array size to attendance[6] or remove this out-of-range assignment.
7	for(int i=0;i<=5;i++) reads attendance[5], which is out of bounds	71	Runtime Error (Array Out of Bounds)	Change loop condition to i<5 so only valid indices are accessed.
8	strcpy(subject,"ComputerScience"); string (15 chars+null) is larger than subject[10]	82	Runtime Error (Buffer Overflow)	Increase array size, e.g. char subject[20]; or use a shorter string.
9	branch = "IT"; tries to assign a string literal directly to an array name	90	Compile-Time Error (Invalid Assignment)	Use strcpy(branch, "IT"); to copy the string into the array instead of assigning.
10	printf("%s\n", college); college[] is filled char by char but never null-terminated	104	Runtime Error (Undefined Behavior / Missing Null Terminator)	Add college[5] = '\0'; after assigning the characters, and size the array as college[6] or larger.
11	fees["two"] = 50000; uses a string literal as an array index	110	Compile-Time Error (Invalid Array Subscript)	Use a valid integer index, e.g. fees[1] = 50000;
12	fees[3.5] = 60000; uses a non-integer (float) array index	112	Compile-Time Warning/Error (Invalid Array Subscript)	Use an integer index, e.g. fees[3] = 60000;

Sr No.	Error	Error Line Number	Error Type	Solution
13	scanf("%d", result[i]); passes the value instead of the address of the element	132	Compile-Time Warning / Runtime Error (Wrong Argument Type to scanf)	Use scanf("%d", &result[i]); to pass the address of the element.
14	if(stock[2] = 300) uses assignment (=) instead of comparison (==)	150	Logical Error (Assignment instead of Comparison)	Use if(stock[2] == 300) to correctly compare the values.
15	backup = stock; tries to assign one array directly to another	159	Compile-Time Error (Invalid Array Assignment)	Copy elements individually in a loop, or use memcpy(backup, stock, sizeof(stock));
16	printf("%d\n", salary[0]); uses %d for a float array element	169	Format Specifier Error	Use %f instead of %d, e.g. printf("%.2f\n", salary[0]);
17	for(int i=0;i<=5;i++) writes inventory[5], which is out of bounds (size 5, valid 0-4)	175	Runtime Error (Array Out of Bounds)	Change loop condition to i<5 so only valid indices are accessed.
18	strcpy(city,"JaipurCity"); string (10 chars+null) is larger than city[8]	191	Runtime Error (Buffer Overflow)	Increase array size, e.g. char city[20]; or use a shorter string.
19	count = inventory; tries to assign one array directly to another	199	Compile-Time Error (Invalid Array Assignment)	Copy elements individually in a loop, or use memcpy(count, inventory, sizeof(inventory));
20	printf("Program Ended\n") is missing a terminating semicolon	205	Compile-Time Error (Syntax Error - Missing Semicolon)	Add a semicolon at the end: printf("Program Ended\n");