

```
#include <stdio.h>
```

```
#include <math.h>
```

```
int calculate(int a, int b);
```

```
int main()
```

```
{
```

```
    int x = 10; // ERROR: Missing semicolon (;)
```

```
        // SOLUTION: int x = 10;
```

```
    int y = 20;
```

```
    printf("Program Started\n");
```

```
    if(x = 10) // ERROR: Assignment operator (=) used instead of comparison operator (==)
```

```
        // SOLUTION: if(x == 10)
```

```
    {
```

```
        printf("X is 10\n");
```

```
    }
```

```
    int marks = "Ninety"; // ERROR: Assigning string to int variable
```

```
        // SOLUTION: int marks = 90;
```

```
        // OR: char marks[] = "Ninety";
```

```
    printf("%d\n", z); // ERROR: Variable z is undeclared
```

```
        // SOLUTION: Declare z before use
```

```
        // Example: int z = 100;
```

```
100 = x; // ERROR: Cannot assign value to a constant
```

```
// SOLUTION: x = 100;
```

```
int arr[5];
```

```
arr[10] = 50; // ERROR: Array index out of bounds
```

```
// SOLUTION: Use index 0 to 4
```

```
// Example: arr[4] = 50;
```

```
float *ptr = &x; // ERROR: Type mismatch (int* assigned to float*)
```

```
// SOLUTION:
```

```
// int *ptr = &x;
```

```
printf("%f\n", x); // ERROR: %f expects float/double but x is int
```

```
// SOLUTION:
```

```
// printf("%d\n", x);
```

```
int a = 10;
```

```
int b = 0;
```

```
printf("%d\n", a/b); // ERROR: Division by zero
```

```
// SOLUTION:
```

```
// if(b != 0) printf("%d\n", a/b);
```

```
char ch = 'AB'; // ERROR: Multi-character constant
```

```
// SOLUTION:
```

```
// char ch = 'A';
```

```
if(x > y)
    printf("X is greater");
else
    printf("X is greater"); // ERROR: Same message in both branches
    // SOLUTION:
    // printf("Y is greater");
```

```
sqrt(25); // WARNING: Result ignored
    // SOLUTION:
    // double result = sqrt(25);
```

```
show(); // ERROR: Function show() not declared/defined
    // SOLUTION:
    // Define show() function or remove call
```

```
while(x < 15); // ERROR: Unwanted semicolon causes infinite loop
    // SOLUTION:
    // while(x < 15)
{
    x++;
}
```

```
continue; // ERROR: continue can only be used inside loops
    // SOLUTION:
    // Place inside a loop or remove
```

```
break; // ERROR: break can only be used inside loop/switch
    // SOLUTION:
```

// Place inside loop/switch or remove

int result = calculate(10); // ERROR: Function requires 2 arguments

// SOLUTION:

// int result = calculate(10, 20);

printf("%d\n", result);

printf("Program Ended\n");

return 0;

}

int calculate(int a, int b)

{

return a + b;

}