

Container Apps Provisioning using Terraform

Prerequisites

1. Azure Account with Subscription.
2. Terraform installed.

Steps

1. Create the **container-apps-terraform** directory.
2. Folders structure for the above-created directory:

```
container-apps-terraform
├── .terraform.lock.hcl
├── locals.tf
├── main.tf
├── outputs.tf
├── providers.tf
├── terraform.tfstate
├── terraform.tfstate.backup
└── .terraform
```

We need to only create *providers.tf*, *main.tf*, *outputs.tf*, & *locals.tf* files. Other files are generated while initiating terraform.

3. Create a *providers.tf* file inside the above-created directory.
4. Inside it, define the following:
 - terraform
 - required_providers
 - provider
 - azurerm
5. Click [code](#) for reference.
6. The definition of *providers.tf* file is complete.
7. Now, create the *main.tf* file.
8. Inside *main.tf* file, we will use the following predefined modules:
 - resource-group
 - virtual-network
 - acr
 - mysql-flexible
 - container-apps
9. Click [code](#) for reference.
10. The definition of *main.tf* file is complete.
11. Now we will create *outputs.tf* file.
12. Inside it, define the following outputs.
 - container-apps-url

- DB_HOST

13. Click [code](#) for reference.
14. The definition of *outputs.tf* file is complete.
15. Now we will create *locals.tf* file.
16. Inside it, define the following variables:
 - resource-group-properties
 - virtual-network-properties
 - acr-properties
 - mysql-flexible-properties
 - container-apps-properties
17. Click [code](#) for reference.
18. The definition of *locals.tf* file is complete.

Make sure you give the appropriate values to the variables defined in *locals.tf* file.

Provisioning the Infrastructure

Now we will provision the Azure infrastructure by applying the above-created configuration files.

Ensure Azure CLI is configured with appropriate Azure account credentials.

Steps:

1. Open the Powershell.
2. Change the directory to the above-created **container-apps-terraform** directory using `cd` command.
3. Run the `terraform init` command to initialize the *terraform*.
4. Run the `terraform fmt --recursive` command to format the syntax of the files.
5. Run the `terraform validate` command to validate the configuration files.
6. Run the `terraform plan` command to plan the resources to be created.
7. Run the `terraform apply` command and if prompted, type `yes` to provision the infrastructure.
8. Run the `terraform output` command to get the values of defined variables in *outputs.tf* file.
9. Then,
 - Copy the DNS address.
 - Paste the address in the browser to access the application.
10. Head to the Azure Console, and verify the created resources.

Screenshots of Provisioned Infrastructure

Resource Group Image




resource-group image

Virtual Network Image



virtual-network image


ACR Image

acr image

MySQL Flexible Server Image

mysql-flexible image

Container Apps Image

container-apps image

Destroy the provisioned infrastructure

1. To destroy infrastructure, change directory to the above created **container-apps-terraform** directory using `cd` command.
 2. Run `terraform destroy` & if prompted, type `yes`.
 3. Infrastructure will be destroyed.
-