

Complex data types in Hive

1. Array

create table result(student_id int, bands array<double>) row format delimited fields terminated by '|' collection items terminated by ','

insert into result select 10 , array(cast(4.5 as double),cast(6.7 as double));

```
hive (mydb)> select * from result;
```

OK

```
result.student_id  result.bands
```

```
10  [4.5,6.7]
```

Time taken: 0.662 seconds, Fetched: 1 row(s)

```
hive (mydb)> select student_id, bands[0] from result;
```

OK

```
student_id  _c1
```

```
10  4.5
```

Time taken: 0.821 seconds, Fetched: 1 row(s)

Hdfs view

```
hduser@shyam:/usr/local/hadoop/etc/hadoop$ hdfs dfs -cat  
/user/hive/warehouse/mydb.db/result/000000_0
```

```
10|4.5,6.7
```

2. Map

create table resultMap(student_id int, bands map<string,double>) row format delimited fields terminated by '|' collection items terminated by ',' map keys terminated by ':'

Input file

```
hduser@shyam:~$ cat tempfile
```

```
10|reading:4.5,speaking:6.7,listening:7.5,writing:7.0
```

```
20|reading:5.5,speaking:6.5,listening:6.5,writing:8.0
```

```
hduser@shyam:~$ hdfs dfs -copyFromLocal tempfile  
/user/hive/warehouse/mydb.db/resultmap/
```

```
hive (mydb)> select * from resultMap;
```

OK

```
resultmap.student_id  resultmap.bands
10  {"reading":4.5,"speaking":6.7,"listening":7.5,"writing":7.0}
20  {"reading":5.5,"speaking":6.5,"listening":6.5,"writing":8.0}
Time taken: 0.126 seconds, Fetched: 2 row(s)
```

```
hive (mydb)> select student_id, bands["listening"] from resultMap;
```

OK

```
student_id  _c1
10  7.5
20  6.5
Time taken: 0.107 seconds, Fetched: 2 row(s)
```

3. Struct

```
create table rider(name string, age int, vehicle_conf struct<reg_no:string, top_speed:int,
cc:int, brand:string>) row format delimited fields terminated by '|' collection items
terminated by ',';
```

```
hduser@shyam:~$ cat tempfile
```

```
Sukhajinder|27|QC123,250,600,YAMAHA
Cesar|35|ON123,300,700,HONDA
```

```
hduser@shyam:~$ hdfs dfs -copyFromLocal tempfile
/user/hive/warehouse/mydb.db/rider/
```

```
hive (mydb)> select * from rider;
OK
rider.name  rider.age  rider.vehicle_conf
Sukhajinder  27  {"reg_no":"QC123","top_speed":250,"cc":600,"brand":"YAMAHA"}
Cesar  35  {"reg_no":"ON123","top_speed":300,"cc":700,"brand":"HONDA"}
Time taken: 0.119 seconds, Fetched: 2 row(s)
```

```
hive (mydb)> select vehicle_conf.brand from rider;
```

OK

```
brand
YAMAHA
HONDA
Time taken: 0.111 seconds, Fetched: 2 row(s)
```

Read XML file in Hive Table

Create TABLE xmltable(xmldata string) STORED AS TEXTFILE;

```
hduser@shyam:~$ cat tempfile
```

```
<dependency><groupId>org.apache.hive</groupId><artifactId>hive-exec</artifactId><version>0.8.0</version></dependency>
<dependency><groupId>org.apache.hadoop</groupId><artifactId>hadoop-core</artifactId><version>1.2.1</version></dependency>
<dependency><groupId>junit</groupId><artifactId>junit</artifactId><version>4.5</version><scope>test</scope></dependency>
```

```
hduser@shyam:~$ hdfs dfs -copyFromLocal tempfile /user/hive/warehouse/mydb.db/xmltable/
```

```
hive (mydb)> select xpath(xmldata, 'dependency/groupId/text()') from xmltable;
```

```
OK
```

```
_c0
```

```
["org.apache.hive"]
```

```
["org.apache.hadoop"]
```

```
["junit"]
```

```
Time taken: 0.109 seconds, Fetched: 3 row(s)
```

Reference:

<https://blog.matthewrathbone.com/2013/08/10/guide-to-writing-hive-udfs.html>

<https://cwiki.apache.org/confluence/display/Hive/GenericUDAFCaseStudy>

<https://cwiki.apache.org/confluence/display/Hive/GenericUDAFCaseStudy#GenericUDAFCaseStudy-WritingGenericUDAFs:ATutorial>

<https://community.hortonworks.com/content/supportkb/150214/how-to-enable-debug-hive-cli-logging.html>

<https://www.edureka.co/blog/apache-hive-installation-on-ubuntu>

http://www.bogotobogo.com/Hadoop/BigData_hadoop_Hive_Install_On_Ubuntu_16_04.php

Hive Serde:

<https://cwiki.apache.org/confluence/display/Hive/LanguageManual+DDL#LanguageManualDDL-RowFormat.StorageFormat.andSerDe>

<https://cwiki.apache.org/confluence/display/Hive/DeveloperGuide#DeveloperGuide-CodeOrganizationandaBriefArchitecture>

<https://stackoverflow.com/questions/24607685/loading-xml-data-into-hive-table-org-apache-hadoop-hive-ql-metadata-hiveexcepti>

Fun to Learn:

<https://stackoverflow.com/questions/20208696/hadoop-restart-datanode-and-tasktracker>

<https://github.com/apache/hive/blob/master/contrib/src/java/org/apache/hadoop/hive/contrib/udaf/example/UDAFExampleAvg.java>

https://courses.cs.ut.ee/MTAT.08.036/2013_fall/uploads/Main/slides5.pdf

<https://cwiki.apache.org/confluence/display/Hive/Tutorial#Tutorial-QueryingandInsertingData>

Java API:

<https://stackoverflow.com/questions/3724415/maven-artifact-and-groupid-naming>