

Basic Calculator Project - HTML, CSS & JavaScript Code

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Basic Calculator</title>

  <style>
    * {
      margin: 0;
      padding: 0;
      box-sizing: border-box;
      font-family: Arial, sans-serif;
    }

    body {
      height: 100vh;
      display: flex;
      justify-content: center;
      align-items: center;
      background: linear-gradient(to right, #4facfe, #00f2fe);
    }

    .calculator {
      background: #ffffff;
      padding: 20px;
      border-radius: 15px;
      box-shadow: 0 5px 15px rgba(0, 0, 0, 0.2);
      width: 320px;
    }

    .display {
      width: 100%;
      height: 60px;
      border: none;
      outline: none;
      text-align: right;
      font-size: 28px;
      padding: 10px;
      margin-bottom: 20px;
      border-radius: 10px;
      background: #f3f4f6;
      color: #111827;
    }

    .buttons {
      display: grid;
      grid-template-columns: repeat(4, 1fr);
      gap: 12px;
    }

    button {
      padding: 18px;
      font-size: 20px;
      border: none;
      border-radius: 10px;
      cursor: pointer;
      background: #e5e7eb;
      transition: 0.2s;
    }

    button:hover {
      background: #d1d5db;
    }

    .operator {
      background: #3b82f6;
      color: white;
    }

    .operator:hover {
      background: #2563eb;
    }

    .equal {
      background: #10b981;
      color: white;
    }
```

```

    grid-column: span 2;
}

.equal:hover {
    background: #059669;
}

.clear {
    background: #ef4444;
    color: white;
}

.clear:hover {
    background: #dc2626;
}
</style>
</head>
<body>

<div class="calculator">
    <input type="text" class="display" id="display" disabled>

    <div class="buttons">
        <button class="clear" onclick="clearDisplay()">C</button>
        <button class="operator" onclick="appendValue('/')">/</button>
        <button class="operator" onclick="appendValue('*')">*</button>
        <button class="operator" onclick="appendValue('-')">-</button>

        <button onclick="appendValue('7')">7</button>
        <button onclick="appendValue('8')">8</button>
        <button onclick="appendValue('9')">9</button>
        <button class="operator" onclick="appendValue('+')">+</button>

        <button onclick="appendValue('4')">4</button>
        <button onclick="appendValue('5')">5</button>
        <button onclick="appendValue('6')">6</button>
        <button onclick="appendValue('.')">.</button>

        <button onclick="appendValue('1')">1</button>
        <button onclick="appendValue('2')">2</button>
        <button onclick="appendValue('3')">3</button>
        <button onclick="appendValue('0')">0</button>

        <button class="equal" onclick="calculateResult()">=</button>
    </div>
</div>

<script>
    let display = document.getElementById('display');

    function appendValue(value) {
        display.value += value;
    }

    function clearDisplay() {
        display.value = '';
    }

    function calculateResult() {
        try {
            display.value = eval(display.value);
        } catch (error) {
            display.value = 'Error';
        }
    }

    // Keyboard Support
    document.addEventListener('keydown', function(event) {
        const key = event.key;

        if ((key >= '0' && key <= '9') || ['+', '-', '*', '/', '.'].includes(key)) {
            appendValue(key);
        } else if (key === 'Enter') {
            calculateResult();
        } else if (key === 'Backspace') {
            display.value = display.value.slice(0, -1);
        } else if (key.toLowerCase() === 'c') {
            clearDisplay();
        }
    });
</script>

```

```
</body>  
</html>
```