



Analysis of Algorithms



An **algorithm** is a step-by-step procedure for solving a problem in a finite amount of time.


Running Time

- ◆ Most algorithms transform input objects into output objects.
- ◆ The running time of an algorithm typically grows with the input size.
- ◆ Average case time is often difficult to determine.
- ◆ We focus on the worst case running time.
 - Easier to analyze
 - Crucial to applications such as games, finance and robotics



Experimental Studies


- ◆ Write a program implementing the algorithm
- ◆ Run the program with inputs of varying size and composition
- ◆ Use a method like `System.currentTimeMillis()` to get an accurate measure of the actual running time
- ◆ Plot the results



Limitations of Experiments

- ◆ It is necessary to implement the algorithm, which is usually difficult
- ◆ In order to compare two algorithms, the same hardware and software environments must be used

Theoretical Analysis



- ◆ Uses a high-level description of the algorithm instead of an implementation
- ◆ Characterizes running time as a function of the input size, n .
- ◆ Takes into account all possible inputs
- ◆ Allows us to evaluate the speed of an algorithm independent of the hardware/software environment

Pseudocode

- ◆ Pseudo-code is a mixture of natural language and high-level programming constructs that describe the main ideas behind a generic implementation of a data structure or algorithm. More structured than English prose.
- ◆ The programming language constructs in pseudocode:

a) Expressions	b) Method declarations
c) Decision structures	d) While-loop
e) Repeat-loops	f) For-loops
g) Array indexing	h) Method calls
i) Method returns	

Pseudocode

- ◆ High-level description of an algorithm
- ◆ More structured than English prose
- ◆ Less detailed than a program
- ◆ Preferred notation for describing algorithms
- ◆ Hides program design issues

Example: find max element of an array

Algorithm *arrayMax*(A, n)

Input array A of n integers

Output maximum element of A

currentMax $\leftarrow A[0]$

for $i \leftarrow 1$ **to** $n - 1$ **do**


if $A[i] > \text{currentMax}$ **then**

currentMax $\leftarrow A[i]$


return *currentMax*

The Random Access Machine (RAM) Model

- ◆ A **CPU**



- ◆ An potentially unbounded bank of **memory** cells, each of which can hold an arbitrary number or character



- ◆ Memory cells are numbered and accessing any cell in memory takes unit time.

Primitive Operations

- ◆ Basic computations performed by an algorithm
- ◆ Identifiable in pseudocode
- ◆ Largely independent from the programming language
- ◆ Exact definition not important (we will see why later)
- ◆ Assumed to take a constant amount of time in the RAM model



◆ Examples:


- Assigning a value to a variable
- Calling a method
- Performing an arithmetic operation (for example, adding two numbers).
- Comparing two numbers
- Indexing, into an array
- Following an object reference
- Returning, from a method.

Counting Primitive Operations

- ◆ By inspecting the pseudocode, we can determine the maximum number of primitive operations executed by an algorithm, as a function of the input size

Algorithm <i>arrayMax</i> (<i>A</i> , <i>n</i>)	# operations
<i>currentMax</i> $\leftarrow A[0]$	2
for <i>i</i> $\leftarrow 1$ to <i>n</i> - 1 do	$2 + n$
if <i>A</i> [<i>i</i>] > <i>currentMax</i> then	$2(n - 1)$
<i>currentMax</i> $\leftarrow A[i]$	$2(n - 1)$
{ increment counter <i>i</i> }	$2(n - 1)$
return <i>currentMax</i>	1
Total	$7n - 1$

Estimating Running Time



- ◆ Algorithm *arrayMax* executes $7n - 1$ primitive operations in the worst case. Define:

a = Time taken by the fastest primitive operation

b = Time taken by the slowest primitive operation

- ◆ Let $T(n)$ be worst-case time of *arrayMax*. Then

$$a(7n - 1) \leq T(n) \leq b(7n - 1)$$

- ◆ Hence, the running time $T(n)$ is bounded by two linear functions


Growth Rates

◆ Growth rates of functions:

- Linear $\approx n$
- Quadratic $\approx n^2$
- Cubic $\approx n^3$

◆ In a log-log chart, the slope of the line corresponds to the growth rate of the function

$T(n)$




Big-Oh Notation

◆ Given functions $f(n)$ and $g(n)$, we say that $f(n)$ is $O(g(n))$ if there are positive constants c and n_0 such that

$$f(n) \leq cg(n) \text{ for } n \geq n_0$$

◆ Example: $2n + 10$ is $O(n)$


- $2n + 10 \leq cn$
- $(c - 2)n \geq 10$
- $n \geq 10/(c - 2)$
- Pick $c = 3$ and $n_0 = 10$



Big-Oh Example

◆ Example: the function n^2 is not $O(n)$

- $n^2 \leq cn$
- $n \leq c$
- The above inequality cannot be satisfied since c must be a constant



More Big-Oh Examples

◆ $7n-2$

$7n-2$ is $O(n)$

need $c > 0$ and $n_0 \geq 1$ such that $7n-2 \leq c \cdot n$ for $n \geq n_0$

this is true for $c = 7$ and $n_0 = 1$

■ $3n^3 + 20n^2 + 5$

$3n^3 + 20n^2 + 5$ is $O(n^3)$

need $c > 0$ and $n_0 \geq 1$ such that $3n^3 + 20n^2 + 5 \leq c \cdot n^3$ for $n \geq n_0$

this is true for $c = 4$ and $n_0 = 21$

■ $3 \log n + \log \log n$

$3 \log n + \log \log n$ is $O(\log n)$

need $c > 0$ and $n_0 \geq 1$ such that $3 \log n + \log \log n \leq c \cdot \log n$ for $n \geq n_0$

this is true for $c = 4$ and $n_0 = 2$

Big-Oh and Growth Rate

- ◆ The big-Oh notation gives an upper bound on the growth rate of a function
- ◆ The statement " $f(n)$ is $O(g(n))$ " means that the growth rate of $f(n)$ is no more than the growth rate of $g(n)$
- ◆ We can use the big-Oh notation to rank functions according to their growth rate

Big-Oh Rules

- ◆ If $f(n)$ is a polynomial of degree d , then $f(n)$ is $O(n^d)$, i.e.,
 1. Drop lower-order terms
 2. Drop constant factors
- ◆ Use the smallest possible class of functions
 - Say " $2n$ is $O(n)$ " instead of " $2n$ is $O(n^2)$ "
- ◆ Use the simplest expression of the class
 - Say " $3n + 5$ is $O(n)$ " instead of " $3n + 5$ is $O(3n)$ "

Asymptotic Algorithm Analysis


- ◆ The asymptotic analysis of an algorithm determines the running time in big-Oh notation
- ◆ To perform the asymptotic analysis
 - We find the worst-case number of primitive operations executed as a function of the input size
 - We express this function with big-Oh notation
- ◆ Example:
 - We determine that algorithm *arrayMax* executes at most $7n - 1$ primitive operations
 - We say that algorithm *arrayMax* “runs in $O(n)$ time”
- ◆ Since constant factors and lower-order terms are eventually dropped anyhow, we can disregard them when counting primitive operations

Computing Prefix Averages

- ◆ We further illustrate asymptotic analysis with two algorithms for prefix averages
- ◆ The i -th prefix average of an array X is average of the first $(i + 1)$ elements of X :

$$A[i] = (X[0] + X[1] + \dots + X[i]) / (i + 1)$$

- ◆ Computing the array A of prefix averages of another array X has applications to financial analysis



Prefix Averages (Quadratic)

- ◆ The following algorithm computes prefix averages in quadratic time by applying the definition

Algorithm *prefixAverages1*(X, n)

Input array X of n integers

Output array A of prefix averages of X #operations

$A \leftarrow$ new array of n integers

n

for $i \leftarrow 0$ **to** $n - 1$ **do**

n

$s \leftarrow X[0]$

n

for $j \leftarrow 1$ **to** i **do**

$1 + 2 + \dots + (n - 1)$

$s \leftarrow s + X[j]$

$1 + 2 + \dots + (n - 1)$

$A[i] \leftarrow s / (i + 1)$


n

return A

1

Arithmetic Progression

- ◆ The running time of *prefixAverages1* is $O(1 + 2 + \dots + n)$
- ◆ The sum of the first n integers is $n(n + 1) / 2$
 - There is a simple visual proof of this fact
- ◆ Thus, algorithm *prefixAverages1* runs in $O(n^2)$ time



Prefix Averages (Linear)

- ◆ The following algorithm computes prefix averages in linear time by keeping a running sum

Algorithm *prefixAverages2*(X, n)

Input array X of n integers

Output array A of prefix averages of X

$A \leftarrow$ new array of n integers

$s \leftarrow 0$

for $i \leftarrow 0$ **to** $n - 1$ **do**

$s \leftarrow s + X[i]$

$A[i] \leftarrow s / (i + 1)$

return A

#operations

n

1

n


n

n

1

- ◆ Algorithm *prefixAverages2* runs in $O(n)$ time

Math you need to Review



◆ Logarithms and Exponents

◆ **properties of logarithms:**

$$\log_b(xy) = \log_b x + \log_b y$$

$$\log_b (x/y) = \log_b x - \log_b y$$

$$\log_b x^a = a \log_b x$$

$$\log_b a = \log_x a / \log_x b$$

◆ **properties of exponentials:**

$$a^{(b+c)} = a^b a^c$$


$$a^{bc} = (a^b)^c$$

$$a^b / a^c = a^{(b-c)}$$

$$b = a^{\log_a b}$$

$$b^c = a^{c \cdot \log_a b}$$

Intuition for Asymptotic Notation



Big-Oh

- $f(n)$ is $O(g(n))$ if $f(n)$ is asymptotically **less than or equal** to $g(n)$

big-Omega

- $f(n)$ is $\Omega(g(n))$ if $f(n)$ is asymptotically **greater than or equal** to $g(n)$

big-Theta

- $f(n)$ is $\Theta(g(n))$ if $f(n)$ is asymptotically **equal** to $g(n)$

little-oh

- $f(n)$ is $o(g(n))$ if $f(n)$ is asymptotically **strictly less** than $g(n)$

little-omega

- $f(n)$ is $\omega(g(n))$ if $f(n)$ is asymptotically **strictly greater** than $g(n)$