

15. Python - List Data Structure

Table of Contents

1. Why should we learn about data structures?	2
2. Python Data structures	3
3. Sequence of elements	3
4. list data structure	4
5. Creating list	6
5.1. Creating empty list	6
5.2. Creating list with elements	6
5.3. Creating list by using list(p) predefined function	9
6. list having mutable nature	10
7. Accessing elements from list	11
7.1. By using index	11
7.2. Slicing	15
7.3. Accessing list by using for loop	17
8. len(p) function	18
9. Methods in list data structure	19
9.1. count(p)method	21
9.2. append(p)method	22
9.3. insert(p1, p2) method:	23
9.4. remove(p) method:	24
9.5. reverse():	25
9.6. sort() method:	26
10. Mathematical + and * operators	27
10.1. Concatenation operator +	27
10.2 Repetition operator *	27
11. Membership operators	28
12. list comprehension	29

15. Python - List Data Structure

1. Why should we learn about data structures?

- ✓ The common requirement in any real time project is like, creating, updating, retrieving, and deleting elements.
- ✓ Few more real times operations are below,
 - Storing
 - Searching
 - Retrieving
 - Deleting
 - Processing

 - Duplicate

 - Ordered
 - Unordered

 - Size
 - Capacity

 - Sorting
 - Un-sorting
 - Random access

 - Keys
 - Values
 - Key – value pairs
- ✓ So, to understand above operations where to use and how to use then we need to learn about data structures.

2. Python Data structures

- ✓ If you wanted to store a group of individual objects in a single entity, then you should go for data structures.

3. Sequence of elements

- ✓ Data structure also called as sequence.
- ✓ A sequence is a datatype that can contains a group of elements.
- ✓ The purpose of any sequence is, to store and process a group of elements.
- ✓ In python, strings, lists, tuples, set and dictionaries are very important sequence datatype.

4. list data structure

- ✓ We can **create** list by using,
 - square brackets `[]` symbols
 - `list()` predefined function.
- ✓ A list can **store** group of objects or elements.
 - A list can store **same** (Homogeneous) type of elements.
 - A list can store **different** type (Heterogeneous) of elements.
- ✓ A list **size** will increase dynamically.
- ✓ In list **insertion** order is preserved or **fixed**.
 - If we insert elements into 10, 20, 30 then output also will display as 10, 20, 30 then this is called as insertion order is preserved or fixed
 - Example
 - Input => [10, 20, 30]
 - Output => [10, 20, 30]
- ✓ **Duplicate** elements are allowed.
- ✓ List having **mutable** nature.
 - Mutable means once we create a list object then we can change or modify the content of list object.
- ✓ Store elements by using **index**.
 - A list data structure supports both positive and negative indexes.
 - Positive index means from left to right
 - Negative index means right to left

Note:

- ✓ Inside list every object can be separated by comma separator.
-

Make a note

- ✓ list is a predefined class in python.
- ✓ Once if we create list object means internally object is creating for list class.
- ✓ What is a class how class works, we will learn in OOPs chapter.

5. Creating list

- ✓ We can create list by using square brackets `[]`
- ✓ Inside list, elements will be separated by comma separator

5.1. Creating empty list

- ✓ An empty list is valid

Program Name Creating empty list
demo1.py

```
a = []  
print(a)  
print(type(a))
```

Output

```
[]  
<class 'list'>
```

5.2. Creating list with elements

- ✓ We can create list directly with elements.

Program Name Creating list with same type of elements
demo2.py

```
numbers = [10, 20, 30, 40]  
print(numbers)
```

Output

```
[10, 20, 30, 40]
```

Program Name Creating list with same type of elements with **duplicates**
demo3.py

```
numbers = [10, 20, 30, 40, 10, 20, 30, 40]  
print(numbers)
```

Output
[10, 20, 30, 40, 10, 20, 30, 40]

Program Name creating list with same type of elements
demo4.py

```
names = ["Daniel", "Prasad", "Ramesh", "Daniel"]  
print(names)
```

Output
["Daniel", "Prasad", "Ramesh", "Daniel"]

Program Name Creating list with **different** type of elements
demo5.py

```
student_info = ["Daniel", 10, 35.9]  
print(student_info)
```

Output
["Daniel", 10, 35.9]

Note

- ✓ Observe the above programs output,
 - Order is preserved
 - Duplicates are allowed.

5.3. Creating list by using list(p) predefined function

- ✓ list(p) is a predefined function in python.
- ✓ By using this function we can create list.
- ✓ list(p) function takes only one parameter.
- ✓ This parameter should be sequence (range, list, set, tuple, etc...) object otherwise we will get error.

Program Name Creating list by using list(p) function
demo6.py

```
r = range(0, 10)
a = list(r)
print(a)
```

output

```
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]
```

6. list having mutable nature

- ✓ Once we created a list object then we can change or modify the elements in the existing list object.
- ✓ So, list having mutable nature.

Program Name list having mutable nature
demo7.py

```
a = [1, 2, 3, 4, 5]
print(a)
print("Before modifying a[0] : ", a[0])

a[0] = 20
print("After modifying a[0] : ", a[0])
print(a)
```

output

```
[1, 2, 3, 4, 5]
Before modifying a[0] : 1
After modifying a[0] : 20
[20, 2, 3, 4, 5]
```


7. Accessing elements from list

✓ We can access elements from list by using,

1. Index.
2. Slice operator.
3. loops

7.1. By using index

✓ **index** represents accessing the elements by their position numbers in the list.



- ✓ **Indexing** represents accessing the elements by their position numbers in the list.
- ✓ Index starts from **0** onwards.
- ✓ List supports both positive and negative indexes.
 - Positive index represents from left to right direction
 - Negative index represents from right to left.
- ✓ If we are trying to access beyond the range of list index, then we will get error like **IndexError**.

Program list indexing
Name demo8.py

```
names = ["Daniel", "Prasad", "Ramesh"]  
  
print(names)  
  
print(names[0])  
print(names[1])  
print(names[2])  
  
print(type(names))
```

output

```
['Daniel', 'Prasad', 'Ramesh']  
Daniel  
Prasad  
Ramesh  
<class 'list'>
```

Program list indexing
Name demo9.py

```
names = ["Daniel", "Prasad", "Ramesh"]

print(names)

print(names[0])
print(names[1])
print(names[2])

print(type(names))

print(type(names[0]))
print(type(names[1]))
print(type(names[2]))
```

output

```
['Daniel', 'Prasad', 'Ramesh']
Daniel
Prasad
Ramesh
<class 'list'>
<class 'str'>
<class 'str'>
<class 'str'>
```

Program Name **IndexError: list index out of range**
demo10.py

```
names = ["Daniel", "Prasad", "Ramesh"]
```


```
print(names)  
print(names[30])
```

output

```
['Daniel', 'Prasad', 'Ramesh']  
IndexError: list index out of range
```

7.2. Slicing

- ✓ Slicing represents extracting a piece of the list from already created list



Syntax

[start: stop: stepsize]

- ✓ **start**
 - It indicates the index where slice can start.
 - Default value is 0
- ✓ **stop**
 - It indicates the index where slice can end.
 - Default value is max allowed index of list i.e. length of the list
- ✓ **Step size**
 - Increment value.
 - Default value is 1

Program Slice example
Name demo11.py

```
n = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
print(n)
print(n[:])
print(n[:])
print(n[0:5:])
```

output

```
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
[1, 2, 3, 4, 5]
```


7.3. Accessing list by using for loop

- ✓ We can access elements from list by using **for** loop.

Program Name accessing elements from list by using for loop
demo12.py

```
values = [100, 200, 300, 400]
```

```
for value in values:  
    print(value)
```

output

```
100  
200  
300  
400
```

8. len(p) function

- ✓ By using len(p) predefined function we can find the length of list.
- ✓ This function returns the number of elements present in the list.

Program Name	To find length of list demo13.py
	<pre>values = [10, 20, 30, 40, 50] print(len(values))</pre>
Output	5

9. Methods in list data structure

- ✓ As discussed, list is a predefined class.
- ✓ So, list class can contain methods because methods can be created inside of class only.
- ✓ We can check these methods by using `dir(parameter1)` predefined function.
- ✓ So, internally list class contains two types of methods,
 - With underscore symbol methods.
 - We no need to focus
 - Without underscore symbol methods.
 - We need to focus much on these

Program Name Printing list data structure methods by using `dir(list)` function
demo14.py

```
print(dir(list))
```

output

```
[  
    '__add__', ....., '__subclasshook__',  
    ...]
```

Important methods

```
'append', 'count', 'insert', 'remove', 'reverse', 'sort'
```

```
]
```

Important point

- ✓ As per object-oriented principle,
 - If we want to access instance methods, then we should access by using object name.
- ✓ So, all list methods we can access by using list object.

Important methods in list

- ✓ count(p) method
- ✓ append(p) method
- ✓ insert() method
- ✓ remove() method
- ✓ reverse() method
- ✓ sort() method

9.1. count(p)method

- ✓ count(p) is a predefined method in list class
- ✓ We should access this method by using list object.
- ✓ This method returns the number of occurrences of specific value in the list.

Program Name To find count of specific value in list
demo15.py

```
n = [1, 2, 3, 4, 5, 5, 5, 3]
print(n.count(5))
print(n.count(2))
```

output

```
3
1
```

9.2. append(p)method

- ✓ append(p) is a predefined method in list class
- ✓ We should access this method by using list object.
- ✓ This method adds object or element to the existing list object.
- ✓ This method will add the object to list at the end of the list.

Program Name appending elements into list
demo16.py

```
a = []  
a.append(10)  
a.append(20)  
a.append(30)  
print(a)
```

output

```
[10, 20, 30]
```

Program Name appending elements into list
demo17.py

```
a = [10, 20, "Daniel"]  
  
a.append("Naresh")  
a.append("Veeru")  
print(a)
```

output

```
[10, 20, "Daniel", "Naresh", "Veeru"]
```

9.3. insert(p1, p2) method:

- ✓ insert(p1, p2) is a predefined method in list class.
- ✓ We should access this method by using list object.
- ✓ By using this method we can insert value at specific position in list.

Program Name inserting elements into list
demo18.py

```
a = [10, 20, 30, 40, 50]
```

```
a.insert(0, 76)  
print(a)
```

output

```
[76, 10, 20, 30, 40, 50]
```

append(element)	insert(index, element)
✓ This method adds element at last position.	✓ This method adds element at specific index position.

9.4. remove(p) method:

- ✓ remove(p) is a predefined method in list class
- ✓ We should access this method by using list object.
- ✓ By using this method we can remove value from list.

Program Removing element from list
Name demo19.py

```
a = [10, 20, 30]
```

```
a.remove(10)  
print(a)
```

output

```
[20, 30]
```


Ordering elements of List:

9.5. reverse():

- ✓ reverse() is a predefined method in list class
- ✓ We should access this method by using list object.
- ✓ By using this method we can reverse values in list.

Program reverse of the list
Name demo20.py

```
a = [10, 20, 30, 40]
```

```
print(a)  
a.reverse()  
print(a)
```

output

```
[10, 20, 30, 40]  
[40, 30, 20, 10]
```

9.6. sort() method:

- ✓ sort() is a predefined method in list class
- ✓ We should access this method by using list object.
- ✓ By default insertion order is fixed.
- ✓ By using this method we can sort values in list.
 - For numbers the order is ascending order.
 - For strings the order is alphabetical order

Program sorting the numbers and names
Name demo21.py

```
a = [10, 40, 50, 20, 30]
a.sort()
print(a)
```

```
b = ['Daniel', 'Ramesh', 'Arjun']
b.sort()
print(b)
```

output

```
[10, 20, 30, 40, 50]
['Arjun', 'Daniel', 'Ramesh']
```

10. Mathematical + and * operators

10.1. Concatenation operator +

- ✓ '+' operator concatenate two list objects to join them and returns single list.

Program Name + operator concatenates the lists
demo22.py

```
a = [10, 20, 30]
b = [40, 50, 60]
c = a + b
```

```
print(c)
```

output

```
[10, 20, 30, 40, 50, 60]
```

10.2 Repetition operator *

- ✓ '*' operator works to repetition of elements in the list.

Program Name * operator repetition the lists
demo23.py

```
a = [10, 20, 30]

print(a)
print(a*2)
```

output

```
[10, 20, 30]
[10, 20, 30, 10, 20, 30]
```

11. Membership operators

- ✓ We can check if the element is a member of a list or not by using membership operators those are,
 - **in** operator
 - **not in** operator
- ✓ If the element is member of list, then **in** operator returns True otherwise False.
- ✓ If the element is not in the list, then **not in** operator returns True otherwise False

Program Membership operators
Name demo24.py

```
a = [10, 20, 30, 40, 50]
```

```
print(20 in a)                # True  
print(20 not in a)            # False
```

```
print(90 in a)                # False  
print(90 not in a)            # True
```

output

```
True  
False  
False  
True
```

12. list comprehension

- ✓ List comprehensions represents creating new lists from Iterable object like a list, set, tuple, dictionary and range.
- ✓ List comprehension takes input as iterable, we can apply conditional logic on every item and returns new list.
- ✓ List comprehensions code is very concise way.

Syntax

```
list = [expression for item1 in iterable1 if statement]
```

- ✓ Here Iterable represents a list, set, tuple, dictionary or range object.
- ✓ The result of list comprehension **is new list** based on the applying conditions.

Program Name list comprehension example
demo25.py

```
values = [10, 20, 30]  
result = [value+2 for value in values]
```

```
print(values)  
print(result)
```

output

```
[10, 20, 30]  
[12, 22, 32]
```

Program Name list comprehension example
demo26.py

```
values = [10, 20, 30]  
result = [value*3 for value in values]
```

```
print(values)  
print(result)
```

output

```
[10, 20, 30]  
[30, 60, 90]
```

Program Name list comprehension example
demo27.py

```
values = [10, 20, 30, 40, 50, 60, 70, 80, 90]  
result = [value for value in values if value <= 50]
```

```
print(values)  
print(result)
```

output

```
[10, 20, 30, 40, 50, 60, 70, 80, 90]  
[10, 20, 30, 40, 50]
```

Program Name square numbers from 1 to 10 by using list comprehension
demo28.py

```
values = range(1, 11)
squares = [value*2 for value in values]
print(squares)
```

output

```
[2, 4, 6, 8, 10, 12, 14, 16, 18, 20]
```