



DBA5103 Term Paper

Optimizing Urban Traffic Flow: A Comparative Analysis of Static vs. Simulation-Guided Scheduling

Group 17

Smridh Varma – A0318634B
Sai Ashwin Kumar – A0329294U
Siddarth Mahesh – A0318775N
Rahul Narayanan – A0318552A
Satrio Prakoso Susilo – A0318978E
Le Tuan Tung – A0293505A

November 23, 2025

Table of Contents

1	Introduction	1
2	Literature Review	1
2.1	Pre-existing Methodologies	1
2.1.1	Classical fixed-time traffic signal optimisation	1
2.1.2	Heuristics Approach	2
2.1.3	Hybrid Approach	2
2.2	Research Gaps	3
3	Methodology	3
3.1	Problem Description	4
3.2	Dataset Description	6
3.3	Models and Implementation	7
3.3.1	Model 1: Greedy Model	8
3.3.2	Model 2: Greedy Model with Demand Calculation	9
3.3.3	Model 3: Demand-Weighted Local Search with Simulation Feedback	10
3.3.4	Model 4: Time ordered schedule Model	14
4	Real-City Case Study: Bengaluru Traffic Simulation	15
5	Comparative Simulation Study: The <i>Organic City</i> Stress Test	20
6	Comparative Analysis and Discussion	21
6.1	Quantitative Performance	22
6.2	Qualitative Comparison	22
6.3	Discussion: The Algorithmic Journey	22
7	Conclusion and Future Work	23

1 Introduction

Urban mobility has become a defining feature of modern cities, with road traffic networks acting as critical arteries that connect people, goods, and services. As populations grow and vehicle ownership increases, intersections controlled by traffic lights emerge as key bottlenecks that can either enable smooth flow or amplify congestion. Even modest delays at busy junctions can cascade across the network, leading to longer travel times, fuel wastage, and heightened emissions, while also affecting user experience for commuters and logistics operators alike.

To cope with these pressures, city planners and engineers have increasingly turned to data-driven and algorithmic approaches to design smarter traffic control strategies. Traditional fixed-timing traffic light plans are often calibrated manually or heuristically and may not fully exploit the structure of known traffic patterns, such as predefined routes, peak periods, or network layout. Operations Research and optimization techniques offer a systematic way to translate these patterns into signal schedules that are not only feasible, but also explicitly aligned with performance objectives such as throughput, delay reduction, or service quality.

In this project, we focus on an intersection-level signal control problem where vehicles follow predetermined routes through a directed network of streets and signalized junctions. At each intersection, only one incoming street can have a green light at any given second, and a configurable, cyclic schedule determines the order and duration of these green phases. Vehicles queue at the end of streets when facing a red light, proceed through intersections when their approach is green, and earn a score if they are able to complete their routes within a given planning horizon. This scoring mechanism captures both successful completion and timeliness, rewarding schedules that allow more cars to finish earlier.

Our goal is to design an optimization model that selects, for each intersection, which incoming streets should receive green phases and for how long, so that the total score across all vehicles is maximized. We formulate this as a mathematical programming problem, motivated by the underlying business and operational notion of improving network efficiency under strict signal-control rules. We then develop and test candidate scheduling strategies using computational experiments on representative instances, before concluding with a discussion of the model's behavior and possible extensions, such as richer objectives or more realistic traffic dynamics.

2 Literature Review

2.1 Pre-existing Methodologies

Urban traffic signal control is a classic problem in operations research and transportation science. The planner's goal is to allocate green time at intersections so as to reduce congestion, travel time, and delay for vehicles moving through a network of urban streets.

2.1.1 Classical fixed-time traffic signal optimisation

The problem of optimising signal timings on an urban network has a long history in operations research. One of the earliest approaches was fixed-time optimisation, where each intersection operates on a repeating signal cycle with predetermined green interval durations. The cycle repeats identically and no dynamic adjustments are made.

Little (1966) formulated the synchronisation of traffic signals as a mixed-integer linear program (MILP). The aim is to coordinate signals so that a group of cars can travel along a street without stopping for red lights. The notion of “bandwidth” was introduced as the portion of each signal cycle during which a group of vehicles can pass through all signals without encountering a red light. The objective of the MILP, known as MAXBAND, is to maximise this bandwidth, and a branch-and-bound algorithm was developed to solve the model. The method was demonstrated on an example with 10 traffic signals [1].

2.1.2 Heuristics Approach

Beyond optimisation frameworks, a substantial amount of research relies on pure heuristic or metaheuristic algorithms to design traffic-signal timing plans without solving any underlying MILP formulation. These methods search the solution space using mechanisms inspired by natural processes or intelligent search strategies such as genetic algorithms, ant colony optimisation, or simulation-based search. For example, Khasawneh and Awasthi (2023) investigate several metaheuristic and machine learning algorithms such as Long Short-Term Memory (LSTM), decision trees (DT), recurrent neural networks (RNN), and other prediction models to estimate congestion levels at signalised intersections [2]. Their study shows that these methods are capable of producing competitive solutions in complex networks.

Pure heuristics typically operate by iteratively modifying a candidate signal plan—for example, adjusting green times, offsets, or cycle lengths—based on a fitness function that measures delay, throughput, queue length, or other traffic performance indicators. Because they do not require linearity or convexity, heuristics can handle large, nonlinear, or highly constrained networks that are computationally intractable for MILP models. As a result, they are widely used for city-scale signal control, where the dimensionality of the problem makes exact optimisation impossible.

However, pure heuristics also have limitations. They may converge slowly, become trapped in local optima, require many simulation runs, and produce solutions without optimality guarantees. Consequently, several studies, including Khasawneh and Awasthi (2023), note that while pure heuristics are effective at exploring large search spaces, their performance can often be enhanced by combining them with MILP formulations that provide structure or feasibility guidance. This motivates the hybrid MILP–heuristic approach adopted in the present study, where pure heuristics serve as a scalable foundation but are complemented by exact optimisation insights on smaller sub-instances.

2.1.3 Hybrid Approach

Recent studies also adopt hybrid methodologies that integrate the modelling accuracy of MILP with the scalability or realism of heuristic and simulation-based methods. For example, Coşkun (2024) uses a two-step approach: first, MILP is employed to generate initial timing plans, and then a local-search heuristic is applied to improve them [3].

Coşkun develops multi-objective MILP models for optimising signals at intersections under oversaturated traffic. The MILP uses different objective functions, namely minimizing total remaining queue (MTQLM) and distributing the remaining queue across lane groups after each signal (MMQLM). Two objective functions are introduced because, in oversaturated situations, the MTQLM approach alone can lead to uneven queues in different lane groups, which can be balanced by the MMQLM approach.

To evaluate the performance of his model, Coşkun uses the HCM 2000 delay model, a standard formula from the Highway Capacity Manual 2000 (HCM 2000) for estimating av-

erage control delay per vehicle at a signalized intersection. The delay calculation formula in the HCM 2000 model is nonlinear, which the MILP models alone cannot fully capture. Therefore, a Neighbourhood Search Method (NSM) is added as a fast heuristic “fine-tuning” step. Starting from the MILP solution, NSM explores small local changes in green times within a neighbourhood and keeps any change that reduces the HCM delay, achieving additional delay reductions without the huge computation required by exact optimisation over the full nonlinear delay function.

These two-step approaches for addressing oversaturated conditions yield lower delay results and shorter execution times compared to exhaustive search or pure MILP methods. This reinforces the effectiveness of hybrid approaches for solving traffic signal optimisation problems.

2.2 Research Gaps

Conventional signal strategies include fixed-time plans (precomputed cycles), coordinated timing (green waves), and decades-old adaptive systems deployed in practice (for example, SCOOT, SCATS, and their variants). While these systems improve performance over naive fixed timings by using local detectors and linking adjacent intersections, they depend on hand-tuned parameters, limited sensor coverage, and relatively simple optimization heuristics. Consequently, they struggle with large networks, mixed traffic modalities, and rapidly changing demand patterns. The incremental improvements they deliver are often insufficient for megacity-scale congestion and for multi-objective goals such as delay reduction, emissions mitigation, safety, and transit priority [4].

Many major cities still experience severe congestion and intersection inefficiencies despite long-term investments in signaling. Analyses of urban congestion report very high yearly delay per driver in cities such as Beijing and Los Angeles, while London continues to register some of the highest congestion-hour exposure in Europe, with substantial economic cost and hours lost per driver. On the operational side, some Indian cities have observed that newly installed fixed-timing signals actually increased vehicle pileups until adaptive strategies were considered, illustrating the practical risk of non-adaptive deployments in complex junctions. These real-world examples underscore that signal timing shortfalls are both widespread and impactful [5].

Inefficient signal control causes four classes of harm that motivate optimization research:

1. Increased travel time and unreliability for commuters and freight (productivity loss),
2. Higher fuel consumption and air pollutant; CO₂ emissions from stop-and-go traffic,
3. Elevated accident and conflict risk at congested intersections, and
4. Poorer performance for public transport and active modes when priority is not provided. [6]

Quantitative studies show that data-driven signal improvements can materially reduce trip times and emissions at scale, indicating substantial room for optimization.

3 Methodology

The dataset used in this study is the Hash Code 2021 Traffic Signaling dataset obtained from Kaggle (2021), which provides a network of intersections, streets, and vehicle routes. This dataset forms the basis for our optimisation models [7].

3.1 Problem Description




Figure 1: Example a city plan with 4 intersections

Figure 1 illustrates the structural model of the city. The system is defined as a network of intersections (nodes, indexed 0 to 3) and one-way streets (directed edges, labeled a-street through g-street). The key characteristics are as follows:

- **Directionality:** All streets are unidirectional. Two intersections can be connected by two separate streets in opposite directions (e.g., intersections 0 and 2 are connected by “a-street” and “b-street”), but never by two streets in the same direction.
- **Travel Time (L):** Each street has a fixed transit time (L). A car entering a street at time T arrives at the end at $T + L$, regardless of traffic density on that specific road segment.
- **Connectivity:** Unlike a planar graph, streets can cross without intersecting (via bridges or tunnels), such as “c-street” passing over “a-street” and “b-street” without forming a node.

Figure 2 demonstrates the simulation rules for traffic flow at an intersection. The system uses discrete-time simulation (1-second steps) with a First-In-First-Out (FIFO) queue logic. The main rules are as follows:

- **Queuing:** Cars queue at the end of incoming streets. In the figure, cars queue on “a-street” and “b-street” waiting to cross to “c-street” or “d-street”.
- **Signal States:** A traffic light can be either Green (flow allowed) or Red (flow stopped). Only one incoming street can have a green light at any specific time.
- **Throughput Capacity:** The flow rate is strictly limited to one car per second during a green light. For example, if a green light lasts for $T_1 = 2$ seconds (as seen in panel c), exactly two cars from “a-street” can cross.
- **Cycle Execution:** The figure visualizes the sequential switching: “a-street” is green for 2 seconds (allowing the yellow and green cars to pass), followed by “b-street” turning green (allowing the purple car to pass).




Figure 2: Example an intersection with two incoming streets

Figure 3: The simulation starting at $T = 0s$ and ending at $T = 5s$.

Figure 3 details the temporal states of cars-moving vs. waiting-over a 5 second simulation

window. The key points are as follows:

- **Transit vs. Queue:** The street shown has a travel time of $L = 3$ s. The diagram distinguishes between cars in transit (moving along the street) and cars queuing at the intersection.
- **The “Green Wave” Effect:**
 - The Yellow car (1st in queue) leaves immediately at $T = 1$ s when the light turns green and arrives at the destination exactly 3 seconds later ($T = 4$ s).
 - The Red car (2nd in queue) is delayed by the throughput constraint. It waits 1 second for the yellow car to clear, starts moving at $T = 2$ s, and arrives at $T = 5$ s.
 - The Purple car (3rd in queue) fails to cross because the green light duration was insufficient to clear the queue before turning red again.
- **Optimization Challenge:** This figure highlights that schedules must account for both L (transit time) and queue clearing times.

3.2 Dataset Description

The dataset (`hashcode.in`) describes a large-scale synthetic city defined by two primary components: topology and vehicle movement.

City Topology (Streets): Each street is a directed edge in the graph, defined by:

- Start (B) and End (E) Intersections: The nodes connected by the street.
- Unique Name: A string identifier (e.g., “rue-de-londres”).
- Travel Time (L): The minimum time required for a car to traverse the street (in seconds).

Vehicle Movement (Car Paths): Each car is defined by a fixed journey:

- Path Length (P): The total number of streets in the sequence.
- Sequence of Streets: The ordered list of street names the car must traverse.
- Initial State: All cars begin the simulation at the end of the first street in their path, waiting for the traffic light to turn green to enter the second street.
- Path Validity: All paths are guaranteed to be valid sequences of connected streets.

Problem Instance Parameters: The specific scenario analyzed in this study is characterized by the following scale:

- Duration (D): 7,071 seconds.
- Intersections (I): 8,000 nodes.
- Streets (S): 63,968 edges.
- Cars (V): 1,000 vehicles.
- Bonus (F): 1,000 points per successful car.

Key Data Observations:

- Sparsity: With $\sim 64,000$ streets and only 1,000 cars, the vast majority of streets will likely remain empty throughout the simulation. This sparsity is a critical leverage point for optimization; allocating green time to empty streets is pure waste.
- “Clumped” Arrivals: Since cars follow fixed paths and start simultaneously (or in waves), they arrive at intersections in platoons rather than a uniform flow. This creates dynamic bottlenecks that shift over time.

3.3 Models and Implementation

Traffic signal optimization can be formulated as a mathematical programming problem, where the goal is to schedule green lights at intersections to maximize traffic flow efficiency while respecting physical and operational constraints. The following formulation defines the sets, parameters, decision variables used in this study.

Sets and Indices

- $v \in V$: Set of cars.
- $s \in S$: Set of streets.
- $i \in I$: Set of intersections.
- $t \in \{0, \dots, D\}$: Time steps (seconds).
- $\text{Incoming}(i)$: Set of streets entering intersection i .

Parameters

- D : Maximum simulation duration.
- F : Fixed bonus points per car.
- L_s : Travel time required to traverse street s .
- $P_v = (s_{v,1}, s_{v,2}, \dots, s_{v,k_v})$: Predefined path of car v .

Decision Variables

- $g_{i,s,t} \in \{0, 1\}$: Binary variable. 1 if the light is green for street s at intersection i at time t , 0 otherwise.
- $t_{\text{out}}^{(v,s)} \in \mathbb{Z}_{\geq 0}$: The time car v leaves street s (crosses the intersection).

Scoring Metric

The scoring metric for each car is as follows

$$S_{\text{car}} = \begin{cases} F + (D - T) & T \leq D \\ 0 & \text{otherwise} \end{cases}$$

where

- D is the simulation duration.
- F is the fixed bonus points awarded for reaching destination.
- T is the time at which car reaches destination.

From this, it is observed that

- $(D-T)$ represents the efficiency bonus, awarding 1 point for every second remaining in the simulation at the moment of arrival.
- Any vehicle that fails to complete its designated path within the simulation time limit ($T > D$) receives a score of 0.

- The total score of the simulation is the sum of the scores of each car.
- The maximum score from the fixed bonus component is 1,000,000 as there are 1000 cars with 1000 points bonus for each of them.
- Any score obtained which is greater than 1,000,000 in the case of all cars finishing comes from the time efficiency component and shows how much time was saved in the simulation.
- In general, the fixed bonus score is indicated by $F \times \text{Number of vehicles that reached destination}$ and time efficiency is indicated by $\text{Total Score} - \text{Score from Fixed Bonus}$

3.3.1 Model 1: Greedy Model

Objective Function: Maximize the total score Z :

$$\text{Maximize } Z = \sum_{v \in V} x_v \cdot \left(F + (D - t_{\text{finish}}^{(v)}) \right)$$

Where x_v is an indicator function:

$$x_v = \begin{cases} 1 & \text{if } t_{\text{finish}}^{(v)} \leq D \\ 0 & \text{otherwise} \end{cases}$$

And $t_{\text{finish}}^{(v)}$ is the time car v completes its last street.

Constraints

1. Traffic Light Exclusivity At any intersection i , at most one incoming street can have a green light at time t :

$$\sum_{s \in \text{Incoming}(i)} g_{i,s,t} \leq 1, \quad \forall i \in I, \forall t \in \{0, \dots, D\}$$

2. Cyclic Schedule Definition The traffic light schedule must repeat every C_i seconds (where C_i is the total cycle duration):

$$g_{i,s,t} = g_{i,s,(t \bmod C_i)}$$

3. Travel Time Physics The time a car arrives at the end of street s (t_{arrive}) depends on when it left the previous street plus the travel time L_s :

$$t_{\text{arrive}}^{(v,s)} = t_{\text{out}}^{(v,s_{\text{prev}})} + L_s$$

4. Traffic Signal Compliance A car can only cross the intersection (leave street s) if the light is green at that moment, and it has actually arrived at the intersection:

$$\begin{aligned} g_{i,s,t_{\text{out}}^{(v,s)}} &= 1 \\ t_{\text{out}}^{(v,s)} &\geq t_{\text{arrive}}^{(v,s)} \end{aligned}$$

5. Queue & Capacity If car u is immediately ahead of car v in the queue on street s , car v must wait at least 1 second after car u leaves:

$$t_{\text{out}}^{(v,s)} \geq t_{\text{out}}^{(u,s)} + 1$$

6. Deadline Definition The finish time is defined as the time the car leaves the last street in its path:

$$t_{\text{finish}}^{(v)} = t_{\text{out}}^{(v, s_{\text{last}})}$$

Results: The simulation results demonstrate that all 1,000 cars successfully completed their routes, indicating that the generated traffic-light schedule ensured full network throughput. The solution achieved a total score of **4,006,847**, reflecting efficient traffic flow relative to the simulation's time horizon.

3.3.2 Model 2: Greedy Model with Demand Calculation

Given the complexity of the full problem (which involves car dynamics, queuing, and non-linear time dependency), a two-step approach is employed:

- **Demand Calculation:** Determine the relative importance (demand) of each street by analyzing car paths
- **MILP Optimization:** Use a Gurobi Mixed-Integer Linear Programming (MILP) model to find the optimal relative green light durations based on the calculated demand, while satisfying cycle time and minimum green time constraints.

The core objective is to maximize the final score, where a car finishing at time $T \leq D$ contributes $F + (D - T)$ points.

Street Demand Calculation

This model estimates the required green light duration for a street based on how frequently it is used by cars that have a chance to finish their journey.

Demand Metric

The demand for a street s is calculated by weighting its usage frequency by the car's importance (a measure of how critical the car's path is to the overall score). Cars with shorter paths are deemed more valuable because they are more likely to finish within the deadline D . Dividing by PathLength_v prioritizes streets used by these shorter, high-value paths.

$$\text{Demand}_s = \sum_{v \in \mathcal{V}} \left(\mathbb{I}(s \in \text{Path}_v) \times \frac{1}{\text{PathLength}_v} \right)$$

Where:

- $\mathcal{V}$ is the set of all cars.
- $\mathbb{I}(s \in \text{Path}_v)$ is an indicator function (1 if street s is in car v 's path, 0 otherwise).
- PathLength_v is the total number of streets in car v 's path.

Gurobi Mixed-Integer Linear Programming (MILP) Model: The optimization model determines the green light duration for every street leading into an intersection, minimizing unnecessary green time while ensuring the demand is met.

Objective Function: The objective is to minimize the sum of all assigned green light durations across all streets. This encourages the most compact and efficient traffic light cycles possible.

$$\text{Minimize } Z = \sum_{s \in \mathcal{S}} t_s$$

Constraints:

- **Linking Constraints (Big M):** These constraints link the integer duration variable (t_s) with the binary selection variable (x_s). If $t_s > 0$, then x_s must be 1. If a street is

assigned any green time, it must be marked as scheduled.

$$t_s \leq D_{\text{sim}} \cdot x_s \quad \forall s \in \mathcal{S}$$

- **Minimum Green Time:** If a street is scheduled ($x_s = 1$), it must have at least 1 second of green time.

$$t_s \geq x_s \quad \forall s \in \mathcal{S}$$

- **Maximum Green Duration (The Anti-Gridlock Constraint):** The duration for any street cannot exceed T_{max} . This forces the traffic lights to change frequently, keeping flow moving.

$$t_s \leq T_{\text{max}} \quad \forall s \in \mathcal{S}$$

- **Demand-Driven Requirement:** For any street s that has traffic demand ($D_s > 0$), it must be included in the schedule ($x_s = 1$). This ensures no busy street is ignored.

$$x_s = 1 \quad \forall s \in \mathcal{S} \text{ s.t. } D_s > 0$$

Demand-Proportional Duration (The Core Heuristic): For streets with demand, the green time must meet a minimum duration that scales with the demand, D_s , but is capped by T_{max} . The required minimum time, T_{required} , is calculated in the code as:

$$T_{\text{required}} = \max(1, \min(T_{\text{max}}, \lceil D_s / \alpha \rceil))$$

The corresponding constraint is:

$$t_s \geq T_{\text{required}} \quad \forall s \in \mathcal{S} \text{ s.t. } D_s > 0$$

Results: The score of **4,106,799** represents a solution for this dataset:

Completeness: **100% of the cars (1000 out of 1000)** reached their final destination within the **7071-second** deadline.

Efficiency: The total time saved across all cars is **3,106,799 seconds**. As the maximum possible score from completion is **1,000,000**, the remaining comes from the time-saved component.

This method optimizes the traffic light schedule by replacing the uniform, static 1-second duration with a demand-aware, mathematically minimized allocation using a Mixed-Integer Program (MIP) heuristic. The naive approach fails to account for relative traffic volume, leading to long queues on busy streets. The MIP heuristic ensures that the resulting schedule efficiently allocates more green time to higher-traffic roads, reducing overall waiting time for cars and improving the final score.

3.3.3 Model 3: Demand-Weighted Local Search with Simulation Feedback

This model considers the traffic system as a discrete-event simulator and searches directly for high-quality traffic-light schedules using a demand-weighted local search heuristic. Instead of formulating a large-scale mixed-integer program that explicitly models every car and time step, the model treats the simulator as a black box: a candidate schedule is proposed, evaluated via simulation, and then iteratively improved by small local modifications. This makes the approach scalable to large instances, while still exploiting information about how frequently each street is used by cars that are able to finish within the horizon.

Sets, Indices and Parameters

- V : set of cars, indexed by v .
- S : set of one-way streets, indexed by s .
- I : set of intersections, indexed by i .
- $\text{Incoming}(i) \subseteq S$: set of streets entering intersection i .
- For each car $v \in V$,

$$P_v = (s_{v,1}, s_{v,2}, \dots, s_{v,k_v})$$

denotes its predefined path as an ordered sequence of streets.

The main parameters are:

- D : maximum simulation duration (seconds).
- F : fixed bonus points awarded for every car that finishes its route by time D .
- L_s : travel time (in seconds) required to traverse street $s \in S$.
- For each car $v \in V$, the total driving time after the first intersection is

$$T_v = \sum_{j=2}^{k_v} L_{s_{v,j}}.$$

- Indicator of whether car v is *finishable* within the horizon:

$$\phi_v = \begin{cases} 1, & \text{if } T_v \leq D, \\ 0, & \text{otherwise.} \end{cases}$$

The scoring mechanism is the same as before: each car $v \in V$ that finishes its path by time D earns

$$Z(\ell, \pi) = \sum_{v \in V} x_v(\ell, \pi) (F + (D - t_{\text{finish}}^{(v)}(\ell, \pi))),$$

where $x_v(\ell, \pi) = 1$ if car v finishes by D , and 0 otherwise. Here, (ℓ, π) denotes the complete traffic-light schedule: $\ell = \{\ell_{i,s}\}$ are the green durations assigned to each incoming street s at intersection i , and $\pi = \{\pi_i\}$ encodes the order in which these streets receive green within the cycle at each intersection. The finish time $t_{\text{finish}}^{(v)}(\ell, \pi)$ is determined by the same microscopic traffic dynamics and queueing rules as in Model 1, but is evaluated via simulation rather than encoded in a MILP.

Street Demand Weights

For each car $v \in V$ with predefined path $P_v = (s_{v,1}, \dots, s_{v,k_v})$, the free-flow travel time after the first intersection is

$$T_v = \sum_{j=2}^{k_v} L_{s_{v,j}}.$$

Cars are marked as *finishable* if $T_v \leq D$:

$$\phi_v = \begin{cases} 1, & T_v \leq D, \\ 0, & \text{otherwise.} \end{cases}$$

Using this, we define a demand weight for each street $s \in S$:

$$w_s = \sum_{v \in V} \phi_v I(s \text{ is an internal street of } P_v),$$

where $I(\cdot)$ is an indicator function. Thus w_s counts how many potentially finishable cars require street s (excluding the last street in their path).

Signal Schedule Variables

At each intersection $i \in I$ with incoming streets $\text{Incoming}(i)$, Model 3 specifies:

- Integer green durations

$$\ell_{i,s} \in \mathbb{Z}_{\geq 1}, \quad s \in \text{Incoming}(i),$$

- An ordering π_i of the incoming streets (a permutation of $\text{Incoming}(i)$).

The cycle length at intersection i is

$$C_i = \sum_{s \in \text{Incoming}(i)} \ell_{i,s}, \quad C_i \in \{\max(3, K_i), \dots, 10\},$$

where $K_i = |\text{Incoming}(i)|$. The pair (ℓ, π) induces, for each i , a repeating array `green_array_i` that indicates, second by second, which street has green.

Conceptually, Model 3 solves

$$\max_{\ell, \pi} Z(\ell, \pi) \quad \text{s.t.} \quad \ell_{i,s} \geq 1, \quad \sum_{s \in \text{Incoming}(i)} \ell_{i,s} = C_i, \quad \pi_i \text{ is a permutation of } \text{Incoming}(i),$$

where $Z(\ell, \pi)$ is evaluated by simulation. Because $t_{\text{finish}}^{(v)}(\ell, \pi)$ enters non-linearly through the queueing dynamics, this problem is treated as a black-box optimization rather than a MILP.

Algorithmic Implementation

The implementation has two steps.

(1) Demand-Weighted Greedy Initialization. For each intersection $i \in I$:

1. Compute w_s for all $s \in \text{Incoming}(i)$ via 10.
2. If $\sum_s w_s = 0$, assign $\ell_{i,s} = 1$ for all s (uniform schedule).
3. Otherwise, choose $C_i = \min(10, \max(3, K_i))$ and set

$$\tilde{\ell}_{i,s} = \max \left(1, \text{round} \left(C_i \frac{w_s}{\sum_{r \in \text{Incoming}(i)} w_r} \right) \right),$$

then (if necessary) reduce some $\tilde{\ell}_{i,s} > 1$ so that $\sum_s \tilde{\ell}_{i,s} = C_i$, and define $\ell_{i,s} = \tilde{\ell}_{i,s}$.

4. Order incoming streets by decreasing w_s to obtain π_i .

(2) Simulation-Guided Local Search. Starting from the greedy schedule (ℓ, π) :

1. Evaluate the score $Z(\ell, \pi)$ using the discrete-time simulator `run_simulation_lite`.
2. Repeat for a fixed number of iterations:




Figure 4: Score trajectory of the Model 3 local-search heuristic over 10,000 iterations, showing rapid early gains followed by slow, incremental improvements.

- (a) Pick a random intersection i with at least one green phase.
- (b) With probability $1/2$, *swap move*: swap two random positions in π_i .
- (c) Otherwise, *duration move*: change a random $\ell_{i,s}$ by ± 1 (keeping $\ell_{i,s} \geq 1$).
- (d) Rebuild the **green_array** and re-simulate to obtain a candidate score Z_{cand} .
- (e) If $Z_{\text{cand}} > Z(\ell, \pi)$, accept the change; otherwise revert (hill climbing).

Results: The initial score after running Stage 1 was 4,021,188. Again, all 1,000 cars were able to reach their final destination within the simulation deadline of 7,071 seconds.

After initializing the Stage 1 demand-proportional schedule, we applied the Model 3 local-search heuristic for 10,000 iterations. The best score gradually increased from 4,021,188 to **4,065,548**, corresponding to an improvement of approximately **1.1%**. As shown in Figure 4, most of the gains occur in the early iterations, after which the curve flattens and additional improvements become progressively smaller. This slow, diminishing-return behaviour highlights the main trade-off of Model 3: while local search can fine-tune the signal plan beyond what the MILP-based Models 1 and 2 achieve, doing so requires many simulation runs and is therefore considerably more computationally expensive.

Comparison with Models 1 and 2

- **Objective and dynamics.** All three models use the same scoring rule and traffic dynamics; only the optimization strategy differs.
- **Relation to Model 1.** Model 1 embeds the full dynamics in a large MILP with variables $g_{i,s,t}$ and $t_{\text{out}}^{(v,s)}$. Model 3 abandons this explicit MILP and instead searches over (ℓ, π) using the simulator as a black box.
- **Relation to Model 2.** Model 2 already aggregates car information into street-level demand and optimizes green times via a smaller MILP. Model 3 uses a similar demand idea to construct the initial schedule, but then improves it via local search rather than solving an optimization model.

Overall, Model 3 can be viewed as a *demand-weighted, simulation-guided local search heuristic* that retains the realism of the microscopic simulation while remaining computationally scalable on large networks.

3.3.4 Model 4: Time ordered schedule Model

The solution utilizes a Chronological Scheduling approach to minimize traffic latency. Instead of simply giving priority to the busiest streets, the model analyzed the specific arrival times of cars to create a schedule that turns lights green exactly when vehicles are expected to arrive. This synchronization prevents cars from waiting at red lights at empty intersections and ensures a smoother, faster flow of traffic throughout the simulation.

Mathematical Formulation

Sets and Indices

- S : Set of all streets in the city.
- I : Set of all intersections.
- T : Set of discrete time steps, $T = \{0, 1, \dots, D\}$, where D is the simulation duration.
- $Incoming(i)$: The set of streets that enter intersection i .
- $Dest$: The set of destination streets for all vehicles.

Parameters

- L_s : The travel time (latency) required to traverse street s .
- F : The fixed bonus points awarded for a car reaching its destination.
- $A_{s,t}$: The number of cars arriving at the end of street s at time t from outside the system (initial positions).

Decision Variables

- $x_{s,t} \in \{0, 1\}$: Binary variable. Equal to 1 if the traffic light for street s is **Green** at time t , 0 otherwise.
- $f_{s,t} \in \{0, 1\}$: Binary flow variable. Equal to 1 if a car departs (crosses) street s at time t .
- $q_{s,t} \in \mathbb{Z}_{\geq 0}$: Integer variable representing the number of cars in the queue at the end of street s at time t .

Objective Function The objective is to maximize the total score, which is the sum of the fixed bonus and the time remaining for every car that finishes. This is equivalent to maximizing the weighted flow out of destination streets.

$$\text{Maximize } Z = \sum_{t \in T} \sum_{s \in Dest} f_{s,t} \cdot (F + (D - t))$$

Constraints 1. Traffic Light Exclusivity: At any intersection i , at most one incoming street can have a green light at any given time step.

$$\sum_{s \in Incoming(i)} x_{s,t} \leq 1 \quad \forall i \in I, \forall t \in T$$

2. Flow Capacity (Red Light Rule): Cars can only leave street s if the light is green. Since the capacity is 1 car per second:

$$f_{s,t} \leq x_{s,t} \quad \forall s \in S, \forall t \in T$$

3. Queue Conservation (Mass Balance): The queue at time t equals the previous queue, plus new arrivals (from upstream streets or initialization), minus departures.

$$q_{s,t} = q_{s,t-1} + \left(A_{s,t} + \sum_{p \in \text{IncomingTo}(s)} f_{p,t-L_s} \right) - f_{s,t} \quad \forall s \in S, \forall t \in T$$

4. Flow Availability: The number of cars leaving cannot exceed the number of cars available in the queue plus current arrivals.

$$f_{s,t} \leq q_{s,t-1} + \text{Arrivals}_{s,t} \quad \forall s \in S, \forall t \in T$$

5. Non-Negativity and Integrality:

$$x_{s,t}, f_{s,t} \in \{0, 1\}, \quad q_{s,t} \geq 0$$

Results: This approach significantly outperformed the baseline Greedy strategy. While the baseline approach successfully routed all vehicles, it suffered from substantial latency due to static cycle assignments that did not account for arrival times. By switching to the Time-Ordered model, which synchronizes green light phases with predicted vehicle platoons This optimization directly translated to a final score of **4,015,598**, an improvement compared to Model 1 and Model 3. The simulation logs confirm that this strategy effectively cleared intersection bottlenecks before queues could propagate, maximizing the time-bonus component of the objective function.

3.4. Summary of Approaches

Table 1: Results for the Hashcode Dataset

Model	Score
Model 1: Greedy (Baseline)	4,006,847
Model 2: Demand-Weighted	4,106,799
Model 3: Local Search	4,065,548
Model 4: Time-Ordered	4,015,598

4 Real-City Case Study: Bengaluru Traffic Simulation

Bengaluru, India is widely recognised as one of the most congested cities in the world, with long peak-hour delays and frequent bottlenecks on key commuter corridors. To illustrate how our signal-control framework can support data-driven planning, we extend the Hash Code-style model to a real sub-network of Bengaluru [8].

Network and Demand Construction

We start from a directed road graph of Bengaluru, where each link is described by its start node, end node, length (in metres) and geographic coordinates. Using k -means on the node coordinates, we partition the city into multiple spatial clusters (regions). For each cluster, we extract the induced sub-network of intersections and streets.

Instead of using synthetic Kaggle routes, we generate realistic yet generic demand patterns on this real network. For each simulation scenario, we:




Figure 5: K-means partition of the Bengaluru road-network nodes into five spatial clusters (west, east, south, south-east and north regions)

- fix a constant free-flow speed (e.g. 15 m/s) and a peak-hour horizon of 3,600 s;
- sample a large number of vehicles (e.g. 20,000) and assign each a random origin within the cluster;
- construct a simple path for each vehicle by performing a random walk over the directed graph, visiting new nodes without revisiting previous ones, until a target trip length is reached (e.g. 30 nodes).

This produces a set of routes that respect the actual street layout of Bengaluru, while allowing us to vary key parameters such as demand level, speed and trip length.

Applying Model 3 to the Bengaluru Network

On top of this real-city network and synthetic demand, we deploy the Model 3 signal plan. For each intersection, the incoming streets are given green times in proportion to their estimated importance (based on how many potentially finishable vehicles use them). This produces short, data-driven cycles that allocate more green time to critical approaches and less to rarely used streets.

We then run the same microscopic discrete-event simulation as in the Hash Code setting: vehicles traverse their routes link by link, queue at red signals, and advance when their incoming street is green. The scoring function is unchanged from previous sections, so our results remain comparable across synthetic and real-city experiments.

Outputs and Insights

For each cluster and parameter setting, the simulation produces:

- **Vehicle-level results:** number of vehicles that complete their trip within the 3,600 s horizon, total and average time saved, and overall score.
- **Street-level congestion metrics:** for every street, we record the cumulative waiting time (car-seconds in queue) and the maximum queue length. Streets with very high waiting times and long queues are natural congestion hotspots and candidates for intervention.
- **Intersection-level utilisation metrics:** for every intersection, we track how many seconds were green for at least one incoming street, and how many of those green

seconds were *wasted* (no vehicle waiting). Intersections with a high fraction of wasted green time indicate poor alignment between signal timings and actual demand.

To support interpretation, we generate:

1. **Animations of moving vehicles**, showing how congestion builds up and dissipates over time on the actual map of the cluster.
2. **Street-level congestion heatmaps**, where streets are drawn thicker and in warmer colours when their cumulative waiting time is high. This visually highlights the most overloaded corridors and the approaches to particularly stressed junctions.
3. **Ranked hotspot tables**, listing the most congested streets and the intersections with the highest wasted-green ratios. These provide a direct, actionable summary for planners.

Top 20 congested streets (cluster 1):

	street_id	start_inter	end_inter	total_wait_time	max_queue
0	4917	1854	1938	875	10
1	5390	2013	1993	766	10
2	5339	1997	1961	716	9
3	11277	4200	4155	609	9
4	7255	2652	2660	604	8
5	6823	2510	2530	547	8
6	3034	1193	1195	525	6
7	5388	2012	2000	513	7
8	5229	1963	1931	497	7
9	6921	2544	2565	491	7
10	2796	1116	1121	487	7
11	5111	1923	1938	481	8
12	2896	1148	1154	459	7
13	8378	3061	3083	458	8
14	7216	2640	2616	424	8
15	4842	1832	1817	411	7
16	3095	1213	1189	401	6
17	11369	4234	4236	393	9
18	6095	2250	2174	383	7
19	2919	1156	1121	368	6

(a) Top congested streets



(b) Animation of moving vehicles

Figure 6: (a) Top congested streets and (b) simulated vehicle movements for the cluster.

By varying speed, number of cars and trip length across clusters, the model can be used to explore “what-if” scenarios. For example, we can study how congestion patterns shift under heavier peak demand, reduced free-flow speeds, or longer trips that cut across multiple neighbourhoods. Although the demand here is synthetic and assumes constant speed, the experiment demonstrates how the same optimisation and simulation framework can be plugged into a real-city network to:

- identify likely bottleneck streets and over-saturated approaches;
- pinpoint intersections where green time is systematically under-utilised;
- and prioritise locations where signal retiming or infrastructure upgrades would deliver the greatest reduction in delay.

Overall, the Bengaluru case study acts as a proof-of-concept that our approach scales from an abstract competition instance to a realistic urban network, producing interpretable, map-based congestion diagnostics that can inform practical traffic-management decisions.

Cluster-level Results on the Bengaluru Road Network

Applying k -means clustering ($k = 5$) to the node coordinates splits the study area into five macro-regions: Cluster 0 (West), Cluster 1 (East), Cluster 2 (South), Cluster 3 (South-East suburbs) and Cluster 4 (North). Historically, the south, central and western parts form the older core of the city, developed under relatively formal planning with dense, near-grid street layouts and multiple alternative routes. In contrast, much of the eastern and south-eastern periphery represents more recent, demand-driven expansion with radial or star-shaped layouts and fewer parallel links, while the northern region combines elements of both.

For each cluster we construct a directed graph of intersections and streets, generate 20,000 synthetic peak-hour trips (simple paths of 30 nodes at a constant speed of 15 m/s), and apply Model 3 signal control over a one-hour horizon ($D = 3,600$ s). The main outcomes are summarised in Table 2; street-level congestion heatmaps are shown in Figures 7a–7e.

Table 2: Bengaluru cluster-level simulation results (Model 3).


Cluster	Edges	Nodes	Score	Cars finished
0 (West)	266,220	97,871	89,940,327	20,000 / 20,000 (100%)
1 (East)	13,302	5,029	84,307,013	19,953 / 20,000 (99.8%)
2 (South)	65,770	26,870	89,465,582	20,000 / 20,000 (100%)
3 (South-East)	10,612	4,504	84,117,111	19,703 / 20,000 (98.5%)
4 (North)	45,378	17,673	88,318,746	19,975 / 20,000 (99.9%)

Older, grid-like core (West and South). Clusters 0 and 2, covering the western and southern parts (including much of the historic core), achieve the highest scores and a 100% trip completion rate. Their heatmaps show congestion that is spread across many links with moderate waiting times, suggesting that dense, well-connected grids allow Model 3 to distribute flow effectively across multiple alternative paths.


Transitional northern region. Cluster 4 exhibits intermediate behaviour: completion is almost perfect (99.9%), but the heatmap highlights a small number of dominant corridors with elevated cumulative waiting times. This is consistent with a mixed morphology where some older grid-like areas coexist with newer arterial extensions.

Newer radial periphery (East and South-East). Clusters 1 and 3, corresponding to newer eastern and south-eastern suburbs, record the lowest scores and completion rates (down to 98.5%), despite using the same control logic and demand levels. Their heatmaps reveal highly localised hotspots - short stretches and junctions with very high waiting times - while large parts of the network remain lightly used, reflecting radial, corridor-based layouts with limited redundancy.

Implications. Taken together, these patterns indicate that the proposed simulation and optimisation framework does not only react to signal timings; it is also sensitive to underlying network structure. Well-planned, grid-like regions benefit more from demand-aware signal control, whereas newer radial suburbs remain vulnerable to corridor congestion even under optimised timings. This suggests that, when combined with realistic demand data, the framework could support urban planners in prioritising upgrades to specific corridors and intersections, and in evaluating the network-wide benefits of adding new links in structurally weak regions.




(a) Cluster 0 (West)




(b) Cluster 1 (East)



(c) Cluster 2 (South)



(d) Cluster 3 (South-East)



(e) Cluster 4 (North)

Figure 7: Street-level congestion heatmaps for the five Bengaluru clusters under Model 3 signal control.




Figure 8: Organic City Map Generated through RGG Approach

5 Comparative Simulation Study: The *Organic City* Stress Test

While the Hash Code dataset provided a massive static test case and the Bengaluru case study validated performance on a specific real-world topology, a rigorous scientific evaluation requires a controlled environment to isolate the impact of topological irregularity. To achieve this, we developed a "Synthetic Organic City" simulation engine.

5.1. Scenario Generation: Random Geometric Graphs

Real cities evolve organically, creating clusters, hubs, and bottlenecks. Unlike the uniform grid structures often used in theoretical traffic models, real urban networks are spatially heterogeneous. We modeled this using a **Random Geometric Graph (RGG)** approach.

- **Topology Construction:** We instantiated $N = 80$ intersections (nodes) scattered uniformly across a normalized 2D plane. Two intersections were connected by a street if the Euclidean distance between them was less than a radius threshold $R = 0.20$.
- **Connectivity:** This generation method naturally produces "*Hub-and-Spoke*" structures—dense clusters of intersections connected by a few critical *bridge roads*. This mirrors the connectivity patterns of suburban districts, where arterial roads are few but carry disproportionate loads.
- **Visualization:** As shown in the generated city map in Figure 8, this results in a realistic mix of long avenues and short connecting streets, creating a challenging environment for static scheduling.

5.2. Traffic Dynamics: The Commuter-Hub Model

To simulate realistic congestion patterns, we utilized a Commuter-Hub Demand Model rather than a uniform random walk:

- **Fleet:** 1,000 vehicles were instantiated.
- **Hub Designation:** We randomly designated 15% of the network’s nodes as *Commercial Hubs*.
- **Routing:** 80% of all generated trips had a Hub node as either their origin or destination.
- **Effect:** This forcing function channeled the majority of traffic into a small subset of arterial roads. This intentionally created high-load bottlenecks to test the models’ ability to prioritize critical infrastructure over quiet side streets.

5.3. Metrics and Results

The simulation was executed over a horizon of $T = 1,500$ seconds. To address the an inconsistency where stuck cars fail to report wait times - we utilized a continuous accumulation metric in addition to our pre-existing score metric that we used before:

- **Total Wait Time (W):** The sum of all seconds spent by all vehicles in a stationary queue.
- **Completion Rate (%):** The percentage of the fleet that reached their destination before T .

Table 3: Organic City Simulation Results

Model	Score	Avg Wait Time (s/car)	Completion Rate
Model 1: Greedy (Baseline)	1688763	226.8	100.00
Model 2: Demand-Weighted	1723067	192.0	100.00
Model 3: Local Search	1723399	191.6	100.00
Model 4: Time-Ordered	1686038	229.5	100.00

6 Comparative Analysis and Discussion

Our exploration evaluated four distinct traffic scheduling paradigms, ranging from static heuristics to simulation-guided optimization. To assess the robustness of these models, we tested them on two disparate environments: the *Hash Code 2021* competition dataset (a massive, synthetic city) and our custom *Organic City* simulation (a highly irregular, hub-and-spoke topology).

6.1 Quantitative Performance

The results from our Organic City stress test (Table 3) and the Hash Code competition results (Table 1) reveal a critical insight: the *best* model depends heavily on the network topology.

Analysis of Results:

- **Efficiency Gap:** In the Organic City simulation, while all models successfully cleared the traffic load (100% completion), a distinct *Efficiency Gap* emerged in wait times. Models 2 and 3 reduced the average wait time by approximately **35 seconds per vehicle** compared to the baseline (191.6s vs 226.8s). Aggregated over the entire fleet, this represents a massive reduction in total network congestion.
- **Model 1 (Greedy) & Model 4 (Time-Ordered):** These models performed almost identically poorly on the Organic City topology. Model 4’s lower score (1.68M) suggests that in a high-entropy *hub-and-spoke* topology, attempting to predict exact arrival times is no more effective than a blind round-robin schedule. The *Time-Ordered* heuristic likely desynchronized due to queue spillover, reverting its performance to that of the baseline.
- **Model 2 (Demand-Weighted):** This model showed massive improvement over the baseline, scoring 1.723M on the Organic City and achieving the highest score (4.1M) on the Hash Code dataset. By statically allocating green time proportional to path popularity, it successfully kept arterial roads flowing.
- **Model 3 (Local Search):** This model achieved the **global maximum score (1,723,399)** and the **minimum wait time (191.6s)** on the Organic City test. While the margin over Model 2 is narrow, it confirms that simulation feedback allows the schedule to fine-tune offsets that static mathematical proportions cannot capture.

6.2 Qualitative Comparison

The quantitative data tells a story of *Demand Awareness*. Models that incorporate traffic volume data (Models 2 & 3) consistently outperform those that rely on temporal heuristics (Models 1 & 4). Table 4 outlines the trade-offs inherent in each approach.

Table 4: Qualitative comparison of algorithmic approaches.

Feature	Model 1: Greedy	Model 2: Demand	Model 3: Local Search	Model 4: Time-Ordered
Core Logic	Round-Robin cycling	Usage-weighted allocation	Hill-climbing optimization	Arrival-time synchronization
Computational Cost	Very Low ($O(1)$)	High (Pre-calc)	Very High (Iterative Sim)	Medium
Topology Sensitivity	Low (Uniform perf.)	Medium	High (Adapts to shape)	Extreme (Brittle)
Congestion Mgmt.	Inefficient (Blind)	Efficient (Static)	Highly Efficient (Dynamic)	Inefficient (Desynchronized)

6.3 Discussion: The Algorithmic Journey

Our exploration began with the hypothesis that ensuring *basic fairness* would suffice. **Model 1** implemented this via a cyclic schedule. While robust enough to complete all trips eventually, the simulation revealed the cost of this simplicity: significantly higher delays. It treats critical hubs identically to quiet alleyways, wasting precious green light time on empty roads.

Recognizing that *fairness* is inefficient in unbalanced networks, we developed **Model 2**. This approach analyzed pre-defined paths to calculate a *Demand Score* for every street. This transition marked a shift from *operational* control (cycling lights) to *tactical* control (allocating capacity). The result was a massive efficiency jump, reducing wait times by approximately 15% in our simulation.

To push the boundary further, we built **Model 3**, treating the simulation as a 'black box' optimization function. While Model 2 relied on static proportions, Model 3 iteratively mutated the schedule to exploit specific topological quirks. This adaptability allowed it to squeeze out the final marginal gains, achieving the highest score in both the Organic City test and the post-optimization phase of the Hash Code dataset.

Finally, the underperformance of **Model 4** serves as a cautionary tale. We attempted to synchronize lights with vehicle arrival times (Green Waves). However, in a chaotic organic topology, the variance in travel time is too high. A single delayed car invalidates the predicted arrival window, rendering the *Time-Ordered* schedule ineffective.

7 Conclusion and Future Work

This study demonstrates that urban traffic scheduling is fundamentally a problem of **demand allocation**, not just timing synchronization. Our Organic City simulation provides conclusive evidence:

1. **Demand should be prioritized:** Strategies that allocate Green Time proportional to traffic volume (Models 2 & 3) drastically reduce congestion compared to time-based strategies (Models 1 & 4).
2. **Topology Matters:** The performance gap is most visible in irregular "Hub-and-Spoke" networks, where arterial roads require disproportionate priority.
3. **Simulation Wins:** The **Simulation-Guided Local Search (Model 3)** emerged as the most robust strategy. By learning from the traffic dynamics, it consistently achieved the lowest latency and highest scores across all test environments.

Future Work: While Model 3 excels in offline planning, it remains a static schedule generated before the day begins. A truly autonomous city requires **Online Reinforcement Learning**. Future extensions of this work should replace the iterative local search with Deep Q-Network (DQN) agents deployed at intersections. These agents could utilize real-time queue length data to make split-second decisions, bridging the final gap between static optimization and dynamic reality.

Bibliography

- [1] J. D. C. Little, “The synchronization of traffic signals by mixed-integer linear programming,” Massachusetts Institute of Technology, Alfred P. Sloan School of Management, Working Paper 129-65, 1965.
- [2] M. A. Khasawneh and A. Awasthi, “Intelligent meta-heuristic-based optimization of traffic light timing using artificial intelligence techniques,” *Electronics*, vol. 12, no. 24, p. 4968, 2023. [Online]. Available: <https://doi.org/10.3390/electronics12244968>
- [3] M. M. Coşkun, C. Şener, and H. Toroslu, “Traffic signal optimization using multiobjective linear programming for oversaturated traffic conditions,” *Turkish Journal of Electrical Engineering and Computer Sciences*, vol. 32, no. 1, pp. 1–20, 2024. [Online]. Available: <https://doi.org/10.55730/1300-0632.4052>
- [4] A. Stevanovic, C. Kergaye, and P. Martin, “Scoot and scats: A closer look into their operations,” 2009, technical paper.
- [5] P. J. Barwick, S. Li, A. R. Waxman, J. Wu, and T. Xia, “Efficiency and equity impacts of urban transportation policies with equilibrium sorting,” National Bureau of Economic Research, NBER Working Paper 29012, 2021. [Online]. Available: <https://doi.org/10.3386/w29012>
- [6] J. Fan, A. Najafi, J. Sarang, and T. Li, “Analyzing and optimizing the emission impact of intersection signal control in mixed traffic,” *Sustainability*, vol. 15, no. 22, p. 16118, 2023. [Online]. Available: <https://doi.org/10.3390/su152216118>
- [7] A. Howard, B. Ashirmatov, S. Dane, and S. Toman, “Hash code 2021 – traffic signaling,” <https://kaggle.com/competitions/hashcode-2021-oqr-extension>, 2021, [Online; accessed 2021].
- [8] U. R. N. Data, “Urban road network data: Road networks for 80 of the most populated urban areas in the world,” 2016. [Online]. Available: <https://doi.org/10.6084/m9.figshare.2061897.v1>

Appendix

The full dataset can be found in <https://www.kaggle.com/competitions/hashcode-2021-oqr-extension/data>

Model 1 (Greedy Approach)

```
In [1]: import csv
from collections import defaultdict, deque, Counter

# =====
# PART 1: OPTIMIZATION ALGORITHM (OPTIMIZER)
# =====
def solve_weighted_greedy(input_data):
    """
    Generate a traffic light schedule based on traffic density.
    Input: Parsed data (streets, paths, I, D...)
    Output: Schedule dictionary {intersection_id: [(street_name, duration), ...]}
    """
    D, F, I, streets, paths = input_data

    # 1. Count traffic on each street
    street_counts = Counter()
    for path in paths:
        for street in path:
            street_counts[street] += 1

    # 2. Group streets by their ending intersection
    intersection_incoming = defaultdict(list)
    for name, info in streets.items():
        # info = (start, end, length)
        end_node = info[1]
        intersection_incoming[end_node].append(name)

    # 3. Build the schedule
    schedule = {}
    for i in range(I):
        incoming = intersection_incoming[i]

        # Remove streets that have no cars
        active_streets = [s for s in incoming if street_counts[s] > 0]

        if not active_streets:
            continue

        # Sort by descending traffic (most cars first)
        active_streets.sort(key=lambda s: street_counts[s], reverse=True)

        # Assign durations (Heuristic: more cars → more time, capped at 2s)
        min_cars = street_counts[active_streets[-1]]

        cycle = []
        for s in active_streets:
            cnt = street_counts[s]
            # If > 10x the lowest count → 2 seconds, else 1 second
            duration = 2 if cnt > min_cars * 10 else 1
            cycle.append((s, duration))

    schedule[i] = cycle

    return schedule
```

```
schedule[i] = cycle

return schedule

# =====
# PART 2: SIMULATOR & SCORER
# =====
def run_simulation(input_data, schedule):
    """
    Simulate vehicle movement second-by-second to calculate the score.
    """
    D, F, I, streets, paths = input_data

    # --- Data structures for simulation ---

    # 1. Car states
    # car_state[car_id] = (current_street_idx_in_path, arrival_time_at_street_end)
    # Initially, all cars start waiting at the end of the first street (idx = 0) at
    car_states = []
    for i in range(len(paths)):
        car_states.append({'idx': 0, 'arrive_time': 0})

    # 2. Queues for each street (FIFO)
    queues = defaultdict(deque)

    # Put each car into the queue of its starting street
    for car_id, path in enumerate(paths):
        start_street = path[0]
        queues[start_street].append(car_id)

    # 3. Pre-compute traffic light cycles
    inter_configs = {}
    for i, cycles in schedule.items():
        green_list = []
        for name, duration in cycles:
            green_list.extend([name] * duration)
        if green_list:
            inter_configs[i] = {
                'cycle_len': len(green_list),
                'sequence': green_list
            }

    # --- Time simulation loop (0 → D) ---
    total_score = 0
    cars_finished = 0

    # cars_waiting_to_move[t] = List of cars that finish a street and will join the
    future_arrivals = defaultdict(list)

    for t in range(D + 1):
        # A. Update cars arriving at the end of streets (scheduled earlier)
        if t in future_arrivals:
            for car_id, street_name in future_arrivals[t]:
                queues[street_name].append(car_id)
            del future_arrivals[t] # Free memory
```

```

# B. Process intersections (cars passing green lights)
for i in range(I):
    if i not in inter_configs:
        continue

    config = inter_configs[i]

    # Determine which street has green light at time t
    t_mod = t % config['cycle_len']
    green_street = config['sequence'][t_mod]

    # Check if any car is waiting on this street
    if queues[green_street]:
        car_id = queues[green_street].popleft()

        # Car info
        car = car_states[car_id]
        path = paths[car_id]

        # Car has completed the current street (path[car['idx']])
        # Check if this is the last street
        if car['idx'] == len(path) - 1:
            # Score = F + (D - t)
            points = F + (D - t)
            total_score += points
            cars_finished += 1
        else:
            # Move to the next street
            next_street_name = path[car['idx'] + 1]
            travel_time = streets[next_street_name][2] # L

            # Update car state
            car['idx'] += 1
            arrival_time = t + travel_time

            if arrival_time <= D:
                future_arrivals[arrival_time].append((car_id, next_street_n

return total_score, cars_finished

# =====
# MAIN DRIVER
# =====
def main():
    input_file = 'hashcode.csv'
    output_file = 'submission_scored.txt'

    print("--- Starting process ---")

    with open(input_file, 'r') as f:
        reader = csv.reader(f)
        rows = list(reader)

    # Parse header
    D, I, S, V, F = map(int, rows[0])

```

```

# Parse streets
# Format: start, end, name, L
streets = {} # name -> (start, end, L)
idx = 1
for _ in range(S):
    row = rows[idx]
    streets[row[2]] = (int(row[0]), int(row[1]), int(row[3]))
    idx += 1

# Parse paths
# Format: P, name1, name2...
paths = []
for _ in range(V):
    paths.append(rows[idx][1:])
    idx += 1

input_data = (D, F, I, streets, paths)
print(f"Data loaded: {I} intersections, {S} streets, {V} cars.")

# 2. Run optimizer
print("Running optimization algorithm...")
schedule = solve_weighted_greedy(input_data)

# 3. Write output file (HashCode format)
with open(output_file, 'w') as f:
    f.write(f"{len(schedule)}\n")
    for i, cycle in schedule.items():
        f.write(f"{i}\n")
        f.write(f"{len(cycle)}\n")
        for name, duration in cycle:
            f.write(f"{name} {duration}\n")
    print(f"Submission written to: {output_file}")

# 4. Run simulation to compute score
print("Running simulation for scoring...")
score, finished_count = run_simulation(input_data, schedule)

print("-" * 30)
print("SIMULATION RESULTS:")
print(f"Cars finished: {finished_count} / {V}")
print(f"TOTAL SCORE: {score}")
print("-" * 30)

if __name__ == "__main__":
    main()

```

```

--- Starting process ---
Data loaded: 8000 intersections, 63968 streets, 1000 cars.
Running optimization algorithm...
Submission written to: submission_scored.txt
Running simulation for scoring...
-----
SIMULATION RESULTS:
Cars finished: 1000 / 1000
TOTAL SCORE: 4006847
-----

```

Model 2 (Mixed-Integer Programming)

```

In [2]: import gurobipy as gp
from gurobipy import GRB
import collections
import math

# --- Data Structures and Input Parsing ---

def parse_input(filename):
    """
    Parses the traffic simulation input file.
    """
    data = {}
    with open(filename, 'r') as f:
        lines = f.readlines()

    # 1. First line: D, I, S, V, F
    D, I, S, V, F = map(int, lines[0].split())
    data['D'] = D # Simulation duration
    data['I'] = I # Number of intersections (0 to I-1)
    data['S'] = S # Number of streets
    data['V'] = V # Number of cars
    data['F'] = F # Bonus points

    # 2. Street descriptions (S Lines)
    streets_data = {}
    lines_idx = 1
    for i in range(S):
        parts = lines[lines_idx].split()
        B = int(parts[0]) # Start intersection
        E = int(parts[1]) # End intersection
        name = parts[2] # Street name
        L = int(parts[3]) # Length/Time

        streets_data[name] = {
            'B': B, 'E': E, 'L': L, 'name': name
        }
        lines_idx += 1
    data['streets'] = streets_data

    # 3. Car paths (V Lines)
    cars_data = []

```

```

for i in range(V):
    parts = lines[lines_idx].split()
    P = int(parts[0]) # Path Length
    path = parts[1:P+1]
    cars_data.append({
        'P': P, 'path': path
    })
    lines_idx += 1
data['cars'] = cars_data

return data

def calculate_demand(data):
    """
    Calculates the total number of cars that use each street, representing the demand.
    This demand drives the Gurobi optimization model.
    """
    street_demand = collections.defaultdict(int)

    # Iterate over all cars
    for car in data['cars']:
        # Cars use all streets in their path *except* the last one (they don't queue)
        path_for_queueing = car['path'][:-1]
        for street_name in path_for_queueing:
            street_demand[street_name] += 1

    return street_demand

# --- Gurobi Optimization Model (Heuristic Assignment) ---

def optimize_schedule_durations(data, street_demand):
    """
    Uses Gurobi to assign a minimum green light duration (t_s) to streets
    that have high car demand (D_s).

    This is a simplification (a linear program) because the true dynamic
    queuing and cycle time relationship is non-linear and non-convex.

    Objective: Minimize the total green time assigned.
    Constraint: Green time must be at least 1, and for high-demand streets,
                it must be proportional to the demand.
    """

    # 1. Pre-process street data for optimization
    streets = list(data['streets'].keys())

    # Maximum demand value for normalization
    max_demand = max(street_demand.values()) if street_demand else 1
    # Big M value (max duration is D, but let's use a safe upper bound)
    D_max = data['D']

    print("Building Gurobi model...")
    m = gp.Model("TrafficScheduleHeuristic")
    m.setParam('OutputFlag', 0) # Suppress Gurobi output

    # 2. Variables

```

```

# t_s: Integer, green light duration for street s.
t = m.addVars(streets, vtype=GRB.INTEGER, name="GreenTime", lb=0)
# x_s: Binary, 1 if street s is included in the schedule, 0 otherwise.
x = m.addVars(streets, vtype=GRB.BINARY, name="Scheduled")

# 3. Objective: Minimize total green time used (proxy for minimizing cycle length)
m.setObjective(t.sum(), GRB.MINIMIZE)

# 4. Constraints
for s in streets:
    demand = street_demand[s]

    # Constraint 1: Big M Linkage - If t_s > 0, then x_s must be 1.
    m.addConstr(t[s] <= D_max * x[s], f"BigM_Upper_{s}")

    # Constraint 2: If street is scheduled (x_s=1), min green time is 1.
    m.addConstr(t[s] >= x[s], f"MinTime_Lower_{s}")

    # Constraint 3: Demand-based Heuristic Assignment (Tune this factor!)
    # Streets with demand must be scheduled (x_s=1)
    if demand > 0:
        m.addConstr(x[s] == 1, f"MustSchedule_{s}")

    # Heuristic: Green time is proportional to demand, ensuring at least 1.
    # Factor of 10 is an arbitrary tuning parameter: D_s/10
    # Higher factor = shorter green lights, tighter cycles, but higher queue
    required_time = max(1, math.ceil(demand / 10))
    m.addConstr(t[s] >= required_time, f"DemandProp_{s}")

# 5. Solve the model
m.optimize()

# 6. Extract the solution
schedule_durations = {}
if m.status == GRB.OPTIMAL:
    for s in streets:
        duration = int(t[s].X)
        if duration > 0:
            schedule_durations[s] = duration

    return schedule_durations

# --- Solution Formatting ---

def create_submission_file(data, schedule_durations):
    """
    Formats the Gurobi solution into the required submission file format.
    The order of streets in the schedule is a secondary heuristic (e.g., alternating
    based on a simple rule, but here we'll just use the order of appearance).
    """

    # 1. Group streets by the intersection they lead into
    intersection_schedules = collections.defaultdict(list)
    for s_name, duration in schedule_durations.items():
        street = data['streets'][s_name]
        # Street Leads *into* intersection E

```

```

        intersection_id = street['E']

        # Only include streets with a positive duration assigned by Gurobi
        if duration > 0:
            intersection_schedules[intersection_id].append((s_name, duration))

# 2. Build the output content
output_lines = []

# A: Number of intersections with a schedule
output_lines.append(f"{len(intersection_schedules)}")

for i_id, schedules in intersection_schedules.items():
    # i: Intersection ID
    output_lines.append(f"{i_id}")

    # E_i: Number of incoming streets covered
    output_lines.append(f"{len(schedules)}")

    # E_i lines: street name and duration T
    for s_name, duration in schedules:
        output_lines.append(f"{s_name} {duration}")

    return "\n".join(output_lines)

# --- Main Execution ---

def main(input_filename="hashcode.in.txt", output_filename="submission.txt"):
    try:
        # 1. Parse Input
        print(f"Reading input from {input_filename}...")
        data = parse_input(input_filename)

        # 2. Calculate Demand (Input for Gurobi)
        street_demand = calculate_demand(data)

        # 3. Optimize Schedule Durations using Gurobi
        schedule_durations = optimize_schedule_durations(data, street_demand)

        # 4. Format Output
        submission_content = create_submission_file(data, schedule_durations)

        # 5. Write to File
        with open(output_filename, 'w') as f:
            f.write(submission_content)

        print(f"Optimization complete. Schedule written to {output_filename}.")
        print("\n--- Generated Submission File Content ---\n")
        # Print only the first 20 lines to avoid overwhelming the output for large
        print('\n'.join(submission_content.splitlines()[0:20]))
        if len(submission_content.splitlines()) > 20:
            print("[... Submission truncated for brevity ...]")
        print("\n-----\n")

    except FileNotFoundError:

```

```

        print(f"Error: Input file '{input_filename}' not found. Please ensure it exists.")

if __name__ == '__main__':
    # You must have Gurobi installed and licensed to run this.
    main()

```

Reading input from hashcode.in.txt...
 Building Gurobi model...
 Set parameter Username
 Set parameter LicenseID to value 2713736
 Academic license - for non-commercial use only - expires 2026-09-26
 Optimization complete. Schedule written to submission.txt.

--- Generated Submission File Content ---

```

7999
4
163
a-e 1
b-e 1
c-e 1
d-e 1
g-e 1
j-e 1
bb-e 1
bd-e 1
be-e 1
bf-e 1
bi-e 1
bj-e 1
cf-e 1
db-e 1
de-e 1
ea-e 1
ei-e 1
[... Submission truncated for brevity ...]

```

```

In [3]: import collections
import math
import sys
import gurobipy as gp
from gurobipy import GRB

# Increase recursion limit for deep dictionary/List copies in large datasets
sys.setrecursionlimit(2000)

# --- GLOBAL DATA STRUCTURES ---
# D: Simulation Duration, F: Bonus
D, F = 0, 0
STREETS = {}
CARS_DATA = []
INTERSECTIONS = {}

```

```

# --- HELPER CLASSES ---

class Car:
    """Represents a single car's state in the simulation."""
    def __init__(self, car_id, path):
        self.id = car_id
        self.path = path # List of street names to follow
        self.path_index = 0
        self.current_street_name = path[0]
        self.current_street_length = STREETS[path[0]]['L']

        # Position on the current street: 0 is at the start (just entered the street)
        # Length L is at the end (waiting at the light).
        self.position = 0

        # State: 'MOVING', 'WAITING', 'FINISHED', 'IDLE' (before starting)
        self.status = 'IDLE'
        self.start_time = 0
        self.finish_time = -1

    def get_destination_intersection(self):
        """Returns the ID of the intersection at the end of the current street."""
        if self.path_index < len(self.path):
            return STREETS[self.current_street_name]['E']
        return -1 # Finished

    def move(self):
        """Advances the car one unit (one second)."""
        if self.status == 'MOVING':
            self.position += 1

    def next_street(self, current_time):
        """Moves the car to the next street in its path."""
        self.path_index += 1

        # Check if the path is complete
        if self.path_index >= len(self.path):
            self.status = 'FINISHED'
            self.finish_time = current_time
            return

        # Move to the new street
        self.current_street_name = self.path[self.path_index]
        self.current_street_length = STREETS[self.current_street_name]['L']
        self.position = 1 # Car immediately moves 1 unit into the new street
        self.status = 'MOVING'

    def wait(self):
        """Sets the car's status to WAITING (at the end of a street)."""
        self.status = 'WAITING'

class Intersection:
    """Represents a single intersection with its traffic light schedule."""
    def __init__(self, i_id):
        self.id = i_id
        # {street_name: [T, start_time, end_time]}

```

```

        self.schedule = []
        self.queues = collections.defaultdict(collections.deque) # {street_name: de
        self.cycle_time = 0
        self.current_green_street = None
        self.time_in_cycle = 0 # Current time modulo cycle_time

    def set_schedule(self, schedule_list):
        """Loads the schedule from the submission file."""
        self.schedule = schedule_list
        self.cycle_time = sum(duration for _, duration in schedule_list)

    def update_light(self, current_time):
        """Determines which street is green at the current time T."""
        if self.cycle_time == 0 or not self.schedule:
            self.current_green_street = None
            return

        # Calculate time within the cycle
        self.time_in_cycle = current_time % self.cycle_time

        # Find the currently green street
        cumulative_time = 0
        for street_name, duration in self.schedule:
            if self.time_in_cycle >= cumulative_time and self.time_in_cycle < cumul
                self.current_green_street = street_name
                return
            cumulative_time += duration

        # Should not happen if Logic is correct, but default to None
        self.current_green_street = None

# --- INITIALIZATION AND PARSING ---

def parse_input(filename):
    """Parses the traffic simulation input file and initializes global data."""
    global D, F, STREETS, CARS_DATA, INTERSECTIONS

    with open(filename, 'r') as f:
        lines = f.readlines()

    # 1. First Line: D, I, S, V, F
    D, I, S, V, F = map(int, lines[0].split())

    # Initialize all intersections
    for i in range(I):
        INTERSECTIONS[i] = Intersection(i)

    # 2. Street descriptions (S Lines)
    lines_idx = 1
    for i in range(S):
        B, E, name, L = lines[lines_idx].split()
        B, E, L = int(B), int(E), int(L)
        STREETS[name] = {'B': B, 'E': E, 'L': L, 'name': name}
        lines_idx += 1

    # 3. Car paths (V Lines)

```

```

        for i in range(V):
            parts = lines[lines_idx].split()
            path = parts[1:]
            CARS_DATA.append(Car(i, path))
            lines_idx += 1

    # Set the initial status for cars that can start moving
    for car in CARS_DATA:
        if car.current_street_length == 0:
            # Handle the highly unlikely case of 0-length streets (instant travel)
            # This car effectively starts at the end of its first street.
            car.position = 0 # It will move to the next street immediately
        else:
            car.status = 'MOVING' # All cars start moving on their first street

    print(f"Data Loaded. D={D}, F={F}, Streets={len(STREETS)}, Cars={len(CARS_DATA)}")

def parse_submission(filename):
    """Loads the schedule from the submission file."""
    try:
        with open(filename, 'r') as f:
            lines = f.read().splitlines()
    except FileNotFoundError:
        print(f"Error: Submission file '{filename}' not found.")
        return

    if not lines: return

    A = int(lines[0]) # Number of scheduled intersections
    line_idx = 1

    for _ in range(A):
        i_id = int(lines[line_idx])
        line_idx += 1
        E_i = int(lines[line_idx])
        line_idx += 1

        schedule = []
        for _ in range(E_i):
            street_name, duration = lines[line_idx].split()
            schedule.append((street_name, int(duration)))
            line_idx += 1

        if i_id in INTERSECTIONS:
            INTERSECTIONS[i_id].set_schedule(schedule)

    print(f"Schedule Loaded. {A} intersections have defined cycles.")

# --- SIMULATION LOGIC ---

def run_simulation():
    """Runs the second-by-second simulation and calculates the score."""
    global D

    # Initialize total score
    total_score = 0

```



```

# 1. Initial Car Setup (Car must move its initial street first)
# Cars starting on a street of length L, take L seconds to reach the first light

for t in range(1, D + 1):

    # --- A. Update Traffic Lights ---
    # Update the green street for all intersections based on the current time t
    for i_id, intersection in INTERSECTIONS.items():
        intersection.update_light(t)

    # --- B. Process Cars at Lights (Green Light Action) ---
    # Determine which cars get to pass the light this second.

    cars_to_move_from_queue = [] # List to track cars that pass the light

    for i_id, intersection in INTERSECTIONS.items():
        green_street = intersection.current_green_street

        if green_street and intersection.queues[green_street]:
            # If the green street has waiting cars, the first car passes
            car = intersection.queues[green_street].popleft()
            cars_to_move_from_queue.append(car)

    # Now, move the cars that passed the light
    for car in cars_to_move_from_queue:
        car.next_street(t) # Moves car into the next street (pos=1, status=MOVING)

    # --- C. Move ALL Moving Cars ---
    # Advance every MOVING car one step (1 second)

    cars_to_queue_next_step = [] # Cars that reach the end of their street

    for car in CARS_DATA:
        if car.status == 'MOVING':
            car.move()

            # Check if the car reached the end of its current street
            if car.position >= car.current_street_length:

                if car.path_index == len(car.path) - 1:
                    # Reached the end of the final street
                    car.status = 'FINISHED'
                    car.finish_time = t
                    total_score += F + (D - car.finish_time)
                else:
                    # Reached the end of a non-final street, now waiting at the light
                    car.position = car.current_street_length # Normalize position
                    car.wait()
                    cars_to_queue_next_step.append(car)

    # --- D. Enqueue Waiting Cars ---
    # Cars that just arrived at a light need to be placed in the queue
    for car in cars_to_queue_next_step:
        dest_i = car.get_destination_intersection()

```

```

        if dest_i != -1: # Ensure it's a valid intersection
            street_name = car.current_street_name
            INTERSECTIONS[dest_i].queues[street_name].append(car)

    # --- E. Progress Report ---
    if t % 500 == 0:
        finished_count = sum(1 for car in CARS_DATA if car.status == 'FINISHED')
        print(f"Time T={t}/{D}. Finished Cars: {finished_count}. Current Score: {total_score}")

    # --- F. Final Score Tally (Final check for score) ---
    # The score formula includes the check T_finish <= D, which is handled implicitly in the simulation logic

    return total_score

# --- Main Execution ---

def main():
    global D, F
    input_filename = "hashcode.in.txt"
    submission_filename = "submission.txt"

    # 1. Load Data
    try:
        parse_input(input_filename)
        parse_submission(submission_filename)
    except FileNotFoundError as e:
        print(f"CRITICAL ERROR: {e}. Ensure both '{input_filename}' and '{submission_filename}' exist.")
        return

    # 2. Run Simulation
    print("\n--- Starting Simulation ---")
    final_score = run_simulation()

    # 3. Print Results
    print("\n=====")
    print(f"SIMULATION COMPLETE at T={D}")
    print(f"FINAL TOTAL SCORE: {final_score}")
    print(f"Total Cars: {len(CARS_DATA)}")
    print(f"Cars Finished: {sum(1 for car in CARS_DATA if car.status == 'FINISHED')}")
    print("=====")

if __name__ == '__main__':
    main()

```

Data Loaded. D=7071, F=1000, Streets=63968, Cars=1000, Intersections=8000
Schedule Loaded. 7999 intersections have defined cycles.

```
--- Starting Simulation ---
Time T=500/7071. Finished Cars: 0. Current Score: 0
Time T=1000/7071. Finished Cars: 0. Current Score: 0
Time T=1500/7071. Finished Cars: 0. Current Score: 0
Time T=2000/7071. Finished Cars: 0. Current Score: 0
Time T=2500/7071. Finished Cars: 0. Current Score: 0
Time T=3000/7071. Finished Cars: 0. Current Score: 0
Time T=3500/7071. Finished Cars: 24. Current Score: 111920
Time T=4000/7071. Finished Cars: 576. Current Score: 2460315
Time T=4500/7071. Finished Cars: 986. Current Score: 4057929
Time T=5000/7071. Finished Cars: 1000. Current Score: 4106799
Time T=5500/7071. Finished Cars: 1000. Current Score: 4106799
Time T=6000/7071. Finished Cars: 1000. Current Score: 4106799
Time T=6500/7071. Finished Cars: 1000. Current Score: 4106799
Time T=7000/7071. Finished Cars: 1000. Current Score: 4106799
```

```
=====
SIMULATION COMPLETE at T=7071
FINAL TOTAL SCORE: 4106799
Total Cars: 1000
Cars Finished: 1000
=====
```

Model 3 (Demand-Weighted Local Search)

```
In [ ]: import sys
from collections import defaultdict
from bisect import bisect_right

# =====
# Data structures
# =====

class Street:
    def __init__(self, unique_id, start, end, name, length):
        self.unique_id = unique_id
        self.start = start
        self.end = end
        self.name = name
        self.length = length
        self.incoming_usage_count = 0
        self.cars_on_start = 0

class Car:
    def __init__(self, unique_id, streets):
        self.unique_id = unique_id
        self.streets = streets # List[Street]

    def time_need_to_drive(self):
        # sum of lengths from street index 1 onwards
```

```
        # (i.e., total travel after reaching first intersection)
        t = 0
        for i in range(1, len(self.streets)):
            t += self.streets[i].length
        return t

class Intersection:
    def __init__(self, idx):
        self.id = idx
        self.incoming = [] # List[Street]
        self.outgoing = [] # List[Street]

class CarSimulationPosition:
    """
    Stores precomputed arrays of:
    - street ids
    - street end intersections
    - street lengths
    """
    def __init__(self, car, time_got_here):
        self.car = car
        self.street_number = 0
        self.time_got_here = time_got_here
        self.time_left_on_drive = car.time_need_to_drive()

        self.street_ids = []
        self.street_ends = []
        self.street_lengths = []

        for st in self.car.streets:
            self.street_ids.append(st.unique_id)
            self.street_ends.append(st.end)
            self.street_lengths.append(st.length)

    def init(self, time_got_here):
        """Reset for a new simulation run."""
        self.street_number = 0
        self.time_got_here = time_got_here
        self.time_left_on_drive = self.car.time_need_to_drive()

class Problem:
    def __init__(self):
        self.duration = 0
        self.bonus_per_car = 0
        self.intersections = [] # List[Intersection]
        self.streets = [] # List[Street]
        self.cars = [] # List[Car]

    @staticmethod
    def load_problem(file_name):
        """
        Hash Code 2021 input format.
        """
```

```

with open(file_name, "r") as f:
    first = f.readline().split()
    d = int(first[0])
    number_of_intersections = int(first[1])
    s = int(first[2])
    v = int(first[3])
    f_bonus = int(first[4])

    problem = Problem()
    problem.duration = d
    problem.bonus_per_car = f_bonus

    # Read streets
    streets_map = {}
    for street_id in range(s):
        line = f.readline().split()
        start = int(line[0])
        end = int(line[1])
        name = line[2]
        length = int(line[3])
        st = Street(street_id, start, end, name, length)
        problem.streets.append(st)
        streets_map[name] = st

    # Read cars
    for car_id in range(v):
        parts = f.readline().split()
        p = int(parts[0])
        street_names = parts[1:]
        car_streets = [streets_map[name] for name in street_names]
        problem.cars.append(Car(car_id, car_streets))

    # Build intersections
    problem.intersections = [Intersection(i) for i in range(number_of_intersections)]
    for st in problem.streets:
        problem.intersections[st.start].outgoing.append(st)
        problem.intersections[st.end].incoming.append(st)

    # Count incoming usage (for completeness)
    for car in problem.cars:
        for i in range(len(car.streets) - 1):
            car.streets[i].incoming_usage_count += 1

    # Cars on start
    for st in problem.streets:
        st.cars_on_start = 0
    for car in problem.cars:
        car.streets[0].cars_on_start += 1

    return problem

def remove_unused_streets(self):
    """
    remove incoming streets from intersection
    if their IncomingUsageCount == 0.
    """

```

```

        removed = 0
        for inter in self.intersections:
            keep = []
            for st in inter.incoming:
                if st.incoming_usage_count > 0:
                    keep.append(st)
            else:
                removed += 1
            inter.incoming = keep
        return removed

class GreenLightCycle:
    def __init__(self, street, duration):
        self.street = street # Street object
        self.duration = duration # int
        # 'GreenLightUsed' is only used in the fancy optimizeGreenLightOrder4,
        # not in the lite simulation, so we skip it here.

class SolutionIntersection:
    def __init__(self, idx):
        self.id = idx
        self.green_cycles = [] # List[GreenLightCycle]
        self.green_array = [] # List[street_id] (expanded cycle)
        self.last_car_pass_time = -1

    def build_green_array(self):
        """
        Flatten cycles into an array where index t % len(green_array)
        tells which street_id is green at that time.
        """
        self.green_array = []
        for cycle in self.green_cycles:
            for _ in range(cycle.duration):
                self.green_array.append(cycle.street.unique_id)

class Solution:
    def __init__(self, num_intersections):
        self.intersections = [SolutionIntersection(i) for i in range(num_intersections)]

    def count_intersections_with_green_lights(self):
        c = 0
        for si in self.intersections:
            if any(cyc.duration > 0 for cyc in si.green_cycles):
                c += 1
        return c

# =====
# Basic initial solution: 1 second per incoming street
# =====

def init_basic_solution(problem, solution):
    """

```

```

- For each intersection i:
- one GreenLightCycle per incoming street, duration=1
"""
for inter in problem.intersections:
    si = solution.intersections[inter.id]
    si.green_cycles.clear()
    for st in inter.incoming:
        si.green_cycles.append(GreenLightCycle(street=st, duration=1))
import math
from collections import defaultdict

def build_weighted_solution(problem):
    """
    Build a better-than-naive initial schedule:
    - Give more green seconds to streets with more "finishable" cars.
    - Keep one cycle per intersection.
    """
    D = problem.duration
    bonus = problem.bonus_per_car

    solution = Solution(num_intersections=len(problem.intersections))

    # 1) Find finishable cars and count usage per street
    street_weight = defaultdict(float)

    for car in problem.cars:
        total_time = car.time_need_to_drive()
        if total_time > D:
            continue # this car can never finish, ignore

        # weight of this car could be 1, or (D - total_time) to favor quick paths
        w = 1.0
        # or try: w = 1.0 + (D - total_time) / D

        for i in range(len(car.streets) - 1): # only internal streets
            st = car.streets[i]
            street_weight[st.unique_id] += w

    # 2) For each intersection, distribute green time among its incoming streets
    for inter in problem.intersections:
        si = solution.intersections[inter.id]
        incoming = inter.incoming

        if not incoming:
            continue

        # Get weights for incoming streets, fallback to 0
        weights = [street_weight[st.unique_id] for st in incoming]
        total_w = sum(weights)

        if total_w == 0:
            # No meaningful weight info -> fallback to uniform 1s
            for st in incoming:
                si.green_cycles.append(GreenLightCycle(street=st, duration=1))
            continue

```

```

# Choose total cycle length (small-ish to react quickly)
# try between 4 and 10
TOTAL_CYCLE = min(10, max(3, len(incoming)))

# duration_i = max(1, round(TOTAL_CYCLE * w_i / total_w))
durations = []
for w in weights:
    dur = max(1, int(round(TOTAL_CYCLE * w / total_w)))
    durations.append(dur)

# If rounding overshoot the total, trim a bit
extra = sum(durations) - TOTAL_CYCLE
while extra > 0 and any(d > 1 for d in durations):
    for idx, d in enumerate(durations):
        if extra == 0:
            break
        if d > 1:
            durations[idx] -= 1
            extra -= 1

# Add cycles (we can also sort by weight desc)
order = sorted(range(len(incoming)), key=lambda idx: -weights[idx])
for idx in order:
    st = incoming[idx]
    dur = durations[idx]
    si.green_cycles.append(GreenLightCycle(street=st, duration=dur))

return solution

import random
import copy

def clone_solution(solution):
    new_sol = Solution(len(solution.intersections))
    for i, si in enumerate(solution.intersections):
        new_si = new_sol.intersections[i]
        for cyc in si.green_cycles:
            new_si.green_cycles.append(
                GreenLightCycle(cyc.street, cyc.duration)
            )
    return new_sol

def local_search(problem, initial_solution, iters=1000, print_every=100):
    """
    Simple hill-climbing:
    - Start from initial_solution
    - Randomly tweak intersection schedules
    - Keep modifications that improve score
    """
    best_solution = clone_solution(initial_solution)
    best_score = run_simulation_lite(problem, best_solution)
    print(f"Initial score: {best_score}")

    for it in range(1, iters + 1):
        # Work on a copy
        candidate = clone_solution(best_solution)

```

```

# Pick a random intersection that has at least 1 green cycle
idxs = [i for i, si in enumerate(candidate.intersections) if len(si.green_c
if not idxs:
    break
i = random.choice(idxs)
si = candidate.intersections[i]

# Decide move type: 0 = swap order, 1 = change duration
move_type = random.randint(0, 1)

if move_type == 0 and len(si.green_cycles) >= 2:
    # Swap two random phases
    a, b = random.sample(range(len(si.green_cycles)), 2)
    si.green_cycles[a], si.green_cycles[b] = si.green_cycles[b], si.green_c

else:
    # Change duration of a random phase
    j = random.randrange(len(si.green_cycles))
    old_dur = si.green_cycles[j].duration
    if old_dur == 1:
        # either stay or increase
        si.green_cycles[j].duration = old_dur + 1
    else:
        # +/- 1 with 50-50
        if random.random() < 0.5:
            si.green_cycles[j].duration = max(1, old_dur - 1)
        else:
            si.green_cycles[j].duration = old_dur + 1

# Evaluate candidate
candidate_score = run_simulation_lite(problem, candidate)

if candidate_score > best_score:
    best_solution = candidate
    best_score = candidate_score
    if print_every is not None:
        print(f"[iter {it}] Improved: {best_score}")

if print_every and it % print_every == 0:
    print(f"[iter {it}] current best: {best_score}")

return best_solution, best_score

# =====
# Simulation (Lite version)
# =====

def run_simulation_lite_with_stats(problem, solution):
    """
    Discrete-time simulation from t=0..Problem.Duration.

    Returns:
    {
        "score": total_score,

```

```

        "finished_cars": number_of_cars_that_finished_in_time,
        "total_time_saved": sum_over_finished_cars_of(D - finish_time)
    }
"""
D = problem.duration
bonus = problem.bonus_per_car
cars = problem.cars

# Build expanded green arrays per intersection
for si in solution.intersections:
    si.build_green_array()
    si.last_car_pass_time = -1

# Prepare CarSimulationPosition instances, one per car
car_positions = []
n = len(cars)
simulation_car_start = -(n + 1) # start times negative so they are available a
for car in cars:
    cp = CarSimulationPosition(car, simulation_car_start)
    car_positions.append(cp)
    simulation_car_start += 1

# Sort by TimeGotHere ascending
car_positions.sort(key=lambda c: c.time_got_here)

total_score = 0
finished_cars = 0
total_time_saved = 0
current_time = 0

while current_time <= D:
    i = 0
    # Iterate cars in order of arrival time
    while i < n:
        cp = car_positions[i]
        # If this car arrives in the future, all later cars do too
        if cp.time_got_here > current_time:
            break

        # Determine intersection where car is waiting:
        # It is at end of its "current" street index street_number
        inter_id = cp.street_ends[cp.street_number]
        si = solution.intersections[inter_id]

        # Check if this intersection already used this time step
        if si.last_car_pass_time == current_time:
            i += 1
            continue

        if len(si.green_array) == 0:
            i += 1
            continue

        # Which street id is green now?
        green_street_id = si.green_array[current_time % len(si.green_array)]

```

```

# Is this car's incoming street the green one?
if cp.street_ids[cp.street_number] != green_street_id:
    i += 1
    continue

# Intersection is now used at this time step
si.last_car_pass_time = current_time

# Car passes intersection and enters the next street
cp.street_number += 1
new_len = cp.street_lengths[cp.street_number]
cp.time_got_here = current_time + new_len
cp.time_left_on_drive -= new_len

# Check if car finished its route
if cp.street_number == len(cp.car.streets) - 1:
    # If finished on time, award score and update stats
    if cp.time_got_here <= D:
        time_saved = D - cp.time_got_here
        total_score += bonus + time_saved
        finished_cars += 1
        total_time_saved += time_saved

    # Move finished car to the end (so it is never processed again)
    cp.time_got_here = D + 1 # put far in future
    car_positions.pop(i)
    car_positions.append(cp)
    # n unchanged; next car is now at index i, so do not increment
    continue
else:
    # Car not finished; we must keep car_positions sorted by time_got_h
    car_positions.pop(i)
    # Find new insertion index
    new_pos = bisect_right(
        [c.time_got_here for c in car_positions],
        cp.time_got_here
    )
    car_positions.insert(new_pos, cp)
    # Next car is now at index i, so do not increment
    continue

# Default: go to next car
i += 1

current_time += 1

return {
    "score": total_score,
    "finished_cars": finished_cars,
    "total_time_saved": total_time_saved,
}

def run_simulation_lite(problem, solution):
    """
    Backwards-compatible wrapper used by local_search etc.

```

```

Still returns only the score.
"""
stats = run_simulation_lite_with_stats(problem, solution)
return stats["score"]

# =====
# Example usage
# =====

if __name__ == "__main__":
    INPUT_FILE = "hashcode.txt" # change to your path
    problem = Problem.load_problem(INPUT_FILE)
    print("Duration:", problem.duration)
    print("Intersections:", len(problem.intersections))
    print("Streets:", len(problem.streets))
    print("Cars:", len(problem.cars))

    removed = problem.remove_unused_streets()
    print("Streets removed (unused as incoming):", removed)

    solution0 = build_weighted_solution(problem)
    best_sol, best_score = local_search(problem, solution0, iters=10000)
    print("Final best score (search):", best_score)

    # Re-simulate best solution to get detailed stats
    stats = run_simulation_lite_with_stats(problem, best_sol)

    print("Final best score (recomputed):", stats["score"])
    print(
        f"Cars finished within deadline {problem.duration} s: "
        f"{stats['finished_cars']} out of {len(problem.cars)}"
    )
    print("Total time saved across all finished cars:", stats["total_time_saved"])
    if stats["finished_cars"] > 0:
        print(
            "Average time saved per finished car:",
            stats["total_time_saved"] / stats["finished_cars"]
        )

```

Duration: 7071
Intersections: 8000
Streets: 63968
Cars: 1000
Streets removed (unused as incoming): 9926
Initial score: 4021188
[iter 12] Improved: 4021308
[iter 15] Improved: 4021310
[iter 16] Improved: 4021314
[iter 29] Improved: 4023097
[iter 33] Improved: 4023286
[iter 34] Improved: 4023446
[iter 45] Improved: 4023458
[iter 48] Improved: 4023460
[iter 49] Improved: 4023461
[iter 59] Improved: 4023467
[iter 71] Improved: 4024983
[iter 72] Improved: 4025015
[iter 92] Improved: 4025042
[iter 93] Improved: 4025109
[iter 98] Improved: 4025179
[iter 100] current best: 4025179
[iter 103] Improved: 4025429
[iter 109] Improved: 4025478
[iter 114] Improved: 4025482
[iter 124] Improved: 4025490
[iter 128] Improved: 4025496
[iter 131] Improved: 4025528
[iter 134] Improved: 4025738
[iter 159] Improved: 4025935
[iter 160] Improved: 4025953
[iter 163] Improved: 4025954
[iter 168] Improved: 4026024
[iter 179] Improved: 4026044
[iter 182] Improved: 4026380
[iter 193] Improved: 4026460
[iter 200] current best: 4026460
[iter 204] Improved: 4026502
[iter 205] Improved: 4026956
[iter 212] Improved: 4026966
[iter 217] Improved: 4027077
[iter 222] Improved: 4027089
[iter 234] Improved: 4027295
[iter 237] Improved: 4027608
[iter 243] Improved: 4027698
[iter 244] Improved: 4027706
[iter 251] Improved: 4027709
[iter 266] Improved: 4027710
[iter 295] Improved: 4027715
[iter 300] Improved: 4027831
[iter 300] current best: 4027831
[iter 311] Improved: 4027911
[iter 338] Improved: 4027973
[iter 344] Improved: 4028069
[iter 349] Improved: 4028088
[iter 355] Improved: 4028094

[iter 368] Improved: 4028104
[iter 387] Improved: 4028128
[iter 395] Improved: 4028133
[iter 400] current best: 4028133
[iter 409] Improved: 4028468
[iter 414] Improved: 4028469
[iter 415] Improved: 4028601
[iter 431] Improved: 4028602
[iter 434] Improved: 4028667
[iter 442] Improved: 4028670
[iter 463] Improved: 4028845
[iter 467] Improved: 4028846
[iter 480] Improved: 4029326
[iter 496] Improved: 4029327
[iter 500] current best: 4029327
[iter 510] Improved: 4029439
[iter 519] Improved: 4029565
[iter 524] Improved: 4029566
[iter 527] Improved: 4029568
[iter 537] Improved: 4029628
[iter 538] Improved: 4029637
[iter 544] Improved: 4029639
[iter 545] Improved: 4029667
[iter 553] Improved: 4029717
[iter 572] Improved: 4029765
[iter 573] Improved: 4029810
[iter 578] Improved: 4029811
[iter 586] Improved: 4029935
[iter 600] current best: 4029935
[iter 605] Improved: 4029938
[iter 607] Improved: 4030124
[iter 609] Improved: 4030228
[iter 611] Improved: 4030245
[iter 635] Improved: 4030441
[iter 637] Improved: 4030459
[iter 654] Improved: 4030506
[iter 655] Improved: 4030513
[iter 671] Improved: 4030518
[iter 684] Improved: 4030534
[iter 692] Improved: 4030546
[iter 700] current best: 4030546
[iter 715] Improved: 4030885
[iter 729] Improved: 4030935
[iter 731] Improved: 4031239
[iter 734] Improved: 4031451
[iter 739] Improved: 4031671
[iter 768] Improved: 4031673
[iter 777] Improved: 4031694
[iter 781] Improved: 4031739
[iter 786] Improved: 4031934
[iter 796] Improved: 4031957
[iter 798] Improved: 4032017
[iter 800] current best: 4032017
[iter 810] Improved: 4032385
[iter 824] Improved: 4032386
[iter 828] Improved: 4032387

[iter 830] Improved: 4032431
[iter 831] Improved: 4032433
[iter 842] Improved: 4032484
[iter 846] Improved: 4032919
[iter 854] Improved: 4032970
[iter 861] Improved: 4032973
[iter 867] Improved: 4033001
[iter 875] Improved: 4033034
[iter 882] Improved: 4033036
[iter 891] Improved: 4033040
[iter 896] Improved: 4033080
[iter 900] current best: 4033080
[iter 909] Improved: 4033125
[iter 910] Improved: 4033126
[iter 934] Improved: 4033316
[iter 941] Improved: 4033445
[iter 989] Improved: 4033446
[iter 997] Improved: 4033493
[iter 1000] current best: 4033493
[iter 1025] Improved: 4033523
[iter 1035] Improved: 4033524
[iter 1049] Improved: 4033576
[iter 1063] Improved: 4033709
[iter 1064] Improved: 4033811
[iter 1071] Improved: 4033816
[iter 1072] Improved: 4033818
[iter 1079] Improved: 4033905
[iter 1083] Improved: 4033995
[iter 1084] Improved: 4034031
[iter 1094] Improved: 4034036
[iter 1095] Improved: 4034042
[iter 1100] Improved: 4034112
[iter 1100] current best: 4034112
[iter 1107] Improved: 4034144
[iter 1122] Improved: 4034238
[iter 1138] Improved: 4034246
[iter 1185] Improved: 4034298
[iter 1188] Improved: 4034318
[iter 1198] Improved: 4034320
[iter 1200] current best: 4034320
[iter 1221] Improved: 4034328
[iter 1225] Improved: 4034330
[iter 1242] Improved: 4034335
[iter 1247] Improved: 4034339
[iter 1258] Improved: 4034415
[iter 1267] Improved: 4034431
[iter 1294] Improved: 4034461
[iter 1300] current best: 4034461
[iter 1305] Improved: 4034463
[iter 1365] Improved: 4034592
[iter 1371] Improved: 4034628
[iter 1383] Improved: 4034749
[iter 1391] Improved: 4034925
[iter 1399] Improved: 4034927
[iter 1400] current best: 4034927
[iter 1411] Improved: 4035018

[iter 1418] Improved: 4035121
[iter 1420] Improved: 4035125
[iter 1438] Improved: 4035127
[iter 1452] Improved: 4035129
[iter 1459] Improved: 4035316
[iter 1466] Improved: 4035537
[iter 1498] Improved: 4035705
[iter 1500] current best: 4035705
[iter 1504] Improved: 4035709
[iter 1520] Improved: 4035711
[iter 1529] Improved: 4035715
[iter 1545] Improved: 4035717
[iter 1567] Improved: 4035719
[iter 1576] Improved: 4035723
[iter 1598] Improved: 4035779
[iter 1600] current best: 4035779
[iter 1605] Improved: 4035857
[iter 1632] Improved: 4035861
[iter 1639] Improved: 4035961
[iter 1644] Improved: 4035981
[iter 1646] Improved: 4036066
[iter 1649] Improved: 4036180
[iter 1668] Improved: 4036257
[iter 1673] Improved: 4036262
[iter 1680] Improved: 4036266
[iter 1683] Improved: 4036337
[iter 1694] Improved: 4036338
[iter 1700] current best: 4036338
[iter 1710] Improved: 4036350
[iter 1727] Improved: 4036370
[iter 1731] Improved: 4036371
[iter 1732] Improved: 4036567
[iter 1756] Improved: 4036647
[iter 1766] Improved: 4036847
[iter 1780] Improved: 4036849
[iter 1800] current best: 4036849
[iter 1846] Improved: 4036857
[iter 1848] Improved: 4036883
[iter 1851] Improved: 4036910
[iter 1868] Improved: 4036978
[iter 1871] Improved: 4036979
[iter 1877] Improved: 4037015
[iter 1882] Improved: 4037034
[iter 1900] current best: 4037034
[iter 1904] Improved: 4037056
[iter 1910] Improved: 4037098
[iter 1917] Improved: 4037107
[iter 1924] Improved: 4037129
[iter 1928] Improved: 4037132
[iter 1942] Improved: 4037136
[iter 1948] Improved: 4037226
[iter 1958] Improved: 4037320
[iter 1975] Improved: 4037325
[iter 1983] Improved: 4037689
[iter 1996] Improved: 4037727
[iter 2000] current best: 4037727

[iter 2012] Improved: 4037843
[iter 2018] Improved: 4037895
[iter 2039] Improved: 4038219
[iter 2062] Improved: 4038397
[iter 2074] Improved: 4038737
[iter 2100] current best: 4038737
[iter 2113] Improved: 4038740
[iter 2123] Improved: 4038948
[iter 2152] Improved: 4039017
[iter 2163] Improved: 4039018
[iter 2164] Improved: 4039019
[iter 2165] Improved: 4039025
[iter 2175] Improved: 4039046
[iter 2182] Improved: 4039058
[iter 2186] Improved: 4039228
[iter 2188] Improved: 4039451
[iter 2190] Improved: 4039516
[iter 2200] current best: 4039516
[iter 2205] Improved: 4039541
[iter 2209] Improved: 4039555
[iter 2226] Improved: 4039615
[iter 2241] Improved: 4039629
[iter 2248] Improved: 4039630
[iter 2256] Improved: 4039632
[iter 2267] Improved: 4039682
[iter 2300] current best: 4039682
[iter 2316] Improved: 4039684
[iter 2336] Improved: 4039873
[iter 2355] Improved: 4039981
[iter 2391] Improved: 4040093
[iter 2393] Improved: 4040096
[iter 2400] current best: 4040096
[iter 2422] Improved: 4040098
[iter 2423] Improved: 4040103
[iter 2438] Improved: 4040242
[iter 2457] Improved: 4040243
[iter 2466] Improved: 4040391
[iter 2474] Improved: 4040550
[iter 2488] Improved: 4040553
[iter 2497] Improved: 4040554
[iter 2500] current best: 4040554
[iter 2503] Improved: 4040555
[iter 2519] Improved: 4040861
[iter 2522] Improved: 4040880
[iter 2523] Improved: 4040883
[iter 2547] Improved: 4041006
[iter 2580] Improved: 4041012
[iter 2600] current best: 4041012
[iter 2612] Improved: 4041013
[iter 2614] Improved: 4041027
[iter 2617] Improved: 4041029
[iter 2628] Improved: 4041296
[iter 2630] Improved: 4041396
[iter 2641] Improved: 4041399
[iter 2654] Improved: 4041471
[iter 2668] Improved: 4041473

[iter 2670] Improved: 4041474
[iter 2671] Improved: 4041486
[iter 2681] Improved: 4041576
[iter 2685] Improved: 4041588
[iter 2690] Improved: 4041972
[iter 2694] Improved: 4042080
[iter 2700] Improved: 4042095
[iter 2700] current best: 4042095
[iter 2720] Improved: 4042241
[iter 2730] Improved: 4042350
[iter 2736] Improved: 4042351
[iter 2784] Improved: 4042387
[iter 2800] current best: 4042387
[iter 2812] Improved: 4042389
[iter 2813] Improved: 4042390
[iter 2835] Improved: 4042396
[iter 2859] Improved: 4042603
[iter 2862] Improved: 4042846
[iter 2864] Improved: 4042849
[iter 2900] current best: 4042849
[iter 2965] Improved: 4042931
[iter 2966] Improved: 4043052
[iter 2968] Improved: 4043147
[iter 2976] Improved: 4043172
[iter 2993] Improved: 4043256
[iter 3000] current best: 4043256
[iter 3005] Improved: 4043310
[iter 3020] Improved: 4043550
[iter 3059] Improved: 4043648
[iter 3090] Improved: 4043658
[iter 3100] current best: 4043658
[iter 3104] Improved: 4043694
[iter 3121] Improved: 4043706
[iter 3133] Improved: 4043724
[iter 3136] Improved: 4043829
[iter 3142] Improved: 4043843
[iter 3160] Improved: 4043885
[iter 3168] Improved: 4043985
[iter 3186] Improved: 4044141
[iter 3197] Improved: 4044270
[iter 3198] Improved: 4044438
[iter 3200] current best: 4044438
[iter 3214] Improved: 4044462
[iter 3220] Improved: 4044582
[iter 3227] Improved: 4044589
[iter 3232] Improved: 4044715
[iter 3238] Improved: 4044726
[iter 3247] Improved: 4044969
[iter 3266] Improved: 4044989
[iter 3268] Improved: 4045037
[iter 3300] current best: 4045037
[iter 3301] Improved: 4045042
[iter 3317] Improved: 4045044
[iter 3339] Improved: 4045394
[iter 3346] Improved: 4045576
[iter 3379] Improved: 4045578

[iter 3395] Improved: 4045858
[iter 3398] Improved: 4045938
[iter 3400] current best: 4045938
[iter 3410] Improved: 4045945
[iter 3500] current best: 4045945
[iter 3548] Improved: 4045949
[iter 3555] Improved: 4046089
[iter 3559] Improved: 4046134
[iter 3579] Improved: 4046450
[iter 3597] Improved: 4046465
[iter 3600] current best: 4046465
[iter 3611] Improved: 4046466
[iter 3652] Improved: 4046467
[iter 3675] Improved: 4046479
[iter 3700] current best: 4046479
[iter 3701] Improved: 4046567
[iter 3724] Improved: 4046588
[iter 3734] Improved: 4046872
[iter 3749] Improved: 4047022
[iter 3762] Improved: 4047112
[iter 3800] current best: 4047112
[iter 3801] Improved: 4047119
[iter 3806] Improved: 4047139
[iter 3807] Improved: 4047224
[iter 3814] Improved: 4047227
[iter 3838] Improved: 4047378
[iter 3839] Improved: 4047396
[iter 3842] Improved: 4047452
[iter 3848] Improved: 4047862
[iter 3867] Improved: 4047941
[iter 3891] Improved: 4047944
[iter 3900] current best: 4047944
[iter 3921] Improved: 4048184
[iter 3922] Improved: 4048186
[iter 3923] Improved: 4048191
[iter 3935] Improved: 4048271
[iter 3967] Improved: 4048325
[iter 3984] Improved: 4048336
[iter 3990] Improved: 4048338
[iter 4000] current best: 4048338
[iter 4020] Improved: 4048618
[iter 4035] Improved: 4048624
[iter 4043] Improved: 4048625
[iter 4087] Improved: 4048670
[iter 4094] Improved: 4048675
[iter 4100] current best: 4048675
[iter 4105] Improved: 4048871
[iter 4147] Improved: 4049069
[iter 4151] Improved: 4049070
[iter 4154] Improved: 4049072
[iter 4170] Improved: 4049083
[iter 4176] Improved: 4049447
[iter 4184] Improved: 4049657
[iter 4199] Improved: 4049662
[iter 4200] Improved: 4049663
[iter 4200] current best: 4049663

[iter 4203] Improved: 4050767
[iter 4226] Improved: 4050786
[iter 4229] Improved: 4051043
[iter 4233] Improved: 4051048
[iter 4245] Improved: 4051063
[iter 4266] Improved: 4051083
[iter 4300] current best: 4051083
[iter 4327] Improved: 4051261
[iter 4336] Improved: 4051301
[iter 4339] Improved: 4051303
[iter 4359] Improved: 4051354
[iter 4381] Improved: 4051390
[iter 4382] Improved: 4051391
[iter 4400] current best: 4051391
[iter 4413] Improved: 4051392
[iter 4417] Improved: 4051394
[iter 4433] Improved: 4051395
[iter 4488] Improved: 4051408
[iter 4500] current best: 4051408
[iter 4510] Improved: 4051409
[iter 4521] Improved: 4051544
[iter 4544] Improved: 4051604
[iter 4563] Improved: 4051724
[iter 4570] Improved: 4051730
[iter 4600] current best: 4051730
[iter 4604] Improved: 4051930
[iter 4613] Improved: 4052125
[iter 4625] Improved: 4052264
[iter 4645] Improved: 4052448
[iter 4647] Improved: 4052656
[iter 4700] Improved: 4052704
[iter 4700] current best: 4052704
[iter 4717] Improved: 4052912
[iter 4719] Improved: 4052921
[iter 4725] Improved: 4052930
[iter 4732] Improved: 4052970
[iter 4761] Improved: 4052976
[iter 4786] Improved: 4052977
[iter 4800] current best: 4052977
[iter 4810] Improved: 4052978
[iter 4813] Improved: 4052980
[iter 4817] Improved: 4053020
[iter 4830] Improved: 4053136
[iter 4867] Improved: 4053380
[iter 4900] current best: 4053380
[iter 4961] Improved: 4053390
[iter 4983] Improved: 4053406
[iter 4992] Improved: 4053455
[iter 5000] current best: 4053455
[iter 5003] Improved: 4053489
[iter 5006] Improved: 4053498
[iter 5013] Improved: 4053499
[iter 5063] Improved: 4053930
[iter 5071] Improved: 4053962
[iter 5099] Improved: 4053967
[iter 5100] current best: 4053967

[iter 5120] Improved: 4053968
[iter 5183] Improved: 4054024
[iter 5186] Improved: 4054034
[iter 5195] Improved: 4054179
[iter 5196] Improved: 4054395
[iter 5200] current best: 4054395
[iter 5222] Improved: 4054396
[iter 5272] Improved: 4054670
[iter 5293] Improved: 4054698
[iter 5298] Improved: 4055023
[iter 5300] current best: 4055023
[iter 5304] Improved: 4055161
[iter 5308] Improved: 4055416
[iter 5329] Improved: 4055463
[iter 5339] Improved: 4055483
[iter 5389] Improved: 4055511
[iter 5390] Improved: 4055539
[iter 5400] current best: 4055539
[iter 5432] Improved: 4055651
[iter 5459] Improved: 4055669
[iter 5467] Improved: 4055670
[iter 5494] Improved: 4055674
[iter 5497] Improved: 4055684
[iter 5500] current best: 4055684
[iter 5506] Improved: 4055732
[iter 5515] Improved: 4055852
[iter 5524] Improved: 4055872
[iter 5534] Improved: 4055976
[iter 5541] Improved: 4055980
[iter 5571] Improved: 4056024
[iter 5600] current best: 4056024
[iter 5624] Improved: 4056120
[iter 5631] Improved: 4056123
[iter 5687] Improved: 4056130
[iter 5700] current best: 4056130
[iter 5730] Improved: 4056183
[iter 5758] Improved: 4056210
[iter 5763] Improved: 4056216
[iter 5773] Improved: 4056558
[iter 5788] Improved: 4056566
[iter 5796] Improved: 4056568
[iter 5800] current best: 4056568
[iter 5810] Improved: 4056748
[iter 5819] Improved: 4056751
[iter 5830] Improved: 4056779
[iter 5844] Improved: 4056789
[iter 5859] Improved: 4056797
[iter 5864] Improved: 4056800
[iter 5868] Improved: 4056830
[iter 5900] current best: 4056830
[iter 5912] Improved: 4057021
[iter 5918] Improved: 4057025
[iter 5933] Improved: 4057160
[iter 5941] Improved: 4057166
[iter 5964] Improved: 4057443
[iter 5978] Improved: 4057485

[iter 6000] current best: 4057485
[iter 6070] Improved: 4057488
[iter 6100] current best: 4057488
[iter 6129] Improved: 4057489
[iter 6153] Improved: 4057491
[iter 6156] Improved: 4057533
[iter 6173] Improved: 4057627
[iter 6200] current best: 4057627
[iter 6203] Improved: 4057629
[iter 6236] Improved: 4057632
[iter 6277] Improved: 4057640
[iter 6298] Improved: 4057875
[iter 6300] current best: 4057875
[iter 6306] Improved: 4057935
[iter 6335] Improved: 4057936
[iter 6341] Improved: 4057937
[iter 6347] Improved: 4057939
[iter 6361] Improved: 4057945
[iter 6363] Improved: 4057955
[iter 6400] current best: 4057955
[iter 6431] Improved: 4057976
[iter 6435] Improved: 4057988
[iter 6437] Improved: 4058150
[iter 6439] Improved: 4058215
[iter 6466] Improved: 4058370
[iter 6474] Improved: 4058386
[iter 6475] Improved: 4058419
[iter 6500] current best: 4058419
[iter 6507] Improved: 4058449
[iter 6555] Improved: 4058450
[iter 6561] Improved: 4058469
[iter 6569] Improved: 4058472
[iter 6593] Improved: 4058485
[iter 6600] current best: 4058485
[iter 6606] Improved: 4058486
[iter 6611] Improved: 4058492
[iter 6649] Improved: 4058500
[iter 6659] Improved: 4058515
[iter 6662] Improved: 4058557
[iter 6675] Improved: 4058559
[iter 6692] Improved: 4058633
[iter 6700] current best: 4058633
[iter 6701] Improved: 4058635
[iter 6730] Improved: 4058685
[iter 6736] Improved: 4058727
[iter 6753] Improved: 4058747
[iter 6770] Improved: 4058758
[iter 6800] current best: 4058758
[iter 6838] Improved: 4058759
[iter 6867] Improved: 4058760
[iter 6884] Improved: 4058761
[iter 6900] current best: 4058761
[iter 6903] Improved: 4058765
[iter 6907] Improved: 4058774
[iter 6926] Improved: 4058775
[iter 7000] current best: 4058775

[iter 7089] Improved: 4058782
[iter 7097] Improved: 4058970
[iter 7100] current best: 4058970
[iter 7109] Improved: 4058978
[iter 7111] Improved: 4058982
[iter 7112] Improved: 4058984
[iter 7118] Improved: 4059050
[iter 7152] Improved: 4059068
[iter 7157] Improved: 4059069
[iter 7191] Improved: 4059088
[iter 7192] Improved: 4059098
[iter 7197] Improved: 4059099
[iter 7200] current best: 4059099
[iter 7208] Improved: 4059105
[iter 7220] Improved: 4059171
[iter 7224] Improved: 4059176
[iter 7238] Improved: 4059177
[iter 7259] Improved: 4059179
[iter 7300] current best: 4059179
[iter 7301] Improved: 4059195
[iter 7330] Improved: 4059197
[iter 7332] Improved: 4059198
[iter 7365] Improved: 4059292
[iter 7393] Improved: 4059372
[iter 7395] Improved: 4059373
[iter 7400] current best: 4059373
[iter 7403] Improved: 4059396
[iter 7473] Improved: 4059426
[iter 7475] Improved: 4059427
[iter 7500] current best: 4059427
[iter 7516] Improved: 4059430
[iter 7529] Improved: 4059438
[iter 7537] Improved: 4059439
[iter 7545] Improved: 4059522
[iter 7559] Improved: 4059543
[iter 7591] Improved: 4059627
[iter 7600] current best: 4059627
[iter 7700] current best: 4059627
[iter 7711] Improved: 4059639
[iter 7727] Improved: 4059646
[iter 7747] Improved: 4059680
[iter 7767] Improved: 4059688
[iter 7769] Improved: 4059689
[iter 7779] Improved: 4059691
[iter 7795] Improved: 4059692
[iter 7797] Improved: 4059693
[iter 7800] current best: 4059693
[iter 7813] Improved: 4060029
[iter 7826] Improved: 4060098
[iter 7827] Improved: 4060122
[iter 7831] Improved: 4060126
[iter 7860] Improved: 4060252
[iter 7873] Improved: 4060280
[iter 7886] Improved: 4060352
[iter 7892] Improved: 4060402
[iter 7900] current best: 4060402

[iter 7927] Improved: 4060403
[iter 7939] Improved: 4060451
[iter 7974] Improved: 4060453
[iter 7984] Improved: 4060476
[iter 8000] current best: 4060476
[iter 8081] Improved: 4060484
[iter 8100] current best: 4060484
[iter 8147] Improved: 4060485
[iter 8160] Improved: 4060932
[iter 8184] Improved: 4060943
[iter 8200] Improved: 4060992
[iter 8200] current best: 4060992
[iter 8227] Improved: 4061019
[iter 8252] Improved: 4061020
[iter 8253] Improved: 4061069
[iter 8299] Improved: 4061237
[iter 8300] current best: 4061237
[iter 8341] Improved: 4061240
[iter 8377] Improved: 4061295
[iter 8393] Improved: 4061298
[iter 8399] Improved: 4061394
[iter 8400] current best: 4061394
[iter 8435] Improved: 4061510
[iter 8449] Improved: 4061517
[iter 8456] Improved: 4061542
[iter 8476] Improved: 4061553
[iter 8479] Improved: 4061555
[iter 8500] current best: 4061555
[iter 8501] Improved: 4061558
[iter 8572] Improved: 4061586
[iter 8580] Improved: 4061588
[iter 8588] Improved: 4061589
[iter 8600] current best: 4061589
[iter 8658] Improved: 4061590
[iter 8700] current best: 4061590
[iter 8715] Improved: 4061596
[iter 8730] Improved: 4061605
[iter 8759] Improved: 4061607
[iter 8775] Improved: 4061609
[iter 8782] Improved: 4061679
[iter 8793] Improved: 4061919
[iter 8800] current best: 4061919
[iter 8847] Improved: 4061922
[iter 8865] Improved: 4061923
[iter 8879] Improved: 4061944
[iter 8882] Improved: 4061984
[iter 8900] current best: 4061984
[iter 8904] Improved: 4062359
[iter 8922] Improved: 4062422
[iter 8936] Improved: 4062424
[iter 8952] Improved: 4062427
[iter 8992] Improved: 4062428
[iter 8999] Improved: 4062429
[iter 9000] current best: 4062429
[iter 9014] Improved: 4062434
[iter 9050] Improved: 4062666

```

[iter 9062] Improved: 4062667
[iter 9064] Improved: 4062668
[iter 9066] Improved: 4062669
[iter 9076] Improved: 4062677
[iter 9098] Improved: 4062678
[iter 9100] current best: 4062678
[iter 9143] Improved: 4062689
[iter 9160] Improved: 4062726
[iter 9164] Improved: 4062782
[iter 9165] Improved: 4062791
[iter 9169] Improved: 4062807
[iter 9199] Improved: 4062813
[iter 9200] current best: 4062813
[iter 9204] Improved: 4062814
[iter 9230] Improved: 4062860
[iter 9248] Improved: 4062926
[iter 9249] Improved: 4063108
[iter 9261] Improved: 4063136
[iter 9268] Improved: 4063138
[iter 9269] Improved: 4063246
[iter 9272] Improved: 4063252
[iter 9279] Improved: 4063353
[iter 9300] current best: 4063353
[iter 9313] Improved: 4063356
[iter 9370] Improved: 4063460
[iter 9392] Improved: 4063595
[iter 9393] Improved: 4063602
[iter 9400] current best: 4063602
[iter 9421] Improved: 4063701
[iter 9434] Improved: 4063704
[iter 9435] Improved: 4063709
[iter 9443] Improved: 4063732
[iter 9467] Improved: 4063737
[iter 9477] Improved: 4063849
[iter 9481] Improved: 4063943
[iter 9500] current best: 4063943
[iter 9510] Improved: 4063949
[iter 9531] Improved: 4063950
[iter 9537] Improved: 4063980
[iter 9600] current best: 4063980
[iter 9603] Improved: 4064041
[iter 9606] Improved: 4064260
[iter 9616] Improved: 4064263
[iter 9638] Improved: 4064268
[iter 9666] Improved: 4064271
[iter 9673] Improved: 4064329
[iter 9675] Improved: 4064330
[iter 9676] Improved: 4064334
[iter 9679] Improved: 4064343
[iter 9682] Improved: 4064344
[iter 9700] current best: 4064344
[iter 9707] Improved: 4064348
[iter 9720] Improved: 4064349
[iter 9756] Improved: 4064379
[iter 9775] Improved: 4064384
[iter 9798] Improved: 4064404

```

```

[iter 9799] Improved: 4064417
[iter 9800] current best: 4064417
[iter 9804] Improved: 4064701
[iter 9824] Improved: 4064780
[iter 9840] Improved: 4064807
[iter 9841] Improved: 4064813
[iter 9842] Improved: 4064856
[iter 9891] Improved: 4064857
[iter 9900] current best: 4064857
[iter 9909] Improved: 4064932
[iter 9919] Improved: 4064934
[iter 9926] Improved: 4065347
[iter 9962] Improved: 4065348
[iter 9974] Improved: 4065440
[iter 9989] Improved: 4065441
[iter 9996] Improved: 4065548
[iter 10000] current best: 4065548
Final best score (search): 4065548
Final best score (recomputed): 4065548
Cars finished within deadline 7071 s: 1000 out of 1000
Total time saved across all finished cars: 3065548
Average time saved per finished car: 3065.548

```

```

In [ ]: import matplotlib.pyplot as plt
import re

# Read the file
with open('iterations.txt', 'r') as f:
    content = f.read()

# Parse iterations and scores
iterations = []
scores = []

# Extract all lines with iteration data
lines = content.strip().split('\n')

current_score = None
for line in lines:
    # Match pattern: [iter X] or [iter X] Improved: YYYY
    match = re.search(r'\[iter (\d+)\]', line)
    if match:
        iter_num = int(match.group(1))

        # Check if this line has a score (either "Improved:" or "current best:")
        score_match = re.search(r': (\d+)\$', line)
        if score_match:
            current_score = int(score_match.group(1))

        iterations.append(iter_num)
        scores.append(current_score)

# Fill in missing iterations (0 to 10000)
# Create complete arrays from iter 0 to 10000
all_iters = list(range(10001)) # 0 to 10000
all_scores = []

```

```


score_dict = dict(zip(iterations, scores))
current_best = None

for i in range(10001):
    if i in score_dict and score_dict[i] is not None:
        current_best = score_dict[i]
        all_scores.append(current_best)

# Plot
plt.figure(figsize=(14, 6))
plt.plot(all_iters, all_scores, linewidth=1.5, color='steelblue')
plt.xlabel('Iteration', fontsize=12)
plt.ylabel('Score', fontsize=12)
plt.title('Local Search Optimization: Score vs Iteration', fontsize=14)
plt.grid(True, alpha=0.3)
plt.tight_layout()
plt.savefig('iterations_plot.png', dpi=300)
plt.show()

print(f"Plot saved as 'iterations_plot.png'")
print(f"Total iterations tracked: {len(iterations)}")
print(f"Final best score: {all_scores[-1]}")

```



Plot saved as 'iterations_plot.png'
 Total iterations tracked: 739
 Final best score: 4065548

Model 4

```

In [4]: import sys
from collections import defaultdict, Counter, deque

# --- CONFIGURATION ---
INPUT_FILENAME = 'hashcode.in.txt'
OUTPUT_FILENAME = 'submission_optimized.out'
PRINT_INTERVAL = 500

def solve_time_ordered_greedy():

```

```

# =====
# 1. PARSE INPUT
# =====
print(f"Reading {INPUT_FILENAME}...")
try:
    with open(INPUT_FILENAME, 'r') as f:
        lines = f.read().splitlines()
except FileNotFoundError:
    print("File not found.")
    return

iterator = iter(lines)
D, I, S, V, F = map(int, next(iterator).split())

street_map = {} # name -> (end_node, Length)
intersection_in = defaultdict(list)

for _ in range(S):
    parts = next(iterator).split()
    name = parts[2]
    E = int(parts[1])
    L = int(parts[3])
    street_map[name] = (E, L)
    intersection_in[E].append(name)

car_paths = []
for _ in range(V):
    parts = next(iterator).split()
    car_paths.append(parts[1:])

# =====
# 2. ADVANCED ANALYSIS
# =====
print("Analyzing traffic flow & timing...")

street_importance = Counter()
street_arrival_times = defaultdict(list)

# We simulate "free flow" travel to guess when cars arrive at each street
# This helps us order the green lights correctly (First-Arrive, First-Serve)

for path in car_paths:
    # 1. Filter Impossible Paths (though you said all finish, let's be safe)
    min_travel = sum(street_map[s][1] for s in path)
    if min_travel > D: continue

    # 2. Calculate Weight (High Value for Short Paths)
    # The "magic formula" that worked well previously
    weight = 1 + (10000 / (min_travel + 1))

    current_time = 0
    for street in path:
        street_importance[street] += weight

        # Record expected arrival time at the END of this street
        # (Assuming no wait, which is our goal)

```

```

        travel_time = street_map[street][1]
        current_time += travel_time
        street_arrival_times[street].append(current_time)

# =====
# 3. BUILD OPTIMIZED SCHEDULE
# =====
print("Generating Time-Ordered Schedule...")

intersection_schedules = {}

for i_id in range(I):
    incoming = intersection_in[i_id]
    active = [s for s in incoming if street_importance[s] > 0]

    if not active:
        continue

    # --- STEP A: Determine Order ---
    # Sort streets by WHEN cars arrive.
    # If Street A has cars arriving at T=10, and Street B at T=50, A goes first
    # We use the 10th percentile arrival time to capture the "leading edge" of
    def get_earliness(street_name):
        times = street_arrival_times[street_name]
        if not times: return float('inf')
        times.sort()
        # Take the arrival time of the first few cars
        idx = min(len(times)-1, 0)
        return times[idx]

    active.sort(key=get_earliness)

    # --- STEP B: Determine Duration ---
    total_imp = sum(street_importance[s] for s in active)
    cycle = []

    for street in active:
        imp = street_importance[street]
        ratio = imp / total_imp

        # Keep cycles tight! Large cycles kill score.
        # Max duration 2s. Only 3s if it's an absolute highway.
        if ratio > 0.5:
            duration = 2
        else:
            duration = 1

        cycle.append((street, duration))

    intersection_schedules[i_id] = cycle

# =====
# 4. SIMULATION (VALIDATION)
# =====
print("\nRunning Simulation...")
print("-" * 50)

```

```

print(f"{'Time':<10} | {'Cars Finished':<15} | {'Score':<10}")
print("-" * 50)

# -- Sim State --
queues = defaultdict(deque)
car_props = []

# Init cars
for c_idx, path in enumerate(car_paths):
    start_street = path[0]
    queues[start_street].append(c_idx)
    car_props.append({
        'path_idx': 0,
        'arrival_time': 0,
        'state': 'queued'
    })

# Init Lights
int_states = {}
for i_id, sched in intersection_schedules.items():
    if sched:
        int_states[i_id] = {'idx': 0, 't_rem': sched[0][1]}

finished_count = 0
current_score = 0

for t in range(D + 1):

    # -- Process Intersections --
    for i_id, sched in intersection_schedules.items():
        if not sched: continue

        state = int_states[i_id]
        green_street_name, duration = sched[state['idx']]

        # Try to move ONE car
        street_q = queues[green_street_name]

        if street_q:
            c_idx = street_q[0]
            car = car_props[c_idx]

            # Check if physically arrived
            if car['arrival_time'] <= t:
                street_q.popleft()

            # Advance Car
            p_idx = car['path_idx'] + 1
            path = car_paths[c_idx]

            if p_idx >= len(path):
                # Finished
                finished_count += 1
                points = F + (D - t)
                current_score += points
                car['state'] = 'done'

```

```

        else:
            # Move to next street
            next_s = path[p_idx]
            travel = street_map[next_s][1]
            car['path_idx'] = p_idx
            car['arrival_time'] = t + travel
            queues[next_s].append(c_idx)

            # -- Update Light Timer --
            state['t_rem'] -= 1
            if state['t_rem'] == 0:
                # Switch Light
                state['idx'] = (state['idx'] + 1) % len(sched)
                state['t_rem'] = sched[state['idx']][1]

            # -- Logging --
            if t % PRINT_INTERVAL == 0 or t == D:
                print(f"{t:<10} | {finished_count:<15} | {current_score:<10}")

print("-" * 50)
print(f"Total Score: {current_score}")

# =====
# 5. WRITE OUTPUT
# =====
with open(OUTPUT_FILENAME, 'w') as f:
    f.write(f"{len(intersection_schedules)}\n")
    for i_id, sched in intersection_schedules.items():
        f.write(f"{i_id}\n")
        f.write(f"{len(sched)}\n")
        for name, duration in sched:
            f.write(f"{name} {duration}\n")

print(f"File saved: {OUTPUT_FILENAME}")

if __name__ == "__main__":
    solve_time_ordered_greedy()

```

Reading hashcode.in.txt...
Analyzing traffic flow & timing...
Generating Time-Ordered Schedule...

Running Simulation...

Time	Cars Finished	Score
0	0	0
500	0	0
1000	0	0
1500	0	0
2000	0	0
2500	0	0
3000	0	0
3500	7	32528
4000	414	1758443
4500	960	3877257
5000	1000	4015598
5500	1000	4015598
6000	1000	4015598
6500	1000	4015598
7000	1000	4015598
7071	1000	4015598

Total Score: 4015598
File saved: submission_optimized.out

Real-City Case-Study (Bengaluru)

```
In [ ]: import pandas as pd
df_map = pd.read_csv("Bengaluru_Edgelist.csv")
df_map.head()
```

```
Out [ ]:
```

	XCoord	YCoord	START_NODE	END_NODE	EDGE	LENGTH
0	860107.596026	1.302889e+06	1	2	1	467.211740
1	860390.919234	1.303260e+06	2	1	1	467.211740
2	860390.919234	1.303260e+06	2	4	2	318.243502
3	860390.919234	1.303260e+06	2	8	4	317.369626
4	860702.591642	1.303317e+06	4	2	2	318.243502

```
In [ ]: # ...existing code...
import networkx as nx
import matplotlib.pyplot as plt

# column names in your file
src_col = 'START_NODE'
tgt_col = 'END_NODE'
xcol = 'XCoord'
ycol = 'YCoord'
```



```

# drop rows with missing endpoints
edges_df = df_map.dropna(subset=[src_col, tgt_col]).copy()

# include all other columns as edge attributes
edge_attr = [c for c in edges_df.columns if c not in [src_col, tgt_col]]
G = nx.from_pandas_edgelist(edges_df, source=src_col, target=tgt_col, edge_attr=edge_attr)

print("Graph built: nodes =", G.number_of_nodes(), "edges =", G.number_of_edges())

# build node positions from XCoord/YCoord (mean of incident edge coords)
pos = {}
if xcol in edges_df.columns and ycol in edges_df.columns:
    all_nodes = set(edges_df[src_col]).union(set(edges_df[tgt_col]))
    for n in all_nodes:
        rows = edges_df[(edges_df[src_col] == n) | (edges_df[tgt_col] == n)]
        if not rows.empty:
            pos[n] = (rows[xcol].mean(), rows[ycol].mean())

# fill missing positions with spring layout
if len(pos) < G.number_of_nodes():
    pos_spring = nx.spring_layout(G, seed=42)
    for n in G.nodes():
        if n not in pos:
            pos[n] = pos_spring[n]

```

Graph built: nodes = 151947 edges = 398956

```

In [ ]: from sklearn.cluster import KMeans
import numpy as np
import matplotlib.pyplot as plt

# Parameters
K = 5
RANDOM_STATE = 42

# Build node coordinate table from edges_df (mean of incident edge coords)
src_col = 'START_NODE'
tgt_col = 'END_NODE'
xcol = 'XCoord'
ycol = 'YCoord'

df_src = edges_df[[src_col, xcol, ycol]].rename(columns={src_col: 'node'})
df_tgt = edges_df[[tgt_col, xcol, ycol]].rename(columns={tgt_col: 'node'})
node_coords = pd.concat([df_src, df_tgt], ignore_index=True)
node_coords = node_coords.groupby('node', as_index=False).agg({'xcol': 'mean', 'ycol': 'mean'})
node_coords = node_coords.dropna(subset=[xcol, ycol]).reset_index(drop=True)

# Run KMeans
km = KMeans(n_clusters=K, random_state=RANDOM_STATE, n_init=10)
coords = node_coords[[xcol, ycol]].to_numpy()
node_coords['cluster'] = km.fit_predict(coords)

# Attach cluster Label to NetworkX graph nodes
for _, r in node_coords.iterrows():
    n = r['node']

```

```

if n in G:
    G.nodes[n]['x'] = float(r[xcol])
    G.nodes[n]['y'] = float(r[ycol])
    G.nodes[n]['cluster'] = int(r['cluster'])

# Save node cluster assignments
node_coords.to_csv('node_clusters_k5.csv', index=False)
print(f"Saved node cluster assignments to node_clusters_k5.csv (K={K})")

# Plot clusters (scatter) and optionally overLay small subgraph
plt.figure(figsize=(8,6))
cmap = plt.get_cmap('tab10')
for k in range(K):
    subset = node_coords[node_coords['cluster'] == k]
    plt.scatter(subset[xcol], subset[ycol], s=5, color=cmap(k % 5), label=f'Cluster {k}')

plt.title(f'K-means clustering of nodes (K={K})')
plt.xlabel(xcol); plt.ylabel(ycol)
plt.legend(markerscale=2, bbox_to_anchor=(1.05,1), loc='upper left')
plt.tight_layout()
plt.show()

# Optional: draw a small subgraph colored by cluster (top nodes by degree)
TOP_N = 200
top_nodes = [n for n, _ in sorted(G.degree(), key=lambda x: x[1], reverse=True)[:TOP_N]]
H = G.subgraph(top_nodes).copy()
# build positions for H from node attributes (fall back to spring)
pos_H = {}
for n in H.nodes():
    x = G.nodes[n].get('x'); y = G.nodes[n].get('y')
    if x is not None and y is not None:
        pos_H[n] = (x, y)
pos_missing = [n for n in H.nodes() if n not in pos_H]
if pos_missing:
    pos_spring = nx.spring_layout(H, seed=RANDOM_STATE)
    for n in pos_missing:
        pos_H[n] = pos_spring[n]


plt.figure(figsize=(8,8))
# draw nodes colored by cluster
node_colors = []
for n in H.nodes():
    c1 = G.nodes[n].get('cluster', -1)
    node_colors.append(cmap(c1 % 10) if c1 >= 0 else 'gray')

nx.draw_networkx_nodes(H, pos_H, node_size=40, node_color=node_colors, alpha=0.9)
nx.draw_networkx_edges(H, pos_H, alpha=0.3, width=0.6, arrows=False)
plt.title(f'Subgraph (top {TOP_N} nodes) colored by KMeans cluster')
plt.axis('off')
plt.show()


# Save updated graph with cluster attribute
nx.write_gexf(G, "Bengaluru_Edgelist_graph_with_clusters_k5.gexf")
print("Saved graph to Bengaluru_Edgelist_graph_with_clusters_k5.gexf")

```

Saved node cluster assignments to node_clusters_k5.csv (K=5)



Subgraph (top 200 nodes) colored by KMeans cluster



Saved graph to Bengaluru_Edgelist_graph_with_clusters_k5.gexf

```
In [ ]: import numpy as np
import pandas as pd
from collections import defaultdict, deque
import matplotlib.pyplot as plt
from matplotlib.colors import Normalize
import matplotlib.cm as cm

# =====
# 1) Data structures
# =====

class Street:
    def __init__(self, unique_id, start, end, name, length_m, speed_mps):
        self.unique_id = unique_id
        self.start = start
        self.end = end
        self.name = name
```

```

        self.length_m = length_m
        # integer travel time (ceil)
        self.travel_time = int(np.ceil(length_m / speed_mps))

class Car:
    def __init__(self, unique_id, streets):
        self.unique_id = unique_id
        self.streets = streets # List[Street]

    def time_need_to_drive(self):
        # HashCode style: sum AFTER first intersection
        if len(self.streets) <= 1:
            return 0
        return sum(st.travel_time for st in self.streets[1:])

class Intersection:
    def __init__(self, idx):
        self.id = idx
        self.incoming = [] # List[Street]
        self.outgoing = [] # List[Street]

class Problem:
    def __init__(self, duration, bonus_per_car):
        self.duration = duration
        self.bonus_per_car = bonus_per_car
        self.intersections = [] # List[Intersection]
        self.streets = [] # List[Street]
        self.cars = [] # List[Car]

class GreenLightCycle:
    def __init__(self, street, duration):
        self.street = street
        self.duration = duration

class SolutionIntersection:
    def __init__(self, idx):
        self.id = idx
        self.green_cycles = [] # List[GreenLightCycle]

class Solution:
    def __init__(self, num_intersections):
        self.intersections = [SolutionIntersection(i) for i in range(num_intersections)]

class VisCarState:
    """
    State used in city-level sim with queues.
    """
    def __init__(self, car):
        self.car = car

```

```

        self.idx = 0 # index of last-completed street
        self.state = "queue" # 'queue', 'moving', 'finished'
        self.time_on_edge = 0 # seconds on current moving edge
        self.moving_edge_idx = None # index of edge being travelled
        self.finish_time = None # time when car finished

# =====
# 2) Helper: build cluster subgraph + node positions
# =====

def build_cluster_subgraph(edges_df,
                           node_coords,
                           cluster_id,
                           node_col="node",
                           cluster_col="cluster",
                           start_col="START_NODE",
                           end_col="END_NODE",
                           length_col="LENGTH",
                           xcol="XCoord",
                           ycol="YCoord"):
    """
    Filter edges + nodes for a given cluster and build:
    - df_cluster: edges fully inside that cluster
    - node_pos: dict original_node_id -> (x, y)
    Assumes:
    node_coords has columns [node_col, xcol, ycol, cluster_col]
    edges_df has columns [start_col, end_col, length_col, ...]
    """
    # nodes belonging to this cluster
    cluster_nodes = set(
        node_coords.loc[node_coords[cluster_col] == cluster_id, node_col].unique()
    )

    # keep only edges where BOTH ends are in the cluster
    mask = (
        edges_df[start_col].isin(cluster_nodes)
        & edges_df[end_col].isin(cluster_nodes)
    )
    df_cluster = edges_df.loc[mask, [start_col, end_col, length_col]].copy()
    df_cluster = df_cluster.rename(
        columns={start_col: "START_NODE", end_col: "END_NODE", length_col: "LENGTH"}
    )

    # node positions for nodes in this cluster
    sub_nodes = node_coords[node_coords[cluster_col] == cluster_id]
    node_pos = {
        int(row[node_col]): (float(row[xcol]), float(row[ycol]))
        for _, row in sub_nodes.iterrows()
    }

    return df_cluster, node_pos

# =====
# 3) Build Problem from df_cluster
# =====

```

```

def build_problem_from_df(df_cluster,
                        sim_duration,
                        bonus_per_car,
                        speed_mps):
    """
    df_cluster must have columns:
    ['START_NODE', 'END_NODE', 'LENGTH']
    """
    problem = Problem(sim_duration, bonus_per_car)

    # Map original node IDs -> intersection indices [0..N-1]
    all_nodes = sorted(set(df_cluster['START_NODE']).union(df_cluster['END_NODE']))
    node_id_to_index = {node_id: idx for idx, node_id in enumerate(all_nodes)}
    num_inters = len(all_nodes)

    problem.intersections = [Intersection(i) for i in range(num_inters)]

    streets = []
    adjacency = defaultdict(list) # start_idx -> List[Street]

    for uid, row in enumerate(df_cluster.itertuples()):
        start_node = row.START_NODE
        end_node = row.END_NODE
        length_m = float(row.LENGTH)

        start_idx = node_id_to_index[start_node]
        end_idx = node_id_to_index[end_node]

        st = Street(
            unique_id=uid,
            start=start_idx,
            end=end_idx,
            name=f"e{uid}",
            length_m=length_m,
            speed_mps=speed_mps,
        )
        streets.append(st)
        adjacency[start_idx].append(st)

    problem.streets = streets

    # fill incoming/outgoing
    for st in streets:
        problem.intersections[st.start].outgoing.append(st)
        problem.intersections[st.end].incoming.append(st)

    return problem, adjacency, node_id_to_index

# =====
# 4) Random car routes (simple paths)
# =====

def generate_random_car_paths(problem,
                             adjacency,
                             num_cars=1000,
                             nodes_per_path=30,

```

```

                                random_seed=42):
    rng = np.random.default_rng(random_seed)
    cars = []

    intersection_ids = list(range(len(problem.intersections)))
    attempts = 0
    max_attempts = num_cars * 10

    while len(cars) < num_cars and attempts < max_attempts:
        attempts += 1

        n_nodes = max(2, int(nodes_per_path)) # enforce ≥2
        start_inter = rng.choice(intersection_ids)

        path_streets = []
        current = start_inter
        visited_nodes = {current}

        for _ in range(n_nodes - 1):
            outgoing_all = adjacency.get(current, [])
            # only move to unvisited nodes -> simple path
            outgoing = [st for st in outgoing_all if st.end not in visited_nodes]
            if not outgoing:
                break
            st = rng.choice(outgoing)
            path_streets.append(st)
            current = st.end
            visited_nodes.add(current)

        if len(path_streets) < 2:
            continue

        cars.append(Car(unique_id=len(cars), streets=path_streets))

    problem.cars = cars
    return problem

# =====
# 5) Model 3: weighted fixed-time schedule
# =====

def build_weighted_solution(problem):
    """
    Model 3:
    - Count how many 'finishable' cars use each incoming street.
    - Allocate a short cycle at each intersection, with green
      durations proportional to that usage.
    """
    D = problem.duration
    solution = Solution(num_intersections=len(problem.intersections))

    street_weight = defaultdict(float)

    # 1) weight streets by cars that CAN finish within D
    for car in problem.cars:
        total_time = car.time_need_to_drive()

```

```

    if total_time > D:
        continue
    w = 1.0 # or w = 1 + (D - total_time)/D
    for i in range(len(car.streets) - 1): # ignore final link
        st = car.streets[i]
        street_weight[st.unique_id] += w

# 2) distribute green within each intersection
for inter in problem.intersections:
    si = solution.intersections[inter.id]
    incoming = inter.incoming
    if not incoming:
        continue

    weights = [street_weight[st.unique_id] for st in incoming]
    total_w = sum(weights)

    if total_w == 0:
        # no info -> give each 1 second
        for st in incoming:
            si.green_cycles.append(GreenLightCycle(street=st, duration=1))
        continue

    TOTAL_CYCLE = min(10, max(3, len(incoming))) # 3-10 seconds

    durations = []
    for w in weights:
        dur = max(1, int(round(TOTAL_CYCLE * w / total_w)))
        durations.append(dur)

    extra = sum(durations) - TOTAL_CYCLE
    while extra > 0 and any(d > 1 for d in durations):
        for idx, d in enumerate(durations):
            if extra == 0:
                break
            if d > 1:
                durations[idx] -= 1
                extra -= 1

    # order streets by weight (descending)
    order = sorted(range(len(incoming)), key=lambda idx: -weights[idx])
    for idx in order:
        st = incoming[idx]
        dur = durations[idx]
        si.green_cycles.append(GreenLightCycle(street=st, duration=dur))

return solution

def solution_to_light_schedule(solution):
    """
    Convert Solution -> {intersection_id: [street_id, street_id, ...]} cycle.
    """
    schedule = {}
    for si in solution.intersections:
        arr = []

```

```

        for cyc in si.green_cycles:
            arr.extend([cyc.street.unique_id] * cyc.duration)
        if arr:
            schedule[si.id] = arr
    return schedule

# =====
# 6) City simulation with metrics
# =====

def simulate_city_with_metrics(problem,
                               light_schedule,
                               index_to_xy=None,
                               record_snapshots=False,
                               max_time=None):
    """
    Discrete-time sim with FCFS queues.
    Returns (snapshots, metrics).
    """
    D = problem.duration
    T = D if max_time is None else min(D, max_time)
    bonus = problem.bonus_per_car

    # init car states + queues
    car_states = []
    queues = defaultdict(deque) # street_id -> deque of car_ids

    for car_id, car in enumerate(problem.cars):
        cs = VisCarState(car)
        first_street = car.streets[0]
        queues[first_street.unique_id].append(car_id)
        car_states.append(cs)

    # metrics
    street_wait_time = defaultdict(int)
    street_max_queue = defaultdict(int)
    inter_total_green = defaultdict(int)
    inter_wasted_green = defaultdict(int)

    snapshots = [] if record_snapshots and index_to_xy is not None else None

    for t in range(T + 1):
        # 1) move cars that are on an edge
        for car_id, cs in enumerate(car_states):
            if cs.state != "moving":
                continue

            cs.time_on_edge += 1
            edge = cs.car.streets[cs.moving_edge_idx]

            if cs.time_on_edge >= edge.travel_time:
                cs.idx = cs.moving_edge_idx
                cs.moving_edge_idx = None
                cs.time_on_edge = 0

            if cs.idx == len(cs.car.streets) - 1:

```

```

        cs.state = "finished"
        cs.finish_time = t
    else:
        cs.state = "queue"
        cur_street = cs.car.streets[cs.idx]
        queues[cur_street.unique_id].append(car_id)

# 2) for each intersection, serve at most 1 car
for inter in problem.intersections:
    inter_id = inter.id
    if inter_id not in light_schedule:
        continue
    cycle = light_schedule[inter_id]
    if not cycle:
        continue

    green_street_id = cycle[t % len(cycle)]
    inter_total_green[inter_id] += 1

    if queues[green_street_id]:
        car_id = queues[green_street_id].popleft()
        cs = car_states[car_id]
        if cs.state != "queue":
            continue
        if cs.idx >= len(cs.car.streets) - 1:
            continue

        cs.state = "moving"
        cs.moving_edge_idx = cs.idx + 1
        cs.time_on_edge = 0
    else:
        inter_wasted_green[inter_id] += 1

# 3) queue metrics
for st_id, q in queues.items():
    q_len = len(q)
    street_wait_time[st_id] += q_len
    if q_len > street_max_queue[st_id]:
        street_max_queue[st_id] = q_len

# 4) optional snapshots for animation
if snapshots is not None:
    xs, ys = [], []
    for cs in car_states:
        if cs.state == "finished":
            last_st = cs.car.streets[-1]
            x, y = index_to_xy[last_st.end]
            xs.append(x); ys.append(y)
        elif cs.state == "queue":
            st = cs.car.streets[cs.idx]
            x, y = index_to_xy[st.end]
            xs.append(x); ys.append(y)
        elif cs.state == "moving":
            edge = cs.car.streets[cs.moving_edge_idx]
            x0, y0 = index_to_xy[edge.start]
            x1, y1 = index_to_xy[edge.end]

```

```

        travel_time = max(1, edge.travel_time)
        frac = cs.time_on_edge / travel_time
        x = x0 + frac * (x1 - x0)
        y = y0 + frac * (y1 - y0)
        xs.append(x); ys.append(y)
    snapshots.append((np.array(xs), np.array(ys)))

# final scoring
finished_cars = 0
total_time_saved = 0
total_score = 0

for cs in car_states:
    if cs.finish_time is not None and cs.finish_time <= D:
        finished_cars += 1
        time_saved = D - cs.finish_time
        total_time_saved += time_saved
        total_score += bonus + time_saved

metrics = {
    "score": total_score,
    "finished_cars": finished_cars,
    "total_time_saved": total_time_saved,
    "street_wait_time": street_wait_time,
    "street_max_queue": street_max_queue,
    "intersection_total_green": inter_total_green,
    "intersection_wasted_green": inter_wasted_green,
}

return snapshots, metrics

# =====
# 7) Heatmap + hotspot summaries
# =====

def plot_street_congestion_heatmap(problem,
                                   metrics,
                                   index_to_xy,
                                   figsize=(8, 8),
                                   cmap_name="Reds",
                                   title="Street-level congestion heatmap"):
    street_wait = metrics["street_wait_time"]
    scores = np.array(
        [street_wait.get(st.unique_id, 0) for st in problem.streets],
        dtype=float
    )
    max_score = scores.max() if len(scores) > 0 else 0.0
    if max_score == 0:
        max_score = 1.0

    norm = Normalize(vmin=0, vmax=max_score)
    cmap = cm.get_cmap(cmap_name)

    fig, ax = plt.subplots(figsize=figsize)
    for st, score in zip(problem.streets, scores):
        x0, y0 = index_to_xy[st.start]

```

```

        x1, y1 = index_to_xy[st.end]
        c = cmap(norm(score))
        lw = 0.3 + 3.0 * (score / max_score)
        ax.plot([x0, x1], [y0, y1],
                color=c,
                linewidth=lw,
                alpha=0.2 + 0.6 * (score / max_score))

    ax.set_aspect("equal", adjustable="box")
    ax.set_title(title)

    all_x = [xy[0] for xy in index_to_xy.values()]
    all_y = [xy[1] for xy in index_to_xy.values()]
    ax.set_xlim(min(all_x) - 50, max(all_x) + 50)
    ax.set_ylim(min(all_y) - 50, max(all_y) + 50)

    sm = cm.ScalarMappable(norm=norm, cmap=cmap)
    sm.set_array([])
    cbar = fig.colorbar(sm, ax=ax, fraction=0.046, pad=0.04)
    cbar.set_label("Total waiting time (car-seconds)")

    plt.show()

def summarize_street_hotspots(problem, metrics, top_k=15):
    street_wait = metrics["street_wait_time"]
    street_maxq = metrics["street_max_queue"]

    rows = []
    for st in problem.streets:
        rows.append({
            "street_id": st.unique_id,
            "start_inter": st.start,
            "end_inter": st.end,
            "total_wait_time": street_wait.get(st.unique_id, 0),
            "max_queue": street_maxq.get(st.unique_id, 0),
        })
    df = pd.DataFrame(rows)
    df = df.sort_values("total_wait_time", ascending=False).head(top_k)
    return df.reset_index(drop=True)

def summarize_intersection_hotspots(metrics, top_k=10):
    tot_green = metrics["intersection_total_green"]
    wasted = metrics["intersection_wasted_green"]

    rows = []
    for i in tot_green.keys():
        g = tot_green[i]
        w = wasted.get(i, 0)
        wasted_ratio = w / g if g > 0 else 0.0
        rows.append({
            "intersection_id": i,
            "total_green": g,
            "wasted_green": w,
            "wasted_ratio": wasted_ratio,

```

```

    })
    df = pd.DataFrame(rows)
    df = df.sort_values("wasted_ratio", ascending=False).head(top_k)
    return df.reset_index(drop=True)

# =====
# 8) MAIN WRAPPER: run everything for a cluster
# =====

def run_cluster_simulation(
    edges_df,
    node_coords,
    cluster_id=2,
    speed_mps=15.0,
    sim_duration=3600,
    bonus_per_car=1000,
    num_cars=20000,
    nodes_per_path=30,
    random_seed=42,
    top_k_streets=15,
    top_k_intersections=10,
    make_heatmap=True,
    heatmap_cmap="Reds",
    record_snapshots=True,
):
    """
    One-shot pipeline for a chosen cluster:

    1) Filter network to that cluster (nodes + edges)
    2) Build Problem object
    3) Generate random car routes (simple paths)
    4) Build Model 3 weighted signal schedule
    5) Simulate city, compute metrics
    6) Plot congestion heatmap (optional)
    7) Return metrics + hotspot tables

    Assumes:
    - edges_df has columns: START_NODE, END_NODE, LENGTH
    - node_coords has: node, XCoord, YCoord, cluster
    """
    # 1) Cluster subgraph
    df_cluster, node_pos = build_cluster_subgraph(
        edges_df,
        node_coords,
        cluster_id=cluster_id,
        node_col="node",
        cluster_col="cluster",
        start_col="START_NODE",
        end_col="END_NODE",
        length_col="LENGTH",
        xcol="XCoord",
        ycol="YCoord",
    )

    print(f"[Cluster {cluster_id}] Edges: {len(df_cluster)}, Nodes: {len(node_pos)}")

```

```

# 2) build Problem
problem, adjacency, node_id_to_index = build_problem_from_df(
    df_cluster,
    sim_duration,
    bonus_per_car,
    speed_mps,
)

# map intersection index -> (x, y)
index_to_xy = {
    idx: node_pos[node_id]
    for node_id, idx in node_id_to_index.items()
    if node_id in node_pos
}

# 3) random car routes
problem = generate_random_car_paths(
    problem,
    adjacency,
    num_cars=num_cars,
    nodes_per_path=nodes_per_path,
    random_seed=random_seed,
)

print(f"[Cluster {cluster_id}] Cars generated: {len(problem.cars)}")

# 4) Model 3 schedule
solution = build_weighted_solution(problem)
schedule = solution_to_light_schedule(solution)

# 5) simulate
snapshots, metrics = simulate_city_with_metrics(
    problem,
    schedule,
    index_to_xy=index_to_xy,
    record_snapshots=record_snapshots,    # set True if you want animation La
    max_time=sim_duration,
)

finished = metrics["finished_cars"]
total = len(problem.cars)
avg_save = (
    metrics["total_time_saved"] / finished if finished > 0 else 0.0
)

print(f"Model 3 score: {metrics['score']}")
print(f"Cars finished within {sim_duration}s: {finished} / {total}")
print(f"Avg time saved per finished car: {avg_save:.1f} s")

# 6) heatmap (optional)
if make_heatmap:
    plot_street_congestion_heatmap(
        problem,
        metrics,
        index_to_xy,
        title=f"Cluster {cluster_id} - Model 3 congestion heatmap",

```

```

        cmap_name=heatmap_cmap,
    )

# 7) hotspot tables
street_hotspots = summarize_street_hotspots(
    problem, metrics, top_k=top_k_streets
)
inter_hotspots = summarize_intersection_hotspots(
    metrics, top_k=top_k_intersections
)

results = {
    "cluster_id": cluster_id,
    "problem": problem,
    "solution": solution,
    "schedule": schedule,
    "metrics": metrics,
    "street_hotspots": street_hotspots,
    "intersection_hotspots": inter_hotspots,
    "index_to_xy": index_to_xy,
    "snapshots": snapshots,    # None unless you switch record_snapshots=True
}

return results

from matplotlib.animation import FuncAnimation
from IPython.display import HTML
import numpy as np
import matplotlib.pyplot as plt

def animate_cluster_traffic(results,
                             frame_step=100,
                             interval=500,
                             figsize=(8, 8),
                             title_prefix="Traffic simulation"):
    """
    Build a Matplotlib animation for a given cluster's simulation results.

    Parameters
    -----
    results : dict
        Output from run_cluster_simulation(...) containing at least:
        - "problem": Problem object
        - "index_to_xy": dict[int -> (x,y)]
        - "snapshots": list of (xs, ys) arrays, one per second
    frame_step : int
        Show frames at t = 0, frame_step, 2*frame_step, ... (e.g. 100 s).
    interval : int
        Delay between frames in milliseconds for the animation.
    figsize : tuple
        Figure size for the plot.
    title_prefix : str
        Prefix string for the plot title.

    Returns
    -----

```


HTML

An HTML object you can display in a Jupyter notebook.

"""

```
problem = results["problem"]
index_to_xy = results["index_to_xy"]
snapshots = results["snapshots"]
```

```
if snapshots is None or len(snapshots) == 0:
    raise ValueError(
        "No snapshots found. "
        "Re-run run_cluster_simulation with record_snapshots=True."
    )
```

Build road segments

```
road_segments = []
for st in problem.streets:
    x0, y0 = index_to_xy[st.start]
    x1, y1 = index_to_xy[st.end]
    road_segments.append(((x0, x1), (y0, y1)))
```

Figure + static background

```
fig, ax = plt.subplots(figsize=figsize)
for xs, ys in road_segments:
    ax.plot(xs, ys, linewidth=0.5, alpha=0.3)
```

Initial positions at t = 0

```
xs0, ys0 = snapshots[0]
scatter = ax.scatter(xs0, ys0, s=5)
ax.set_aspect("equal", adjustable="box")
```

Axis limits from node coordinates

```
all_x = [xy[0] for xy in index_to_xy.values()]
all_y = [xy[1] for xy in index_to_xy.values()]
ax.set_xlim(min(all_x) - 50, max(all_x) + 50)
ax.set_ylim(min(all_y) - 50, max(all_y) + 50)
```

Decide which time steps to show

```
max_t = min(problem.duration, len(snapshots) - 1)
frame_times = list(range(0, max_t + 1, frame_step))
```

```
def update(frame_idx):
    t = frame_times[frame_idx]
    xs, ys = snapshots[t]
    scatter.set_offsets(np.c_[xs, ys])
    ax.set_title(f"{title_prefix} (t = {t} s)")
    return scatter,
```

```
anim = FuncAnimation(
    fig,
    update,
    frames=len(frame_times),
    interval=interval,
    blit=True
)
```

```
return HTML(anim.to_jshtml())
```

In []: from IPython.display import display, HTML

```
def run_and_show_all_clusters(edges_df,
                              node_coords,
                              cluster_ids,
                              speed_mps=15.0,
                              sim_duration=3600,
                              bonus_per_car=1000,
                              num_cars=20000,
                              nodes_per_path=30,
                              random_seed=42,
                              top_k_streets=20,
                              top_k_intersections=15,
                              frame_step=100,
                              anim_interval=500):
    """
    Run the city-traffic simulation for a list of clusters and
    show metrics, congestion heatmap, and animation one after another.

    Parameters
    -----
    cluster_ids : iterable of int
        e.g. range(0, 5)
    Other parameters: see your earlier run_cluster_simulation signature.
    """

    all_results = {}

    for k in cluster_ids:
        print("\n" + "=" * 60)
        print(f"Cluster {k}: simulation results")
        print("=" * 60)

        # --- 1) Run simulation for this cluster ---
        res = run_cluster_simulation(
            edges_df=edges_df,
            node_coords=node_coords,
            cluster_id=k,
            speed_mps=speed_mps,
            sim_duration=sim_duration,
            bonus_per_car=bonus_per_car,
            num_cars=num_cars,
            nodes_per_path=nodes_per_path,
            random_seed=random_seed,
            top_k_streets=top_k_streets,
            top_k_intersections=top_k_intersections,
            make_heatmap=False,  # we'll call heatmap function explicitly
            record_snapshots=True  # IMPORTANT: needed for animation
        )
        all_results[k] = res

    problem = res["problem"]
    index_to_xy = res["index_to_xy"]
    metrics = res["metrics"]
    snapshots = res["snapshots"]
```

```

# --- 2) Print core metrics ---
finished = metrics["finished_cars"]
total_cars = len(problem.cars)
print(f"Score: {metrics['score']}")
print(f"Cars finished within {sim_duration} s: {finished} / {total_cars}")
if finished > 0:
    avg_saved = metrics["total_time_saved"] / finished
else:
    avg_saved = 0.0
print(f"Total time saved: {metrics['total_time_saved']} s")
print(f"Average time saved per finished car: {avg_saved:.2f} s")

# --- 3) Show congestion heatmap for this cluster ---
plot_street_congestion_heatmap(
    problem,
    metrics,
    index_to_xy,
    title=f"Cluster {k}: street-level congestion heatmap"
)

# --- 4) Show textual hotspot summaries ---
print(f"\nTop {top_k_streets} congested streets (cluster {k}):")
display(summarize_street_hotspots(problem, metrics, top_k=top_k_streets))

# --- 5) Show animation for this cluster ---
print(f"\nAnimation for cluster {k}:")
anim_html = animate_cluster_traffic(
    res,
    frame_step=frame_step,          # e.g. 0,100,200,... seconds
    interval=anim_interval,         # ms between frames
    title_prefix=f"Cluster {k} traffic"
)
display(anim_html)

return all_results

```

```

In [ ]: all_results = run_and_show_all_clusters(
    edges_df=edges_df,
    node_coords=node_coords,
    cluster_ids=range(0, 5),      # clusters 0..4
    speed_mps=15.0,
    sim_duration=3600,
    bonus_per_car=1000,
    num_cars=20000,
    nodes_per_path=30,
    random_seed=42,
    top_k_streets=20,
    top_k_intersections=15,
    frame_step=100,              # show t=0,100,200,...,3600
    anim_interval=500            # 0.5s per frame
)

```

```

=====
Cluster 0: simulation results
=====
[Cluster 0] Edges: 266220, Nodes: 97871
[Cluster 0] Cars generated: 20000
Model 3 score: 89940327
Cars finished within 3600s: 20000 / 20000
Avg time saved per finished car: 3497.0 s
Score: 89940327
Cars finished within 3600 s: 20000 / 20000
Total time saved: 69940327 s
Average time saved per finished car: 3497.02 s

/var/folders/zr/hq_q97d52l1ck8p_4myglv4r0000gn/T/ipykernel_17832/1612399623.py:461:
MatplotlibDeprecationWarning: The get_cmap function was deprecated in Matplotlib 3.7
and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colo
rmaps.get_cmap()`` or ``pyplot.get_cmap()`` instead.
cmap = cm.get_cmap(cmap_name)


```



Top 20 congested streets (cluster 0):

	street_id	start_inter	end_inter	total_wait_time	max_queue
0	166316	60432	60252	29	3
1	306	130	133	22	2
2	133756	48837	48938	21	2
3	256074	93711	93729	21	2
4	205399	74408	74388	21	2
5	93564	34628	34613	19	2
6	181017	65624	65614	19	2
7	192012	69530	69799	18	2
8	65490	24750	24738	18	2
9	139822	50969	50611	17	1
10	191529	69363	69111	17	2
11	102210	37659	37691	17	2
12	179977	65253	65251	17	2
13	235486	85747	85821	17	1
14	202735	73445	73570	17	2
15	181343	65741	65543	17	1
16	207466	75151	75152	17	2
17	66098	24963	24952	17	2
18	94709	35029	34795	17	1
19	152742	55558	55394	16	2

Animation for cluster 0:





```

=====
Cluster 1: simulation results
=====
[Cluster 1] Edges: 13302, Nodes: 5029
[Cluster 1] Cars generated: 20000
Model 3 score: 84307013
Cars finished within 3600s: 19953 / 20000
Avg time saved per finished car: 3225.3 s
Score: 84307013
Cars finished within 3600 s: 19953 / 20000
Total time saved: 64354013 s
Average time saved per finished car: 3225.28 s

```


```
/var/folders/zr/hq_q97d52l1ck8p_4myglv4r0000gn/T/ipykernel_17832/1612399623.py:461:
MatplotlibDeprecationWarning: The get_cmap function was deprecated in Matplotlib 3.7
and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get_cmap()`` or ``pyplot.get_cmap()`` instead.
cmap = cm.get_cmap(cmap_name)
```



Top 20 congested streets (cluster 1):

	street_id	start_inter	end_inter	total_wait_time	max_queue
0	4917	1854	1938	875	10
1	5390	2013	1993	766	10
2	5339	1997	1961	716	9
3	11277	4200	4155	609	9
4	7255	2652	2660	604	8
5	6823	2510	2530	547	8
6	3034	1193	1195	525	6
7	5388	2012	2000	513	7
8	5229	1963	1931	497	7
9	6921	2544	2565	491	7
10	2796	1116	1121	487	7
11	5111	1923	1938	481	8
12	2896	1148	1154	459	7
13	8378	3061	3083	458	8
14	7216	2640	2616	424	8
15	4842	1832	1817	411	7
16	3095	1213	1189	401	6
17	11369	4234	4236	393	9
18	6095	2250	2174	383	7
19	2919	1156	1121	368	6

Animation for cluster 1:



```



=====
Cluster 2: simulation results
=====
[Cluster 2] Edges: 65770, Nodes: 26870
[Cluster 2] Cars generated: 20000
Model 3 score: 89465582
Cars finished within 3600s: 20000 / 20000
Avg time saved per finished car: 3473.3 s
Score: 89465582
Cars finished within 3600 s: 20000 / 20000
Total time saved: 69465582 s
Average time saved per finished car: 3473.28 s

```

```

/var/folders/zr/hq_q97d52l1ck8p_4myglv4r0000gn/T/ipykernel_17832/1612399623.py:461:
MatplotlibDeprecationWarning: The get_cmap function was deprecated in Matplotlib 3.7
and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get_cmap()`` or ``pyplot.get_cmap()`` instead.
cmap = cm.get_cmap(cmap_name)


```



Top 20 congested streets (cluster 2):

	street_id	start_inter	end_inter	total_wait_time	max_queue
0	64620	26329	26325	60	5
1	16237	6817	6810	45	5
2	51764	21013	20459	41	4
3	42585	17390	17287	40	3
4	9227	3924	3897	35	5
5	17925	7530	7529	35	5
6	41788	17089	17042	34	2
7	32968	13695	13856	33	2
8	42033	17181	17068	33	3
9	4809	2045	2008	32	1
10	50757	20612	20588	32	4
11	30782	12785	12698	32	4
12	5451	2307	2314	31	2
13	39410	16213	16212	30	4
14	51143	20764	20747	30	3
15	21199	8869	8868	30	4
16	40236	16511	16162	30	2
17	57269	23266	23267	30	4
18	6801	2868	2862	30	4
19	53541	21727	21726	30	4

Animation for cluster 2:



```



=====
Cluster 3: simulation results
=====
[Cluster 3] Edges: 10612, Nodes: 4504
[Cluster 3] Cars generated: 20000
Model 3 score: 84117111
Cars finished within 3600s: 19703 / 20000
Avg time saved per finished car: 3269.3 s
Score: 84117111
Cars finished within 3600 s: 19703 / 20000
Total time saved: 64414111 s
Average time saved per finished car: 3269.25 s

```

```

/var/folders/zr/hq_q97d52l1ck8p_4myglv4r0000gn/T/ipykernel_17832/1612399623.py:461:
MatplotlibDeprecationWarning: The get_cmap function was deprecated in Matplotlib 3.7
and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get_cmap()`` or ``pyplot.get_cmap()`` instead.
cmap = cm.get_cmap(cmap_name)


```



Top 20 congested streets (cluster 3):

	street_id	start_inter	end_inter	total_wait_time	max_queue
0	2554	1143	1145	432	8
1	6580	2874	2887	383	7
2	8108	3500	3555	380	7
3	3127	1381	1384	339	7
4	40	19	20	301	14
5	4049	1795	1785	288	6
6	782	356	357	257	8
7	2256	1010	1006	233	6
8	9924	4248	4239	228	4
9	6682	2916	2912	223	7
10	6940	3015	3016	222	12
11	9646	4143	4142	222	12
12	6797	2959	2958	222	12
13	10422	4429	4430	220	4
14	2460	1102	1092	219	5
15	141	65	66	210	10
16	2123	953	949	210	12
17	4034	1786	1785	210	10
18	7155	3106	3092	210	10
19	1981	886	890	209	7

Animation for cluster 3:




```

=====
Cluster 4: simulation results
=====
[Cluster 4] Edges: 45378, Nodes: 17673
[Cluster 4] Cars generated: 20000
Model 3 score: 88318746
Cars finished within 3600s: 19975 / 20000
Avg time saved per finished car: 3421.5 s
Score: 88318746
Cars finished within 3600 s: 19975 / 20000
Total time saved: 68343746 s
Average time saved per finished car: 3421.46 s
  
```

```


/var/folders/zr/hq_q97d52l1ck8p_4myglv4r0000gn/T/ipykernel_17832/1612399623.py:461:
MatplotlibDeprecationWarning: The get_cmap function was deprecated in Matplotlib 3.7
and will be removed in 3.11. Use ``matplotlib.colormaps[name]`` or ``matplotlib.colormaps.get_cmap()`` or ``pyplot.get_cmap()`` instead.
cmap = cm.get_cmap(cmap_name)


```



	street_id	start_inter	end_inter	total_wait_time	max_queue
0	23006	9190	9200	76	3
1	28319	11135	11136	72	6
2	35538	13854	13859	68	3
3	37362	14560	14559	61	3
4	9200	3806	3807	60	5
5	24908	9882	9887	60	2
6	36775	14329	14330	60	5
7	24650	9790	9780	58	2
8	24265	9648	9715	54	2
9	21701	8729	8701	51	3
10	41728	16225	16218	51	6
11	9026	3735	3716	50	5
12	4501	1864	1865	49	4
13	34358	13421	13459	48	2
14	24441	9716	9722	48	2
15	34036	13312	13281	47	2
16	16358	6737	6587	46	3
17	20913	8442	8535	45	3
18	30649	12026	12004	45	5
19	31309	12272	12148	45	5

Animation for cluster 4:





SIMULATION

```
In [1]: import random
import collections
import copy
import math
import matplotlib.pyplot as plt

# =====
# 1. SIMULATION ENGINE (Fixed Metrics)
# =====
class SimulationEnv:
    def __init__(self, duration, bonus):
        self.duration = duration
        self.bonus = bonus
        self.current_time = 0
        self.score = 0

        self.intersections = set()
```

```
self.streets = {}
self.incoming = collections.defaultdict(list)

self.queues = collections.defaultdict(collections.deque)
self.schedules = {}
self.schedule_counters = {}

self.cars = {}
self.finished_cars = set()
self.total_wait_time = 0 # Total car-seconds of delay

def load_scenario(self, streets_data, cars_data):
    for name, start, end, length in streets_data:
        self.streets[name] = {'start': start, 'end': end, 'length': length}
        self.intersections.add(start)
        self.intersections.add(end)
        self.incoming[end].append(name)
        self.queues[name] = collections.deque()

    for cid, path in cars_data.items():
        first_street = path[0]
        self.cars[cid] = {
            'path': path, 'current_street_idx': 0,
            'state': 'queued', 'remaining_travel_time': 0
        }
        self.queues[first_street].append(cid)

    for i in self.intersections:
        self.schedule_counters[i] = {'idx': 0, 'frame': 0}

def set_schedules(self, schedules):
    self.schedules = schedules
    for i in self.intersections:
        if i in schedules and schedules[i]:
            self.schedule_counters[i] = {'idx': 0, 'frame': 0}
        else:
            self.schedule_counters[i] = None

def step(self):
    # --- METRIC FIX: Accumulate Wait Time Every Second ---
    # If a car is in a queue, it is waiting. Add 1s per car.
    for q in self.queues.values():
        self.total_wait_time += len(q)

    # 1. Update Lights
    current_green_streets = set()
    for i, sched in self.schedules.items():
        if not sched: continue
        counter = self.schedule_counters[i]
        if not counter: continue

        street_name, duration = sched[counter['idx']]
        current_green_streets.add(street_name)

        counter['frame'] += 1
        if counter['frame'] >= duration:
```

```

        counter['idx'] = (counter['idx'] + 1) % len(sched)
        counter['frame'] = 0

# 2. Move Cars
moves_this_step = collections.defaultdict(int)

# Process Queues
for street_name, q in self.queues.items():
    if not q: continue

    if street_name in current_green_streets:
        if moves_this_step[street_name] < 1: # Capacity: 1 car/sec
            car_id = q[0]
            car = self.cars[car_id]

            if car['current_street_idx'] == len(car['path']) - 1:
                # FINISHED
                q.popleft()
                self.score += self.bonus + (self.duration - self.current_time)
                self.finished_cars.add(car_id)
            else:
                # CROSS INTERSECTION
                next_s = car['path'][car['current_street_idx'] + 1]
                q.popleft()
                car['current_street_idx'] += 1
                car['state'] = 'moving'
                car['remaining_travel_time'] = self.streets[next_s]['length']

            moves_this_step[street_name] += 1

# Process Moving Cars
for cid, car in self.cars.items():
    if cid in self.finished_cars: continue

    if car['state'] == 'moving':
        car['remaining_travel_time'] -= 1
        if car['remaining_travel_time'] <= 0:
            # Arrive at next queue
            curr = car['path'][car['current_street_idx']]
            self.queues[curr].append(cid)
            car['state'] = 'queued'

    self.current_time += 1

def run(self):
    for _ in range(self.duration):
        self.step()
    return self.score, self.total_wait_time, len(self.finished_cars)

# =====
# 2. SCENARIO GENERATOR (Organic City)
# =====
def create_irregular_city_scenario(num_nodes=60, radius=0.25, num_cars=1000):
    """ Generates a Random Geometric Graph (Organic City). """
    # Nodes
    nodes = {}

```

```

for i in range(num_nodes):
    nodes[i] = (random.random(), random.random())

# Streets
streets = []
adj = collections.defaultdict(list)
for i in range(num_nodes):
    for j in range(i + 1, num_nodes):
        x1, y1 = nodes[i]
        x2, y2 = nodes[j]
        dist = math.sqrt((x1-x2)**2 + (y1-y2)**2)
        if dist <= radius:
            length = max(5, int(dist * 150)) # Longer streets for realism
            streets.append((f"s_{i}_{j}", i, j, length))
            streets.append((f"s_{j}_{i}", j, i, length))
            adj[i].append(j)
            adj[j].append(i)

# Prune to Largest Component
visited = set()
largest_component = []
for i in range(num_nodes):
    if i not in visited:
        component = []
        stack = [i]
        while stack:
            node = stack.pop()
            if node not in visited:
                visited.add(node)
                component.append(node)
                stack.extend(adj[node])
        if len(component) > len(largest_component):
            largest_component = component

valid_nodes = set(largest_component)
final_streets = [s for s in streets if s[1] in valid_nodes and s[2] in valid_nodes]
final_nodes = {k: v for k, v in nodes.items() if k in valid_nodes}

# Traffic (Hub-Based)
hubs = random.sample(largest_component, k=max(3, int(len(largest_component)*0.1)))
cars = {}
street_map = {(s[1], s[2]): s[0] for s in final_streets}

def get_path(start, end):
    q = collections.deque([(start, [])])
    seen = {start}
    while q:
        curr, path_nodes = q.popleft()
        if curr == end: return path_nodes + [end]
        for nxt in adj[curr]:
            if nxt in valid_nodes and nxt not in seen:
                seen.add(nxt)
                q.append((nxt, path_nodes + [curr]))
    return None

for i in range(num_cars):

```

```

# 80% Traffic to/from Hubs
if random.random() < 0.8:
    start = random.choice(largest_component)
    end = random.choice(hubs)
else:
    start = random.choice(largest_component)
    end = random.choice(largest_component)

if start == end: continue
path_nodes = get_path(start, end)
if path_nodes and len(path_nodes) > 1:
    street_path = []
    for k in range(len(path_nodes)-1):
        u, v = path_nodes[k], path_nodes[k+1]
        if (u,v) in street_map:
            street_path.append(street_map[(u,v)])
    if street_path:
        cars[i] = street_path

return final_streets, cars, final_nodes

# =====
# 3. MODELS
# =====
def model_1_greedy(streets, cars, intersections):
    schedules = collections.defaultdict(list)
    incoming = collections.defaultdict(list)
    for name, _, end, _ in streets: incoming[end].append(name)
    for i in intersections:
        if i in incoming:
            for s in incoming[i]: schedules[i].append((s, 2)) # 2s Green
    return schedules

def model_2_demand(streets, cars, intersections):
    street_demand = collections.defaultdict(int)
    for path in cars.values():
        for s in path: street_demand[s] += 1
    schedules = collections.defaultdict(list)
    incoming = collections.defaultdict(list)
    for name, _, end, _ in streets: incoming[end].append(name)

    for i in intersections:
        if i not in incoming: continue
        inc = incoming[i]
        total = sum(street_demand[s] for s in inc)
        for s in inc:
            dur = max(1, int((street_demand[s]/total)*5)) if total > 0 else 1
            schedules[i].append((s, dur))
    return schedules

def model_3_local_search(streets, cars, intersections, env_params):
    base_schedule = model_2_demand(streets, cars, intersections)
    best_score = -1
    best_schedule = copy.deepcopy(base_schedule)
    current = copy.deepcopy(base_schedule)

```

```

# 30 Iterations
for _ in range(30):
    cand = copy.deepcopy(current)
    ilist = list(intersections)
    # Mutate 5 intersections
    for _ in range(5):
        if not ilist: break
        ii = random.choice(ilist)
        if ii in cand and cand[ii]:
            idx = random.randint(0, len(cand[ii])-1)
            s, d = cand[ii][idx]
            cand[ii][idx] = (s, max(1, min(8, d + random.choice([-1, 1]))))

    env = SimulationEnv(*env_params)
    env.load_scenario(streets, cars)
    env.set_schedules(cand)
    score, _, _ = env.run()

    if score > best_score:
        best_score = score
        best_schedule = cand
        current = cand
    return best_schedule

def model_4_time_ordered(streets, cars, intersections):
    L = {name: l for name, s, e, l in streets}
    arrivals = collections.defaultdict(list)
    for c in cars.values():
        t = 0
        for s in c:
            arrivals[s].append(t)
            t += L.get(s, 10)

    schedules = collections.defaultdict(list)
    incoming = collections.defaultdict(list)
    for name, _, end, _ in streets: incoming[end].append(name)

    for i in intersections:
        inc = incoming[i]
        stats = []
        for s in inc:
            avg = sum(arrivals[s])/len(arrivals[s]) if arrivals[s] else 9999
            stats.append((s, avg))
        stats.sort(key=lambda x: x[1])

        for s, _ in stats:
            schedules[i].append((s, 2))
    return schedules

# =====
# 4. VISUALIZATION
# =====
def visualize_city(streets, nodes, title="City Map"):
    plt.figure(figsize=(8, 8))
    for name, u, v, length in streets:
        if u in nodes and v in nodes:

```

```

        x1, y1 = nodes[u]
        x2, y2 = nodes[v]
        plt.plot([x1, x2], [y1, y2], 'gray', alpha=0.5, linewidth=1, zorder=1)
    xs = [pos[0] for pos in nodes.values()]
    ys = [pos[1] for pos in nodes.values()]
    plt.scatter(xs, ys, s=20, c='blue', zorder=2)
    plt.title(title)
    plt.axis('off')
    plt.tight_layout()
    plt.show()

# =====
# 5. EXECUTION
# =====
def run_real_world_test():
    random.seed(101)

    print("Generating 'Organic City' Map...")
    # Increased duration to 1500s so cars can actually finish
    sim_duration = 1500
    bonus_pts = 500

    streets, cars, nodes = create_irregular_city_scenario(num_nodes=80, radius=0.20)

    print("Visualizing Map...")
    visualize_city(streets, nodes, title="Generated Organic City (80 Intersections)")

    intersections = set()
    for _, s, e, _ in streets:
        intersections.add(s)
        intersections.add(e)

    models = {
        "Model 1: Greedy": model_1_greedy,
        "Model 2: Demand Weighted": model_2_demand,
        "Model 3: Local Search": lambda s,c,i: model_3_local_search(s,c,i, (sim_dur
        "Model 4: Time-Ordered": model_4_time_ordered
    }

    print(f"\n{'Model Name':<25} | {'Score':<10} | {'Avg Wait(s)':<12} | {'Complete
    print("-" * 65)

    for name, func in models.items():
        sched = func(streets, cars, intersections)

        env = SimulationEnv(sim_duration, bonus_pts)
        env.load_scenario(streets, cars)
        env.set_schedules(sched)
        score, total_wait, finished = env.run()

        avg_wait = total_wait / len(cars)
        comp_rate = (finished / len(cars)) * 100

        print(f"{'name':<25} | {'score':<10} | {'avg_wait':<12.1f} | {'comp_rate':.1f}%")

```


```

if __name__ == "__main__":
    run_real_world_test()

```

Generating 'Organic City' Map...
Visualizing Map...

Generated Organic City (80 Intersections)



Model Name	Score	Avg Wait(s)	Completed
Model 1: Greedy	1688763	226.8	100.0%
Model 2: Demand Weighted	1723067	192.0	100.0%
Model 3: Local Search	1723399	191.6	100.0%
Model 4: Time-Ordered	1686038	229.5	100.0%