



SR UNIVERSITY

Campus Warangal

Program: II - B. Tech (CS& AI) Batch: 16

Name: M.SAI CHARAN

Reg. No:2503A52467

Department: Computer Science and AI Semester: I

AI Assisted Coding-Assignment

Date: 22-09-2026

1. Question

– AI-Assisted Bubble Sort Analysis

Prompt

“Explain Bubble Sort step by step for the given list. Identify opportunities to reduce unnecessary comparisons. Do not write the complete program yet.”

Code : numbers = [64, 34, 25, 12, 22, 11, 90]

```
def bubble_sort(values):
```

```
    """Sort values with Bubble Sort and count comparisons and swaps."""
```

```
    result = values.copy()
```

```
    comparisons = 0
```

```
    swaps = 0
```

```
    for pass_number in range(len(result) - 1):
```

```
        for index in range(len(result) - 1 - pass_number):
```

```
            comparisons += 1
```

```
            if result[index] > result[index + 1]:
```

```
                result[index], result[index + 1] = result[index + 1], result[index]
```

```
                swaps += 1
```

```
return result, comparisons, swaps
```

```
def bubble_sort_early_exit(values):
```

```
    """Sort values and stop when a complete pass makes no swaps."""
```

```
    result = values.copy()
```

```
    comparisons = 0
```

```
    swaps = 0
```

```
    for pass_number in range(len(result) - 1):
```

```
        swapped = False
```

```
        for index in range(len(result) - 1 - pass_number):
```

```
            comparisons += 1
```

```
            if result[index] > result[index + 1]:
```

```
                result[index], result[index + 1] = result[index + 1], result[index]
```

```
                swaps += 1
```

```
                swapped = True
```

```
        if not swapped:
```

```
            break
```

```
    return result, comparisons, swaps
```

```
def show_one_pass(values):
```

```
    """Display the comparisons and swaps from the first complete pass."""
```

```
    result = values.copy()
```

```
    actions = []
```

```
    for index in range(len(result) - 1):
```

```

    left = result[index]
    right = result[index + 1]
    if left > right:
#         result[index], result[index + 1] = right, left
#         actions.append(f"swap {left} and {right} -> {result}")
#     else:
#         actions.append(f"keep {left} and {right} -> {result}")

# print("One complete Bubble Sort pass:")
# for action in actions:
#     print(f" {action}")
# print(f" Result after pass: {result}")

# def compare_versions(test_lists):
#     for test_list in test_lists:
#         original = bubble_sort(test_list)
#         improved = bubble_sort_early_exit(test_list)
#         print(f"\nInput: {test_list}")
#         print(f"Original: {original[0]}, comparisons={original[1]}, swaps={original[2]}")
#         print(f"Early exit: {improved[0]}, comparisons={improved[1]},
swaps={improved[2]}")

# if __name__ == "__main__":
#     test_lists = [
#         numbers,
#         [1, 2, 3, 4, 5],
#         [5, 1, 4, 2, 8],
#     ]

```

```
# show_one_pass(numbers)
# print("\nEarly-exit optimisation: stop after a pass with no swaps.")
# compare_versions(test_lists)
```

Output

[64, 34, 25, 12, 22, 11, 90]

Original: [11, 12, 22, 25, 34, 64, 90], comparisons=21, swaps=14

Early exit: [11, 12, 22, 25, 34, 64, 90], comparisons=21, swaps=14

Observation:

Linear Search checks each element one by one, so comparisons grow with list size ($O(n)$).

Binary Search halves the search space each step, requiring far fewer comparisons ($O(\log n)$) but only works on sorted data.

For small or unsorted lists, Linear Search is fine; for large sorted lists, Binary Search is much more efficient.

Testing shows Linear Search is faster for the first element but slower for middle, last, or absent elements compared to Binary Search.

#-----2 question:

Linear Search vs Binary Search

Prompt: "Compare Linear Search and Binary Search for the given sorted list [5, 12, 18, 23, 31, 45, 56, 72, 89]. Explain why Binary Search requires sorted data, count the comparisons for both methods, and test first, middle, last, and absent elements. Suggest one valid optimization."

Code: `earch_numbers = [5, 12, 18, 23, 31, 45, 56, 72, 89]`

`search_target = 45`

`def linear_search(values, target):`

`"""Find target from left to right and count inspected elements."""`

```
comparisons = 0
for index, value in enumerate(values):
    comparisons += 1
    if value == target:
        return index, comparisons
return -1, comparisons
```

```
def binary_search(values, target):
    """Find target in sorted values by repeatedly checking the middle."""
    left = 0
    right = len(values) - 1
    comparisons = 0

    while left <= right:
        middle = (left + right) // 2
        comparisons += 1
        if values[middle] == target:
            return middle, comparisons
        if values[middle] < target:
            left = middle + 1
        else:
            right = middle - 1

    return -1, comparisons
```

```
def compare_searches(values, targets):
    for target in targets:
        linear_result = linear_search(values, target)
```

```

binary_result = binary_search(values, target)
print(f"\nTarget: {target}")
print(
    f"Linear Search: index={linear_result[0]}, "
    f"comparisons={linear_result[1]}"
)
print(
    f"Binary Search: index={binary_result[0]}, "
    f"comparisons={binary_result[1]}"
)

if __name__ == "__main__":
    print("\nQ2 - Linear Search vs Binary Search")
    print("Binary Search needs sorted data so it can discard half the remaining")
    print("values after each middle-element comparison.")
    compare_searches(search_numbers, [search_numbers[0], search_numbers[4],
search_numbers[-1], 100])
    print("\nValid optimisation: for many repeated lookups, keep the data sorted and")
    print("use Binary Search, reducing each lookup from O(n) to O(log n).")

```

output:

Linear Search vs Binary Search

Binary Search needs sorted data so it can discard half the remaining
values after each middle-element comparison.

Target: 5

Linear Search: index=0, comparisons=1

Binary Search: index=0, comparisons=3

Target: 31

Linear Search: index=4, comparisons=5

Binary Search: index=4, comparisons=1

Target: 89

Linear Search: index=8, comparisons=9

Binary Search: index=8, comparisons=4

Target: 100

Linear Search: index=-1, comparisons=9

Binary Search: index=-1, comparisons=4

Observation:

Linear Search scans each element sequentially, giving $O(n)$ comparisons, while Binary Search halves the search space each step, giving $O(\log n)$ comparisons but requiring sorted data. Linear Search is simple for small or unsorted lists, whereas Binary Search is far more efficient for large, sorted datasets.

3 question:

Compare Sorting Algorithms

Prompt :

“Compare Bubble Sort, Selection Sort, and Insertion Sort using the given list [45, 12, 78, 34, 23, 89, 5, 67, 10, 56]. Count their comparisons and swaps/shifts, explain their strengths and weaknesses, and identify which algorithm is most suitable for nearly sorted data. Compare the results with their theoretical time complexities.”

Code: `def q3_bubble_sort(values):`

`result = values.copy()`

`comparisons = 0`

`swaps = 0`

```
for pass_number in range(len(result) - 1):
    for index in range(len(result) - 1 - pass_number):
        comparisons += 1
        if result[index] > result[index + 1]:
            result[index], result[index + 1] = result[index + 1], result[index]
            swaps += 1
    return result, comparisons, swaps
```

```
def selection_sort(values):
    result = values.copy()
    comparisons = 0
    swaps = 0
    for start in range(len(result) - 1):
        minimum_index = start
        for index in range(start + 1, len(result)):
            comparisons += 1
            if result[index] < result[minimum_index]:
                minimum_index = index
        if minimum_index != start:
            result[start], result[minimum_index] = result[minimum_index], result[start]
            swaps += 1
    return result, comparisons, swaps
```

```
def insertion_sort(values):
    result = values.copy()
    comparisons = 0
    shifts = 0
    for index in range(1, len(result)):
```

```

current = result[index]
position = index - 1
while position >= 0:
    comparisons += 1
    if result[position] <= current:
        break
    result[position + 1] = result[position]
    shifts += 1
    position -= 1
result[position + 1] = current
return result, comparisons, shifts

```

```

def compare_sorting_algorithms(values):
    algorithms = [
        ("Bubble Sort", q3_bubble_sort, "swaps"),
        ("Selection Sort", selection_sort, "swaps"),
        ("Insertion Sort", insertion_sort, "shifts"),
    ]
    print(f"\nInput used for every algorithm: {values}")
    print("Algorithm    Comparisons Swaps/Shifts Sorted result")
    for name, algorithm, movement_name in algorithms:
        result, comparisons, movements = algorithm(values)
        print(f"{name:<16}{comparisons:<13}{movements:<14}{result}")

```

```

if __name__ == "__main__":
    print("\nQ3 - Sorting algorithm analysis")
    compare_sorting_algorithms(sorting_data)
    print("\nStrengths and weaknesses:")

```

```

print("- Bubble Sort is simple, but usually makes many comparisons and swaps.")
print("- Selection Sort makes few swaps, but still makes O(n^2) comparisons.")
print("- Insertion Sort is simple and efficient for small or nearly sorted data.")
print("\nNearly sorted data: Insertion Sort is usually the best choice here.")
print("All three algorithms are O(n^2) in the average and worst cases;")
print("Insertion Sort can be O(n) when the data is already nearly sorted.")

```

output:

Input used for every algorithm: [45, 12, 78, 34, 23, 89, 5, 67, 10, 56]

Algorithm	Comparisons	Swaps/Shifts	Sorted result
Bubble Sort	45	24	[5, 10, 12, 23, 34, 45, 56, 67, 78, 89]
Selection Sort	45	6	[5, 10, 12, 23, 34, 45, 56, 67, 78, 89]
Insertion Sort	31	24	[5, 10, 12, 23, 34, 45, 56, 67, 78, 89]

Strengths and weaknesses:

- Bubble Sort is simple, but usually makes many comparisons and swaps.
- Selection Sort makes few swaps, but still makes O(n^2) comparisons.
- Insertion Sort is simple and efficient for small or nearly sorted data.

Nearly sorted data: Insertion Sort is usually the best choice here.

All three algorithms are O(n^2) in the average and worst cases;

Insertion Sort can be O(n) when the data is already nearly sorted.

Observation : All three algorithms successfully sort the same input list, but their comparisons and swaps/shifts differ.

Insertion Sort is generally more efficient for nearly sorted data because it requires fewer shifts.

The experimental results can be compared with the theoretical **O(n²)** time complexity of these algorithms.

4 question:

– Optimising a Student Search and Sort Program

Prompt :

“Analyze the student records [("Arun",82), ("Bala",65), ("Chitra",91), ("Divya",74), ("Esha",88)]. Create functions to find the highest mark, sort students by marks, and search by name. Identify unnecessary operations and suggest an efficient approach, then compare the time complexity of the original and improved solutions.”

Code: students = [

```
("Arun", 82),  
("Bala", 65),  
("Chitra", 91),  
("Divya", 74),  
("Esha", 88),
```

```
]
```

```
def highest_mark_basic(student_list):
```

```
    if not student_list:
```

```
        return None
```

```
    current_highest = student_list[0]
```

```
    for student in student_list[1:]:
```

```
        if student[1] > current_highest[1]:
```

```
            current_highest = student
```

```
    return current_highest
```

```
def sort_students_basic(student_list):
```

```
    return sorted(student_list, key=lambda student: student[1], reverse=True)
```

```
def find_student_basic(student_list, name):
```

```
    for student in student_list:
```

```
    if student[0] == name:
        return student
return None
```

```
def straightforward_student_report(student_list, name):
    """Run each basic operation independently with a linear name search."""
    return {
        "highest": highest_mark_basic(student_list),
        "sorted": sort_students_basic(student_list),
        "found": find_student_basic(student_list, name),
    }
```

```
def build_student_index(student_list):
    """Compute the highest mark and build a name index in one scan."""
    if not student_list:
        return None, {}
```

```
    highest = student_list[0]
    by_name = {}
    for student in student_list:
        by_name[student[0]] = student
        if student[1] > highest[1]:
            highest = student
    return highest, by_name
```

```
def sort_students_improved(student_list):
    return sorted(student_list, key=lambda student: student[1], reverse=True)
```

```

def find_student_improved(student_index, name):
    return student_index.get(name)

def improved_student_report(student_list, name):
    highest, by_name = build_student_index(student_list)
    return {
        "highest": highest,
        "sorted": sort_students_improved(student_list),
        "found": find_student_improved(by_name, name),
    }

if __name__ == "__main__":
    print("\nQ4 - Student search and sort")
    basic = straightforward_student_report(students, "Chitra")
    improved = improved_student_report(students, "Chitra")
    print(f"Basic highest mark: {basic['highest']}")
    print(f"Basic sorted students: {basic['sorted']}")
    print(f"Basic name search: {basic['found']}")
    print(f"Improved highest mark: {improved['highest']}")
    print(f"Improved sorted students: {improved['sorted']}")
    print(f"Improved name search: {improved['found']}")
    print("\nOptimisation: avoid scanning the list again for every repeated name search;")
    print("build a dictionary once, changing each later search from O(n) to O(1) average.")
    print("Both versions sort in O(n log n), while the one-pass highest-mark scan is O(n).")
    print("The improved approach uses O(n) extra space for the name index; the basic")
    print("approach uses O(1) extra search space and is fine for occasional lookups.")

```

output :

Basic highest mark: ('Chitra', 91)

Basic sorted students: [('Chitra', 91), ('Esha', 88), ('Arun', 82), ('Divya', 74), ('Bala', 65)]

Basic name search: ('Chitra', 91)

Improved highest mark: ('Chitra', 91)

Improved sorted students: [('Chitra', 91), ('Esha', 88), ('Arun', 82), ('Divya', 74), ('Bala', 65)]

Improved name search: ('Chitra', 91)

Optimisation: avoid scanning the list again for every repeated name search;

build a dictionary once, changing each later search from $O(n)$ to $O(1)$ average.

Both versions sort in $O(n \log n)$, while the one-pass highest-mark scan is $O(n)$.

The improved approach uses $O(n)$ extra space for the name index; the basic approach uses $O(1)$ extra search space and is fine for occasional lookups.

Observation : The program successfully finds the highest mark, sorts the students, and searches for a student by name.

The improved approach can reduce unnecessary repeated operations by using suitable data structures and efficient searching.

The original and improved solutions can be compared based on their time complexity and number of operations.

5 question:

Optimisation Challenge: Best Combination

Prompt :

"For the given items and budget of ₹50,000, find the combination of items with the maximum total price without exceeding the budget. Compare Brute Force, Greedy, and Dynamic Programming approaches, identify which method guarantees an optimal solution, and explain its time and space complexity. Test the solution with at least three different budgets."

```
Code : items = [  
    ("Laptop", 60000),  
    ("Phone", 30000),  
    ("Tablet", 20000),
```

```
    ("Watch", 10000),  
    ("Headphones", 5000),  
]
```

```
budget = 50000
```

```
def brute_force_combination(item_list, maximum_budget):  
    """Try every subset and return the most valuable valid subset."""  
    best_items = []  
    best_total = 0
```

```
def search(index, chosen_items, total):  
    nonlocal best_items, best_total  
    if index == len(item_list):  
        if total > best_total:  
            best_items = chosen_items.copy()  
            best_total = total  
    return
```

```
    search(index + 1, chosen_items, total)  
    name, price = item_list[index]  
    if total + price <= maximum_budget:  
        chosen_items.append(name)  
        search(index + 1, chosen_items, total + price)  
        chosen_items.pop()
```

```
search(0, [], 0)  
return best_items, best_total
```

```
def greedy_combination(item_list, maximum_budget):
    """Choose the most expensive remaining item that fits each time."""
    chosen_items = []
    total = 0
    for name, price in sorted(item_list, key=lambda item: item[1], reverse=True):
        if total + price <= maximum_budget:
            chosen_items.append(name)
            total += price
    return chosen_items, total
```

```
def dynamic_programming_combination(item_list, maximum_budget):
    """Solve the 0/1 knapsack problem and reconstruct an optimal subset."""
    item_count = len(item_list)
    dp = [[0] * (maximum_budget + 1) for _ in range(item_count + 1)]

    for item_index in range(1, item_count + 1):
        price = item_list[item_index - 1][1]
        for current_budget in range(maximum_budget + 1):
            dp[item_index][current_budget] = dp[item_index - 1][current_budget]
            if price <= current_budget:
                dp[item_index][current_budget] = max(
                    dp[item_index][current_budget],
                    dp[item_index - 1][current_budget - price] + price,
                )

    chosen_items = []
    current_budget = maximum_budget
```

```
for item_index in range(item_count, 0, -1):
    if dp[item_index][current_budget] != dp[item_index - 1][current_budget]:
        name, price = item_list[item_index - 1]
        chosen_items.append(name)
        current_budget -= price
```

```
chosen_items.reverse()
return chosen_items, dp[item_count][maximum_budget]
```

```
def compare_combinations(item_list, budgets):
    for current_budget in budgets:
        brute_force = brute_force_combination(item_list, current_budget)
        greedy = greedy_combination(item_list, current_budget)
        optimal = dynamic_programming_combination(item_list, current_budget)
        print(f"\nBudget: {current_budget}")
        print(f"Brute Force: {brute_force}")
        print(f"Greedy: {greedy}")
        print(f"Dynamic Programming: {optimal}")
```

```
if __name__ == "__main__":
    print("\nQ5 - Best combination under a budget")
    compare_combinations(items, [budget, 35000, 15000])
    print("\nBrute Force always finds the optimum but takes  $O(2^n)$  time.")
    print("Greedy takes  $O(n \log n)$  after sorting, but it is not guaranteed optimal")
    print("for 0/1 knapsack problems because an early choice can block a better set.")
    print("Dynamic Programming guarantees the optimum in  $O(n * \text{budget})$  time and")
    print(" $O(n * \text{budget})$  space here. For larger inputs, a 1D DP array reduces space")
    print("to  $O(\text{budget})$ , or item values can be scaled when prices are very large.")
```

output :

Brute Force always finds the optimum but takes $O(2^n)$ time.

Greedy takes $O(n \log n)$ after sorting, but it is not guaranteed optimal for 0/1 knapsack problems because an early choice can block a better set.

Dynamic Programming guarantees the optimum in $O(n * \text{budget})$ time and $O(n * \text{budget})$ space here. For larger inputs, a 1D DP array reduces space to $O(\text{budget})$, or item values can be scaled when prices are very large.

Observation :

The goal is to maximize the total item value without exceeding the given budget. Brute Force and Dynamic Programming can guarantee an optimal solution, while Greedy does not always guarantee the best combination.

Dynamic Programming is more efficient than Brute Force for larger inputs, but requires additional memory.