



Certificate No : EN-60335-1



Super Flow[®]

EXCELUM ENTERPRISES



Product
Eco
System

209, 2nd Floor, Banarasi Heritage, Behind Inorbit Mall, Chincholi Bunder,
Mind Space, Malad (West), Mumbai 400 064. INDIA.

Tel.: 022 -49633828 / 9820740914

● E-mail : marketing@excelum.in

● www.excelum.in / www.superflow.co.in



LARGE AXIAL FANS



Model	Bearing	Rating Voltage	Frequency	Rated Current	Input Power	Speed	Capacitor	Air Volume	Air Volume	Noise Level
SUPER FLOW [®]	Ball	V	Hz	A	W	RPM	μ F/VAC	m3/h	CFM	dB(A)
SF 2E 200	Ball	230	50	0.24	60	2550	2/440	800	480	58
SF 2E 200	Ball	230	60	0.34	74	2600	2/440	870	522	61
SF 4E 200	Ball	230	50	0.20	41	1450	1/440	450	270	45
SF 4E 200	Ball	230	60	0.16	35	1700	1/440	500	300	49
SF 2D 200	Ball	415	50	0.18	65	2600	-	800	480	58
SF 2D 200	Ball	415	60	0.13	64	2900	-	870	522	61



SF 2E 250	Ball	230	50	0.38	90	2350	2/440	1600	1050	66
SF 2E 250	Ball	230	60	0.39	95	2400	2/440	1600	1050	67
SF 4E 250	Ball	230	50	0.30	55	1450	2/440	950	570	60
SF 4E 250	Ball	230	60	0.26	58	1700	2/440	1100	660	61
SF 2D 250	Ball	415	50	0.20	98	2500	-	1600	960	66
SF 25 250	Ball	415	60	0.21	135	2450	-	1600	960	67



SF 2E 300	Ball	230	50	0.60	140	2100	4/440	2300	1380	66
SF 2E 300	Ball	230	60	0.75	170	2100	4/440	2200	1320	67
SF 4E 300	Ball	230	50	0.37	90	1400	3.15/440	1800	1080	60
SF 4E 300	Ball	230	60	0.50	120	1600	3.15/440	2100	1260	62
SF 2D 300	Ball	415	50	0.26	150	2100	-	2300	1380	66
SF 2D 300	Ball	415	60	0.29	180	2300	-	2350	1410	67
SF 4D 300	Ball	415	50	0.36	92	1400	-	1800	1080	60
SF 4D 300	Ball	415	60	0.30	105	1600	-	2100	1260	62



SF 4E 350	Ball	230	50	0.63	140	1400	4/450	2500	1500	58
SF 4E 350	Ball	230	60	0.73	170	1650	4/450	2700	1620	60
SF 4D 350	Ball	415	50	0.48	140	1400	-	2500	1500	58
SF 4D 350	Ball	415	60	0.38	170	1600	-	2700	1620	60



SF 4E 400	Ball	230	50	0.75	180	1400	6/450	4150	2490	64
SF 4E 400	Ball	230	60	0.95	220	1600	6/450	4700	2820	67
SF 4D 400	Ball	415	50	0.57	180	1400	-	4150	2490	64
SF 4D 400	Ball	415	60	0.50	220	1600	-	4700	2820	67



SF 4E 450	Ball	230	50	1.02	250	1400	8/440	5500	3240	65
SF 4E 450	Ball	230	60	1.55	350	1500	8/440	5700	3420	68
SF 4D 450	Ball	415	50	0.60	250	1400	-	5500	3300	65
SF 4D 450	Ball	415	60	0.67	310	1500	-	5700	3420	67





LARGE AXIAL FANS



Model	Bearing	Rating Voltage	Frequency	Rated Current	Input Power	Speed	Capacitor	Air Volume	Air Volume	Noise Level
SUPER FLOW [®]	Ball	V	Hz	A	W	RPM	μ F/VAC	m3/h	CFM	dB(A)

SF 4E 500	Ball	230	50	1.75	390	1350	10/450	6800	4080	70
SF 4E 500	Ball	230	60	2.40	530	1400	10/450	7300	4380	72
SF 4D 500	Ball	415	50	0.78	390	1350	–	6800	4080	70
SF 4D 500	Ball	415	60	0.90	500	1500	–	7300	4380	72

SF 4E 550	Ball	230	50	2.45	560	1300	12.5/440	9000	5400	72
SF 4E 550	Ball	230	60	2.18	510	1350	12.5/440	9700	5820	74
SF 4D 550	Ball	415	50	1.15	525	1400	–	9000	5400	72
SF 4D 550	Ball	415	60	1.30	750	1500	–	9800	5880	75

SF 4E 600	Ball	230	50	3.00	710	1150	16.0/440	11000	6600	76
SF 4D 600	Ball	415	50	1.45	780	1350	–	11500	6900	78
SF 4D 600	Ball	415	60	1.97	1290	1450	–	12000	7200	80

SF 4D 630	Ball	415	50	1.50	815	1350	–	13500	8100	78
SF 4D 630	Ball	415	60	1.91	1120	1450	–	14000	8400	80

SF 6D 710	Ball	415 Δ	50	1.80	1150	900	–	16000	9425	76
SF 6D 710	Ball	415 Y	50	1.20	750	680	–	13000	7660	65

SF 6D 800	Ball	415 Δ	50	3.00	1550	920	–	21350	12575	80
SF 6D 800	Ball	415 Y	50	1.90	1200	780	–	19100	11250	72

AC AXIAL FAN



Model	Bearing	Rating Voltage	Frequency	Rated Current	Input Power	Speed	Capacitor	Air Volume	Air Volume	Noise Level
SUPER FLOW [®]	Ball	V	Hz	A	W	RPM	μ F/VAC	m3/h	CFM	dB(A)

SF 2E 22580 B2 MB	Ball	230	50	0.30	70	2400	2/440	1000	600	58
SF 2E 22580 B2 MB	Ball	230	60	0.35	78	2600	2/440	1100	660	61
SF 2D 22580 B2 MB	Ball	415	50	0.18	78	2400	–	1000	600	58
SF 2D 22580 B2 MB	Ball	415	60	0.15	78	2600	–	1100	660	61

SF 2E 28080 B2 MB	Ball	230	50	0.50	115	2600	3.15/440	1750	1050	66
SF 2E 28080 B2 MB	Ball	230	60	0.60	140	2800	3.15/440	1900	1140	67
SF 2D 28080 B2 MB	Ball	415	50	0.27	115	2600	–	1750	1050	66
SF 2D 28080 B2 MB	Ball	415	60	0.23	128	2800	–	1900	1140	67



CENTRIFUGAL BACKWARD FAN



Model	Bearing	Rating Voltage	Frequency	Rated Current	Input Power	Speed	Capacitor	Air Volume	Air Volume	Noise Level
SUPER FLOW [®]	Ball	V	Hz	A	W	RPM	μ F/VAC	m3/h	CFM	dB(A)

SF CB 2E 133	Ball	230	50	0.14	30	2550	1/440	240	144	50
--------------	------	-----	----	------	----	------	-------	-----	-----	----



SF CB 2E 175	Ball	230	50	0.27	66	2550	2.00	550	330	58
SF CB 2E 175	Ball	230	60	0.31	73	2710	2.00	620	372	60



SF CB 2E 190	Ball	230	50	0.22	52	2100	1/440	450	270	66
SF CB 2E 190	Ball	230	60	0.24	56	2100	1/440	450	270	67



SF CB 2E 220	Ball	230	50	0.42	92	2450	2/440	900	540	70
SF CB 2E 220	Ball	230	60	0.49	110	2650	2/440	950	570	72
SF CB 2D 220	Ball	415	50	0.22	95	2450	—	900	540	70
SF CB 2D 220	Ball	415	60	0.20	110	2650	—	950	570	72



SF CB 2E 225	Ball	230	50	0.65	150	2400	4/440	1200	720	74
SF CB 2E 225	Ball	230	60	0.88	197	2600	4/440	1300	780	76



SF CB 2E 250	Ball	230	50	0.74	168	2400	4/440	1400	840	72
SF CB 2E 250	Ball	230	60	0.92	210	2450	4/440	1400	840	74



SF CB 2E 280	Ball	230	50	1.15	260	2550	8/440	2100	1260	79
SF CB 2E 280	Ball	230	60	0.50	340	2750	8/440	2200	1320	81
SF CB 2D 280	Ball	415	50	0.60	260	2550	—	2000	1200	79
SF CB 2D 280	Ball	415	60	0.35	265	2750	—	2200	1320	81



SF CB 4E 315	Ball	230	50	0.64	130	1400	4/440	2000	1200	65
SF CB 4E 315	Ball	230	60	—	—	—	—	—	—	—
SF CB 4D 315	Ball	415	50	0.47	135	1400	—	2000	1200	65
SF CB 4D 315	Ball	415	60	—	—	—	—	—	—	—



SF CB 4E 355	Ball	230	50	0.85	190	1400	6/440	3000	1800	71
SF CB 4E 355	Ball	230	60	1.70	245	1450	6/440	3100	1860	73
SF CB 4D 355	Ball	415	50	0.70	200	1400	—	3000	1800	71
SF CB 4D 355	Ball	415	60	—	—	—	—	—	—	—



SF CB 4E 355-S	Ball	230	50	1.70	350	1400	10/440	3350	2010	75
SF CB 4E 355-S	Ball	230	60	—	—	—	—	—	—	—
SF CB 4D 355-S	Ball	415	50	0.87	245	1450	—	3350	2010	75
SF CB 4D 355-S	Ball	415	60	—	—	—	—	—	—	—



HOUSING CENTRIFUGAL BLOWERS (SINGLE INLET)



Model	Bearing	Rating Voltage	Frequency	Rated Current	Input Power	Speed	Capacitor	Air Volume	Air Volume	Noise Level
SUPER FLOW [®]	Ball	V	Hz	A	W	RPM	μ F/VAC	m3/h	CFM	dB(A)

SF HCB 2E 133	Ball	230	50	0.20	50	2100	1/440	260	156	70
SF HCB 2E 133	Ball	230	60	0.25	57	2050	1/440	225	135	72

SF HCB 2E 140	Ball	230	50	0.40	100	2350	2/440	415	249	73
SF HCB 2E 140	Ball	230	60	0.52	121	2350	2/440	425	255	75
SF HCB 2D 140	Ball	415	50	0.19	104	2350	–	415	249	73
SF HCB 2D 140	Ball	415	50	0.20	120	2500	–	425	255	75

SF HCB 2E 150	Ball	230	50	0.75	175	2100	4/440	520	312	74
SF HCB 2E 150	Ball	230	60	0.87	200	2250	4/440	560	336	76
SF HCB 2D 150	Ball	415	50	0.30	175	2200	–	520	312	74
SF HCB 2D 150	Ball	415	60	0.37	231	2200	–	560	336	76

SF HCB 2E 160	Ball	230	50	0.48	115	2050	2/440	450	270	74
SF HCB 2E 160	Ball	230	60	0.56	125	2100	2/440	500	300	76
SF HCB 2E 160-S	Ball	230	50	0.82	200	2250	4/440	630	378	76
SF HCB 2E 160-S	Ball	230	60	1.04	239	2450	4/440	700	420	76
SF HCB 2D160	Ball	415	50	0.22	125	2100	-	450	270	74
SF HCB 2D 160	Ball	415	60	0.24	149	2150	-	500	300	76
SF HCB 2D 160-S	Ball	415	50	0.35	195	2350	-	630	378	76
SF HCB 2D 160-S	Ball	415	60	0.37	215	2300	-	700	420	78

SF HCB 2E 180	Ball	230	50	1.23	280	2500	6/440	730	438	81
SF HCB 2E 180	Ball	230	60	1.58	360	2400	6/440	670	402	83
SF HCB 2D 180	Ball	415	50	0.45	280	2550	–	730	440	81
SF HCB 2D 180	Ball	415	60	0.65	390	2750	–	670	400	83

SF HCB 4E 240	Ball	230	50	1.60	375	1350	10/440	1400	840	76
SF HCB 4E 240	Ball	230	60	2.26	515	1550	10/440	1580	948	78
SF HCB 4D 240	Ball	415	50	0.75	375	1400	–	1400	840	76
SF HCB 4D 240	Ball	415	60	0.85	500	1500	–	1580	948	78

HOUSING CENTRIFUGAL BLOWERS (DOUBLE INLET)



Model	Bearing	Rating Voltage	Frequency	Rated Current	Input Power	Speed	Capacitor	Air Volume	Air Volume	Noise Level
SUPER FLOW [®]	Ball	V	Hz	A	W	RPM	μ F/VAC	m3/h	CFM	dB(A)

SF HCB 2E 133-D	Ball	230	50	0.73	180	1450	3.15/440	850	510	75
SF HCB 4E 133-D	Ball	230	50	0.38	92	1400	3.15/440	475	285	67
SF HCB 2D 133-D	Ball	415	50	0.32	198	2150	–	925	555	75

SF HCB 2E 146-D	Ball	230	50	1.50	365	2250	10/440	1350	810	73
-----------------	------	-----	----	------	-----	------	--------	------	-----	----



HOUSING CENTRIFUGAL BLOWERS (DOUBLE INLET)



Model	Bearing	Rating Voltage	Frequency	Rated Current	Input Power	Speed	Capacitor	Air Volume	Air Volume	Noise Level
SUPER FLOW [®]	Ball	V	Hz	A	W	RPM	μ F/VAC	m3/h	CFM	dB(A)
SF HCB 2E 150-D	Ball	230	50	1.75	405	2250	10/440	1250	750	72
SF HCB 2D 150-D	Ball	415	50	1.15	550	2600	—	1500	900	74
SF HCB 2E 160-D	Ball	230	50	1.80	420	2300	10/440	1250	750	76
SF HCB 4E 160-D	Ball	230	50	0.47	115	1200	3.15/440	815	490	69
SF HCB 2D 160-D	Ball	415	50	0.75	420	2300	—	1250	750	76
SF HCB 4E 180-D	Ball	230	50	0.90	210	1000	5.0/440	1700	1020	68
SF HCB 4D 180-D	Ball	415	50	0.45	250	1000	—	1700	1020	68
SF HCB 4E 200-D	Ball	230	50	1.50	360	1350	10/440	1550	1395	74
SF HCB 2D 200-D	Ball	415	50	2.63	1750	2350	—	3100	1860	72
SF HCB 4D 200-D	Ball	415	50	0.78	360	1400	—	1550	1395	74
SF HCB 4D 250-D	Ball	415	50	1.60	900	1350	—	3500	2100	71
SF HCB 4D 250-D	Ball	415	60	2.15	1190	1400	—	3700	2220	73

DUCT FANS



Model	Bearing	Rating Voltage	Frequency	Rated Current	Input Power	Speed	Capacitor	Air Volume	Air Volume	Noise Level
SUPER FLOW [®]	Ball	V	Hz	A	W	RPM	μ F/VAC	m3/h	CFM	dB(A)
SF DF 2E 100	Ball	230	50	0.21	55	2350	1.5/440	300	180	60
SF DF 2E 125	Ball	230	50	0.37	80	2650	2/440	375	225	65
SF DF 2E 150	Ball	230	50	0.40	92	2400	2/440	800	480	69
SF DF 2E 160	Ball	230	50	0.45	105	2650	4/440	925	555	72
SF DF 2E 200	Ball	230	50	0.55	135	2350	4/440	1075	645	73
SF DF 2E 250	Ball	230	50	0.58	315	2350	4/440	1100	660	74
SF DF 2E 315	Ball	230	50	1.10	240	2650	8/440	1750	1050	80

All Products are made in 100% Pure Copper Winding



Murali Krishna
Head Sales & Operations
9980060647



Hari Prasad
Head Business Development
9945933111

SAI COMPONENTS INDIA PRIVATE LIMITED
SUPPLIERS OF INDUSTRIAL & ELECTRONIC COMPONENTS
No. 69/3, 3rd Main Road, Conservancy Road, Chamarajpet, Bangalore - 560018
Phone : 080 - 40982422, 41600647, 41140446, Off. Mobile : 8088791291
E-mail : saicomponents@gmail.com, rexnordkap@gmail.com



Since - 1984
"A Cooling System to Rely On"

Raychem RPG

ALCON ELECTRONICS PRIVATE LIMITED