

RSA Digital Signature: Security

- **Necessary hardness assumptions:**

- Factoring hardness assumption: Given n large, it is hard to find primes $p, q = n$
- Discrete logarithm hardness assumption: Given n large, $hash$, and $hash^d \bmod n$, it is hard to find d *private key*

- Salt also adds security

- Even the same message and private key will get different signatures

$$\begin{aligned}
 & e \cdot d \equiv 1 \pmod{\phi(n)} \\
 & \phi(n) = (p-1) \cdot (q-1) \\
 & \text{Signature } S = [h(m)]^d \pmod{n} \\
 & H = H(m) \\
 & d \log y \equiv d \log H(m) \pmod{n} \\
 & \Rightarrow d = \frac{d \log y}{d \log H(m)}
 \end{aligned}$$

Hybrid Encryption


- Issues with public-key encryption

- Notice: We can only encrypt small messages because of the modulo operator
- Notice: There is a lot of math, and computers are slow at math
- Result: We don't use asymmetric for large messages

- **Hybrid encryption:** Encrypt data under a randomly generated key K using symmetric encryption, and encrypt K using asymmetric encryption

- $\text{Enc}_{\text{Asym}}(\text{PK}, K)$; $\text{Enc}_{\text{Sym}}(K, \text{large message})$
- Benefit: Now we can encrypt large amounts of data quickly using symmetric encryption, and we still have the security of asymmetric encryption

TLS



Network Security

- Key Distribution and User Authentication

Chapter 4

Remote User Authentication Principles

4.1

Remote User Authentication Principles

- RFC 4949 defines user authentication as: “The process of verifying an identity claimed by or for a system entity.” This process consists of two steps:
 - Identification step: presenting an identifier to the security system
 - Verification step: presenting or generating authentication information that corroborates the binding between the entity and the identifier
- Fundamental security building block
 - Basis of access control & user accountability

Means of User Authentication

- Something the individual knows
 - password, PIN, answers to prearranged questions
- Something the individual possesses
 - token: cryptographic ~~keys~~, electronic keycards, smart cards, and physical keys
- Something the individual is (static biometrics)
 - fingerprint, retina, and face
- Something the individual does (dynamic biometrics)
 - voice pattern, handwriting characteristics, and typing rhythm

News about Bitcoins

- In October 2025, the U.S. District Court for the Eastern District of New York disclosed an unprecedented case of cryptocurrency asset seizure: the U.S. government confiscated 127,271 bitcoins, worth about \$15 billions at market price.
- **Root Cause: Weak Randomness in Key Generation:** It argues the underlying vulnerability is not a broken algorithm per se, but the use of a **non-cryptographically secure PRNG** during wallet/private-key generation. In particular, many “weak wallets” used the **MT19937** (Mersenne Twister) generator with **low entropy** seeds, making private keys predictable.
- Lesson: Ensuring Cryptographic Randomness (i.e. not use system time as seed). Randomness and Private Key Security is the Lifeline of the Blockchain World

Solution?

When Randomness Isn't So Random: The Truth Behind the Theft of 120,000 BTC,
<https://www.bitget.com/amp/news/detail/12560605022352>