


Secure?


no user authentication

- Ticket hijacking
 - Malicious user may **steal the service ticket** of another user on the same workstation and try to use it
 - Network address verification does not help
 - Servers must verify that the user who is presenting the ticket is the same user to whom the ticket was issued
- No server authentication
 - Attacker may misconfigure the network so that he receives messages addressed to a legitimate user – man in the middle attack
 - Cause a denial of service
 - Servers must prove their identity to users
- **Solution: session key**
 - Once per user logon session
 - (1) $C \rightarrow AS: ID_C || ID_{tgs}$
 - (2) $AS \rightarrow C: E(K_C, Ticket_{tgs})$
 - Once per type of service:
 - (3) $C \rightarrow TGS: ID_C || ID_v || Ticket_{tgs}$
 - (4) $TGS \rightarrow C: Ticket_v$
 - Once per service session:
 - (5) $C \rightarrow V: ID_C || Ticket_v$


Kerberos v4. - once per user logon session



Kerberos v4. - once per type of service




Kerberos v4. - once per service session



For each service request, client uses the short-term key, K_{C,V}, for that service and the ticket he received from TGS

$$Ticket_v = E(K_v, [K_{c,v} || ID_C || AD_C || ID_v || TS_4 || Lifetime_4])$$

Overview of Kerberos




Important Ideas in Kerberos

- Short-term session keys
 - Long-term secrets used only to derive short-term keys
 - Separate session key for each user-server pair
 - Re-used by multiple sessions between same user and server
- Proofs of identity based on authenticators
 - Client encrypts his identity, addr, time with session key; knowledge of key proves client has authenticated to KDC/AS
 - Also prevents replays (if clocks are globally synchronized)
 - Server learns this key separately (via encrypted ticket that client can't decrypt), then verifies client's authenticator
- Symmetric cryptography only

Kerberos in Large Networks

- One KDC isn't enough for large networks
- Network is divided into realms
 - KDCs in different realms have different key databases
- To access a service in another realm, users must...
 - Get ticket for home-realm TGS from home-realm KDC
 - Get ticket for remote-realm TGS from home-realm TGS
 - As if remote-realm TGS were just another network service
 - Get ticket for remote service from that realm's TGS
 - Use remote-realm ticket to access service

→ scalability




(1)

(2)

(3)

(4)



Practical Uses of Kerberos

- Microsoft Windows – Active Directory
- Email, FTP, network file systems, many other applications have been kerberized
 - Use of Kerberos is transparent for the end user
 - Transparency is important for usability!
- Authentication for network protocols
 - rsh
- Local authentication
 - login and su in OpenBSD
- Secure windowing systems

Readings

- Kerberos: The Network Authentication Protocol
<https://web.mit.edu/kerberos/>

Practice – no submission

- William Stallings, “Network Security Essentials”, 6 Edition, 2017
 - Chapter 4’s problems: 4.8, 4.9, 4.10