DRIVEX

VIP BUSINESS CARDS · SPEC SHEET

Print Specification Sheet
VIP Business Cards

Drivex Transport LLC · Version 1.0 · October 2026 · Design: eSinergia

1. Job summary

Item	Specification
Product	VIP business card, printed on both sides
Versions	2: Juan C. Acevedo and Claudia Valencia
Front	Same for both versions
Back	Name and phone number change per version
Quantity per version	To be confirmed
Files supplied	.AI and .PDF, text outlined, print-ready

2. Size

Measurement	Inches	Millimeters	Centimeters
Trim size (final)	3.5" × 2"	88.9 × 50.8 mm	8.89 × 5.08 cm
Bleed per side	0.125"	3.175 mm	0.3175 cm
File size with bleed	3.75" × 2.25"	95.25 × 57.15 mm	9.525 × 5.715 cm
Safe zone (inset from trim line)	0.125"	3.175 mm	0.3175 cm

- Square corners. If rounded corners are wanted, the radius is set with the printer.
- No text, icon or QR code goes past the safe zone toward the trim line.

3. Stock

The brief calls for a 16 pt / 350 GSM matte black card with a Soft-Touch feel. Conventional CMYK inks do not show on black stock: white is not a process ink, and Navy (#0B2545) disappears against black. Two routes are therefore proposed.

Option A — Recommended: premium white stock printed black

The black is printed full-bleed on white stock and covered with Soft-Touch lamination. The result looks and feels like a matte black card with a velvet touch, as the brief requests.

Item	Specification
Stock	Premium white uncoated or silk, 16 pt / 350 GSM minimum (400 GSM or heavier recommended for rigidity)
Printing	CMYK 4/4: full-bleed black on both sides
Background black	Rich black C60 M40 Y40 K100 (300% maximum ink coverage)
Fine black text and lines	K100 only, never rich black
White	The paper itself: white text is knocked out of the black
Navy	Pantone PMS 2767 C as a spot ink, or its CMYK equivalent approved on proof
Lamination	Matte Soft-Touch on both sides
Edges	Edge painting in black (or gold) so the white core does not show after trimming. Optional, highly recommended

Advantages: Navy and white reproduce accurately, cost is lower, and any commercial printer can produce it.

Watch white text knocked out of rich black: use 7 pt minimum at Medium (500) weight or heavier, and ask the printer to apply trapping so letters do not fill in from misregistration.

Option B — True to the brief: through-dyed black stock

Item	Specification
Stock	Through-dyed black, 16 pt / 350 GSM minimum, matte finish or with a built-in Soft-Touch feel
White	Special processes only: opaque white foil (hot stamping), white screen printing, or digital printing with white toner or ink (usually two passes for full coverage)
Navy	Not viable on black: the stripe and divider lines are lost
Lamination	Not needed if the stock already has a Soft-Touch feel

Advantages: the edges are black by nature and the paper feels more exclusive.

Disadvantages: white adds cost and is less precise on small text and icons, and Navy has to be replaced. If this option is chosen, the Navy stripe and divider lines become a fine gold foil rule or a tone-on-tone Spot-UV application.

4. Gold: hot foil stamping

Gold is never printed in CMYK. It is always a separate process, under either option.

Item	Specification
Recommended process	Hot foil stamping with a metal die
Foil	Matte or warm satin gold, chosen from the printer's swatch book to approximate #C5A572. Approved on a physical sample
Production order	Printing → Soft-Touch lamination → foil → Spot-UV
Foil elements	Front: DRIVEX logo. Back: only if gold icons are approved
Minimum stroke	0.3 pt (0.1 mm)
Minimum gap between shapes	0.2 mm
Minimum foil text size	6 pt
Alternative for short runs	Digital foil (e.g. Scodix or MGI JETvarnish-type systems). No die required; approve the shine on a sample

Cost tip: since the front is the same for both versions, the front foil uses a single die. If the back icons are white rather than foil, no additional die is needed.

5. Spot-UV Gloss (QR code)

Item	Specification
Position	Bottom-right corner of the back, over the QR code
QR base	White (Option A: paper knocked out; Option B: special white) or gold foil. Never varnish alone on black, which no camera can read
Minimum QR size	2 × 2 cm (0.8" × 0.8")
Quiet zone	4 clear modules around the code
Destination	www.drivexgreenville.com
Test	Scan the physical sample with at least two different phones before approving the run

6. File preparation

Item	Specification
Formats	.AI (editable) and .PDF/X-4 for print
Color mode	CMYK, profile specified by the printer (default in the US: GRACoL 2013 / CRPC6)
Text	Converted to outlines
Artboards	3: Front · Back Juan · Back Claudia, at 3.75" × 2.25" including bleed
Crop marks	Included in the PDF, offset outside the bleed
Images	No raster images. If any are added, 300 ppi minimum at actual size

Layers and spot colors

Each finish sits on its own layer with its own spot color swatch, at 100% and set to overprint. The swatch only defines the shape; its on-screen color is not the color of the finish.

Layer	Spot color swatch	Content
ARTE_CMYK	—	Background, text, icons, Navy
FOIL_GOLD	FOIL_GOLD	Logo and gold elements
SPOT_UV	SPOT_UV	QR code area
WHITE (Option B only)	WHITE	White text, icons and QR

On the ARTE_CMYK layer, the area under the foil carries no ink (it is knocked out) so the gold does not darken, unless the printer advises otherwise.

7. Proofs and approval

1. Color proof on the production stock, with Navy checked against a physical Pantone PMS 2767 C swatch.
2. Physical sample of the foil and Spot-UV before production.
3. QR scan with two phones on the physical sample.
4. Check of the Navy stripe contrast against black (Option A) and of white coverage (Option B).
5. Written client approval before production.

8. Open items

Item	Owner
Final stock: Option A or Option B	Client
Quantity per version	Client
Back icons in white or gold foil	Client
Edge painting: black, gold or none	Client
Print vendor	Client. The Staples guide included in the brief accepts only JPG, PNG or PDF; confirm whether it produces foil, Spot-UV and Soft-Touch from layered files, or choose a specialty printer
Foil and exact paper weight	Printer