DRIVEX

VIP BUSINESS CARDS · SPEC SHEET

Print Specification Sheet
VIP Business Cards

Drivex Transport LLC · Version 1.1 · October 2026

1. Job summary

Item	Specification
Product	VIP business card, printed on both sides
Versions	2: Juan C. Acevedo and Claudia Valencia
Front	Same for both versions: foil logo, tagline and legal text in white
Back	Name and phone number change per version
Quantity per version	To be confirmed
Files supplied	Per version: editable .AI, print .AI and PDF/X-4, with text outlined in the print files

The design has no Navy stripe: against black it does not give the expected contrast in print. Navy is used only in the corner markers of the QR code, on a white background.

2. Size

Measurement	Inches	Millimeters	Centimeters
Trim size (final)	3.5" × 2"	88.9 × 50.8 mm	8.89 × 5.08 cm
Bleed per side	0.125"	3.175 mm	0.3175 cm
File size with bleed	3.75" × 2.25"	95.25 × 57.15 mm	9.525 × 5.715 cm
Safe zone (inset from trim line)	0.125"	3.175 mm	0.3175 cm

- Square corners. If rounded corners are wanted, the radius is set with the printer.
- No text, icon or QR code goes past the safe zone toward the trim line.

3. Stock

The brief calls for a 16 pt / 350 GSM matte black card with a Soft-Touch feel. Conventional CMYK inks do not show on black stock: white is not a process ink, and dark colors such as Navy (#0B2545) disappear against black. Two routes are therefore proposed.

Option A — Recommended: premium white stock printed black

The black is printed full-bleed on white stock and covered with Soft-Touch lamination. The result looks and feels like a matte black card with a velvet touch, as the brief requests.

Item	Specification
Stock	Premium white uncoated or silk, 16 pt / 350 GSM minimum (400 GSM or heavier recommended for rigidity)
Printing	CMYK 4/4: full-bleed black on both sides
Background black	Rich black C60 M40 Y40 K100 (240% ink coverage; 300% maximum allowed)
Fine black text and lines	K100 only, never rich black
White	The paper itself: white text is knocked out of the black
Navy (QR markers only)	C100 M85 Y43 K47 on the white QR panel, or Pantone PMS 2767 C as a spot ink. Approved on proof
Lamination	Matte Soft-Touch on both sides
Edges	Edge painting in black (or gold) so the white core does not show after trimming. Optional, highly recommended

Advantages: white and the QR Navy reproduce accurately, cost is lower, and any commercial printer can produce it.

Watch white text knocked out of rich black: use 7 pt minimum at Medium (500) weight or heavier, and ask the printer to apply trapping so letters do not fill in from misregistration.

Option B — True to the brief: through-dyed black stock

Item	Specification
Stock	Through-dyed black, 16 pt / 350 GSM minimum, matte finish or with a built-in Soft-Touch feel
White	Special processes only: opaque white foil (hot stamping), white screen printing, or digital printing with white toner or ink (usually two passes for full coverage)
Navy	Only in the QR markers, printed on the special white base of the QR panel
Lamination	Not needed if the stock already has a Soft-Touch feel

Advantages: the edges are black by nature and the paper feels more exclusive.

Disadvantages: white adds cost and is less precise on small text and icons.

4. Gold: hot foil stamping

Gold is never printed in CMYK. It is always a separate process, under either option.

Item	Specification
Recommended process	Hot foil stamping with a metal die
Foil	Matte or warm satin gold, chosen from the printer's swatch book to approximate #C5A572. Approved on a physical sample
Production order	Printing → Soft-Touch lamination → foil → Spot-UV
Foil elements	Front: DRIVEX logo and shield icon. Back: name, contact icons and diagonal lines
File	Masks on pages 3 (front) and 4 (back) of the print PDF
Diagonal lines	Shown with a gradient in the artwork for reference; in foil they become solid gold
Minimum stroke	0.3 pt (0.1 mm)
Minimum gap between shapes	0.2 mm
Minimum foil text size	6 pt
Alternative for short runs	Digital foil (e.g. Scodix or MGI JETvarnish-type systems). No die required; approve the shine on a sample

Dies: the front is the same for both versions, so its foil uses a single die. The back needs one die per version, because the name changes. Digital foil needs no dies.

5. Spot-UV Gloss (QR code)

Item	Specification
Position	Bottom-right corner of the back, over the QR code modules
File	Mask on page 5 of the print PDF
QR base	2.35 cm white panel (Option A: paper knocked out; Option B: special white), black modules and Navy corner markers. Never varnish alone on black, which no camera can read
QR size	2 × 2 cm (0.8" × 0.8")
White margin	1.8 mm around the code (about 3 modules). Scanning verified on the files
Destination	www.drivexgreenville.com
Test	Scan the physical sample with at least two different phones before approving the run

6. File preparation

Item	Specification
Formats	Per version: editable .AI (live text), print .AI and PDF/X-4
Color mode	CMYK. Profile embedded in the PDF: Coated GRACoL 2006. If the printer requires another, the files are re-exported
Colors	Background black C60 M40 Y40 K100 · Reference gold C22 M32 Y58 K8 · Navy C100 M85 Y43 K47 · White: paper
Text	Converted to outlines in the print files
Artboards	5 per file, at 3.75" × 2.25" including bleed (see table below)
Crop marks	Included in the PDF, offset outside the bleed
Images	No raster images

PDF pages and finish masks

Page	Type	Content
1	CMYK artwork	Front
2	CMYK artwork	Back
3	Foil mask	Front: logo and shield icon
4	Foil mask	Back: name, icons and diagonal lines
5	Spot-UV mask	QR code

Each finish sits on its own page, aligned with the artwork. On the masks, the 100% black shape marks where the finish goes; that color is not printed. On the artwork pages, the foil elements appear in CMYK gold for reference. The recommendation is to knock out the foil area (no ink underneath) so the gold does not darken: the printer advises whether they prefer this and the file is adjusted. For Option B, a white mask with the text, icons and QR panel is added.

7. Proofs and approval

1. Color proof on the production stock: background black, and QR Navy checked against a physical Pantone PMS 2767 C swatch.
2. Physical sample of the foil and Spot-UV before production.
3. QR scan with two phones on the physical sample.
4. Check of black coverage and legibility of knocked-out white text (Option A), or of white coverage (Option B).
5. Written client approval before production.

8. Open items

Item	Owner
Final stock: Option A or Option B	Client
Quantity per version	Client
Back elements in foil: name, icons and lines, as supplied in the files	Client
Edge painting: black, gold or none	Client
Print vendor	Client. The Staples guide included in the brief accepts only JPG, PNG or PDF; confirm whether it produces foil, Spot-UV and Soft-Touch from files with finish masks, or choose a specialty printer
Foil area knocked out or with CMYK gold underneath	Printer
Color profile, if different from GRACoL 2006	Printer
Foil and exact paper weight	Printer