



Department of Computer Science
Columbia University

Group Project: implement an iris recognition algorithm

Instructor: Xiaofu He

Fall 2020

Requirement

- 1) Implement the exact same design as Ma et al., 2003 paper (see the reference) but focus on Image Preprocessing, Feature Extraction, and Iris Matching **only** and use provided dataset.
- 2) Download the CASIA Iris Image Database (version 1.0) (CASIA-IrisV1) from the Coursework and unzip the dataset to the **same directory** as your Matlab or python scripts.
- 3) Three or two students per group (need to submit peer evaluation form). If you can't find group members, please let my TA know.

<https://docs.google.com/spreadsheets/d/1kQi99YGL4ImTtVVNPRQ1DBYWE7ct0apdFud1nQjdveA/edit?usp=sharing>

Experiment design

- Database: 108 eyes, 7 iris images per eye, which were captured in two sessions (3 in the first session, 4 in the second session). All images are stored as BMP format with 320x280 pixel size.
- Experiment design: images from the first session will be used for training and images from the second session will be used for testing
- Experimental results:
 - The Correct Recognition Rate (CRR) for the identification mode (refer to Tables 3 & 10 of Ma's paper)
 - Receiver Operating Characteristic (ROC) curve for the verification mode (refer to Table 4 and Fig. 13. of Ma's paper)

Submission

- Source codes
 - IrisRecognition.m/py: the **main** function, which will use all the following sub functions:
 - IrisLocalization.m/py: detecting pupil and outer boundary of iris. You can choose other iris localization methods if they work better;
 - IrisNormalization.m/py: mapping the iris from Cartesian coordinates to polar coordinates;
 - ImageEnhancement.m/py: enhancing the normalized iris;
 - FeatureExtraction.m/py: filtering the iris and extracting features;
 - IrisMatching.m/py: using Fisher linear discriminant for dimension reduction and nearest center classifier for classification;
 - PerformanceEvaluation.m/py: calculating the CRR for the identification mode (CRR for all three measures, i.e., L1, L2, and Cosine similarity, should be $\geq 75\%$, the higher the better), which will output Tables 3 & 10 (refer to Ma's paper); calculating ROC curve for verification mode, which will output Table 4 and Fig. 11 (**using Bootstrap and calculating confidence interval is not required**).

For each script, 1). explain the logic behind the script, e.g., what is the loop for? what is that piece of code for? 2). specify and explain **ALL** key variables/parameters used in the script.

Extra bonus

- calculating the CRR for the identification mode (CRR should be $\geq 85\%$, you can get extra 5% of the point)

- A readme file
(UNI_UNI2_UNI3_IrisRecognition.README)
 - Explain the whole logic of your design.
 - Briefly discuss the limitation(s) of the current design.
How can you improve it?
 - Peer evaluation form
- Compress all files into a single zip file with
UNI_UNI2_UNI3_IrisRecognition.zip/.rar as its
name
- All scripts must be runnable (we won't debug for
you).
- Do not submit the dataset.

Submit to the coursework, due on Oct 28th (11:59PM)

Reference

- Ma et al., Personal Identification Based on Iris Texture Analysis, IEEE TRANSACTIONS ON PATTERN ANALYSIS AND MACHINE INTELLIGENCE, VOL. 25, NO. 12, DECEMBER 2003
- Note_CASIA-IrisV1.pdf