Status	Finished
Started	Wednesday, 28 October 2026, 7:15 PM
Completed	Wednesday, 28 October 2026, 7:21 PM
Duration	6 mins 33 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

a. The encoding of the file
b. The access mode of the file
c. The file's read/write position
d. The buffer size for the file operations ✓

The correct answer is: The buffer size for the file operations

Question **2**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

a. The operation is ignored
b. An empty file object is returned
c. An error is raised ✓
d. A new file is created

The correct answer is: An error is raised

Question **3**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

- a. readlines() ✓
- b. readline()
- c. read()
- d. readlist()

The correct answer is: readlines()

Question **4**

Correct

Mark 1.00 out of 1.00

What does the mode attribute of a file object indicate?

- a. The name of the file
- b. The current position of the file cursor
- c. The size of the file
- d. The access mode in which the file was opened ✓

The correct answer is: The access mode in which the file was opened

Question **5**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

- a. readline()
- b. read(size) ✓
- c. readlines()
- d. readchar()

The correct answer is: read(size)

Question **6**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

a. None
b. 0
c. An empty string ✓
d. EOFError

The correct answer is: An empty string

Question **7**

Correct

Mark 1.00 out of 1.00

What does the seek() method do in file handling?

a. Reads the file line by line
b. Moves the file cursor to the specified position ✓
c. Writes data to the file
d. Deletes the file

The correct answer is: Moves the file cursor to the specified position

Question **8**

Correct

Mark 1.00 out of 1.00

Which of the following methods is used to read a single line from a file?

a. readline() ✓
b. readline(size)
c. readlines()
d. read()

The correct answer is: readline()

Question **9**

Correct

Mark 1.00 out of 1.00

Select the correct method to write a list of lines to a file

- a. writelines(list) ✓
- b. None of the mentioned
- c. writelist(list)
- d. write(list)

The correct answer is: writelines(list)

Question **10**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

- a. seek() ✓
- b. ftell()
- c. fseek()
- d. tell()

The correct answer is: seek()

Question **11**

Correct

Mark 1.00 out of 1.00

What does the flush() method do in file handling?

- a. Closes the file
- b. Flushes the internal buffer to the file ✓
- c. Deletes the file content
- d. Moves the file cursor to the beginning

The correct answer is: Flushes the internal buffer to the file

Question **12**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

a. write()
b. writelines() ✓
c. write_list()
d. write_all()

The correct answer is: writelines()

Question **13**

Correct

Mark 1.00 out of 1.00

Which method is used to write data to a file?

a. append()
b. read()
c. insert()
d. write() ✓

The correct answer is: write()

Question **14**

Correct

Mark 1.00 out of 1.00

How can you read a file line by line efficiently in Python?

a. Using a for loop ✓
b. Using the readlines() method
c. Using the readline() method
d. Using the read() method

The correct answer is: Using a for loop

Question **15**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a. Move file pointer five characters ahead from the beginning

b.
- Move file pointer five characters behind from the current position.

c.
- Move file pointer five characters behind ahead from the end of a file.

d.
- Move file pointer five characters ahead from the current position. ✓

The correct answer is:

- Move file pointer five characters ahead from the current position.