HireX — Database Schema & Data Model Reference

Document ID: `HXP-HANDOVER-08`
Platform Version: HireX V0 / PostgreSQL + Prisma ORM
Target Audience: Database Administrators, Backend Engineers, Data Engineers
Last Updated: October 2026

---

1. Database Overview & Migration History

HireX uses PostgreSQL 15+ managed through Prisma ORM (v5+). The database schema contains **25 models** and **13 enums**.

Historical Migrations (`hirex-Backend/prisma/migrations`)

1. `init`: Initial multi-tenant schema with Company, User, Recruiter, Candidate, Job, Application.
2. `20261007_schedular_interview_columns`: Added `hostJoinUrl` and `candidateJoinUrl` to `interviews` table.
3. `jr_missing_fields`: Added resume snapshot and explicitly enforced `Application.resume onDelete SetNull`.
4. `20261023_prd_gap_closure`:
   - Added `ApplicationStatus.DOCUMENT_VERIFICATION`
   - Added `OfferStatus.DRAFT`, `OfferStatus.EXPIRED`
   - Added `Recommendation.LEANING_HIRE`
   - Added `InterviewFeedback.culturalFitScore`
   - Added multi-file `DocumentFile` table and document audit stamps (`verifiedAt`, `verifiedBy`, `rejectionReason`)
   - Added `Interviewer.sharePhotoWithCandidates`

---

2. Complete Enum Catalog (13 Enums)

Enum Name	Allowed Values	Usage / Context
`UserRole`	`CANDIDATE`, `RECRUITER`, `INTERVIEWER`, `ADMIN`	High-level authentication boundary

Enum Name	Allowed Values	Usage / Context
`RecruiterRole`	`ADMIN`, `RECRUITER`, `HIRING_MANAGER`	Recruiter organizational permissions
`RecruiterStatus`	`ACTIVE`, `INVITED`, `SUSPENDED`	Recruiter seat lifecycle
`JobStatus`	`DRAFT`, `OPEN`, `PAUSED`, `CLOSED`	Job posting visibility state
`SectionType`	`DEFAULT`, `CUSTOM`	Application form section categorization
`QuestionType`	`SHORT_TEXT`, `LONG_TEXT`, `MULTIPLE_CHOICE`, `CHECKBOX`, `DROPDOWN`, `NUMBER`, `DATE`, `FILE_UPLOAD`	Dynamic form field data types
`ApplicationStatus`	`APPLIED`, `SCREENING`, `INTERVIEW`, `OFFER_STAGE`, `DOCUMENT_VERIFICATION`, `HIRED`, `REJECTED`, `HOLD`	Recruitment finite state machine
`InterviewType`	`VIDEO`, `PHONE`, `IN_PERSON`	Interview medium
`InterviewStatus`	`ASSIGNED`, `CONFIRMED`, `COMPLETED`, `CANCELLED`	Interview session state
`SlotStatus`	`AVAILABLE`, `BOOKED`, `CANCELLED`	Self-service calendar slots
`Recommendation`	`STRONG_HIRE`, `HIRE`, `LEANING_HIRE`, `NO_HIRE`	Interviewer scorecard decision
`OfferStatus`	`DRAFT`, `EXTENDED`, `ACCEPTED`, `DECLINED`, `EXPIRED`	Offer letter lifecycle
`DocumentStatus`	`PENDING`, `VERIFIED`, `REJECTED`	Compliance document status

---

3. Core Models & Field Catalog

3.1 Company (Tenant Root)

```
model Company {
  id                      String      @id @default(uuid())
  name                    String
  slug                    String      @unique
  logoUrl                 String?
  website                 String?
  industry                String?
  location                String?
  companySize             String?
  about                   String?
  careerPageCustomDomain  String?     @unique // CNAME custom domain
  careerPagePublished     Boolean     @default(true)
  createdAt               DateTime    @default(now())
  updatedAt               DateTime    @updatedAt

  recruiters              Recruiter[]
  jobs                    Job[]
  candidates              Candidate[]
  applications            Application[]
}
```

3.2 User & Account (Better-Auth Primitives)

```
model User {
  id            String       @id @default(uuid())
  name          String
  email         String       @unique
  emailVerified Boolean      @default(false)
  image         String?
  role          UserRole     @default(CANDIDATE)
  createdAt     DateTime     @default(now())
  updatedAt     DateTime     @updatedAt

  accounts      Account[]
  sessions      Session[]
  recruiter     Recruiter?
  interviewer   Interviewer?
  candidates    Candidate[]
  resumes       Resume[]
}
```

3.3 Job & Dynamic Form Schema

```
model Job {
  id              String            @id @default(uuid())
  companyId       String
  recruiterId     String
  title           String
  description     String
  location        String
  workMode        String            // On-site, Hybrid, Remote
  employmentType  String            // Full-time, Part-time, Contract
  salary          String?
  skills          String[]
  status          JobStatus         @default(OPEN)
  createdAt       DateTime          @default(now())

  company         Company           @relation(fields: [companyId], references: [id])
  recruiter       Recruiter         @relation(fields: [recruiterId], references: [id])
  applicationForm ApplicationForm?
  applications    Application[]
}

model ApplicationForm {
  id          String               @id @default(uuid())
  jobId       String               @unique
  title       String               @default("Application Form")
  createdAt   DateTime             @default(now())

  job         Job                  @relation(fields: [jobId], references: [id], onDelete:
Cascade)
  sections    ApplicationSection[]
}
```

3.4 Application & Interview Pipeline

```
model Application {
  id                  String            @id @default(uuid())
  companyId           String
  candidateId         String
  jobId               String
  status              ApplicationStatus @default(APPLIED)
  formSnapshot        Json?             // Snapshot of form schema at submit time
  screeningAnswers    Json?             // Answers mapped by questionId
  resumeSnapshotUrl   String?
  aiScore             Int?              // 0-100% resume match
  createdAt           DateTime          @default(now())
  updatedAt           DateTime          @updatedAt

  company             Company           @relation(fields: [companyId], references: [id])
  candidate           Candidate         @relation(fields: [candidateId], references:
[id])
  job                 Job               @relation(fields: [jobId], references: [id])
  interviews          Interview[]
  offers              Offer[]
  documents           Document[]
}

model Interview {
  id                  String            @id @default(uuid())
  applicationId       String
  interviewerId       String?
  scheduledAt         DateTime?
  durationMinutes     Int               @default(60)
  type                InterviewType     @default(VIDEO)
  status              InterviewStatus   @default(ASSIGNED)
  meetingId           String?           // Schedular / MeetX internal ID
  meetingLink         String?           // Fallback/candidate meeting link
  hostJoinUrl         String?           // Privileged interviewer host link
  candidateJoinUrl    String?           // Attendee join link
  candidateNotes      String?           // Public candidate agenda
  interviewerNotes    String?           // Private recruiter briefing
  createdAt           DateTime          @default(now())

  application         Application       @relation(fields: [applicationId], references:
[id])
  feedback            InterviewFeedback?
}

model InterviewFeedback {
  id                  String            @id @default(uuid())
  interviewId         String            @unique
  interviewerId       String
  ratings             Json              // Skill criteria ratings (1-5)
  culturalFitScore    Int?              // 1-5 cultural fit score
  feedback            String?           // Evaluation notes
  recommendation      Recommendation
  createdAt           DateTime          @default(now())
```

```
  updatedAt           DateTime          @updatedAt

  interview           Interview         @relation(fields: [interviewId], references:
[id])
}
```

3.5 Offer & Document Compliance

```
model Offer {
  id                  String            @id @default(uuid())
  applicationId       String
  status              OfferStatus       @default(DRAFT)
  salary              String
  startDate           DateTime
  expiresAt           DateTime?         // Used by hourly expiration cron
  pdfUrl              String?           // Cloudflare R2 file URL
  signature           String?
  createdAt           DateTime          @default(now())
  updatedAt           DateTime          @updatedAt

  application         Application       @relation(fields: [applicationId], references:
[id])
}

model Document {
  id                  String            @id @default(uuid())
  applicationId       String
  type                String            // GOVERNMENT_ID, DEGREE_CERTIFICATE
  status              DocumentStatus    @default(PENDING)
  rejectionReason     String?           // Mandatory on rejection
  verifiedAt          DateTime?
  verifiedBy          String?           // Recruiter ID
  createdAt           DateTime          @default(now())

  application         Application       @relation(fields: [applicationId], references:
[id])
  files               DocumentFile[]
}

model DocumentFile {
  id                  String            @id @default(uuid())
  documentId          String
  fileName            String
  fileUrl             String            // Cloudflare R2 URL
  fileKey             String
  mimeType            String?
  sizeBytes           Int?
  createdAt           DateTime          @default(now())

  document            Document          @relation(fields: [documentId], references: [id],
onDelete: Cascade)
}
```

---

4. Key Constraints, Indexes & Integrity Rules

1. **Multi-Tenant Composite Keys:** `Candidate` enforces unique compound constraint `@@unique([userId, companyId])` ensuring candidate profiles are scoped per tenant.
2. **Cascade Deletions:**
   - Deleting a `Job` cascades to `ApplicationForm`, `ApplicationSection`, and `ApplicationQuestion`.
   - Deleting a `Document` cascades to child `DocumentFile` records.
   - Deleting an `Interview` cascades to `InterviewSlot` records.
3. **SetNull Protection:** `Application.resume` enforces `onDelete: SetNull` preventing candidate account deletion from crashing historical job application records.
4. **Performance Indexes:**
   - `Company.slug` (B-tree unique index)
   - `Company.careerPageCustomDomain` (B-tree unique index for CNAME resolution)
   - `User.email` (B-tree unique index)
   - `Verification.value` (B-tree index for invite token lookup)