



Selection Structure

Mirza Mohammad Lutfe Elahi

Outline

- Control Structures
- Conditions, Relational, and Logic Operators
- The **if** Statement and Flowchart
- **if** with Compound Statements
- Nested **if** statements
- The **switch** Statement
- Operator Precedence, Complementing a Condition
- Common Programming Errors

Control Structure

- Control structure
 - Control the flow of execution in a program or a function
- Three kinds of control structures
 - **Sequence** (Compound Statement)
 - **Selection** (**if** and **switch** Statements)
 - **Repetition** [Chapter 5]
- **Selection control structure**
 - Chooses among alternative program statements

Compound Statement

- A group of statements bracketed by { and }
- Executed Sequentially
- A function body consists of a compound statement

{

statement₁ ;

statement₂ ;

. . .

statement_n ;

}



**Compound
Statement
Specifies
Sequential
Execution**

Conditions

- **Condition**

- An expression that evaluates to **false (0)** or **true (1)**

- Conditions are used in **if** statements, such as:

```
if (a >= b)
```

```
    printf("a is greater or equal to b");
```

```
else
```

```
    printf("a is less than b");
```

- The condition in the above example: **(a >= b)**

Relational and Equality Operators

Operator	Meaning	Type
<	less than	relational
>	greater than	relational
<=	less than or equal to	relational
>=	greater than or equal to	relational
==	equal to	equality
!=	not equal to	equality

Evaluate to either **false (0)** or **true (1)**

Relational and Equality Operators

x	i	MAX	y	item	mean	ch	num
-5	1024	1024	7	5.5	7.2	'M'	999

Operator	Condition	Value
<code><=</code>	<code>x <= 0</code>	true (1)
<code><</code>	<code>i < MAX</code>	false (0)
<code>>=</code>	<code>x >= y</code>	false (0)
<code>></code>	<code>item > mean</code>	false (0)
<code>==</code>	<code>ch == 'M'</code>	true (1)
<code>!=</code>	<code>num != MAX</code>	true (1)

Logical Operators

- Three Logical Operators

&& logical AND

|| logical OR

! logical NOT

- Truth Table for logical operators

A	B	(A && B)	(A B)	!A
true	true	true	true	false
true	false	false	true	false
false	true	false	true	true
false	false	false	false	true

Logical Expression

- Logical Expression
 - Condition that uses one or more logical operators

salary	children	temperature	humidity	n
1050	6	38.2	0.85	101

Logical Expression	Value
<code>salary < 1000 children > 4</code>	true (1)
<code>temperature > 35.0 && humidity > 0.90</code>	false (0)
<code>n >= 0 && n <= 100</code>	false (0)
<code>!(n >= 0 && n <= 100)</code>	true (1)

Comparing Characters

- We can also compare characters in C
 - Using the relational and equality operators

Expression	Value
'9' >= '0'	1 (true)
'a' < 'e'	1 (true)
'B' <= 'A'	0 (false)
'Z' == 'z'	0 (false)
'A' <= 'a'	1 (true)
ch >= 'a' && ch <= 'z'	ch is lowercase?

English Conditions as C Expression

English Condition	Logical Expression
x and y are greater than z	<code>x > z && y > z</code>
x is equal to 1 or 3	<code>x == 1 x == 3</code>
x is in the range min to max	<code>x >= min && x <= max</code>
x is outside the range z to y	<code>x < z x > y</code>



if Statement (One Alternative)

if (condition) statement_T ;

if **condition** evaluates to **true** then **statement_T** is executed; Otherwise, **statement_T** is skipped

Example:

if (x != 0.0)

 product = product * x ;

if Statement (Two Alternative)

if (condition) statement_T ;

else statement_F ;


if **condition** evaluates to **true** then **statement_T** is executed and **statement_F** is skipped; Otherwise, **statement_T** is skipped and **statement_F** is executed

Example:


if (x >= 0.0) printf("Positive");

else printf("Negative");

Flowcharts of if Statements



**Two Alternatives
if-else statement**



**One Alternative
if statement**

if with Compound Statements

```
if (ch >= 'A' && ch <= 'Z') {  
    printf("Letter '%c' is Uppercase\n", ch);  
    ch = ch - 'A' + 'a';  
    printf("Converted to lowercase '%c'\n", ch);  
}  
  
else {  
    printf("'%c' is not Uppercase letter\n", ch);  
    printf("No conversion is done\n");  
}
```

Hand Tracing an if Statement

```

if (x > y) {  /* switch x and y  */
    temp = x;   /* save x in temp  */
    x = y;      /* x becomes y      */
    y = temp;   /* y becomes old x */
}

```

if statement	x	y	temp	Effect
	12.5	5.0	?	
if (x>y) {				12.5>5.0 is true
temp = x ;			12.5	Store old x in temp
x = y ;	5.0			Store y in x
y = temp ;		12.5		Store old x in y

Nested if Statements

- Nested **if** statement
 - **if** statement inside another **if** statement
 - Program decisions with **multiple alternatives**
- Example

```
if (x > 0)
    num_pos = num_pos + 1;
else
    if (x < 0)
        num_neg = num_neg + 1;
    else /* x equals 0 */
        num_zero = num_zero + 1;
```

Multiple-Alternatives Decision Form

- The conditions are evaluated in sequence until a true condition is reached
- If a condition is true, the statement following it is executed, and the rest is skipped

```
if (x > 0)
    num_pos = num_pos + 1;
else if (x < 0)
    num_neg = num_neg + 1;
else /* x equals 0 */
    num_zero = num_zero + 1;
```

**More
Readable**

Sequence of if Statement

- All conditions are always tested (none is skipped)
- Less efficient than nested **if** for alternative decisions

```
if (x > 0)
    num_pos = num_pos + 1;
if (x < 0)
    num_neg = num_neg + 1;
if (x == 0)
    num_zero = num_zero + 1;
```

Less
Efficient
than
nested **if**

Implementing a Decision Table

Use a multiple-alternative **if** statement to implement a decision table that describes several alternatives


Salary Range (\$)	Base Tax	Rate
Salary < \$15,000	\$0	15%
\$15,000 ≤ Salary < \$30,000	\$2,250	18%
\$30,000 ≤ Salary < \$50,000	\$4,950	22%
\$50,000 ≤ Salary < \$80,000	\$9,350	27%
Salary ≥ \$80,000	\$17,450	33%

Computing the Tax from a Table

```
if (salary < 15000)
    tax = 0.15*salary;
else if (salary < 30000)
    tax = 2250 + (salary - 15000)*0.18;
else if (salary < 50000)
    tax = 4950 + (salary - 30000)*0.22;
else if (salary < 80000)
    tax = 9350 + (salary - 50000)*0.27;
else
    tax = 17450 + (salary - 80000)*0.33;
```

Road Sign Decision

- You are writing a program to control the warning signs at the exists of major tunnels.



Road Sign Nested if Statement

```
if (road_status == 'S')  
    if (temp > 0) {  
        printf("Wet roads ahead\n");  
        printf("Stopping time = 10 minutes\n");  
    }  
    else {  
        printf("Icy roads ahead\n");  
        printf("Stopping time = 20 minutes\n");  
    }  
else  
    printf("Drive carefully!\n");
```

C associates **else** with the most recent incomplete **if**

The switch Statement

- Can be used to select one of several alternatives
- Based on the value of a variable or simple expression
- Variable or expression may be of type **int** or **char**
- But not of type **double**
- **Example:** Simple Calculator

User Input	Operation
'+'	result = a + b;
'-'	result = a - b;
'*'	result = a * b;
'/'	result = a / b;

Example of switch Statement

```
switch (op) {           // op must be of type char
    case '+':
        result = a + b;
        break;
    case '-':
        result = a - b;
        break;
    case '*':
        result = a * b;
        break;
    case '/':
        result = a / b;
        break;
    default:
        printf("Error: unknown operation %c\n", op);
        return;         // to terminate the function
}
```

Explanation of switch Statement

- It takes the value of the character **op** and compares it to each of the cases in a top down approach.
- It stops after it finds the first **case** that is equal to the value of the variable **op**.
- It then starts to execute each line following the matching case till it finds a **break** statement.
- If no case is equal to the value of **op**, then the **default** case is executed.
- **default** is **optional**. If no other case is equal to the value of the *controlling expression* and there is no default case, the entire switch body is skipped.

More About The switch Statement

- One or more C statements may follow a **case** label.
- You do not need to enclose multiple statements in curly brackets after a **case** label.
- You cannot use a string as a **case** label.


case "Add" : is not allowed

- Do not forget **break** at the end of each alternative.
 - If the **break** statement is omitted then execution falls through into the next alternative.
- Do not forget the { } of the **switch** statement.


Nested if vs switch

- Nested **if** statements
 - More general than a **switch** statement
 - Can implement any multiple-alternative decision
 - Can be used to check ranges of values
 - Can be used to compare double values
- **switch** statement
 - Syntax is more readable
 - Implemented more efficiently in machine language
 - Use **switch** whenever there are few **case** labels
 - Use **default** for values outside the set of case labels

Testing Function `rect_diagonal`

Operator	Precedence
function calls	highest
! + - & (unary operators)	
* / %	
+ -	
< <= >= >	
== !=	
&& (logical AND)	
(logical OR)	
= (assignment operator)	lowest

Example Tree, Step-by-Step Evaluation



Short-Circuit Evaluation

- Stopping the evaluation of a logical expression as soon as its value can be determined
- Logical-OR expression of the form **(a || b)**
 - If **a** is **true** then **(a || b)** must be **true**, regardless of **b**
 - No need to evaluate **b**
 - However, if **a** is **false** then we should evaluate **b**
- Logical-AND expression of the form **(a && b)**
 - If **a** is **false** then **(a && b)** must be **false**, regardless of **b**
 - No need to evaluate **b**
 - However, if **a** is **true** then we should evaluate **b**
- Can be used to prevent division by zero

(divisor != 0 && x / divisor > 5)

Logical Assignment

- Use assignment to set **int** variables to **false** or **true**
- The **false** value is **zero**
- C accepts any **non-zero value** as **true**

Examples of Logical Assignment

```
senior_citizen = (age >= 65);
```

```
even = (n%2 == 0);
```

```
uppercase = (ch >= 'A' && ch <= 'Z');
```

```
lowercase = (ch >= 'a' && ch <= 'z');
```

```
is_letter = (uppercase || lowercase);
```


Complementing a Condition

- DeMorgan's Theorem**

$\neg(\text{expr1} \ \&\& \ \text{expr2}) == (\neg\text{expr1} \ || \ \neg\text{expr2})$

$\neg(\text{expr1} \ || \ \text{expr2}) == (\neg\text{expr1} \ \&\& \ \neg\text{expr2})$

Example	Equivalent Expression
<code>!(item == 5)</code>	<code>item != 5</code>
<code>!(age >= 65)</code>	<code>age < 65</code>
<code>!(n > 0 && n < 10)</code>	<code>n <= 0 n >= 10</code>
<code>!(x == 1 x == 3)</code>	<code>x != 1 && x != 3</code>
<code>!(x>y && (c=='Y' c=='y'))</code>	<code>(x<=y) (c!='Y' && c!='y')</code>

Common Programming Errors

- **Do Not write:** `if (0 <= x <= 4)`
 - `0 <= x` is either **false (0)** or **true (1)**
 - Then, **false(0) or true(1) are always <= 4**
 - Therefore, **(0 <= x <= 4) is always true**
- **Instead, write:** `if (0 <= x && x <= 4)`
- **Do Not write:** `if (x = 10)`
 - `=` is the **assignment operator**
 - **x becomes 10** which is **non-zero (true)**
 - **if (x = 10) is always true**
- **Instead, write:** `if (x == 10)`

More Common Errors

- In **if** statements:
 - Don't forget to parenthesize the **if (condition)**
 - Don't forget **{** and **}** in **if** with compound statements
- Correct pairings of **if** and **else** statements:
 - C matches **else** with the closest unmatched **if**
- In **switch** statements:
 - Make sure the controlling expression and case labels are of the same permitted type (**int** or **char**)
 - Remember to include the **default** case
 - Don't forget **{** and **}** for the **switch** statement
 - Don't forget the **break** at the end of each case