

# UNIT 1

Lecture 27 & 28

E R Model to Relational Mapping

# ER Model to Relational Mapping

Step 1: Mapping of Regular Entity Types

Step 2: Mapping of Weak Entity Types

Step 3: Mapping of Binary 1:1 Relation Types

Step 4: Mapping of Binary 1:N Relationship Types.


Step 5: Mapping of Binary M:N Relationship Types.

Step 6: Mapping of Multivalued attributes.

Step 7: Mapping of N-ary Relationship Types.

# Step 1: Mapping of Regular Entity Types.

1. For each regular (strong) entity type E in the ER schema, create a relation R that includes all the simple attributes of E.
2. Choose one of the key attributes of E as the primary key for R. If the chosen key of E is composite, the set of simple attributes that form it will together form the primary key of R.




**STUDENT (rollno, fname, middle, lname, sem, branch)**

## Step 2: Mapping of Weak Entity Types

1. For each weak entity type  $W$  in the ER schema with owner entity type  $E$ , create a relation  $R$  and include all simple attributes (or simple components of composite attributes) of  $W$  as attributes of  $R$ .
2. In addition, include as foreign key attributes of  $R$  the primary key attribute(s) of the relation(s) that correspond to the owner entity type(s).
3. The primary key of  $R$  is the combination of the primary key(s) of the owner(s) and the partial key of the weak entity type  $W$ , if any.

# Mapping of Weak Entity Sets



loan (loan-number, amount)

payment (loan-number, payment-number, payment-date, payment-amount)

# Step 3: Mapping of Binary 1:1 Relation Types


For each binary 1:1 relationship type  $R$  in the ER schema, identify the relations  $S$  and  $T$  that correspond to the entity types participating in  $R$ . There are three possible approaches :

**(1) Foreign Key approach:** Choose one of the relations- $S$ , say- and include a foreign key in  $S$  the primary key of  $T$ . It is better to choose an entity type with total participation in  $R$  in the role of  $S$ .

**(2) Merged relation option:** An alternate mapping of a 1:1 relationship type is possible by merging the two entity types and the relationship into a single relation. This may be appropriate when both participations are total.

**(3) Cross-reference or relationship relation option:** The third alternative is to set up a third relation  $R$  for the purpose of cross-referencing the primary keys of the two relations  $S$  and  $T$  representing the entity types.

# Step 3: Mapping of Binary 1:1 Relation Types



STUDENT

rollno	sname
1	RAM
2	SHYAM
3	MOHAN
4	GOPAL


PROJECT

pno	pname	rollno
121	P1	1
122	P2	2

**STUDENT (rollno, sname)**

**PROJECT (pno, pname, rollno)**

# Step 3: Mapping of Binary 1:1 Relation Types



STUDENTPROJECT

STUDENT

rollno	sname	pno
1	RAM	121
2	SHYAM	122
3	MOHAN	123
4	GOPAL	124

PROJECT


pno	pname	rollno
121	P1	1
122	P2	2
123	P3	3
124	P4	4

rollno	sname	pno	pname
1	RAM	121	P1
2	SHYAM	122	P2
3	MOHAN	123	P3
4	GOPAL	124	P4

**STUDENTPROJECT (rollno, sname, pno, pname)**



# Step 3: Mapping of Binary 1:1 Relation Types



STUDENT

rollno	sname
1	RAM
2	SHYAM
3	MOHAN
4	GOPAL

WORKS

rollno	pno
1	121
2	122

PROJECT

pno	pname
121	P1
122	P2
123	P3
124	P4

**STUDENT (rollno, sname)**


**WORKS (rollno, pno)**

**PROJECT (pno, pname)**

## Step 4: Mapping of Binary 1:N Relationship Types.

1. For each regular binary 1:N relationship type R, identify the relation S that represent the participating entity type at the N-side of the relationship type.
2. Include as foreign key in S the primary key of the relation T that represents the other entity type participating in R.
3. Include any simple attributes of the 1:N relation type as attributes of S.

# Step 4: Mapping of Binary 1:N Relationship Types.



STUDENT

rollno	sname	pno
1	RAM	121
2	SHYAM	122
3	MOHAN	
4	GOPAL	

PROJECT

pno	pname
121	P1
122	P2
123	P3
124	P4


**STUDENT (rollno, sname, pno)**

**PROJECT (pno, pname)**

# Step 5: Mapping of Binary M:N Relationship Types.

1. For each regular binary M:N relationship type R, create a new relation S to represent R.
2. Include as foreign key attributes in S the primary keys of the relations that represent the participating entity types; their combination will form the primary key of S.
3. Also include any simple attributes of the M:N relationship type (or simple components of composite attributes) as attributes of S.

# Step 5: Mapping of Binary M:N Relationship Types.



STUDENT

rollno	sname
1	RAM
2	SHYAM
3	MOHAN
4	GOPAL

WORKS

rollno	pno
1	121
1	122
2	121
2	122
2	123

PROJECT

pno	pname
121	P1
122	P2
123	P3
124	P4


**STUDENT (rollno, sname)**

**WORKS (rollno, pno)**

**PROJECT (pno, pname)**

# Step 6: Mapping of Multivalued attributes

1. For each multivalued attribute A, create a new relation R. This relation R will include an attribute corresponding to A, plus the primary key attribute K-as a foreign key in R-of the relation that represents the entity type of relationship type that has A as an attribute.
2. The primary key of R is the combination of A and K. If the multivalued attribute is composite, we include its simple components.




**STUDENT** (rollno, fname, middle, lname, sem, branch)

**STUDPHONE** (rollno, phone)

# Step 7: Mapping of N-ary Relationship Types

1. For each n-ary relationship type R, where  $n > 2$ , create a new relation S to represent R.
2. Include as foreign key attributes in S the primary keys of the relations that represent the participating entity types.
3. Also include any simple attributes of the n-ary relationship type (or simple components of composite attributes) as attributes of S.

# Step 5 : Complete E R Diagram



PERSON (pid, pname, address)


CAR (engineno, model, year)

OWNS (pid, engineno)

ACCIDENT (reportno, location, accdate)

PARTICIPATED (pid, engineno, reportno, damageamount)





EMPLOYEE									
FNAME	MINIT	LNAME	<u>SSN</u>	BDATE	ADDRESS	SEX	SALARY	SUPERSSN	DNO

DEPARTMENT			
DNAME	<u>DNUMBER</u>	MGRSSN	MGRSTARTDATE

DEPT_LOCATIONS	
<u>DNUMBER</u>	<u>DLOCATION</u>

PROJECT			
PNAME	<u>PNUMBER</u>	PLOCATION	DNUM

WORKS_ON		
<u>ESSN</u>	<u>PNO</u>	HOURS

DEPENDENT				
<u>ESSN</u>	<u>DEPENDENT_NAME</u>	SEX	BDATE	RELATIONSHIP

# GATE Questions

In an Entity-Relationship (ER) model, suppose  $R$  is a many-to-one relationship from entity set  $E1$  to entity set  $E2$ . Assume that  $E1$  and  $E2$  participate totally in  $R$  and that the cardinality of  $E1$  is greater than the cardinality of  $E2$ . Which one of the following is true about  $R$ ?

- (A) Every entity in  $E1$  is associated with exactly one entity in  $E2$ .
- (B) Some entity in  $E1$  is associated with more than one entity in  $E2$ .
- (C) Every entity in  $E2$  is associated with exactly one entity in  $E1$ .
- (D) Every entity in  $E2$  is associated with at most one entity in  $E1$ .

**[GATE 2018]**

# GATE Questions

An ER model of a database consists of entity types A and B. These are connected by a relationship R which does not have its own attribute. Under which one of the following conditions, can the relational table for R be merged with that of A?

- (A) Relationship R is one-to-many and the participation of A in R is total.
- (B) Relationship R is one-to-many and the participation of A in R is partial.
- (C) Relationship R is many-to-one and the participation of A in R is total.
- (D) Relationship R is many-to-one and the participation of A in R is partial.

**[GATE 2017]**

# GATE Questions

Consider an Entity-Relationship(ER) model in which entity sets E1 and E2 are connected by an m:n relationship R12. E1 and E3 are connected by a 1: n (1 on the side of E1 and n on the side of E3) relationship R13.


E1 has two single-valued attributes a11 and a12 of which a11 is the key attribute. E2 has two single-valued attributes a21 and a22 of which is a21 the key attribute. E3 has two single-valued attributes a31 and a32 of which a31 is the key attribute. The relationships do not have any attributes.

If a relational model is the derived from the above ER model, then the minimum number of relations that would be generated if all the relations are in 3NF is \_\_\_\_\_.

**[GATE 2015]**

# GATE Questions

Consider the following ER diagram.




The minimum number of tables needed to represent M, N, P, R1, R2 is  
(a) 2 (b) 3 (c) 4 (d) 5

**[GATE 2008]**

# GATE Questions

Consider the following ER diagram.



Which of the following is a correct attribute set for one of the tables for the correct answer to the above question?

- (a) {M1, M2, M3, P1}
- (b) {M1, P1, N1, N2}
- (c) {M1, P1, N1}
- (d) {M1, P1}

**[GATE 2008]**

# GATE Questions

Let E1 and E2 be two entities in an ER diagram with simple single-valued attributes. R1 and R2 are two relationships between E1 and E2, where R1 is one-to-many and R2 is many-to-many. R1 and R2 do not have any attributes of their own. What is the minimum number of tables required to represent this situation in the relational model?  
(a) 2   (b) 3   (c) 4   (d) 5

**[GATE 2005]**

For Video lecture on this topic please subscribe to my youtube channel.

The link for my youtube channel is

[https://www.youtube.com/channel/UCRWGtE76JITp1iim6aOTRuW?sub\\_confirmation=1](https://www.youtube.com/channel/UCRWGtE76JITp1iim6aOTRuW?sub_confirmation=1)