

Capturing from eth0

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

Apply a display filter ... <Ctrl-/>

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000000	192.168.52.128	139.84.142.141	NTP	90	NTP Version 4, client
2	0.134243229	139.84.142.141	192.168.52.128	NTP	90	NTP Version 4, server
3	20.713180395	192.168.52.128	192.168.52.2	DNS	71	Standard query 0x7fb2a AAAA example.com
4	20.713510146	192.168.52.128	192.168.52.2	DNS	71	Standard query 0x7fb2a AAAA example.com
5	20.801579849	192.168.52.2	192.168.52.128	DNS	103	Standard query response 0x7fb2a AAAA example.com AAAA 2606:479...
6	20.866602959	192.168.52.2	192.168.52.128	DNS	99	Standard query response 0x7fb2a AAAA example.com AAAA 2606:479...
7	20.869956439	192.168.52.128	104.20.23.154	TCP	74	57356 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSv...
8	20.994015743	104.20.23.154	192.168.52.128	TCP	60	80 → 57356 [SYN, ACK] Seq=0 Ack=1 Win=64240 Len=0 MSS=1460
9	20.994242305	192.168.52.128	104.20.23.154	TCP	54	57356 → 80 [ACK] Seq=1 Ack=1 Win=64240 Len=0
10	20.995787970	192.168.52.128	104.20.23.154	HTTP	129	GET / HTTP/1.1
11	20.996859834	104.20.23.154	192.168.52.128	TCP	60	80 → 57356 [ACK] Seq=1 Ack=76 Win=64240 Len=0
12	21.086911921	104.20.23.154	192.168.52.128	TCP	923	80 → 57356 [PSH, ACK] Seq=1 Ack=76 Win=64240 Len=869 [TCP PDU...
13	21.087017994	192.168.52.128	104.20.23.154	TCP	54	57356 → 80 [ACK] Seq=76 Ack=870 Win=63371 Len=0
14	21.092662237	104.20.23.154	192.168.52.128	HTTP	60	HTTP/1.1 200 OK (text/html)
15	21.092758170	192.168.52.128	104.20.23.154	TCP	54	57356 → 80 [ACK] Seq=76 Ack=875 Win=63366 Len=0
16	21.093361404	192.168.52.128	104.20.23.154	TCP	54	57356 → 80 [FIN, ACK] Seq=76 Ack=875 Win=63366 Len=0

Frame 9: 54 bytes on wire (432 bits), 54 bytes captured (432 bits) on 0
Ethernet II, Src: VMware_50:f9:47 (00:0c:29:50:f9:47), Dst: VMware_f
Internet Protocol Version 4, Src: 192.168.52.128, Dst: 104.20.23.154
Transmission Control Protocol, Src Port: 57356, Dst Port: 80, Seq: 1

0000 00 50 56 f4 15 d2 00 0c 29 50 f9 47 08 00 45 00 PV...)P
0010 00 28 29 43 40 00 40 06 9c b6 c0 a8 34 80 68 14 ()C@
0020 17 9a e0 0c 00 50 b4 2a 84 bb 37 af 35 43 50 10 P... 7
0030 fa f0 74 f1 00 00 t...

wireshark_eth0R27CW3.pcapng Packets: 388 Profile: Default

4:45 AM 24/09/2026

Home X kali-linux-2025.1c-vmware-... X

Capturing from eth0

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

tcp

No.	Time	Source	Destination	Protocol	Length	Info
7	20.869956439	192.168.52.128	104.20.23.154	TCP	74	57356 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM TSv...
8	20.994015743	104.20.23.154	192.168.52.128	TCP	60	80 → 57356 [SYN, ACK] Seq=0 Ack=1 Win=64240 Len=0 MSS=1460
9	20.994242305	192.168.52.128	104.20.23.154	TCP	54	57356 → 80 [ACK] Seq=1 Ack=1 Win=64240 Len=0
10	20.995787970	192.168.52.128	104.20.23.154	HTTP	129	GET / HTTP/1.1
11	20.996859834	104.20.23.154	192.168.52.128	TCP	60	80 → 57356 [ACK] Seq=1 Ack=76 Win=64240 Len=0
12	21.086911921	104.20.23.154	192.168.52.128	TCP	923	80 → 57356 [PSH, ACK] Seq=1 Ack=76 Win=64240 Len=869 [TCP PDU...
13	21.087017994	192.168.52.128	104.20.23.154	TCP	54	57356 → 80 [ACK] Seq=76 Ack=870 Win=63371 Len=0
14	21.092662237	104.20.23.154	192.168.52.128	HTTP	60	HTTP/1.1 200 OK (text/html)
15	21.092758170	192.168.52.128	104.20.23.154	TCP	54	57356 → 80 [ACK] Seq=76 Ack=875 Win=63366 Len=0
16	21.093361404	192.168.52.128	104.20.23.154	TCP	54	57356 → 80 [FIN, ACK] Seq=76 Ack=875 Win=63366 Len=0
17	21.093997545	104.20.23.154	192.168.52.128	TCP	60	80 → 57356 [ACK] Seq=875 Ack=77 Win=64239 Len=0
18	21.189778971	104.20.23.154	192.168.52.128	TCP	60	80 → 57356 [FIN, PSH, ACK] Seq=875 Ack=77 Win=64239 Len=0
19	21.189835039	192.168.52.128	104.20.23.154	TCP	54	57356 → 80 [ACK] Seq=77 Ack=876 Win=63366 Len=0

Frame 9: 54 bytes on wire (432 bits), 54 bytes captured (432 bits) on
Ethernet II, Src: VMware_50:f9:47 (00:0c:29:50:f9:47), Dst: VMware_f
Internet Protocol Version 4, Src: 192.168.52.128, Dst: 104.20.23.154
Transmission Control Protocol, Src Port: 57356, Dst Port: 80, Seq: 1

0000 00 50 56 f4 15 d2 00 0c 29 50 f9 47 08 00 45 00 PV...)P:
0010 00 28 29 43 40 09 40 06 9c b6 c0 a8 34 80 68 14 (.)C@...
0020 17 9a e0 0c 00 50 b4 2a 84 bb 37 af 35 43 50 10P*...7
0030 fa f0 74 f1 00 00 t...

Transmission Control Protocol: Protocol

Packets: 390 - Displayed: 13 (3.3%) Profile: Default

4:47 AM 24/09/2026

Wireshark · Packet 7 · eth0

▶ Frame 7: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface eth0, id 0

▶ Ethernet II, Src: VMware_50:f9:47 (00:0c:29:50:f9:47), Dst: VMware_f4:15:d2 (00:50:56:f4:15:d2)

▶ Internet Protocol Version 4, Src: 192.168.52.128, Dst: 104.20.23.154

▶ Transmission Control Protocol, Src Port: 57356, Dst Port: 80, Seq: 0, Len: 0

0000	00	50	56	f4	15	d2	00	0c	29	50	f9	47	08	00	45	00		PV		)P	G..E		
0010	00	3c	29	42	40	00	40	06	9c	a3	c9	a8	34	80	68	14		<.)B@·@·		4·h·			
0020	17	9a	e0	0c	00	50	b4	2a	84	ba	00	00	00	00	a0	02		·	·	P·*	·		
0030	fa	f0	75	05	00	00	02	04	05	b4	04	02	08	0a	4a	db		·	u	·	·	·	J·
0040	2a	b2	00	00	00	00	01	03	03	07								*	·	·	·	·	·

Internet Protocol Version 4 (ip), 20 bytes

✓ Show packet bytes

Layout: Vertical (Stacked)

× Close

Help

kali-linux-2025.1c-vmware-amd64 | Wireshark - Packets: eth0

▶ Frame 8: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface eth0, id 0
▶ Ethernet II, Src: VMware_f4:15:d2 (00:50:56:f4:15:d2), Dst: VMware_50:f9:47 (00:0c:29:50:f9:47)
▶ Internet Protocol Version 4, Src: 104.20.23.154, Dst: 192.168.52.128
▶ Transmission Control Protocol, Src Port: 80, Dst Port: 57356, Seq: 0, Ack: 1, Len: 0

0000	00 0c 29 50 f9 47 00 50	56 f4 15 d2 08 00 45 00	)P.G.P.V.....E.
0010	00 2c fe fe 00 00 80 06	c6 f6 68 14 17 9a c0 a8	h.....
0020	34 80 00 50 e0 0c 37 af	35 42 b4 2a 84 bb 60 12	4..P..7..5B*..^..
0030	fa f0 a2 1a 00 00 02 04	05 b4 00 00	

No.: 8 - Time: 20.994015743 - Source: 104.20.23.154 - Destination: 192.168.52.128 - Protocol: TCP - Length: 60 - Info: 80 → 57356 [SYN, ACK] Seq=0 Ack=1 Win=64240 Len=0 MSS=1460

✓ Show packet bytes Layout: Vertical (Stacked) ▼

× Close ? Help

