

[Home](#)

[DBMS](#)

[SQL](#)

[PL/SQL](#)

[SQLite](#)

[MongoDB](#)

[Cassandra](#)

[MySQL](#)

[Oracle](#)


[CouchDB](#)

SQL Aggregate Functions




- SQL aggregation function is used to perform the calculations on multiple rows of a single column of a table. It returns a single value.
- It is also used to summarize the data.

Types of SQL Aggregation Function



1. COUNT FUNCTION

- COUNT function is used to Count the number of rows in a database table. It can work on both numeric and non-numeric data types.
- COUNT function uses the COUNT(*) that returns the count of all the rows in a specified table. COUNT(*) considers duplicate and Null.



Syntax

```
COUNT(*)  
or  
COUNT( [ALL|DISTINCT] expression )
```

Sample table:**PRODUCT_MAST**

PRODUCT	COMPANY	QTY	RATE	COST
Item1	Com1	2	10	20
Item2	Com2	3	25	75
Item3	Com1	2	30	60
Item4	Com3	5	10	50
Item5	Com2	2	20	40
Item6	Cpm1	3	25	75
Item7	Com1	5	30	150
Item8	Com1	3	10	30
Item9	Com2	2	25	50
Item10	Com3	4	30	120

Example: COUNT()

```
SELECT COUNT(*)  
FROM PRODUCT_MAST;
```

Output:

10

Example: COUNT with WHERE

```
SELECT COUNT(*)  
FROM PRODUCT_MAST;  
WHERE RATE>=20;
```

Output:

7

Example: COUNT() with DISTINCT

```
SELECT COUNT(DISTINCT COMPANY)
FROM PRODUCT_MAST;
```

Output:

3

Example: COUNT() with GROUP BY

```
SELECT COMPANY, COUNT(*)
FROM PRODUCT_MAST
GROUP BY COMPANY;
```

Output:

Com1	5
Com2	3
Com3	2

Example: COUNT() with HAVING

```
SELECT COMPANY, COUNT(*)
FROM PRODUCT_MAST
GROUP BY COMPANY
HAVING COUNT(*)>2;
```

Output:

Com1	5
Com2	3

2. SUM Function

Sum function is used to calculate the sum of all selected columns. It works on numeric fields only.

Syntax

```
SUM()  
or  
SUM( [ALL|DISTINCT] expression )
```

Example: SUM()

```
SELECT SUM(COST)  
FROM PRODUCT_MAST;
```

Output:



670

Example: SUM() with WHERE

```
SELECT SUM(COST)  
FROM PRODUCT_MAST  
WHERE QTY>3;
```

Output:

320

Example: SUM() with GROUP BY

```
SELECT SUM(COST)  
FROM PRODUCT_MAST
```

```
WHERE QTY>3  
GROUP BY COMPANY;
```

Output:

Com1	150
Com2	170

Example: SUM() with HAVING

```
SELECT COMPANY, SUM(COST)  
FROM PRODUCT_MAST  
GROUP BY COMPANY  
HAVING SUM(COST)>=170;
```

Output:

Com1	335
Com3	170

3. AVG function

The AVG function is used to calculate the average value of the numeric type. AVG function returns the average of all non-Null values.

Syntax

```
AVG()  
or  
AVG( [ALL|DISTINCT] expression )
```

Example:

```
SELECT AVG(COST)
FROM PRODUCT_MAST;
```

Output:

67.00

4. MAX Function

MAX function is used to find the maximum value of a certain column. This function determines the largest value of all selected values of a column.

Syntax

```
MAX()
or
MAX( [ALL|DISTINCT] expression )
```

Example:

```
SELECT MAX(RATE)
FROM PRODUCT_MAST;
```

30

5. MIN Function

MIN function is used to find the minimum value of a certain column. This function determines the smallest value of all selected values of a column.

Syntax


```
MIN()
or
MIN( [ALL|DISTINCT] expression )
```

Example:

```
SELECT MIN(RATE)
FROM PRODUCT_MAST;
```

Output:

10

[< Prev](#)[Next >](#)

For Videos Join Our Youtube Channel: [Join Now](#)

Feedback

- Send your Feedback to feedback@javatpoint.com

Help Others, Please Share

Learn Latest Tutorials



Splunk



SPSS



Swagger



Transact-SQL



Tumblr



ReactJS



Regex



Reinforcement
Learning



R Programming



RxJS



React Native



Python Design
Patterns



Python Pillow



Python Turtle



Keras

Preparation



Aptitude



Logical
Reasoning
Reasoning



Verbal Ability
Verbal Ability




Interview
Questions
Interview Questions



Company
Interview
Questions
Company Questions

Trending Technologies



B.Tech / MCA





[.Net Framework tutorial](#)
[.Net](#)

[Python tutorial](#)
[Python](#)

[List of Programs](#)
[Programs](#)

[Control Systems tutorial](#)
[Control System](#)

[Data Mining Tutorial](#)
[Data Mining](#)

[Data Warehouse Tutorial](#)
[Data Warehouse](#)

