



# CSS Pseudo-elements

[< Previous](#)[Next >](#)

## What are Pseudo-Elements?

A CSS pseudo-element is used to style specified parts of an element.

For example, it can be used to:

- Style the first letter, or line, of an element
- Insert content before, or after, the content of an element

## Syntax

The syntax of pseudo-elements:

```
selector::pseudo-element {  
  property: value;  
}
```

## The ::first-line Pseudo-element

The `::first-line` pseudo-element is used to add a special style to the first line of a text.

The following example formats the first line of the text in all <p> elements:

## Example

```
p::first-line {  
  color: #ff0000;  
  font-variant: small-caps;  
}
```

Try it Yourself »

**Note:** The `::first-line` pseudo-element can only be applied to block-level elements.

The following properties apply to the `::first-line` pseudo-element:

- font properties
- color properties
- background properties
- word-spacing
- letter-spacing
- text-decoration
- vertical-align
- text-transform
- line-height
- clear

**Notice the double colon notation - `::first-line` versus `:first-line`**

The double colon replaced the single-colon notation for pseudo-elements in CSS3. This was an attempt from W3C to distinguish between **pseudo-classes** and **pseudo-elements**.

The single-colon syntax was used for both pseudo-classes and pseudo-elements in CSS2 and CSS1.

For backward compatibility, the single-colon syntax is acceptable for CSS2 and CSS1 pseudo-elements.

# The ::first-letter Pseudo-element

The `::first-letter` pseudo-element is used to add a special style to the first letter of a text.

The following example formats the first letter of the text in all `<p>` elements:

## Example

```
p::first-letter {  
  color: #ff0000;  
  font-size: xx-large;  
}
```

Try it Yourself »

**Note:** The `::first-letter` pseudo-element can only be applied to block-level elements.

The following properties apply to the `::first-letter` pseudo- element:

- font properties
- color properties
- background properties
- margin properties
- padding properties
- border properties
- text-decoration
- vertical-align (only if "float" is "none")
- text-transform
- line-height
- float
- clear

## Pseudo-elements and HTML Classes

Pseudo-elements can be combined with HTML classes:

## Example

```
p.intro::first-letter {  
  color: #ff0000;  
  font-size: 200%;  
}
```

[Try it Yourself »](#)

The example above will display the first letter of paragraphs with class="intro", in red and in a larger size.

---

## Multiple Pseudo-elements

Several pseudo-elements can also be combined.

In the following example, the first letter of a paragraph will be red, in an xx-large font size. The rest of the first line will be blue, and in small-caps. The rest of the paragraph will be the default font size and color:

## Example

```
p::first-letter {  
  color: #ff0000;  
  font-size: xx-large;  
}  
  
p::first-line {  
  color: #0000ff;  
  font-variant: small-caps;  
}
```

[Try it Yourself »](#)

---

## CSS - The ::before Pseudo-element

The `::before` pseudo-element can be used to insert some content before the content of an element.

The following example inserts an image before the content of each `<h1>` element:

## Example

```
h1::before {  
  content: url(smiley.gif);  
}
```

[Try it Yourself »](#)

---

## CSS - The ::after Pseudo-element

The `::after` pseudo-element can be used to insert some content after the content of an element.

The following example inserts an image after the content of each `<h1>` element:

## Example

```
h1::after {  
  content: url(smiley.gif);  
}
```

[Try it Yourself »](#)

---

## CSS - The ::marker Pseudo-element

The `::marker` pseudo-element selects the markers of list items.

The following example styles the markers of list items:

## Example

```
::marker {  
  color: red;  
  font-size: 23px;  
}
```

[Try it Yourself »](#)

---

## CSS - The ::selection Pseudo-element

The `::selection` pseudo-element matches the portion of an element that is selected by a user.

The following CSS properties can be applied to `::selection`: `color`, `background`, `cursor`, and `outline`.

The following example makes the selected text red on a yellow background:

## Example

```
::selection {  
  color: red;  
  background: yellow;  
}
```

[Try it Yourself »](#)

---

## Test Yourself With Exercises

### Exercise:

Set the background-color to red, of the first line of the paragraph.

```
<style>
    {
    background-color: red;
}
</style>
```

```
<body>
```

```
<p class="intro">
```

```
In my younger and more vulnerable years
my father gave me some advice that I've
been turning over in my mind ever since.
```

```
'Whenever you feel like criticizing anyone,' he told me,
'just remember that all the people in this world
haven't had the advantages that you've had.'
```

```
</p>
```

```
</body>
```



[Submit Answer »](#)

[Start the Exercise](#)

## All CSS Pseudo Elements

Selector	Example	Example description
<u>::after</u>	p::after	Insert something after the content of each <p> element

<u>::before</u>	p::before	Insert something before the content of each <p> element
<u>::first-letter</u>	p::first-letter	Selects the first letter of each <p> element
<u>::first-line</u>	p::first-line	Selects the first line of each <p> element
<u>::marker</u>	::marker	Selects the markers of list items
<u>::selection</u>	p::selection	Selects the portion of an element that is selected by a user

## All CSS Pseudo Classes

Selector	Example	Example description
<u>:active</u>	a:active	Selects the active link
<u>:checked</u>	input:checked	Selects every checked <input> element
<u>:disabled</u>	input:disabled	Selects every disabled <input> element
<u>:empty</u>	p:empty	Selects every <p> element that has no children
<u>:enabled</u>	input:enabled	Selects every enabled <input> element
<u>:first-child</u>	p:first-child	Selects every <p> elements that is the first child of its parent
<u>:first-of-type</u>	p:first-of-type	Selects every <p> element that is the first <p> element of its parent
<u>:focus</u>	input:focus	Selects the <input> element that has focus
<u>:hover</u>	a:hover	Selects links on mouse over
<u>:in-range</u>	input:in-range	Selects <input> elements with a value within a specified range
<u>:invalid</u>	input:invalid	Selects all <input> elements with an invalid value
<u>:lang(<i>language</i>)</u>	p:lang(it)	Selects every <p> element with a lang attribute value starting with "it"
<u>:last-child</u>	p:last-child	Selects every <p> elements that is the last child of its parent




<u>:last-of-type</u>	p:last-of-type	Selects every <p> element that is the last <p> element of its parent
<u>:link</u>	a:link	Selects all unvisited links
<u>:not(selector)</u>	:not(p)	Selects every element that is not a <p> element
<u>:nth-child(n)</u>	p:nth-child(2)	Selects every <p> element that is the second child of its parent
<u>:nth-last-child(n)</u>	p:nth-last-child(2)	Selects every <p> element that is the second child of its parent, counting from the last child
<u>:nth-last-of-type(n)</u>	p:nth-last-of-type(2)	Selects every <p> element that is the second <p> element of its parent, counting from the last child
<u>:nth-of-type(n)</u>	p:nth-of-type(2)	Selects every <p> element that is the second <p> element of its parent
<u>:only-of-type</u>	p:only-of-type	Selects every <p> element that is the only <p> element of its parent
<u>:only-child</u>	p:only-child	Selects every <p> element that is the only child of its parent
<u>:optional</u>	input:optional	Selects <input> elements with no "required" attribute
<u>:out-of-range</u>	input:out-of-range	Selects <input> elements with a value outside a specified range
<u>:read-only</u>	input:read-only	Selects <input> elements with a "readonly" attribute specified
<u>:read-write</u>	input:read-write	Selects <input> elements with no "readonly" attribute
<u>:required</u>	input:required	Selects <input> elements with a "required" attribute specified
<u>:root</u>	root	Selects the document's root element
<u>:target</u>	#news:target	Selects the current active #news element (clicked on a URL containing that anchor name)
<u>:valid</u>	input:valid	Selects all <input> elements with a valid value

:visited

a:visited

Selects all visited links

[< Previous](#)[Next >](#)

COLOR PICKER



Get certified  
by completing  
a CSS  
course today!



Get started

**Start**  
**DEVELOPING**  
Without Installations

Try Now

**BACKEND**  
Support Included



---

Report Error

Spaces

Upgrade

Newsletter

Get Certified

---

**Top Tutorials**

- HTML Tutorial
- CSS Tutorial
- JavaScript Tutorial
- How To Tutorial
- SQL Tutorial
- Python Tutorial
- W3.CSS Tutorial
- Bootstrap Tutorial
- PHP Tutorial
- Java Tutorial
- C++ Tutorial
- jQuery Tutorial

## Top References

- HTML Reference
- CSS Reference
- JavaScript Reference
- SQL Reference
- Python Reference
- W3.CSS Reference
- Bootstrap Reference
- PHP Reference
- HTML Colors
- Java Reference
- Angular Reference
- jQuery Reference

## Top Examples

- HTML Examples
- CSS Examples
- JavaScript Examples
- How To Examples
- SQL Examples
- Python Examples
- W3.CSS Examples
- Bootstrap Examples
- PHP Examples
- Java Examples
- XML Examples
- jQuery Examples

## Get Certified

- HTML Certificate
- CSS Certificate
- JavaScript Certificate
- Front End Certificate
- SQL Certificate
- Python Certificate
- PHP Certificate
- jQuery Certificate
- Java Certificate
- C++ Certificate
- C# Certificate
- XML Certificate

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie](#) and [privacy policy](#).

Copyright 1999-2023 by Refsnes Data. All Rights Reserved.  
W3Schools is Powered by W3.CSS.

