



PHP OOP - Static Methods

[< Previous](#)[Next >](#)

PHP - Static Methods

Static methods can be called directly - without creating an instance of the class first.

Static methods are declared with the `static` keyword:

Syntax

```
<?php
class ClassName {
    public static function staticMethod() {
        echo "Hello World!";
    }
}
?>
```

To access a static method use the class name, double colon (::), and the method name:

Syntax

```
ClassName::staticMethod();
```

Let's look at an example:

Example

```
<?php
class greeting {
    public static function welcome() {
        echo "Hello World!";
    }
}

// Call static method
greeting::welcome();
?>
```

[Try it Yourself »](#)

Example Explained

Here, we declare a static method: `welcome()`. Then, we call the static method by using the class name, double colon (`::`), and the method name (without creating an instance of the class first).

PHP - More on Static Methods

A class can have both static and non-static methods. A static method can be accessed from a method in the same class using the `self` keyword and double colon (`::`):

Example

```
<?php
class greeting {
    public static function welcome() {
        echo "Hello World!";
    }

    public function __construct() {
```

```
        self::welcome();
    }
}

new greeting();
?>
```

Try it Yourself »

Static methods can also be called from methods in other classes. To do this, the static method should be **public** :

Example

```
<?php
class greeting {
    public static function welcome() {
        echo "Hello World!";
    }
}

class SomeOtherClass {
    public function message() {
        greeting::welcome();
    }
}
?>
```

Try it Yourself »

To call a static method from a child class, use the **parent** keyword inside the child class. Here, the static method can be **public** or **protected** .

Example

```
<?php
class domain {
    protected static function getWebsiteName() {
        return "W3Schools.com";
    }
}
```

```
}  
}  
  
class domainW3 extends domain {  
    public $websiteName;  
    public function __construct() {  
        $this->websiteName = parent::getWebsiteName();  
    }  
}  
  
$domainW3 = new domainW3;  
echo $domainW3 -> websiteName;  
?>
```

Try it Yourself »

◀ Previous

Next ▶



COLOR PICKER





Get certified
by completing
a PHP
course today!



Get started

Visual Learner?



Be taught by an instructor
through our video tutorial!

WATCH NOW



Report Error

Spaces

[Upgrade](#)

[Newsletter](#)

[Get Certified](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)

JavaScript Certificate
Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate
jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

