

Name:

Course: DSA I Lab

Trimester & Year: Spring 2025

## UNITED INTERNATIONAL UNIVERSITY

Department of Computer Science and Engineering (CSE) CT-01

**Course Code: CSE 2216** 

Section: D
Total Marks: 20

ID:



35 mins

١	Questions		Mari	
ļ	Your company has introduced a special type of lottery. In this lottery, participants are randomly paired. After pairing, it is checked whether the names of the paired participants are <b>anagrams</b> of each other.			
	A name is considered an <b>anagram</b> of another the letters of the other name without adding			
Since a large number of people are participating in the lottery, you need to automate the verification process. Your task is to write a program that, given two names, determines whether one can be rearranged to form the other.				
	Input:			
	<ul> <li>The first line contains a string A — the name of the first participant.</li> <li>The second line contains a string B — the name of the second participant</li> <li>Both names consist of only uppercase and lowercase English letters. The comparison is case-sensitive, meaning "John" and "john" are considered different.</li> </ul>			
		ing "John" and "john" are considered		
	<ul> <li>different.</li> <li>Output: <ul> <li>Print "YES" (without quotes) if the Otherwise, print "NO".</li> </ul> </li> </ul>	ne names are anagrams of each other.		
	<ul> <li>different.</li> <li>Output: <ul> <li>Print "YES" (without quotes) if the Otherwise, print "NO".</li> </ul> </li> <li>Sample Input</li> </ul>			
	different.  Output:  • Print "YES" (without quotes) if the Otherwise, print "NO".  Sample Input  listen	ne names are anagrams of each other.  Sample Output  YES		
	<ul> <li>different.</li> <li>Output: <ul> <li>Print "YES" (without quotes) if the Otherwise, print "NO".</li> </ul> </li> <li>Sample Input <ul> <li>listen silent</li> </ul> </li> <li>Explanation: "listen" can be rearranged to form.</li> </ul>	ne names are anagrams of each other.  Sample Output  YES		
	<ul> <li>different.</li> <li>Output: <ul> <li>Print "YES" (without quotes) if the Otherwise, print "NO".</li> </ul> </li> <li>Sample Input <ul> <li>listen silent</li> </ul> </li> <li>Explanation: "listen" can be rearranged to for rahat</li> </ul>	ne names are anagrams of each other.  Sample Output  YES  orm "silent".		
	different.  Output:  Print "YES" (without quotes) if the Otherwise, print "NO".  Sample Input  listen silent  Explanation: "listen" can be rearranged to for rahat nasif  Marking Criteria	ne names are anagrams of each other.  Sample Output  YES  orm "silent".		
	Output:  • Print "YES" (without quotes) if the Otherwise, print "NO".  Sample Input  listen silent  Explanation: "listen" can be rearranged to for rahat nasif  Marking Criteria  Logic	ne names are anagrams of each other.  Sample Output  YES  orm "silent".		

Qι	uestions		Mar	
You are given two integer arrays <b>nums1</b> and <b>nums2</b> . Your task is to find their <b>intersection</b> , which consists of elements that appear in <b>both</b> arrays. Each element in the result must be <b>unique</b> , and you may return the result in <b>any order</b> .			10	
Input:				
<ul> <li>The first line contains an integer n — the size of the array nums1.</li> <li>The second line contains n space-separated integers nums1[i].</li> <li>The third line contains an integer m — the size of the array nums2.</li> <li>The fourth line contains m space-separated integers nums2[i]</li> </ul>				
	<ul> <li>Print a space-separated list of unique order of output elements does not m</li> </ul>	pace-separated list of unique integers that appear in both arrays. The output elements does not matter.		
s	Sample Input	Sample Output		
1 2 2	1 2 2 1 2	2		
5	195	4 9		
Marking Criteria				
٦	.ogic	4		
	<u></u>		1	
┞	mplementation	4		