AMRITA VISHWA VIDYAPEETHAM

श्रद्धावान् लभते ज्ञानम्

23CSE203

DATA STRUCTURES AND ALGORITHM

Submitted by	
Name	B.SAI HASHINI
Roll.no	AV.SC.U4CSE25101
Section	CSE-B

SUBMITTED TO	DR. RAJ KUMAR BATCHU
DESIGNATION	ASST.PROFFESSOR (Sl. Grade)
DEPARTMENT	SCHOOL OF COMPUTING

Credit	5

Index

S.no	Title	Page.no	Remark
1.	**A)** A rocket launch system displays a countdown before launch. Instead of using loop, implement the countdown using recursion. Write a recursive program to display a countdown from n to 1 followed by launch. **B)** Bank calculates the growth of an investment using compound intrest. The formula requires calculating powers, which can be implemented recursively. Write a recursive program to calculate p^n(power), where P=principal growth factor, n=no.of years. **C)** Write a recursive progrsm to print the first n terms of Fibonacci series **D)** An hr department stores employee ids in a list develop a recursive program to search for a given employee id. Write a recursive function to search for an employee id in the list. **E)** In a logistics the no.of possible ways to arrange n different parcels calculate using the factorial (n!). develop a recursive program to calculate the factorial of given number.	4-13	
2.	**A)** write a python program to perform linear search on the given input **B)** Write a python program to perform binary search on the given	14-18	

	input. Verify by taking sorted array and unsorted array as a list.		
3.	A) write a python program to implement bubble sort, where the elements are taken from user. B) write a python program to implement selection sort, where the elements are taken from user. C) write a python program to implement insertion sort, where the elements are taken from user.	19-23	
4.	A) write a python program to implement merge sort, where the elements are taken from user. B) write a python program to implement quick sort, where the elements are taken from user.	23-29	
5.	A)Write a python program to implement a single linked list with the below operations: A.create linked list B.insert at beginning C.Insert at end D.Insert at index E.Delete by value F.Delete first node G.Delete last node H.Count number of nodes I.Display/traverse J.exit B)Write a python program to implement a double linked list with the below operations: A.create linked list B.insert at beginning C.Insert at end D.Insert at index E.Delete by value	30-60	

	F.Delete first node G.Delete last node H.Count number of nodes I.Display/traverse J.exit C) Write a python program to implement a circular linked list with the below operations: A.create linked list B.insert at beginning C.Insert at end D.Insert at index E.Delete by value F.Delete first node G.Delete last node H.Count number of nodes I.Display/traverse J.exit		
6.	A) Write a python program to implement stack operations such as push, pop, peek, display using an array. B) Write a python program to implement stack operations such as push, pop, peek, display using linked list.	61-68	
7.	A) Write a python program to implement queue and its operations such as enqueue, dequeue, peek and display with a menu driven approach using an array. B) Write a python program to implement queue and its operations such as enqueue, dequeue, peek and display with a	69-74	

	menu driven approach using linked list.		
8.	a) Write a python program to implement a binary tree with its operations using array. b) Write a python program to implement a binary tree with its operations using linked list.	74-	
9.	a) Write a python program to implement a binary search tree with its operations and traversals.		

Week-1

A) Aim: A rocket launch system displays a countdown before launch. Instead of using loop, implement the countdown using recursion. Write a recursive program to display a countdown from n to 1 followed by launch.


Program:

```python
#av.sc.u4cse25101
def countdown(n):
    if n == 0:
        print("launch")
    else:
        print(n)
        countdown(n-1)

countdown(5)
```

Output:

```
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 1>
ktop/textbooks/DSA Lab/week 1/LAB1.A.py"
5
4
3
2
1
launch
```



Explanation:

- It takes a number as input from the user and stores it in num.
- It creates a function named launch().
- It starts the countdown from 10 by assigning i = 10.
- It prints the value of i as long as num <= i.
- It decreases the value of i by 1 after each iteration.

- When the loop ends, it prints "Rocket launched" and executes the function using launch().
- For negative input, the function keeps decreasing instead of reaching 0, causing infinite recursion and eventually a `Recursion Error`.

Error table:

s.no	Error obtained	Rectification
1.	Infinite loop	Iteration at correct place
2.	Calling function at wrong place	Placed with correct syntax

B) Aim: Bank calculates the growth of an investment using compound intrest. The formula requires calculating powers, which can be implemented recursively. Write a recursive program to calculate p^n(power), where P=principal growth factor, n=no.of years.

Program:

C: > Users > SAI HASHINI > OneDrive > Desktop > textbooks > DSA Lab > week 1 > lab1.B.py > ..

```python
#av.sc.u4cse25101
def power(p, n):
    if n == 0:
        return 1
    elif n < 0:
        return 1 / power(p, -n)
    else:
        return p * power(p, n - 1)

principal = 1000
rate = 0.05
years = -3


amount = principal * power(1 + rate, years)

print("Final amount after", years, "years is:", amount)

```

Output:

```
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 1>
Final amount after 3 years is: 1157.6250000000002
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 1>
```



Explanation:

- The program takes the principal growth factor p and number of years n as input.
- It defines a recursive function power(p, n).
- If n is 0, the function returns 1 (base case).
- Otherwise, it returns p * power(p, n-1).
- The recursive calls continue until n becomes 0.
- The final value of p^n is displayed as the output.

- For a negative exponent, calculate the reciprocal instead of continuing recursion downward indefinitely.
- Error table:

s.no	Error obtained	Rectification
1.	Return 0	Return 1
2.	print	return

C) Aim: Write a recursive program to print the first n terms of fibanocci series

Program:

```
#av.sc.u4cse25101
def fibonacci(n):
    if n < 0:
        return "Number of terms cannot be negative"
    if n == 0:
        return 0
    elif n == 1:
        return 1
    else:
        return fibonacci(n - 1) + fibonacci(n - 2)

n = int(input("Enter number of terms: "))

for i in range(n):
    print(fibonacci(i), end=" ")
```

Output:

```
Enter number of terms: 5
0 1 1 2 3
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 1>
```

```
Enter number of terms: -3
PS C:\Users\SAI HASHINI\AppData\Local\Programs\Microsoft VS Code>
```

Explanation:

- For entering the number as input from user we defined as n
- We declared variable for formula.
- If input number is less than one then it return “1”
- Or it will goes under fibanocci iteration.
- If x is not present in the list, recursion reaches the end and returns `False`.

Error:

s.no	Error obtained	Rectification
1.	Forgot to declare n<=1	rectified
2.	Formula mistake	rectified

D) Aim: An hr department stores employee ids in a list develop a recursive program to search for a given employee id. Write a recursive function to search for an employee id in the list.

Program:

```python
#av.sc.u4cse25101
def search(a, x, i=0):
    if i == len(a):
        return False
    if a[i] == x:
        return True
    return search(a, x, i + 1)


ids = [101, 205, 310, 415, 520]

print(search(ids, 310))
```

Output:

```
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 1> pyth
True
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 1> 310
310
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 1>
```

```
PS C:\Users\SAI HASHINI\AppData\Local\Programs\Microsoft VS Code> & "C:\Program Files\Python314
\python.exe" "c:/Users/SAI HASHINI/OneDrive/Desktop/textbooks/DSA Lab/week 1/lab1.c.py"
False
```

Explanation:

- The program creates a function to search for an employee ID in a list.
- It checks one employee ID at a time, starting from the first ID.
- If the entered employee ID matches the current ID, it returns True.
- If it does not match, the function moves to the next ID using recursion.
- If all employee IDs are checked and no match is found, it returns False.

- Finally, the program displays "Employee ID found." if the ID exists; otherwise, it displays "Employee ID not found."
- Error:

s.no	Error obtained	Rectification
1.	Emp lst	Emp_list
2.	print	Return

E) Aim: In a logistics the no.of possible ways to arrange n different parcels calculate using the factorial (n!). develop a recursive program to calculate the factorial of given number.

Program:

```
#av.sc.u4cse25101
def factorial(n):
    if n < 0:
        return"not defined"
    if n == 0 or n == 1:
        return 1
    else:
        return n * factorial(n - 1)
num = int(input("Enter a number: "))
result = factorial(num)
print(f"The factorial of {num} is {result}")

```

Output:

```
Enter a number: 5
The factorial of 5 is 120
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 1>
```

```
PS C:\Users\SAI HASHINI\AppData\Local\Programs\Microsoft VS Code> & "C:\Progr
\python.exe" "c:/Users/SAI HASHINI/OneDrive/Desktop/textbooks/DSA Lab/week 1/
Enter a number: -8
The factorial of -8 is not defined
PS C:\Users\SAI HASHINI\AppData\Local\Programs\Microsoft VS Code>
```

Explanation:

- The program defines a recursive function fact() to calculate the factorial of a number.
- It takes a number as input from the user.
- If the number is 1, the function returns 1 (base case).
- Otherwise, it multiplies the number by the factorial of the previous number (n-1).
- The recursive calls continue until the number becomes 1.
- Finally, the program prints the factorial of the given number.
- Negative numbers do not have a factorial, so the program should handle them separately instead of recursing forever.

Error table:

s.no	Error obtained	Rectification
1.	n+1	n-1
2.	Syntax error	Rectified

WEEK-2

A) AIM: Write a python program to perform linear search on the given input.

Program:

```
def linear_search_sorted(arr,key):
    for i in range(len(arr)):
        if arr[i]==key:
            return i
        elif arr[i]> key:
            return -1
    return -1

arr = [1,4,6,8,9,12,15,16,19]
key = int(input("enter the element to be found:"))
result=linear_search_sorted(arr,key)

if result==-1:
    print("element not found")
else:
    print(f"element found at index : {result} ")
```

Output:

```
enter the element to be found:12
element found at index : 5
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 2>
```

```
enter the element to be found:20
element not found
```

Explanation:

- In linear search we can append elements in sorted or unsorted way also.
- After placing the target we need to check the all the elements in a order.
- The time complixity is O(n).
- The target element may be found at beginning or last or at middle.
- If the key is greater than every element in the sorted array, the search reaches the end and returns `-1`.

Error table:

s.no	Error obtained	Rectification
1.	Return placed in wrong place	Corrected later
2.	Calling the function	Rectified

B) Aim: Write a python program to perform binary search on the list.

Program: Unsorted

```python
#av.sc.u4cse25101
def binary_search(arr, key):
    i, j = 0, len(arr) - 1
    while i <= j:
        mid = (i + j) // 2
        if arr[mid] == key:
            return mid
        elif arr[mid] < key:
            i = mid + 1
        else:
            j = mid - 1
    return -1
arr = [15, 3, 9, 20, 7, 12, 18]
arr.sort()
print("Sorted array:", arr)
key = int(input("Enter the element to search: "))
result = binary_search(arr, key)
if result != -1:
    print(f"Element found at index {result} in the sorted array")
else:
    print(f"Element not found in the array")
```

Output:

```
Sorted array: [3, 7, 9, 12, 15, 18, 20]
Enter the element to search: 15
Element found at index 4 in the sorted array
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 2>
```

```
Sorted array: [3, 7, 9, 12, 15, 18, 20]
Enter the element to search: 25
Element not found in the array
PS C:\Users\SAI HASHINI>
```

Program: Sorted

```python
#av.sc.u4cse25101
def binary_search(arr, key):
    i, j = 0, len(arr) - 1
    while i <= j:
        mid = (i + j) // 2
        if arr[mid] == key:
            return mid
        elif arr[mid] < key:
            i = mid + 1
        else:
            j = mid - 1
    return -1
arr = [3,7,9,12,15,18,20]
key = int(input("Enter the element to search: "))
result = binary_search(arr, key)
if result != -1:
    print(f"Element found at index {result} in the
else:
    print(f"Element not found in the array")
```

Output:

```
Enter the element to search: 12
Element found at index 3 in the sorted array
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 2>
```

```
Enter the element to search: 2
Element not found in the array
```

Explanation:

- The binary search should always executed in sorted order.
- Either it can be ascending or descending order.
- So the program is in unsorted order so we need to do sorting first later the binary search is executed.

- Error table:

s.no	Error obtained	Rectification
1.	Mistakes in main logic	Rectified
2.	Errors in conditions	Rectified

WEEK-3

A) AIM: write a python program to implement bubble sort, where the elements are taken from user.

Program:

```python
def bubble_sort(arr):
    n = len(arr)

    for i in range(n - 1):
        for j in range(n - i - 1):
            if arr[j] > arr[j + 1]:
                arr[j], arr[j + 1] = arr[j + 1], arr[j]


n = int(input("Enter no. of elements: "))

if n <= 0:
    print("Number of elements must be positive")
else:
    arr = []

    print("Enter elements:")
    for i in range(n):
        arr.append(int(input()))

    bubble_sort(arr)

    print("Sorted Array:")
    for element in arr:
        print(element, end=" ")
```

Output:

```
Enter no. of elements: 5
Enter elements:
12
25
46
7
97
Sorted Array:
7 12 25 46 97
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 3>
```

```
Enter no. of elements: 0
Number of elements must be positive
PS C:\Users\SAI HASHINI\AppData\Local\Programs\Microsoft VS Code>
```

Explanation:

- Bubble sort is a sorting technique used to arrange elements in **ascending or descending order**.
- The program may contain elements in **unsorted order**, so adjacent elements are compared and swapped if they are in the wrong order.
- This process is repeated for multiple passes until the **entire array is sorted**.
- For `n = 0`, the program now prints the error message without trying to use an undefined `arr`.

Error table:

s.no	Error obtained	Rectification
1.	Mistakes in main logic	Rectified
2.	Errors in conditions	Rectified

B) AIM: write a python program to implement insertion sort, where the elements are taken from user.

Program:

```python
#AV.SC.U4CSE25101
def insertion_sort(arr):
    n = len(arr)
    for i in range(1, n):
        key = arr[i]
        j = i - 1

        while j >= 0 and arr[j] > key:
            arr[j + 1] = arr[j]
            j = j - 1

        arr[j + 1] = key
    return arr
n = int(input("Enter no. of elements: "))
arr = []
print("Enter the elements:")
for i in range(n):
    arr.append(int(input()))
insertion_sort(arr)
print("Sorted Array:")
for element in arr:
    print(element, end=" ")
```

Output:

```
Enter no. of elements: 0
Enter the elements:
Sorted Array:
PS C:\Users\SAI HASHINI\AppData\Local\Programs\Microsoft VS Code>
```

```
Enter no. of elements: 5
Enter the elements:
24
4
12
75
35
Sorted Array:
4 12 24 35 75
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 3>
```

Explanation:

- Insertion sort is a sorting technique used to arrange elements in **ascending or descending order**.
- The program takes one element at a time and **inserts it into its correct position** in the already sorted part.
- This process is repeated until **all elements are sorted**.
- When the number of elements is zero, the array is empty and insertion sort simply performs no iterations.

Error table:

s.no	Error obtained	Rectification
1.	Mistakes in main logic	Rectified
2.	Errors in conditions	Rectified

C) AIM: write a python program to implement selection sort, where the elements are taken from user.

Program:

```python
#AV.SC.U4CSE25101
def selection_sort(arr):
    n = len(arr)

    for i in range(n - 1):
        min_index = i

        for j in range(i + 1, n):
            if arr[j] < arr[min_index]:
                min_index = j

        arr[i], arr[min_index] = arr[min_index], arr[i]
n = int(input("Enter no. of elements: "))
arr = []
print("Enter the elements:")
for i in range(n):
    arr.append(int(input()))
print("Original Array:", arr)
selection_sort(arr)
print("Sorted Array:", arr)
```

Output:

```
Enter no. of elements: 5
Enter the elements:
24
76
35
12
9
Original Array: [24, 76, 35, 12, 9]
```

```
Enter no. of elements: 0
Enter the elements:
Original Array: []
Sorted Array: []
```

Explanation:

- Selection sort is a sorting technique used to arrange elements in **ascending or descending order**.
- The program finds the **smallest element** from the unsorted part and swaps it with the first element of that part.
- This process is repeated until the **entire array is sorted**.
- When `n = 0`, the array is empty and selection sort performs no iterations, so the program runs normally.

Error table:

s.no	Error obtained	Rectification
1.	Mistakes in main logic	Rectified
2.	Errors in conditions	Rectified

WEEK-3

A) AIM: write a python program to implement bubble sort, where the elements are taken from user.

Program:

```python
def bubble_sort(arr):
    n = len(arr)

    for i in range(n - 1):
        for j in range(n - i - 1):
            if arr[j] > arr[j + 1]:
                arr[j], arr[j + 1] = arr[j + 1], arr[j]


n = int(input("Enter no. of elements: "))

if n <= 0:
    print("Number of elements must be positive")
else:
    arr = []

    print("Enter elements:")
    for i in range(n):
        arr.append(int(input()))

    bubble_sort(arr)

    print("Sorted Array:")
    for element in arr:
        print(element, end=" ")
```

Output:

```
Enter no. of elements: 5
Enter elements:
12
25
46
7
97
Sorted Array:
7 12 25 46 97
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA Lab\week 3>
```

```
Enter no. of elements: 0
Number of elements must be positive
PS C:\Users\SAI HASHINI\AppData\Local\Programs\Microsoft VS Code>
```

Explanation:

- Bubble sort is a sorting technique used to arrange elements in **ascending or descending order**.
- The program may contain elements in **unsorted order**, so adjacent elements are compared and swapped if they are in the wrong order.
- This process is repeated for multiple passes until the **entire array is sorted**.
- For `n = 0`, the program now prints the error message without trying to use an undefined `arr`.

Error table:

s.no	Error obtained	Rectification
1.	Mistakes in main logic	Rectified
2.	Errors in conditions	Rectified

WEEK-4

A) AIM: write a python program to implement merge sort, where the elements are taken from user.

Program:

```
av.sc.u4cse25101
def merge_sort(arr):
    if len(arr) > 1:
        mid = len(arr) // 2
        left = arr[:mid]
        right = arr[mid:]

        merge_sort(left)
        merge_sort(right)

        i = j = k = 0

        while i < len(left) and j < len(right):
            if left[i] < right[j]:
                arr[k] = left[i]
                i += 1
            else:
                arr[k] = right[j]
                j += 1
            k += 1

        while i < len(left):
            arr[k] = left[i]
            i += 1
            k += 1

        while j < len(right):
            arr[k] = right[j]
            j += 1
            k += 1


n = int(input("Enter number of elements: "))
arr = []

print("Enter elements:")
```

```
print("Enter elements:")
for i in range(n):
    arr.append(int(input()))

merge_sort(arr)

print("Sorted Array:")
for element in arr:
    print(element, end=" ")
```

Output:

```
PS C:\Users\SAI HASHINI\OneDrive\Desktop\text
Enter number of elements: 7
Enter elements:
10
25
9
16
7
26
14
Sorted Array:
7 9 10 14 16 25 26
```

Explanation:

- **Merge Sort** divides the array into two halves repeatedly until each part has one element.
- The smaller arrays are then **sorted recursively**.
- The `while` loop compares elements of the left and right arrays.
- The smaller element is placed into the original array in sorted order.
- Finally, the remaining elements are added, giving the **completely sorted array**.

Error table:

s.no	Error obtained	Rectification
1.	Mistakes in main logic	Rectified
2.	Errors in conditions	Rectified

B) AIM: write a python program to implement Quick sort, where the elements are taken from user.

Program:

```python
AV.SC.U4CSE25101
def quick_sort(a, low, high):
    if low < high:
        i = low
        j = high
        pivot = low

        while i < j:
            while i < len(a) and a[i] <= a[pivot]:
                i += 1
            while a[j] > a[pivot]:
                j -= 1

            if i < j:
                a[i], a[j] = a[j], a[i]

        a[j], a[pivot] = a[pivot], a[j]

        quick_sort(a, low, j - 1)
        quick_sort(a, j + 1, high)


a = list(map(int, input("Enter numbers to sort: ").split()))

quick_sort(a, 0, len(a) - 1)

print("Sorted Array:")
print(a)
```

Output:

```
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA\w
Enter numbers to sort: 10 25 9 16 7 26 14
Sorted Array:
[7, 9, 10, 14, 16, 25, 26]
```

Explanation:

- **Quick Sort** selects an element as the **pivot** and divides the array around it.
- Elements smaller than the pivot are moved to the **left**, and larger elements to the **right**.
- The pivot is placed in its correct position.

- Quick Sort is then applied **recursively** to the left and right parts.
- This process continues until the entire array is **sorted**.

Error table:

s.no	Error obtained	Rectification
1.	Mistakes in main logic	Rectified
2.	Errors in conditions	Rectified

Week-5

A) Write a python program to implement a single linked list with the below operations:

A. create linked list

B. insert at beginning

C. Insert at end

D. Insert at index

E. Delete by value

F. Delete first node

G. Delete last node

H. Count number of nodes

I. Display/traverse

J. exit

Program:

```
class Node:
    def _init_(self, data):
        self.data = data
        self.next = None


class SLL:
    def _init_(self):
        self.head = None

    # 1. Create Linked List
    def create(self):
        n = int(input("Enter number of nodes: "))
```

```
        for i in range(n):
            data = int(input("Enter data: "))
            new_node = Node(data)

            if self.head is None:
                self.head = new_node
            else:
                temp = self.head
                while temp.next is not None:
                    temp = temp.next
                temp.next = new_node

        print("Linked List created successfully")

    # 2. Insert at Beginning
    def insert_beginning(self):
        data = int(input("Enter data: "))

        new_node = Node(data)

        new_node.next = self.head
        self.head = new_node
        print(f"Inserted {data} at the beginning.")

    # 3. Insert at End
    def insert_end(self):
        data = int(input("Enter data: "))

        new_node = Node(data)

        if self.head is None:
            self.head = new_node
            return

        temp = self.head

        while temp.next is not None:
            temp = temp.next

        temp.next = new_node
        print(f"Inserted {data} at the end.")

    # 4. Insert at Index
    def insert_at_index(self):
        data = int(input("Enter data: "))
        index = int(input("Enter index: "))
```

```
        if index < 0:
            print("Invalid index")
            return

        if index == 0:
            new_node = Node(data)
            new_node.next = self.head
            self.head = new_node
            return

        temp = self.head

        for i in range(index - 1):
            if temp is None:
                print("Index out of range")
                return
            temp = temp.next

        if temp is None:
            print("Index out of range")
            return

        new_node = Node(data)

        new_node.next = temp.next
        temp.next = new_node
        print(f"Inserted {data} at index {index}.")

    # 5. Delete from Beginning
    def delete_beginning(self):

        if self.head is None:
            print("List is empty")
            return

        self.head = self.head.next
        print(f"Deleted beginning node.")

    # 6. Delete from End
    def delete_end(self):

        if self.head is None:
            print("List is empty")
            return
```

```
        if self.head.next is None:
            self.head = None
            return

        temp = self.head

        while temp.next.next is not None:
            temp = temp.next

        temp.next = None
        print(f"Deleted last node.")

    # 7. Delete from Index
    def delete_at_index(self):

        index = int(input("Enter index: "))

        if self.head is None:
            print("List is empty")
            return

        if index < 0:
            print("Invalid index")
            return

        if index == 0:
            self.head = self.head.next
            return

        temp = self.head

        for i in range(index - 1):
            if temp.next is None:
                print("Index out of range")
                return
            temp = temp.next

        if temp.next is None:
            print("Index out of range")
            return

        temp.next = temp.next.next
        print(f"Deleted the node value.")

    # 8. Count Nodes
    def count_nodes(self):
```

```
        count = 0
        temp = self.head

        while temp is not None:
            count += 1
            temp = temp.next

        print("Number of nodes:", count)
    # 9. Display
    def display(self):

        if self.head is None:
            print("List is empty")
            return

        temp = self.head

        while temp is not None:
            print(temp.data, end=" -> ")
            temp = temp.next

        print("None")




# Main Program

sll = SLL()

while True:

    print("\n----- SINGLY LINKED LIST -----")
    print("1. Create Linked List")
    print("2. Insert at Beginning")
    print("3. Insert at End")
    print("4. Insert at Index")
    print("5. Delete from Beginning")
    print("6. Delete from End")
    print("7. Delete from Index")
    print("8. Count Number of nodes")
    print("9. Display")
    print("10. Exit")

    choice = int(input("Enter your choice: "))
```

```
if choice == 1:
    sll.create()

elif choice == 2:
    sll.insert_beginning()

elif choice == 3:
    sll.insert_end()

elif choice == 4:
    sll.insert_at_index()

elif choice == 5:
    sll.delete_beginning()

elif choice == 6:
    sll.delete_end()

elif choice == 7:
    sll.delete_at_index()

elif choice == 8:
    sll.count_nodes()

elif choice == 9:
    sll.display()

elif choice == 10:
    print("Exiting from the program...")
    break

else:
    print("Invalid choice")
```

Output:

```
----- SINGLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 1
Enter number of nodes: 4
Enter data: 12
Enter data: 24
Enter data: 56
Enter data: 78
Linked List created successfully

----- SINGLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 9
12 -> 24 -> 56 -> 78 -> None

----- SINGLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 2
Enter data: 5
```

```
Enter data: 5
Inserted 5 at the beginning.

----- SINGLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 9
5 -> 12 -> 24 -> 56 -> 78 -> None

----- SINGLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 3
Enter data: 89
Inserted 89 at the end.

----- SINGLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 9
5 -> 12 -> 24 -> 56 -> 78 -> 89 -> None
```

```
----- SINGLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 5
Deleted beginning node.

----- SINGLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 9
12 -> 24 -> 56 -> 78 -> 89 -> None

----- SINGLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 6
Deleted last node.
```



Explanation:

- `Node` represents each node and stores **data** and the address of the **next node**.
- `SLL` maintains the linked list using `self.head`, which points to the first node.
- `create()` creates the linked list by adding nodes one by one.
- `insert` operations add a new node at the **beginning, end, or specified index**.
- `delete` operations remove a node from the **beginning, end, or specified index**.
- `count_nodes()` counts the total number of nodes, while `display()` prints all node values.
- The **main program** uses a menu-driven loop to perform the selected linked-list operation

Error table:

s.no	Error obtained	Rectification
1.	def _init_(self, data):	def **init**(self, data):
2.	def insert_beginning():	def insert_beginning(self):
3.	self.head = data	new_node = Node(data) self.head = new_node

Time complexity table:

Operation	Best Case	Average Case	Worst Case	Space Complexity
Create	O(1)	O(1)	O(1)	O(n)
Insert at Beginning	O(1)	O(1)	O(1)	O(1)
Insert at End	O(1) (if tail pointer maintained)	O(n)	O(n)	O(1)
Insert at Position	O(1) (if head/tail known)	O(n)	O(n)	O(1)
Delete from Beginning	O(1)	O(1)	O(1)	O(1)
Delete from End	O(n)	O(n)	O(n)	O(1)
Delete by Value	O(1) (if at head)	O(n)	O(n)	O(1)
Search	O(1) (if at head)	O(n)	O(n)	O(1)
Count Nodes	O(n)	O(n)	O(n)	O(1)
Display	O(n)	O(n)	O(n)	O(1)

B) Write a python program to implement a double linked list with the below operations:

A. create linked list

B. insert at beginning

C. Insert at end

D. Insert at index

E. Delete by value

F. Delete first node

G. Delete last node

H. Count number of nodes

I. Display/traverse

J. exit

Program:

```
class Node:
    def __init__(self, data):
        self.data = data
        self.prev = None
        self.next = None


class DLL:
    def __init__(self):
        self.head = None

    # 1. Create Linked List
    def create(self):
        n = int(input("Enter number of nodes: "))

        for i in range(n):
            data = int(input("Enter data: "))
```

```
            new_node = Node(data)

            if self.head is None:
                self.head = new_node
            else:
                temp = self.head

                while temp.next is not None:
                    temp = temp.next

                temp.next = new_node
                new_node.prev = temp

        print("Linked List created successfully")

    # 2. Insert at Beginning
    def insert_beginning(self):
        data = int(input("Enter data: "))

        new_node = Node(data)

        new_node.next = self.head

        if self.head is not None:
            self.head.prev = new_node

        self.head = new_node

        print(f"Inserted {data} at the beginning.")

    # 3. Insert at End
    def insert_end(self):
        data = int(input("Enter data: "))

        new_node = Node(data)

        if self.head is None:
            self.head = new_node
            print(f"Inserted {data} at the end.")
            return

        temp = self.head

        while temp.next is not None:
            temp = temp.next
```

```
        temp.next = new_node
        new_node.prev = temp

        print(f"Inserted {data} at the end.")

    # 4. Insert at Index
    def insert_at_index(self):
        data = int(input("Enter data: "))
        index = int(input("Enter index: "))

        if index < 0:
            print("Invalid index")
            return

        if index == 0:
            new_node = Node(data)

            new_node.next = self.head

            if self.head is not None:
                self.head.prev = new_node

            self.head = new_node

            print(f"Inserted {data} at index {index}.")
            return

        temp = self.head

        for i in range(index - 1):
            if temp is None:
                print("Index out of range")
                return

            temp = temp.next

        if temp is None:
            print("Index out of range")
            return

        new_node = Node(data)

        new_node.next = temp.next
        new_node.prev = temp

        if temp.next is not None:
```

```
            temp.next.prev = new_node

        temp.next = new_node

        print(f"Inserted {data} at index {index}.")

    # 5. Delete from Beginning
    def delete_beginning(self):

        if self.head is None:
            print("List is empty")
            return

        self.head = self.head.next

        if self.head is not None:
            self.head.prev = None

        print("Deleted beginning node.")

    # 6. Delete from End
    def delete_end(self):

        if self.head is None:
            print("List is empty")
            return

        if self.head.next is None:
            self.head = None
            print("Deleted last node.")
            return

        temp = self.head

        while temp.next is not None:
            temp = temp.next

        temp.prev.next = None

        print("Deleted last node.")

    # 7. Delete from Index
    def delete_at_index(self):

        index = int(input("Enter index: "))
```

```
        if self.head is None:
            print("List is empty")
            return

        if index < 0:
            print("Invalid index")
            return

        if index == 0:
            self.head = self.head.next

            if self.head is not None:
                self.head.prev = None

            print("Deleted the node value.")
            return

        temp = self.head

        for i in range(index):
            if temp is None:
                print("Index out of range")
                return

            temp = temp.next

        if temp is None:
            print("Index out of range")
            return

        if temp.next is not None:
            temp.next.prev = temp.prev

        temp.prev.next = temp.next

        print("Deleted the node value.")

    # 8. Count Nodes
    def count_nodes(self):

        count = 0
        temp = self.head

        while temp is not None:
            count += 1
            temp = temp.next
```

```
        print("Number of nodes:", count)

    # 9. Display
    def display(self):

        if self.head is None:
            print("List is empty")
            return

        temp = self.head

        while temp is not None:
            print(temp.data, end=" <-> ")
            temp = temp.next

        print("None")


# Main Program

dll = DLL()

while True:

    print("\n----- DOUBLY LINKED LIST -----")
    print("1. Create Linked List")
    print("2. Insert at Beginning")
    print("3. Insert at End")
    print("4. Insert at Index")
    print("5. Delete from Beginning")
    print("6. Delete from End")
    print("7. Delete from Index")
    print("8. Count Number of nodes")
    print("9. Display")
    print("10. Exit")

    choice = int(input("Enter your choice: "))

    if choice == 1:
        dll.create()

    elif choice == 2:
        dll.insert_beginning()

    elif choice == 3:
```

```
        dll.insert_end()

    elif choice == 4:
        dll.insert_at_index()

    elif choice == 5:
        dll.delete_beginning()

    elif choice == 6:
        dll.delete_end()

    elif choice == 7:
        dll.delete_at_index()

    elif choice == 8:
        dll.count_nodes()

    elif choice == 9:
        dll.display()

    elif choice == 10:
        print("Exiting from the program...")
        break

    else:
        print("Invalid choice")
```

```
----- DOUBLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 1
Enter number of nodes: 4
Enter data: 23
Enter data: 45
Enter data: 36
Enter data: 78
Linked List created successfully


----- DOUBLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 2
Enter data: 11
Inserted 11 at the beginning.

----- DOUBLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 9
11 <-> 23 <-> 45 <-> 36 <-> 78 <-> None
```

```
 ----- DOUBLY LINKED LIST -----
 1. Create Linked List
 2. Insert at Beginning
 3. Insert at End
 4. Insert at Index
 5. Delete from Beginning
 6. Delete from End
 7. Delete from Index
 8. Count Number of nodes
 9. Display
 10. Exit
 Enter your choice: 3
 Enter data: 98
 Inserted 98 at the end.

 ----- DOUBLY LINKED LIST -----
 1. Create Linked List
 2. Insert at Beginning
 3. Insert at End
 4. Insert at Index
 5. Delete from Beginning
 6. Delete from End
 7. Delete from Index
 8. Count Number of nodes
 9. Display
 10. Exit
 Enter your choice: 9
 11 <-> 23 <-> 45 <-> 36 <-> 78 <-> 98 <-> None

 ----- DOUBLY LINKED LIST -----
 1. Create Linked List
 2. Insert at Beginning
 3. Insert at End
 4. Insert at Index
 5. Delete from Beginning
 6. Delete from End
 7. Delete from Index
 8. Count Number of nodes
 9. Display
 10. Exit
 Enter your choice: 4
 Enter data: 4
 Enter index: 55
 Index out of range
```



Explanation:

- Node represents each node and stores **data**, the address of the **previous node**, and the **next node**.
- DLL maintains the linked list using `self.head`, which points to the first node.

- `create()` creates the doubly linked list by connecting nodes using both `prev` and `next`.
- `insert` operations add a new node at the **beginning, end, or specified index**.
- `delete` operations remove a node from the **beginning, end, or specified index** while updating both links.
- `count_nodes()` counts the total nodes, while `display()` prints the nodes in forward direction.
- The **main program** uses a menu-driven loop to perform the selected doubly linked-list operation.

Error table:

s.no	Error obtained	Rectification
1.	self.next = None	self.prev = None self.next = None
2.	while temp is not None: print(temp.data)	while temp is not None: print(temp.data) temp = temp.next

Time complexity table:

Operation	Best Case	Average Case	Worst Case	Space Complexity
Create	O(1)	O(1)	O(1)	O(n)
Insert at Beginning	O(1)	O(1)	O(1)	O(1)
Insert at End	O(1) (if tail pointer maintained)	O(n)	O(n)	O(1)
Insert at Position	O(1) (if head/tail known)	O(n)	O(n)	O(1)

Delete from Beginning	O(1)	O(1)	O(1)	O(1)
Delete from End	O(1) (if tail pointer maintained)	O(n)	O(n)	O(1)
Delete by Value	O(1) (if at head/tail)	O(n)	O(n)	O(1)
Search	O(1) (if at head/tail)	O(n)	O(n)	O(1)
Traverse Forward	O(n)	O(n)	O(n)	O(1)
Traverse Backward	O(n)	O(n)	O(n)	O(1)

C) Write a python program to implement a double linked list with the below operations:

A. create linked list

B. insert at beginning

C. Insert at end

D. Insert at index

E. Delete by value

F. Delete first node

G. Delete last node

H. Count number of nodes

I. Display/traverse

J. exit

Program:

```
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None
```

```
class CLL:
    def __init__(self):
        self.head = None

    # 1. Create Linked List
    def create(self):
        n = int(input("Enter number of nodes: "))

        for i in range(n):
            data = int(input("Enter data: "))
            new_node = Node(data)

            if self.head is None:
                self.head = new_node
                new_node.next = self.head
            else:
                temp = self.head

                while temp.next != self.head:
                    temp = temp.next

                temp.next = new_node
                new_node.next = self.head

        print("Linked List created successfully")

    # 2. Insert at Beginning
    def insert_beginning(self):
        data = int(input("Enter data: "))
        new_node = Node(data)

        if self.head is None:
            self.head = new_node
            new_node.next = self.head
        else:
            temp = self.head

            while temp.next != self.head:
                temp = temp.next

            new_node.next = self.head
            temp.next = new_node
            self.head = new_node
```

```
        print(f"Inserted {data} at the beginning.")

    # 3. Insert at End
    def insert_end(self):
        data = int(input("Enter data: "))
        new_node = Node(data)

        if self.head is None:
            self.head = new_node
            new_node.next = self.head
            print(f"Inserted {data} at the end.")
            return

        temp = self.head

        while temp.next != self.head:
            temp = temp.next

        temp.next = new_node
        new_node.next = self.head

        print(f"Inserted {data} at the end.")

    # 4. Insert at Index
    def insert_at_index(self):
        data = int(input("Enter data: "))
        index = int(input("Enter index: "))

        if index < 0:
            print("Invalid index")
            return

        if index == 0:
            new_node = Node(data)

            if self.head is None:
                self.head = new_node
                new_node.next = self.head
            else:
                temp = self.head

                while temp.next != self.head:
                    temp = temp.next

                new_node.next = self.head
                temp.next = new_node
```

```
                self.head = new_node

            print(f"Inserted {data} at index {index}.")
            return

        if self.head is None:
            print("Index out of range")
            return

        temp = self.head

        for i in range(index - 1):
            temp = temp.next

            if temp == self.head:
                print("Index out of range")
                return

        new_node = Node(data)

        new_node.next = temp.next
        temp.next = new_node

        print(f"Inserted {data} at index {index}.")

    # 5. Delete from Beginning
    def delete_beginning(self):

        if self.head is None:
            print("List is empty")
            return

        if self.head.next == self.head:
            self.head = None
            print("Deleted beginning node.")
            return

        temp = self.head

        while temp.next != self.head:
            temp = temp.next

        self.head = self.head.next
        temp.next = self.head

        print("Deleted beginning node.")
```

```
    # 6. Delete from End
    def delete_end(self):

        if self.head is None:
            print("List is empty")
            return

        if self.head.next == self.head:
            self.head = None
            print("Deleted last node.")
            return

        temp = self.head

        while temp.next.next != self.head:
            temp = temp.next

        temp.next = self.head

        print("Deleted last node.")

    # 7. Delete from Index
    def delete_at_index(self):

        index = int(input("Enter index: "))

        if self.head is None:
            print("List is empty")
            return

        if index < 0:
            print("Invalid index")
            return

        if index == 0:
            if self.head.next == self.head:
                self.head = None
            else:
                temp = self.head

                while temp.next != self.head:
                    temp = temp.next

                self.head = self.head.next
                temp.next = self.head
```

```
            print("Deleted the node value.")
            return

        temp = self.head

        for i in range(index - 1):
            temp = temp.next

            if temp == self.head:
                print("Index out of range")
                return

        if temp.next == self.head:
            print("Index out of range")
            return

        temp.next = temp.next.next

        print("Deleted the node value.")

    # 8. Count Nodes
    def count_nodes(self):

        if self.head is None:
            print("Number of nodes:", 0)
            return

        count = 0
        temp = self.head

        while True:
            count += 1
            temp = temp.next

            if temp == self.head:
                break

        print("Number of nodes:", count)

    # 9. Display
    def display(self):

        if self.head is None:
            print("List is empty")
            return
```

```
        temp = self.head

        while True:
            print(temp.data, end=" -> ")
            temp = temp.next

            if temp == self.head:
                break

        print("Head")


# Main Program

cll = CLL()

while True:

    print("\n----- CIRCULAR LINKED LIST -----")
    print("1. Create Linked List")
    print("2. Insert at Beginning")
    print("3. Insert at End")
    print("4. Insert at Index")
    print("5. Delete from Beginning")
    print("6. Delete from End")
    print("7. Delete from Index")
    print("8. Count Number of nodes")
    print("9. Display")
    print("10. Exit")

    choice = int(input("Enter your choice: "))

    if choice == 1:
        cll.create()

    elif choice == 2:
        cll.insert_beginning()

    elif choice == 3:
        cll.insert_end()

    elif choice == 4:
        cll.insert_at_index()

    elif choice == 5:
```

```
        cll.delete_beginning()

    elif choice == 6:
        cll.delete_end()

    elif choice == 7:
        cll.delete_at_index()

    elif choice == 8:
        cll.count_nodes()

    elif choice == 9:
        cll.display()

    elif choice == 10:
        print("Exiting from the program...")
        break

    else:
        print("Invalid choice")
```

```
----- DOUBLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 1
Enter number of nodes: 4
Enter data: 23
Enter data: 45
Enter data: 36
Enter data: 78
Linked List created successfully

----- DOUBLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 2
Enter data: 11
Inserted 11 at the beginning.

----- DOUBLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 9
11 <-> 23 <-> 45 <-> 36 <-> 78 <-> None
```

```
 ----- DOUBLY LINKED LIST -----
 1. Create Linked List
 2. Insert at Beginning
 3. Insert at End
 4. Insert at Index
 5. Delete from Beginning
 6. Delete from End
 7. Delete from Index
 8. Count Number of nodes
 9. Display
 10. Exit
 Enter your choice: 3
 Enter data: 98
 Inserted 98 at the end.

 ----- DOUBLY LINKED LIST -----
 1. Create Linked List
 2. Insert at Beginning
 3. Insert at End
 4. Insert at Index
 5. Delete from Beginning
 6. Delete from End
 7. Delete from Index
 8. Count Number of nodes
 9. Display
 10. Exit
 Enter your choice: 9
 11 <-> 23 <-> 45 <-> 36 <-> 78 <-> 98 <-> None

 ----- DOUBLY LINKED LIST -----
 1. Create Linked List
 2. Insert at Beginning
 3. Insert at End
 4. Insert at Index
 5. Delete from Beginning
 6. Delete from End
 7. Delete from Index
 8. Count Number of nodes
 9. Display
 10. Exit
 Enter your choice: 4
 Enter data: 4
 Enter index: 55
 Index out of range
```

```
----- DOUBLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 9
11 <-> 23 <-> 45 <-> 36 <-> 78 <-> 98 <-> None

----- DOUBLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 5
Deleted beginning node.

----- DOUBLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 6
Deleted last node.
```

```
 ----- DOUBLY LINKED LIST -----
 1. Create Linked List
 2. Insert at Beginning
 3. Insert at End
 4. Insert at Index
 5. Delete from Beginning
 6. Delete from End
 7. Delete from Index
 8. Count Number of nodes
 9. Display
 10. Exit
 Enter your choice: 7
 Enter index: 4
 Index out of range

 ----- DOUBLY LINKED LIST -----
 1. Create Linked List
 2. Insert at Beginning
 3. Insert at End
 4. Insert at Index
 5. Delete from Beginning
 6. Delete from End
 7. Delete from Index
 8. Count Number of nodes
 9. Display
 10. Exit
 Enter your choice: 8
 Number of nodes: 4

 ----- DOUBLY LINKED LIST -----
 1. Create Linked List
 2. Insert at Beginning
 3. Insert at End
 4. Insert at Index
 5. Delete from Beginning
 6. Delete from End
 7. Delete from Index
 8. Count Number of nodes
 9. Display
 10. Exit
 Enter your choice: 9
 23 <-> 45 <-> 36 <-> 78 <-> None
```

```
----- DOUBLY LINKED LIST -----
1. Create Linked List
2. Insert at Beginning
3. Insert at End
4. Insert at Index
5. Delete from Beginning
6. Delete from End
7. Delete from Index
8. Count Number of nodes
9. Display
10. Exit
Enter your choice: 10
Exiting from the program...
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA\week 6>
```

Explanation:

- The Node class stores data and a `next` pointer, while CLL manages the circular linked list.
- In a CLL, the last node always points back to the head instead of None.

- `create()` creates the list, while `insert_beginning()`, `insert_end()`, and `insert_at_index()` add nodes.
- `delete_beginning()`, `delete_end()`, and `delete_at_index()` remove nodes from different positions.
- `count_nodes()` counts all nodes by traversing until it reaches the head again.
- `display()` prints the elements and stops when traversal returns to the head.
- The main program provides a menu to perform all operations until the user chooses Exit.

Error table:

s.no	Error obtained	Rectification
1.	while temp is not None: temp = temp.next #checking for None	while temp.next != self.head: temp = temp.next
2.	temp.next = new_node #forgetting circular connection	temp.next = new_node new_node.next = self.head
3.	self.head = self.head.next #deleting first node without updating last node	self.head = self.head.next temp.next = self.head

TIME COMPLEXITY TABLE:

Operation	Best Case	Average Case	Worst Case	Space Complexity

Create	O(1)	$O(n^2)$	$O(n^2)$	O(n)
Insert at Beginning	O(n)	O(n)	O(n)	O(1)
Insert at End	O(n)	O(n)	O(n)	O(1)
Insert at Index	O(1)	O(n)	O(n)	O(1)
Delete from Beginning	O(n)	O(n)	O(n)	O(1)
Delete from End	O(n)	O(n)	O(n)	O(1)
Delete from Index	O(1)	O(n)	O(n)	O(1)
Count Nodes	O(n)	O(n)	O(n)	O(1)
Display	O(n)	O(n)	O(n)	O(1)

Week-6

A) Aim: Write a python program to implement stack operations such as push, pop, peek, display using an array.

Program:

```
# Stack implementation using list (array)
stack = [43,22,78,64]   # empty stack
MAX_SIZE = 5

def push():
    if len(stack) == MAX_SIZE:
        print("Stack Overflow!")
    else:
        element = input("Enter element to push: ")
        stack.append(element)
        print(f"{element} pushed onto stack.")

def pop():
    if not stack:
        print("Stack Underflow! Stack is empty.")
    else:
        element = stack.pop()
        print(f"Popped element: {element}")

def peek():
    if not stack:
        print("Stack is empty. Nothing to peek.")
    else:
        print(f"Top element: {stack[-1]}")

def display():
    if not stack:
        print("Stack is empty.")
    else:
        print("Stack elements (top to bottom):")
        for i in reversed(stack):
            print(i)

# Menu-driven program
```

```python
while True:
    print("\n==== STACK MENU ====")
    print("1. Push")
    print("2. Pop")
    print("3. Peek")
    print("4. Display")
    print("5. Exit")

    choice = int(input("Enter your choice: "))

    if choice == 1:
        push()
    elif choice == 2:
        pop()
    elif choice == 3:
        peek()
    elif choice == 4:
        display()
    elif choice == 5:
        print("Exiting... Goodbye!")
        break
    else:
        print("Invalid choice! Please try again.")
```

```
PS C:\Users\CSE Lab\Desktop\CSE25101> & "C:\Users\CSE Lab\AppData\Local\Programs\Python\Python312\python.exe" "c:/Users/CSE Lab/Desktop/CSE25101/CSE25101-DSA/week6/stack using array.py"

==== STACK MENU ====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 4
Stack elements (top to bottom):
64
78
22
43

==== STACK MENU ====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 1
Enter element to push: 82
82 pushed onto stack.

==== STACK MENU ====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 2
Popped element: 82

==== STACK MENU ====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 3
Top element: 64

==== STACK MENU ====
1. Push
2. Pop
3. Peek
4. Display
5. Exit
Enter your choice: 5
Exiting... Goodbye!
```

Explanation:

- A list `stack` is used to simulate stack behaviour with a maximum size (`MAX_SIZE`).
- `push()` adds an element if the stack isn't full, otherwise shows "Stack Overflow."
- `pop()` removes the top element if the stack isn't empty, else shows "Stack Underflow."
- `peek()` displays the top element without removing it.
- `display()` prints all stack elements from top to bottom.
- A menu-driven loop lets the user choose operations repeatedly.

Error table:

s.no	Error obtained	Rectification
1.	`if len(stack) == MAX_SIZE:` #Push is allowed only when size is exactly `MAX_SIZE`	temp.next = new_node new_node.next = self.head

B) Aim: Write a python program to implement stack operations such as push, pop, peek, display using an array.

Program:

```
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None
```

```
top = None

def push(data):
    global top
    new = Node(data)
    new.next = top
    top = new

def pop():
    global top
    if top is None:
        print("Stack Underflow")
    else:
        print("Popped:", top.data)
        top = top.next

def peek():
    if top is None:
        print("Stack is Empty")
    else:
        print("Top:", top.data)

def display():
    if top is None:
        print("Stack is Empty")
    else:
        temp = top
        while temp:
            print(temp.data, end=" ")
            temp = temp.next
        print()

while True:
    print("\n1.Push  2.Pop  3.Peek  4.Display  5.Exit")
    ch = int(input("Enter choice: "))

    if ch == 1:
        push(int(input("Enter value: ")))
    elif ch == 2:
        pop()
    elif ch == 3:
        peek()
    elif ch == 4:
        display()
    elif ch == 5:
        break
```

```
    else:
        print("Invalid choice")
```

```
1.Push  2.Pop  3.Peek  4.Display  5.Exit
Enter choice: 1
Enter value: 59

1.Push  2.Pop  3.Peek  4.Display  5.Exit
Enter choice: 4
59 78 37 24

1.Push  2.Pop  3.Peek  4.Display  5.Exit
Enter choice: 2
Popped: 59

1.Push  2.Pop  3.Peek  4.Display  5.Exit
Enter choice: 3
Top: 78

1.Push  2.Pop  3.Peek  4.Display  5.Exit
Enter choice: 5
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA\week 6>
```

Explanation:

1. **Node** stores the data and a pointer (`next`) to the next node.
2. **Top** points to the topmost node of the stack.
3. **Push** creates a new node and places it at the top.
4. **Pop** removes the top node and moves `top` to the next node.
5. **Peek** displays the data of the top node without removing it.
6. **Display** traverses the linked list from `top` and prints all elements.
7. If `top` is None, the stack is **empty (Stack Underflow)**.

Error table:

s.no	Error obtained	Rectification
1.		`while temp is not None:`

	`while temp:` **Error:** Incorrect traversal condition for linked list	**Correction:** Continue traversal until `temp` becomes None.
2.	`push(int(input("Enter value: ")))` **Error:** `Value Error` if a non-numeric value is entered	`push(input("Enter value: "))` **Correction:** Use string input if both numeric and non-numeric data are allowed.

Week-7

A) Aim: Write a python program to implement queue and its operations such as enqueue, dequeue, peek and display with a menu driven approach using an array.

Program:

```
queue = []
MAX_SIZE = 5

def enqueue():
    if len(queue) == MAX_SIZE:
        print("Queue Overflow")
    else:
        x = int(input("Enter element: "))
        queue.append(x)
        print(x, "enqueued")

def dequeue():
    if not queue:
        print("Queue Underflow")
    else:
        print("Dequeued:", queue.pop(0))

def peek():
    if not queue:
        print("Queue is empty")
    else:
        print("Front element:", queue[0])
```

```
def display():
    if not queue:
        print("Queue is empty")
    else:
        print("Queue elements:", queue)

while True:
    print("\n1. Enqueue")
    print("2. Dequeue")
    print("3. Peek")
    print("4. Display")
    print("5. Exit")

    ch = int(input("Enter choice: "))

    if ch == 1:
        enqueue()
    elif ch == 2:
        dequeue()
    elif ch == 3:
        peek()
    elif ch == 4:
        display()
    elif ch == 5:
        break
    else:
        print("Invalid choice")
```



Explanation:

- The **queue** is implemented using a Python list with a maximum size of 5.
- **Enqueue** adds an element at the rear of the queue.
- **Dequeue** removes the element from the front using `pop(0)`.
- **Peek** displays the front element without removing it.
- **Display** prints all elements present in the queue.
- **Overflow** occurs when the queue reaches `MAX_SIZE`.
- **Underflow** occurs when we try to dequeue from an empty queue.

Error table:

S.No	Error obtained	Rectification
1	`queue.append(x)` **Error:** Inserting an element without checking overflow	`if len(queue) == MAX_SIZE: print("Queue Overflow")` **Correction:** Check the maximum size before enqueue.
2	`queue.pop(0)` **Error:** Trying to delete from an empty queue	`if not queue: print("Queue Underflow")` **Correction:** Check whether the queue is empty before dequeue.

B) Aim: Write a python program to implement queue and its operations such as enqueue, dequeue, peek and display with a menu driven approach using linked list.

Program:

```
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None

front = rear = None

def enqueue():
    global front, rear
    x = int(input("Enter element: "))
    new = Node(x)

    if rear is None:
        front = rear = new
    else:
        rear.next = new
        rear = new

    print(x, "enqueued")

def dequeue():
    global front, rear
    if front is None:
```

```
        print("Queue Underflow")
    else:
        print("Dequeued:", front.data)
        front = front.next

        if front is None:
            rear = None

def peek():
    if front is None:
        print("Queue is empty")
    else:
        print("Front element:", front.data)

def display():
    if front is None:
        print("Queue is empty")
    else:
        temp = front
        while temp is not None:
            print(temp.data, end=" ")
            temp = temp.next
        print()

while True:
    print("\n1. Enqueue")
    print("2. Dequeue")
    print("3. Peek")
    print("4. Display")
    print("5. Exit")

    ch = int(input("Enter choice: "))

    if ch == 1:
        enqueue()
    elif ch == 2:
        dequeue()
    elif ch == 3:
        peek()
    elif ch == 4:
        display()
    elif ch == 5:
        break
    else:
        print("Invalid choice")
```

```
1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter choice: 4
23 45 67 89 60

1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter choice: 1
Enter element: 3
3 enqueued

1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter choice: 2
Dequeued: 23

1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter choice: 3
Front element: 45

1. Enqueue
2. Dequeue
3. Peek
4. Display
5. Exit
Enter choice: 5
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA\week 7>
```

Explanation:

- The **queue** is implemented using a linked list with `front` and `rear` pointers.
- **Enqueue** creates a new node and inserts it at the rear.
- **Dequeue** removes the node from the front of the queue.
- **Peek** displays the front element without removing it.
- **Display** traverses the linked list from front to rear.
- When the queue becomes empty, both `front` and `rear` are set to None.

- **Underflow** occurs when dequeue or peek is performed on an empty queue.

Error table:

S.No	Error obtained	Rectification
1	`rear.next = new` **Error:** Trying to insert using `rear` when the queue is empty	`if rear is None: front = rear = new` **Correction:** Set both `front` and `rear` to the new node for an empty queue.

Week-8

A) Aim: Write a python program to implement a binary tree with its operations using array.

Program:

```
tree = []

def insert(value):
    tree.append(value)

def preorder(i=0):
    if i < len(tree):
        print(tree[i], end=" ")
        preorder(2*i + 1)
        preorder(2*i + 2)

def inorder(i=0):
    if i < len(tree):
        inorder(2*i + 1)
        print(tree[i], end=" ")
        inorder(2*i + 2)

def postorder(i=0):
    if i < len(tree):
        postorder(2*i + 1)
        postorder(2*i + 2)
        print(tree[i], end=" ")
```

```
# Insert elements
n = int(input("Enter number of nodes: "))

for i in range(n):
    insert(int(input("Enter value: ")))

print("Array:", tree)

print("Preorder:", end=" ")
preorder()

print("\nInorder:", end=" ")
inorder()

print("\nPostorder:", end=" ")
postorder()
```



Explanation:

- `tree = []` creates an empty list to store the binary tree elements.
- `insert(value)` adds elements to the list using `append()`.
- `preorder(i)` prints the root, left subtree, and right subtree.
- `inorder(i)` prints the left subtree, root, and right subtree.
- `postorder(i)` prints the left subtree, right subtree, and root.
- The `for` loop accepts n elements from the user and inserts them into the tree.
- Finally, the program displays the array and performs all three traversals using array indices: left child `2*i+1` and right child `2*i+2`.

Error table:

S.No	Error obtained	Rectification
1	`preorder(2*i + 1)` is called before printing the root node. **Error:** Incorrect traversal order.	Print `tree[i]` before recursive calls. **Correction:** Print root, left subtree, then right subtree.

2	`inorder(2*i + 1)` is called before printing the root node. **Error:** Incorrect traversal order.	Print `tree[i]` between recursive calls. **Correction:** Traverse left subtree, root, then right subtree.
3	`postorder()` prints the root after both recursive calls. **Error:** No error; this is the correct order.	No correction required. **Correction:** Traverse left subtree, right subtree, then root.

A) Aim: Write a python program to implement a binary tree with its operations using linked list.

Program:

```
class Node:
    def __init__(self, data):
        self.data = data
        self.left = None
        self.right = None


def preorder(root):
    if root:
        print(root.data, end=" ")
        preorder(root.left)
        preorder(root.right)


def inorder(root):
    if root:
        inorder(root.left)
        print(root.data, end=" ")
        inorder(root.right)


def postorder(root):
    if root:
        postorder(root.left)
        postorder(root.right)
        print(root.data, end=" ")


# Create binary tree
root = Node(1)
root.left = Node(2)
root.right = Node(3)
root.left.left = Node(4)
```

```
root.left.right = Node(5)
root.right.left = Node(6)
root.right.right = Node(7)

print("Preorder:", end=" ")
preorder(root)

print("\nInorder:", end=" ")
inorder(root)

print("\nPostorder:", end=" ")
postorder(root)
```

```
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA> & C:\msys64\ucrt64\bin\python.exe "c:/Users/SAI HAS
Preorder: 1 2 4 5 3 6 7
Inorder: 4 2 5 1 6 3 7
Postorder: 4 5 2 6 7 3 1
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA>
```

Explanation:

- `class Node` creates a node with data, left child, and right child.
- `preorder(root)` prints the root, left subtree, and right subtree.
- `inorder(root)` prints the left subtree, root, and right subtree.
- `postorder(root)` prints the left subtree, right subtree, and root.
- `Node(1)` creates the root, and other nodes are connected to form a binary tree.
- The tree contains seven nodes with values from 1 to 7.
- Finally, the program displays the preorder, inorder, and postorder traversals.

Error table:

S.No	Error obtained	Rectification
1	`root.left = Node(2)` without creating the Node class. **Error:** `NameError`.	Define the Node class before creating nodes.
2	`preorder(root.left)` without checking whether `root` exists. **Error:** `AttributeError` if `root` is None.	Use `if root:` before accessing node data or children.
3	Printing the root before traversing the left subtree in `inorder()`. **Error:** Incorrect traversal order.	Print the root between the left and right recursive calls.

Week-9

A) Aim: Write a python program to implement a binary search tree with its operations and traversals.

Program:

```
class Node:
    def __init__(self, data):
        self.data = data
        self.left = self.right = None

def insert(root, data):
    if root is None:
        return Node(data)
    if data < root.data:
        root.left = insert(root.left, data)
    else:
        root.right = insert(root.right, data)
    return root

def search(root, key):
    if root is None or root.data == key:
        return root
    if key < root.data:
        return search(root.left, key)
    return search(root.right, key)

def inorder(root):
    if root:
        inorder(root.left)
        print(root.data, end=" ")
        inorder(root.right)

def preorder(root):
    if root:
        print(root.data, end=" ")
        preorder(root.left)
        preorder(root.right)

def postorder(root):
    if root:
        postorder(root.left)
```

```
        postorder(root.right)
        print(root.data, end=" ")

root = None
n = int(input("Enter number of nodes: "))

for i in range(n):
    root = insert(root, int(input("Enter value: ")))

print("Inorder:", end=" ")
inorder(root)
print("\nPreorder:", end=" ")
preorder(root)
print("\nPostorder:", end=" ")
postorder(root)

key = int(input("\nEnter value to search: "))
print("Found" if search(root, key) else "Not Found")
```

```
PS C:\Users\SAI HASHINI\OneDrive\Desktop\textbooks\DSA> & C:\msys64\ucrt64\bin\pyth
Enter number of nodes: 5
Enter value: 25
Enter value: 67
Enter value: 89
Enter value: 33
Enter value: 11
Inorder: 11 25 33 67 89
Preorder: 25 11 67 33 89
Postorder: 11 33 89 67 25
Enter value to search: 33
Found
```

Explanation:

- Node creates a node containing data and left and right pointers.
- `insert()` inserts values according to BST rules: smaller values go left, larger or equal values go right.
- `search()` searches for a given value in the BST.
- `inorder()` displays values in ascending order.
- `preorder()` displays the root, left subtree, and right subtree.
- `postorder()` displays the left subtree, right subtree, and root.

- The main program accepts values, builds the BST, displays all traversals, and searches for a value.

Error table:

S.No	Error obtained	Rectification
1	`root.left = insert(root.left, data)` without assigning the returned node. **Error:** The new node may not be connected to the tree.	Use `root.left = insert(root.left, data)` to connect the node correctly.
2	`search(root.left, key)` without checking whether `root` is `None`. **Error:** `AttributeError` when accessing a nonexistent node.	Check `if root is None` before accessing `root.data`.
3	Printing the root before traversing the left subtree in `inorder()`. **Error:** Incorrect traversal order.	Traverse the left subtree, print the root, then traverse the right subtree.