

```
In [1]: 1 import pandas as pd
2 from keras.models import Sequential
3 from keras.layers import Dense, LayerNormalization, Dropout, LSTM, Embedding
4 from keras.layers.advanced_activations import PReLU
5 from sklearn.model_selection import train_test_split
6 from tensorflow import keras
7 import matplotlib.pyplot as plt
8 from sklearn.model_selection import train_test_split
9 from sklearn.metrics import mean_squared_error
10 import tensorflow as tf
11 import numpy as np
```

```
In [2]: 1 df = pd.read_csv("raw_size25_vector_size8000.csv")
```

```
In [3]: 1 X = df.iloc[:, 7:157]
2 AX = df[['accelerometer_reading_x_0', 'accelerometer_reading_y_0', 'accelerometer_reading_z_0', 'gyroscope_reading_phi_0', 'gyro
3 xt = df[['linear_position_x', 'linear_position_y', 'linear_position_z', 'angular_position_phi', 'angular_position_theta', 'angula
4 xt = df[['phi_change', 'theta_change', 'psi_change']]
5 t = df[['phi_change']]
```

```
In [4]: 1 t.shape
```

```
Out[4]: (8000, 1)
```

```
In [5]: 1 in_dim = X.shape[1]
2 out_dim = t.shape[1]
```

```
In [6]: 1 in_dim
```

```
Out[6]: 150
```

```
In [7]: 1 out_dim
```

```
Out[7]: 1
```

```
In [8]: 1 X_train, X_test, t_train, t_test = train_test_split(X, t, test_size=0.2)
```

```
In [9]: 1 t_train.shape
```

```
Out[9]: (6400, 1)
```

```
In [10]: 1 model = Sequential()
2 model.add(Dense(256, input_dim=in_dim, activation="sigmoid"))
3 model.add(PReLU())
4 model.add(Dropout(.4))
5 model.add(Dense(128, activation="sigmoid"))
6 model.add(PReLU())
7 model.add(LayerNormalization())
8 model.add(Dropout(.25))
9 model.add(Dense(64, activation="sigmoid"))
10 model.add(PReLU())
11 model.add(LayerNormalization())
12 model.add(Dropout(.1))
13 model.add(Dense(12, activation="sigmoid"))
14 model.add(PReLU())
15 model.add(LayerNormalization())
16 model.add(Dense(out_dim, activation="sigmoid"))
17 model.compile(loss="mse", optimizer="sgd")
```

```
In [11]: 1 model.fit(X_train, t_train, epochs=75, batch_size=12, verbose=2)
```


```
Epoch 67/75
534/534 - ls - loss: 1.2153e-05
Epoch 68/75
534/534 - ls - loss: 1.2253e-05
Epoch 69/75
534/534 - ls - loss: 1.2481e-05
Epoch 70/75
534/534 - ls - loss: 1.3217e-05
Epoch 71/75
534/534 - ls - loss: 1.0409e-05
Epoch 72/75
534/534 - ls - loss: 1.4014e-05
Epoch 73/75
534/534 - ls - loss: 1.1906e-05
Epoch 74/75
534/534 - ls - loss: 1.1045e-05
Epoch 75/75
534/534 - ls - loss: 1.0297e-05
```

```
Out[11]: <tensorflow.python.keras.callbacks.History at 0x44120a5e20>
```


```
In [12]: 1 ypred = model.predict(X_test)
2 print('y1 MSE: ', mean_squared_error(t_test.iloc[:, 0], ypred[:, 0]))
3 print('y1 MSE: ', mean_squared_error(t_test.iloc[:, 1], ypred[:, 1]))
4 print('y1 MSE: ', mean_squared_error(t_test.iloc[:, 2], ypred[:, 2]))
5
```

```
y1 MSE: 1.248065772567733e-06
```

```
In [13]: 1 x_ax = range(len(X_test))
2
3 plt.scatter(x_ax, t_test.iloc[:, 0], s=6, label='y1-test')
4 plt.scatter(x_ax, ypred[:, 0], label='y1-pred', c='red', alpha = 0.1)
5
6 plt.legend()
7 plt.show()
```



```
In [14]: 1 x_ax = range(len(X_test))
2
3 y_test_index = np.argsort(t_test.iloc[:, 0], axis=0).to_numpy()
4
5 f = plt.figure()
6 plt.scatter(x_ax, t_test.iloc[y_test_index], s=6, label='y_test')
7 plt.scatter(x_ax, ypred[y_test_index], s=6, label='pred', c='orange', alpha=0.5)
8 plt.plot(t_test.iloc[y_test_index[0]].to_numpy()[0])
9 plt.legend()
10 plt.show()
11
12 f.savefig("fou.pdf", bbox_inches='tight')
```



```
In [ ]: 1
```

```
In [ ]: 1
```