

TP 3

1.

```
SQL> SELECT name, open_mode FROM v$pdb$;

NAME
-----
OPEN_MODE
-----
PDB$SEED
READ ONLY

PDB1
READ WRITE

SQL>
```

```
SQL> ALTER SESSION SET CONTAINER=PDB1;

Session altered.

SQL> SHOW CON_NAME;

CON_NAME
-----
PDB1
SQL>
```

- Créer un utilisateur local (HR_RO) :

```
SQL> ALTER SESSION SET CONTAINER=PDB1;
Session altered.

SQL> SHOW CON_NAME;
CON_NAME
-----
PDB1
SQL> CREATE USER HR_RO IDENTIFIED BY Welcome1 DEFAULT TABLESPACE USERS QUOTA 50M ON USERS;
User created.

SQL> GRANT CREATE SESSION TO HR_RO;
Grant succeeded.

SQL> GRANT SELECT ON HR.EMPLOYEES TO HR_RO;
Grant succeeded.

SQL> GRANT SELECT ON HR.DEPARTMENTS TO HR_RO;
Grant succeeded.

SQL> GRANT SELECT ON HR.JOBS TO HR_RO;
Grant succeeded.

SQL> GRANT SELECT ON HR.LOCATIONS TO HR_RO;
Grant succeeded.
```

-

```

SQL> CONNECT / AS SYSDBA
Connected.
SQL> SHOW CON_NAME;

CON_NAME
-----
CDB$ROOT
SQL> ALTER SESSION SET CONTAINER=PDB1;

Session altered.

SQL> SHOW CON_NAME;

CON_NAME
-----
PDB1
SQL> ALTER USER HR_RO IDENTIFIED BY Welcome1;

User altered.

```

```

SQL> CONNECT HR_RO/Welcome1@PDB1
Connected.
SQL> SELECT COUNT(*) FROM HR.EMPLOYEES;

COUNT(*)
-----
107

```

2.

-

```

SQL> CREATE PLUGGABLE DATABASE PDB2 ADMIN USER pdb2admin IDENTIFIED BY Welcome1 FILE_NAME_CONVERT = ('pdbseed','pdb2');
Pluggable database created.

SQL> CREATE PLUGGABLE DATABASE PDB3 ADMIN USER pdb3admin IDENTIFIED BY Welcome1 FILE_NAME_CONVERT = ('pdbseed','pdb3');
Pluggable database created.

SQL> ALTER PLUGGABLE DATABASE PDB2 OPEN;
Pluggable database altered.

SQL> ALTER PLUGGABLE DATABASE PDB3 OPEN;
Pluggable database altered.

SQL> SELECT NAME, OPEN_MODE FROM V$PDBS;

NAME
-----
OPEN_MODE
-----
PDB$SEED
READ ONLY

PDB1
READ WRITE

PDB2
READ WRITE

NAME
-----
OPEN_MODE
-----
PDB3
READ WRITE

```

```

SQL> CREATE TABLESPACE USERS DATAFILE 'users01.dbf' SIZE 100M AUTOEXTEND ON;
Tablespace created.

SQL> CREATE USER DW_INT IDENTIFIED BY Welcome1 DEFAULT TABLESPACE USERS QUOTA 100M ON USERS;
User created.

SQL> GRANT CREATE SESSION TO DW_INT;
Grant succeeded.

SQL> GRANT CREATE TABLE TO DW_INT;
Grant succeeded.

SQL> GRANT CREATE VIEW TO DW_INT;
Grant succeeded.

SQL> GRANT CREATE DATABASE LINK TO DW_INT;
Grant succeeded.

```

```
SQL> SELECT COUNT( * ) FROM HR.EMPLOYEES@LNK_PDB1_HR;
```

```
  COUNT(*)  
-----  
      107
```

3.

```

SQL> CONNECT / AS SYSDBA
Connected.
SQL> ALTER SESSION SET CONTAINER=PDB2;

Session altered.

SQL> SHOW CON_NAME;

CON_NAME
-----
PDB2
SQL> SELECT COUNT( * ) FROM HR.EMPLOYEES@LNK_PDB1_HR;

COUNT(*)
-----
107

SQL> SELECT * FROM HR.EMPLOYEES@LNK_PDB1_HR;

EMPLOYEE_ID FIRST_NAME          LAST_NAME
-----
EMAIL          PHONE_NUMBER      HIRE_DATE  JOB_ID      SALARY
-----
COMMISSION_PCT MANAGER_ID DEPARTMENT_ID
-----
100 Steven          King
SKING          515.123.4567      17-JUN-03  AD_PRES      24000
90

101 Neena          Kochhar
NKOCHHAR      515.123.4568      21-SEP-05  AD_VP        17000
100          90

EMPLOYEE_ID FIRST_NAME          LAST_NAME
-----
EMAIL          PHONE_NUMBER      HIRE_DATE  JOB_ID      SALARY
-----
COMMISSION_PCT MANAGER_ID DEPARTMENT_ID
-----

102 Lex          De Haan
LDEHAAN      515.123.4569      13-JAN-01  AD_VP        17000
100          90

```

4.

```

SQL> CREATE TABLE STG_EMPLOYEES AS SELECT * FROM HR.EMPLOYEES@LNK_PDB1_HR;
Table created.

SQL> CREATE TABLE STG_DEPARTMENTS AS SELECT * FROM HR.DEPARTMENTS@LNK_PDB1_HR;
Table created.

SQL> SELECT COUNT( * ) FROM STG_EMPLOYEES;

COUNT(*)
-----
      107

SQL> SELECT COUNT( * ) FROM STG_DEPARTMENTS;

COUNT(*)
-----
       27

```

```
SQL> ALTER SESSION SET CONTAINER=PDB2;
```

Session altered.

```
SQL> CREATE VIEW VW_DEPT_HEADCOUNT AS SELECT department_id, COUNT( * ) AS nb_employees FROM STG_EMPLOYEES GROUP BY department_id;
```

View created.

```
SQL> SELECT * FROM VW_DEPT_HEADCOUNT;
```

DEPARTMENT_ID	NB_EMPLOYEES
---------------	--------------

50	45
40	1
110	2
90	3
30	6
70	1
	1
10	1
20	2
60	5
100	6

DEPARTMENT_ID	NB_EMPLOYEES
---------------	--------------

80	34
----	----

12 rows selected.