

TP2 — EXTENSION : PRÉPARATION ENVIRONNEMENT

Objectif : vous habituez à la démarche réelle DBA
(connexion serveur → vérifications → puis création PDB)

```
SQL> CREATE PLUGGABLE DATABASE PDB2
ADMIN USER admin_pdb2 IDENTIFIED BY Welcome1
FILE_NAME_CONVERT= 2 3 ('/u01/app/oracle/oradata/ORCL/pdbseed/',
'/u01/app/oracle/oradata/ORCL/pdb2/');
```

```
ALTER PLUGGABLE DATABASE PDB2 OPEN;
ALTER PLUGGABLE DATABASE PDB2 SAVE STATE;CREATE PLUGGABLE DATABASE
PDB2
```

```
SQL> SQL> ALTER PLUGGABLE DATABASE PDB2 OPEN
```

```
SQL>
```

```
SQL> CREATE PLUGGABLE DATABASE PDB3
ADMIN USER admin_pdb3 IDENTIFIED BY Welcome1
FILE_NAME_CONVERT= 2 3 ('/u01/app/oracle/oradata/ORCL/pdbseed/',
'/u01/app/oracle/oradata/ORCL/pdb3/');
```

```
ALTER PLUGGABLE DATABASE PDB3 OPEN;
ALTER PLUGGABLE DATABASE PDB3 SAVE STATE;CREATE PLUGGABLE DATABASE
PDB3
```

```
SQL> SQL> ALTER PLUGGABLE DATABASE PDB3 OPEN
```

```
SQL> CREATE PLUGGABLE DATABASE PDB2
```

```
ADMIN USER admin_pdb2 IDENTIFIED BY Welcome1
FILE_NAME_CONVERT=('/u01/oradata/C 2 3 DB1/pdbseed/', '/u01/oradata/CDB1/pdb2/');
```

```
ALTER PLUGGABLE DATABASE PDB2 OPEN;
ALTER PLUGGABLE ALTER PLUGGABLE DATABASE PDB3 SAVE STATE;CREATE
PLUGGABLE DATABASE PDB2
```

*

ERROR at line 1:

ORA-00933: SQL command not properly ended

```
SQL> SQL> ALTER PLUGGABLE DATABASE PDB2 OPEN
```

*

ERROR at line 1:

ORA-65011: Pluggable database PDB2 does not exist.

```
SQL> DATABASE PDB2 SAVE STATE;
ALTER PLUGGABLE DATABASE PDB2 SAVE STATE
```

*

ERROR at line 1:

ORA-65011: Pluggable database PDB2 does not exist.

```
SQL> CREATE PLUGGABLE DATABASE PDB2
ADMIN USER admin_pdb2 IDENTIFIED BY Welcome1
FILE_NAME_CONVERT= 2 3 ('/u01/oradata/CDB1/pdbseed/', '/u01/oradata/CDB1/pdb2/');
```

Pluggable database created.

```
SQL> ALTER PLUGGABLE DATABASE PDB2 OPEN;
```

Pluggable database altered.

```
SQL> ALTER PLUGGABLE DATABASE PDB2 SAVE STATE;
```

Pluggable database altered.

```
SQL> CREATE PLUGGABLE DATABASE PDB3  
ADMIN USER admin_pdb3 IDENTIFIED BY Welcome1  
FILE_NAME_CONVERT=('/u01/oradata/C 2 3 DB1/pdbseed/', '/u01/oradata/CDB1/pdb3/');
```

Pluggable database created.

```
SQL> ALTER PLUGGABLE DATABASE PDB3 OPEN;  
ALTER PLUGGABLE DATABASE PDB3 SAVE STATE;  
Pluggable database altered.
```

```
SQL>
```

Pluggable database altered.

```
SQL>  
SQL> ALTER PLUGGABLE DATABASE PDB2 CLOSE IMMEDIATE;
```

Pluggable database altered.

```
SQL> ALTER PLUGGABLE DATABASE PDB3 OPEN READ ONLY FORCE;
```

Pluggable database altered.

```
SQL> ALTER PLUGGABLE DATABASE PDB3 OPEN READ WRITE FORCE;
```

Pluggable database altered.

```
SQL> COLUMN name FORMAT A15;  
SELECT con_id, name, open_mode FROM v$pdb ORDER BY con_id;SQL>
```

CON_ID	NAME	OPEN_MODE
2	PDB\$SEED	READ ONLY
3	PDB1	READ WRITE
4	PDB2	MOUNTED
5	PDB3	READ WRITE

```
SQL> ALTER PLUGGABLE DATABASE PDB2 OPEN;
```

Pluggable database altered.

```
SQL> ALTER PLUGGABLE DATABASE ALL SAVE STATE;
```

Pluggable database altered.

```
SQL> COLUMN name FORMAT A15;  
SELECT con_id, name, open_mode FROM v$pdb ORDER BY con_id;SQL>
```

CON_ID	NAME	OPEN_MODE
2	PDB\$SEED	READ ONLY
3	PDB1	READ WRITE
4	PDB2	READ WRITE
5	PDB3	READ WRITE

```
SQL> shutdown
```

```
/u01/oradata/CDB1/pdbseed PDB$SEED SOURCE  
/u02/oradata/CDB1 PDB2  
/u03/oradata/CDB1 PDB3
```

```
SQL>  
CREATE PLUGGABLE DATABASE PDB4  
ADMIN USER admin_pdb2 IDENTIFIED BY Welcome1  
FILE_NAME_CONVERT=('/u01/oradata/CDB1/pdbseed', '/u02/oradata/CDB1/pdb4');
```

```
CREATE PLUGGABLE DATABASE PDB2 ADMIN USER admin_pdb2 IDENTIFIED BY  
Welcome1 FILE_NAME_CONVERT=('/u01/oradata/CDB1/pdbseed', '/u02/oradata/CDB1/pdb2');
```

```
SELECT con_id, v$pdb.name AS PDB_NAME, v$datafile.name AS FILE_PATH FROM  
v$datafile JOIN v$pdb USING (con_id) ORDER BY con_id;
```

```
CREATE PLUGGABLE DATABASE PDB2 ADMIN USER admin_pdb2 IDENTIFIED BY  
Welcome1 FILE_NAME_CONVERT=('/u01/oradata/CDB1/pdbseed', '/u02/oradata/CDB1/pdb2');
```

```
CREATE PLUGGABLE DATABASE PDB3 ADMIN USER admin_pdb3 IDENTIFIED BY  
Welcome1 FILE_NAME_CONVERT=('/u01/oradata/CDB1/pdbseed', '/u03/oradata/CDB1/pdb3');
```

```
SELECT v$pdb.name, v$datafile.name FROM v$datafile JOIN v$pdb USING (con_id)  
WHERE v$pdb.name IN ('PDB2', 'PDB3');
```

```
SELECT name  
FROM v$datafile ;
```