

PYTHON OOPs

Database Programming :

- Python Database API supports a wide range of database servers such as –

GadFly

mSQL

MySQL

PostgreSQL

Microsoft SQL Server 2000

Informix

Interbase

Oracle

- You must download a separate DB API module for each database you need to access. For example, if you need to access an Oracle database as well as a MySQL database, you must download both the Oracle and the MySQL database modules.

- DB API provides a minimal standard for working with databases using Python structures and syntax wherever possible.

This API include following :

- Importing the API module.
- Acquiring a connection with the database.
- Issuing SQL statements and stored procedures.
- Closing the connection.
- We would learn all the concepts using MySQL, so let us talk about MySQLdb module.

What is MySQLdb?

- MySQLdb is an interface for connecting to a MySQL database server from Python. It implements the Python Database API v2.0 and is built on top of the MySQL C API.

How To Install MySQLdb?

- Before proceeding, you make sure you have MySQLdb installed on your machine.

```
import MySQLdb
```

- If it produces the following result, then it means MySQLdb module is not installed.

```
Traceback (most recent call last):  
  File "test.py", line 3, in <module>  
    import MySQLdb  
ImportError: No module named MySQLdb
```

```
Traceback (most recent call last):  
  File "test.py", line 3, in <module>  
    import MySQLdb  
ImportError: No module named MySQLdb
```

Database Connection :

Before connecting to a MySQL database,see following:

- You have created a database TESTDB.
- You have created a table EMPLOYEE in TESTDB.
- This table has fields FIRST_NAME, LAST_NAME, AGE, SEX and

INCOME

Example :

Following is the example of connecting with MySQL database "TESTDB".

```
import MySQLdb

db = MySQLdb.connect("localhost","testuser","test123","TESTDB")

cursor = db.cursor()

cursor.execute("SELECT VERSION()")

data = cursor.fetchone()

print ("Database version : %s " % data)

db.close()
```

Creating Database Table :

- Once a database connection is established, we are ready to create tables or records into the database tables using **execute** method of the created cursor.

Example :

Let us create Database table EMPLOYEE

```
import MySQLdb

db = MySQLdb.connect("localhost","testuser","test123","TESTDB")

cursor = db.cursor()

cursor.execute("DROP TABLE IF EXISTS EMPLOYEE")

sql = """CREATE TABLE EMPLOYEE (

            FIRST_NAME CHAR(20) NOT NULL,

            LAST_NAME CHAR(20),

            AGE INT,

            SEX CHAR(1),

            INCOME FLOAT)"""

cursor.execute(sql)

db.close()
```

INSERT operation :

- It is required when you want to create your records into a database table.

Example :

- The following example, executes SQL *INSERT* statement to create a record into EMPLOYEE table.

```
import MySQLdb

db = MySQLdb.connect("localhost","testuser","test123","TESTDB")

cursor = db.cursor()

sql = "INSERT INTO EMPLOYEE(FIRST_NAME, LAST_NAME, AGE, SEX, INCOME)
VALUES('%s','%s','%d','%c','%d') % ('Mac','Mohan',20,'M',2000)"

try:

    cursor.execute(sql)

    db.commit()

except:

    db.rollback()

db.close()
```

READ operation :

- Once our database connection is established, you are ready to make a query into this database. You can use either **fetchone()** method to fetch single record or **fetchall()** method to fetch multiple values from a database table.

- **fetchone()**: It fetches the next row of a query result set. A result set is an object that is returned when a cursor object is used to query a table.

- **fetchall()**: It fetches all the rows in a result set. If some rows have already been extracted from the result set, then it retrieves the remaining rows from the result set.

• **rowcount:** This is a read-only attribute and returns the number of rows that were affected by an execute() method.

```
import MySQLdb

db = MySQLdb.connect("localhost","testuser","test123","TESTDB")

cursor = db.cursor()

sql = "SELECT * FROM EMPLOYEE WHERE INCOME > '%d'" % (1000)

try:

    cursor.execute(sql)

    results = cursor.fetchall()

    for row in results:

        fname = row[0]

        lname = row[1]

        age = row[2]

        sex = row[3]

        income = row[4]

        print ("fname=%s,lname=%s,age=%d,sex=%s,income=%d" % (fname,
lname, age, sex, income))

except:

    print ("Error: unable to fetch data")

db.close()
```

UPDATE Operation : UPDATE Operation on any database means to update one or more records, which are already available in the database.

```
import MySQLdb

db = MySQLdb.connect("localhost","testuser","test123","TESTDB")

cursor = db.cursor()

sql = "UPDATE EMPLOYEE SET AGE = AGE + 1 WHERE SEX = '%c'" % ('M')

try:

    cursor.execute(sql)
```

```
        db.commit()

except:

    db.rollback()

db.close()
```

DELETE Operation : DELETE operation is required when you want to delete some records from your database.

```
import MySQLdb

db = MySQLdb.connect("localhost","testuser","test123","TESTDB")

cursor = db.cursor()

sql = "DELETE FROM EMPLOYEE WHERE AGE > '%d'" % (20)

try:

    cursor.execute(sql)

    db.commit()

except:

    db.rollback()

db.close()
```

COMMIT Operation :

- Commit is the operation, which gives a green signal to database to finalize the changes, and after this operation, no change can be reverted back.

ROLLBACK Operation :

- If you are not satisfied with one or more of the changes and you want to revert back those changes completely, then use **rollback()** method.

Disconnecting Database :

- To disconnect Database connection, use close() method.