


LEARN. DO. EARN


ACADGILD



FRONT END WEB DEVELOPMENT FUNDAMENTALS

Website : <http://www.acadgild.com>
LinkedIn : <https://www.linkedin.com/company/acadgild>
Facebook : <https://www.facebook.com/acadgild>

© copyright ACADGILD



Session 7 – JavaScript





Agenda – JavaScript

1. **DOM**
2. **How DOM works?**
3. **DOM Manipulation**
4. **Modifying HTML Using innerHTML**
5. **Events**
6. **Event Types**
7. **Event Bubbling and Event Capturing**
8. **Action Dialog**
9. **Form Validation**





DOM (Document Object Model)

- **DOM** is cross-platform and language-independent programming interface for building, accessing, and manipulating valid HTML and well-formed XML documents.
- Ultimate goal is to make it possible for programmers to write applications that work properly on all browsers and servers, and on all platforms.
- When a web page is loaded, Browser creates a **Document Object Model** of the page.





DOM (contd.)

- With Object model, JavaScript gets power that it need to create dynamic HTML.
- Now JavaScript can:
 - change the HTML elements in the page
 - change the HTML attributes in the page
 - change the CSS styles in the page
 - remove existing HTML elements and attributes
 - add new HTML elements and attributes
 - react to all existing HTML events in the page
 - create new HTML events in the page





How DOM Works ?

<head>

<script>

function **toggle()**


```
{ document.img.button1.src=
  "button_on.gif"; }
```

</script>

</head>

<body> <a href="test.html"
 onmouseover="toggle()">

 </body>





DOM Manipulation

- **document.getElementsByTagName(tagname)** - This method returns a collection of all elements reference in the document with the specified tag name.
- **document.getElementsByClassName(classname)** - This method returns a collection of all elements reference in the document with the specified class name.
- **document.getElementById(id)** - This method returns a element reference in the document with the specified id.






Modifying HTML Using innerHTML

- innerHTML is the property of DOM object nodes. Using this property we can get/set the html inside a tag.

Example :

```
<head> <script type = "text/javascript">  
    function addHeading(){  
        var ref = document.getElementById("container");  
        var htmlToInsert= '<h3> This is the Heading</h3>';  
        ref.innerHTML = htmlToInsert;  
    } </script>  
</head>  
<body> <button onclick = "addHeading()">Add Heading</button>  
        <div id="container"></div> </body>
```





Events





Events

- **JavaScript** can respond to events which can also be actions by the user.
 - **Example**, clicking on an element, hovering over an element are all actions by user and JavaScript uses events which can react to these actions.
- **JavaScript** attaches a function called an event listener or event handler to a specific event and the function invokes when the event occurs.

Events can be attached in the following ways:

1. Inline HTML attributes
2. Adding to element properties with JavaScript
3. Using DOM Event Listeners





Inline HTML Elements

- Events can be attached as attributes to the elements as shown below:

```
<div onclick = "showMsg()">Click</div>
```





Adding to Element Properties

- We can also assign a function to the onclick property of a DOM node element.
Have a look at the code snippet below:

```
<div id = "container">click here</div>
```

```
<script type = "text/javascript">var ref = document.getElementById('container');  
ref.onclick = function () {  
  alert('The div area is clicked');  
};  
</script>
```





Using DOM Event Listener

- The best way to handle events is to use the event listener approach.
- We can assign listeners to the click event using the **addEventListener()** method.
`ref.addEventListener(event,function)`
- **addEventListener()** method attaches an event handler to the specified element.
- You can add event listeners to any DOM object.
- The **removeEventListener()** method removes event handlers that have been attached with the `addEventListener()` method.

Syntax:

element.removeEventListener("Event Name", function);





Event Types

- **Mouse Events** – mouseup, mousedown, mouseover, mousemove, etc.
- **Keyboard Events** – keydown, keypress and keyup
- **Window Events** – load, unload
- **Form events** – focus, change





Event Bubbling and Event Capturing

- **Event Propagation** is the way of defining the element order when an event occurs.
- Two ways of event propagation in the HTML DOM:
 - Bubbling and Capturing
- **Event Bubbling:** inner most element's event is handled first and then the outer element's event.
- **Event Capturing:** outer most element's event is handled first and then the inner element's event.





Action Dialog

```
<script type="text/javascript">
```

```
function confirmDelete() {  
    var answer = confirm("Are you sure you want"  
        + "to delete this player?");  
    return answer  
}
```

```
</script>
```


```
<form method="post" action="/delete">
```

```
    <p>
```

```
        <input type="submit" value="Delete" onclick="return confirmDelete()" />
```

```
    </p>
```


```
</form>
```





Form Validation

```
<script>
function validate() {
  if (document.getElementById("name").value.length == 0) {
    alert("Please complete the required fields\n" +
      "and resubmit.");
    return false;
  }
  return true;
}
</script>
```




```
<h3>Add Player:</h3>
<form id="form1" action="addplayer" onsubmit="return validate()" >
  <p>Name: <input type="text" id="name" /></p>
  ...
  <p><input type="submit" value="Register" /></p>
</form>
```





Lets Discuss Assignments



Assignment

