


Wireshark can capture not only passwords but any type of information transmitted over the network: usernames, email addresses, personal information, etc. As long as we can capture network traffic, Wireshark can sniff passing passwords.

So, here we will see how we can capture the password using the Wireshark network capture analyzer. and see the outputs of the following steps.


The screenshot displays the Wireshark interface with a packet capture of an HTTP GET request. The packet list shows 'Frame 4: Packet, 504 bytes on wire (4032 bits), 504 bytes captured (4032 bits) on interface 0'. The packet details pane shows 'Ethernet II, Src: 08:00:00:00:00:00 (08:00:00:00:00:00), Dst: 08:00:00:00:00:00 (08:00:00:00:00:00), Protocol Version 4, Src: 127.0.0.1, Port: 55446, Destination: 127.0.0.1, Length: 504, Type: 0, Internet Protocol Version 4, Src: 127.0.0.1, Port: 55446, Destination: 127.0.0.1, Length: 504, Type: 0, Transmission Control Protocol, Src Port: 55446, Dst Port: 55446, Length: 504, Type: 0, Hypertext Transfer Protocol'. The packet bytes pane shows the raw data of the HTTP GET request.

Step 2: After starting the packet capturing we will go to the website and login the credential on that website as you can see in the image.



Step 3: Now after completing the login credential we will go and capture the password in Wireshark. for that we have to use some filter that helps to find the login credential through the packet capturing.

Step 4: Wireshark has captured some packets but we specifically looking for HTTP packets. so in the display filter bar we use some command to find all the captured HTTP packets. as you can see in the below image the green bar where we apply the filter.
http



Step 5: So there are some HTTP packets are captured but we specifically looking for form data that the user submitted to the website. for that, we have a separate filter


As we know that there are main two methods used for submitting form data from web pages like login forms to the server. the methods are-

- GET

- POST

Step 6: So firstly for knowing the credential we use the first method and apply the filter for the GET methods as you can see below.

`http.request.method == "GET"`



GET method

As you can see in the image there are two packets where the login page was requested with a GET request as well, but there is no form data submitted with a GET request.

Step 7: Now after checking the GET method if we didn't find the form data, then we will try the POST method for that we will apply the filter on Wireshark as you can see.

`http.request.method == "POST"`

As you can see we have a packet with form data click on the packet with user info and the application URL encoded. and click on the down-HTML form URL Encoded where the login credential is found. login credential as it is the same that we filed on the website in step 2.

Form item: "uname" = "**Tonystark_44**"

Form item: "pass" = "**tony@1234**"