



ANDHRA PRADESH POLLUTION CONTROL BOARD
D.No. 33-26-14 D/2, Near Sunrise Hospital, Pushpa Hotel Centre,
Chalamalavari Street, Kasturibaipet, Vijayawada – 520010.

Website : www.appcb.ap.nic.in

AMENDMENT TO THE CFE ORDER

Order No. 409 /APPCB/CFE/RO-VSP/HO/2017

Dt. 17.03.2019

Sub: APPCB - CFE - M/s. Vasudha Pharma Chem Limited, Unit – V, Plot No. 24, 24A & 24B, De-Notified Area, APSEZ, Lalamkoduru(V), Rambilli (M), Visakhapatnam District - Amendment to the CFE order – Issued – Reg.

- Ref: 1) CFE order dt. 11.01.2017.
2) Industry's representation dt. 08.02.2019.
3) E.E., R.O: Visakhapatnam report dt. 13.02.2019.
4) CFE Committee meeting held on 28.02.2019.
5) Industry's letter dt.28.02.2019.

In the reference 1st cited, the Board had issued CFE to the industry for establishment of an industry to manufacture 60 no. of products with a maximum production capacity of 9341.3 kg/day of which 22 products are API and 38 products are bulk drug intermediates with an investment of Rs. 152.0 Crores.

In the reference 2nd cited, the industry requested the Board for certain amendments in the CFE order dt. 11.01.2017.

The EE, RO: Visakhapatnam vide reference 3rd cited submitted report in this regard.

The item was placed before the CFE Committee in the meeting held on 28.02.2019. After detailed discussions, the Committee recommended to issue CFE amendment as requested by the industry.

The Board after careful scrutiny of the representation of the unit, report of the Regional Officer and recommendations of the CFE Committee, hereby issues Amendment to the CFE order issued vide reference 1st cited as following:

- Treatment & disposal of waste water in the condition No.2 of the CFE order issued vide reference 1st cited shall be read as following:

Treatment & disposal:

Source of effluent	Treatment	Mode of final disposal
HTDS	Equalization cum neutralization tank	To the CETP, Ramky Pharmacity till the M/s. AETL commences the operations.
LTDS	Equalization cum neutralization tank	
Domestic	Septic tank	Overflow of septic tank shall be sent to CETP along with LTDS effluent.

➤ The condition No. 7 in the CFE order issued shall be read as following:

7. The Air pollution Control equipment shall be installed along with the commissioning of the activity and shall comply with the following for controlling air pollution:

Sl. No	Details of Stack	Stack 1			Stack 2
a)	Attached to	Boiler	Boiler	Thermic fluid heater	DG Set
b)	Capacity	1 X 10.0 TPH	10.0 TPH (standby)	15.0 Lakh K. Cal	2 X 2000 KVA (one standby)
c)	Fuel	Coal	Coal	Coal	Diesel
d)	Stack height above ground	30 m			10 m above roof
e)	Air Pollution Control Equipment	Cyclone separator followed by Bag filter for each boiler			Silencer and Acoustic enclosure

➤ The condition No. 17 in the CFE order shall be read as following:

17. The proponent shall comply with the following:

S. No.	Solid / Hazardous waste	Quantity	Mode of final disposal
a)	Used Oil / Waste Lubrication Oil	1000 L/ month	To authorized Re-processors / Recyclers / to the Cement industries for co-processing.
b)	Containers & Container Liners	300 Nos/ month	To authorized agencies, after complete detoxification for re-use/ recycle.
c)	Glass Bottles / Scrap	50 kg/month	To scrap vendors.
d)	HDPE Bags and Polythene Bags	500 nos/ month	To TSDF / Authorized recyclers
e)	Boiler Ash	9400 kg/day	To Brick Manufacturers.
f)	Used Lead Acid Batteries	40 Nos / annum	To dealers on buy back system
g)	Spent Solvents	20.0 TPD	Shall be recovered within the premises / to authorized agency for recovery.
h)	Mixed Spent Solvents	2.0 TPD	To authorized recovery units / Authorized cement Industries for co-processing.
i)	Insulation Waste	150 kg/month	To authorized agencies (or) TSDF, Parawada for incineration / Cement Industries for co-processing.
j)	Process Organic Residues and Distillation Bottom Residue	5320 kg/day	To the authorized Cement industries for co-processing (or) TSDF, Parawada for incineration
k)	Spent Carbon	1180 kg/day	
l)	Inorganic Residue	2540 kg/day	To TSDF, Parawada for secured land filling.
m)	ETP Sludge	2000 kg/day	To cement industries for co-processing/ TSDF for secured landfill.
n)	PPFRP Waste	20 kg/ Annum	To TSDF / Authorized recyclers



CONSENT ORDER FOR ESTABLISHMENT

Order No. 409 /APPCB/CFE/RO-VSP/HO/2017

Dt. 11.01.2017

Sub: APPCB – CFE - M/s. Vasudha Pharma Chem Limited, Unit – V, Plot No. 24, 24A & 24B, De-Notified Area, APSEZ, Lalamkoduru(V), Rambilli (M), Visakhapatnam District - Consent for Establishment (CFE) of the Board under Sec.25 of Water (P & C of P) Act, 1974 and Under Sec.21 of Air (P&C of P) Act, 1981 - Issued - Reg.

Ref: 1) Industry's CFE application received through Single Desk Portal on 29.12.2016.
2) R.O's inspection report dt. 02.01.2017.
3) CFE Committee meeting held on 07.01.2017.

1. In the reference 1st cited, an application was submitted to the Board seeking Consent for Establishment (CFE) to produce the following products with installed capacities as mentioned below, with a project cost of Rs. 152.009 Crores.

S. N o.	Name of the Product	Capacity in kg/day	No. of Stages	Starting Raw material	Quantity (kg/day)
	API – Bulk Drugs				
1	Domperidone (DOM)	666.7	2	1-(3-Chloropropyl)-1,3-dihydro-2H-benzimidazole-2-one (DOM-II), (CPDB)	382.7
2	Losartan Potassium (LTP)	600.0	3	4'-Bromomethyl -2-biphenylcarbonitrile	450.0
3	Pantoprazole Sesquihydrate (PZL)	566.7	3	2-(Chloromethyl)-3,4-dimethoxy pyridine(100%)(PZL-700)	378.0
4	Fexofenadine Hydrochloride (FFH)	500.0	3	Methyl 2-(4-(4-chlorobutanoyl) phenyl) methyl propanoate	410.7
5	Diatrizoic acid Dihydrate (DZA)	333.3	3	3,5-Diaminobenzoic acid	148.1
6	Telmisartan (TLS)	266.7	3	4'-(Bromomethyl)-biphenyl-2-carbonitrile (Bromo OTBN)	179.6
7	Cyproheptadine (CYP)	166.7	3	4-Chloro-1-methyl piperidine	140.0
8	Loratadine (LRD)	133.3	2	(8-Chloro-11-(1-methylpiperidin-4-ylidene)-6,11-dihydro-5H-benzo [5, 6] cyclohepta [1,2-b] pyridine) [Methyl Loratadine]	152.5
9	Dextromethorphan Hydrobromide (DBR)	100.0	1	3-Methoxy Morphinan	111.0
10	Domperidone Maleate (DM)	100.0	1	Domperidone	83.3
11	Esomeprazole Magnesium Trihydrate (ES)	100.0	3	2-Chloromethyl-4-methoxy-3, 5-Dimethyl pyridine. HCl	95.7
12	Clopidogrel Bisulphate (CDS)	100.0	4	2-Chloro phenyl glycine	150.1
13	Itopride Hydrochloride (ITP)	83.3	5	N, N-Dimethyl amino ethanol	62.9
14	Flurbiprofen (FBF)	70.0	2	2-Bromo Propionic Acid	87.3
15	Amitriptyline Hydrochloride (AMPT)	56.7	3	1-Bromo-3-Chloropropane (BCP)	75.9
16	Quetiapine fumarate (QHF)	50.0	2	11-piperazin-1-yl dibenzo [b, f] [1,4] thiazepine Dihydrochloride (QHF-600)	50.0
17	Pregabalin (PGN)	33.3	4	Isovaleraldehyde	34.5
18	Omeprazole (OMP)	33.3	2	2-(Chloromethyl)-4-methoxy-3,5-dimethyl pyridine hydrochloride	28.0
19	Lansoprazole (LPZ)	33.3	2	2-(Chloromethyl)-3-methyl-4-(2,2,2-trifluoroethoxy) pyridine hydrochloride	34.8
20	Carvedilol (CDL)	10.0	3	4-Hydroxy Carbazole	16.0
21	Nortriptyline Hydrochloride (NOPT)	6.7	3	5-Hydroxy Amitriptyline (AMPT-I)	10.7

22	Ketorolac Tromethamine (KTT)	6.7	3	Triethyl (5-benzyl-1H-pyrrol-2-yl) methane tricarboxylate (TM-IV)	12.0
	API – Bulk Drug Intermediates				
23	N-Methyl-4-piperidone (NMP)	1000.0	3	Methyl Acrylate	1894.0
24	N-Carboxy-4-Piperidone (NCP)	766.7	1	N-Methyl-4-Piperidone (NMP)	573.0
25	5-chloro-1,3-dihydro-1-(4-piperidinyl)-2H-benzimidazol-2-one (DOM-IX)	500.0	5	N-carboxy-4-piperidone (NCP)	460.8
26	1-(3-chloropropyl)-1,3-dihydro-2H-benzimidazol-2-one (DOM-II)	400.0	2	Ortho phenyldiamine	307.5
27	N-Methyl-4-Chloro Piperidine (NMCP)	366.7	2	N-Methyl-4-Piperidone (NMP)	431.7
28	Dibenzosuberone (DBS)	333.3	4	Phenyl Acetic Acid	446.7
29	2-(Chloromethyl)-3,4-dimethoxypyridine hydrochloride (PZL-700)	300.0	7	Maltol	393.4
30	2-Butyl-1H-imidazole-5-carboxaldehyde (BFI)	166.7	1	2-Butyl-4-chloro-1H-imidazole-5-carboxaldehyde (BCFI-IV)	228.1
31	5-Dibenzosuberone (DDBS)	166.7	1	Dibenzosuberone (DBS)	200.0
32	5-(Difluoromethoxy)-1H-benzimidazole-2-thiol (BZL)	134.0	1	5-(Difluoromethoxy)-1H-Benzo[d]imidazole-2-thiol Crude	140.0
33	3-[2-(3-chlorophenyl) ethyl] pyridine-2-carbonitrile (UK-V)	126.7	1	3-[2-(3-chlorophenyl) ethyl] pyridine] (UK -III)	157.2
34	N-Benzyl-4-Piperidone (NBP-III)	116.7	3	Benzaldehyde	95.0
35	{3-[2-(3-chlorophenyl) ethyl] pyridin-2-yl} (1-methylpiperidin-4-yl) methanone hydrochloride (UK-VI)	83.3	2	3-[2-(3-chlorophenyl) ethyl] pyridine] (UK-III)	75.1
36	1- (Diphenyl methyl) piperazine (DPMP)	83.3	3	Benzhydrol (Diphenyl Methanol)	81.3
37	Fexofenadine Base	66.7	3	Methyl 2-(4-(4-chlorobutanoyl) phenyl) methyl propanoate	57.8
38	N,N-Dimethyl Amino Propyl Chloride (DAPC-I)	66.7	1	1-Bromo-3-Chloropropane (BCP)	112.0
39	4-Bromo-2,2-Diphenylbutanoic acid (LPD-III)	66.7	3	Diphenyl Acetonitrile	50.0
40	8-chloro-11-(1-methylpiperidin-4-ylidene)-6,11-dihydro-5H-benzo [5,6] cyclohepta[1,2-b] pyridine (UK-VII)	50.0	3	3-[2-(3-chlorophenyl) ethyl] pyridine] (UK-III)	63.3
41	N, N- Dimethyl (Tetra Hydro – 3, 3- Diphenyl)- 2- Furliden Ammonium Bromide (LPD-V)	43.3	1	4-Bromo-2, 2-diphenyl butanoic acid (LPD-III)	66.7
42	1-[bis(4-fluorophenyl) methyl] piperazine (FLH-III)	41.7	3	4,4-Di fluoro benzophenone	46.0
43	4-(4-Chlorophenyl) 4-Hydroxy Piperidine (PCP-II)	40.0	2	N-Carboxy-4-Piperidone (NCP)	53.3
44	2-Butyl -4-chloro-1H-imidazole -5-carbaldehyde (BCFI)	34.0	1	2-Butyl-4-chloro-1H-imidazole-5-carboxaldehyde (BCFI-IV)	35.0
45	8-Chloro-5, 6-Dihydro-11H-Benzo [5, 6] Cyclohepta [1, 2-B] Pyridin-11-One (Lora Ketone)- LKT	33.3	3	3-[2-(3-chlorophenyl) ethyl] pyridine] (UK-III)	54.1
46	1-(4-Tert-Butylphenyl)-4-Chlorobutan-1-One (EB-IV)	21.7	1	4-Chloro-butyl- chloride (4CBC)	17.5
47	4-Hydroxy Piperidine (4HP)	20.0	2	N-Carboxy-4-Piperidone (NCP)	39.6
48	4-(1-Hydroxy-1-	16.7	1	1-H-Imidazole-5-carboxylic acid 4-	5.7

	methylethyl)-2-propyl-1-[[2-(triphenylmethyl)-1H-tetrazole-5-yl] [1,1biphenyl]-4-yl] methyl] 1H-imidazol-5-carboxylic acid ethyl ester (OMI)			(1-hydroxy-1-methyl ethyl) -2-propyl -ethyl ester (OMI-101)	
49	Methyl Loratadine (ML)	11.7	4	3-[2-(3-chlorophenyl) ethyl] pyridine (UK-III)	18.4
50	2- [4-(amino methyl) phenoxy]-N, N-dimethyl ethanamine (ITP-300)	10.7	3	N, N-Dimethyl amino ethanol	12.0
51	Triethyl Methanetricarboxylate(TM-III)	10.0	1	Diethyl malonate	10.7
52	N-Methyl - 4-Hydroxy Piperidine (NMHP)	8.3	1	N-Methyl-4-Piperidone (NMP)	8.3
53	1-(2-phenylethyl) piperidin-4-one (PEP-II)	8.3	4	2-Phenylethanamine	8.7
54	Penta Fluoro LAP side chain (PPL)	6.7	2	Penta fluorophenol	4.2
55	Phenyl (1H-pyrrol-2-yl) methanone (TM-II)	6.7	2	Benzoyl chloride	5.8
56	Triethyl [5-Benzoyl-1h Pyrrol-2yl] Methane Tri Carboxylate (TM-IV)	6.7	4	Benzoyl chloride	4.1
57	N-carboethoxy-4-Hydroxy piperidine (4HNCP)	6.7	1	N-Carbethoxy-4-Piperidone (NCP)	7.0
58	4-Amino-5-Chloro-2-Methoxy-N-(3-Methoxypiperidin-4yl) Benzamide (CIS-VI)	4.3	6	Ethyl -4-oxopiperidine-1-carboxylate (NCP)	8.0
59	Piperidone Derivatives	100.0	-	---	
60	Validation Products	100.0	-	---	-
	TOTAL	9341.3			

- As per the application, the above activity is to be located at Plot No. 24, 24A & 24B, De-Notified Area, APSEZ, Lalamkoduru(V), Rambilli (M), Visakhapatnam District in an area of 105300.00 Sq. m.
- The above site was inspected by the Asst. Environmental Engineer - II, Regional Office, Visakhapatnam A.P Pollution Control Board on 02.01.2017 and observed that the site is surrounded by

North : APIIC Internal Road
South : APIIC Internal Road
East : M/s Posh chemical
West : APIIC Internal Road
- The Board, after careful scrutiny of the application, verification report of Regional Officer and recommendations of the CFE Committee, hereby issues **CONSENT FOR ESTABLISHMENT** to your activity Under Section 25 of Water (Prevention & Control of Pollution) Act 1974 and Section 21 of Air (Prevention & Control of Pollution) Act, 1981 and the rules made there under. **This order is issued to manufacture the products as mentioned at para (1) only.**
- This Consent order issued is subject to the conditions mentioned in the Annexure.

6. This order is issued from pollution control point of view only. Zoning and other regulations are not considered.
7. This order is valid for period of 7 years from the date of issue.

Encl: Annexure

MEMBER SECRETARY

To

M/s. Vasudha Pharma Chem Limited, Unit – V,
Plot No. 79, JNPC, Parawada,
JN Pharmacy,
Vishakhapatnam District.
raman72000@gmail.com

Copy to: 1. The JCEE, Z.O., Visakhapatnam for information and necessary action.
2. The EE, R.O., Visakhapatnam for information and necessary action.

Annexure

1. The proponent shall obtain Consent for Operation (CFO) from APPCB, as required Under Sec.25/26 of the Water (P&C of P) Act, 1974 and under sec. 21/22 of the Air (P&C of P) Act, 1981, before commencement of the trial runs.
2. The applicant shall provide separate energy meters for Effluent Treatment Plant (ETP) and Air pollution Control equipments to record energy consumed. An alternative electric power source sufficient to operate all pollution control systems shall be provided.
3. The industry shall construct separate storm water drains and provide rain water harvesting structures. No effluents shall be discharged in to the storm water drains.

Water:

1. The source of water is APIIC Supply and the maximum permitted water consumption is as following:

S. No.	Purpose	Quantity (KLD)
1.	Industrial cooling, boiler feed.	100.0
2.	Domestic and gardening purposes.	27.0
3.	Processing, whereby water gets polluted and pollutants are easily bio- degradable.	----
4.	Processing, whereby water gets polluted and the pollutants are not easily bio-degradable.	168.0
	Total	295.0

Separate meters with necessary pipe-line shall be provided for assessing the quantity of water used for each of the purposes mentioned above.

2. The maximum waste water generation shall not exceed the following:

S.No.	Source	Effluent generation in KLD		
		HTDS	LTDS	Total
1	Process	168.0	18.0	186.0
2	Washings	0.0	10.0	10.0
3	Boiler Blow down	0.0	5.0	5.0
4	Cooling Towers Blow down	0.0	5.0	5.0
5	Scrubbers System	0.0	10.0	10.0
6	R&D, QC	0.0	4.0	4.0
7	DM Plant Regeneration	0.0	2.0	2.0
8	Domestic	0.0	10.0	10.0
	Total	168.0	64.0	232.0

Treatment & disposal:

Source of effluent	Treatment	Mode of final disposal
HTDS	Equalization cum neutralization tank	Common effluent treatment plant
LTDS	Equalization cum neutralization tank	Common effluent treatment plant
Domestic	Septic tank	Overflow shall be sent to CETP provided by APIIC along with LTDS effluents.

3. The Effluent Treatment Plant (ETP) shall be constructed and commissioned along with the commissioning of the activity. All the units of the ETP shall be impervious to prevent ground water pollution. The ETP units shall be constructed above the ground level

Effluents shall not be discharged on land or into any water bodies or aquifers under any circumstances.

4. The industry shall provide magnetic flow meters with totalisers at the outlets of storage tanks of effluents.
5. Floor washing shall be admitted into the effluent collection system only and shall not be allowed to find their way in storm drains or open areas. All pipe valves, sewers, drains shall be leak proof.
6. The industry shall comply with the following conditions:
- Storm water drains shall be provided and connect to the rainwater runoff collection tank.
 - Rainwater runoff tank for collection of rainwater for first 15 minutes of rain shall be provided.
 - The industry shall install web camera to flow meters along with commissioning of the plant.
 - The industry shall collect the effluents into a HDPE tank in masonry tank (i.e., tank in tank) and store the effluents in the above ground effluent storage tanks.

Air:

7. The Air pollution Control equipment shall be installed along with the commissioning of the activity and shall comply with the following for controlling air pollution.

Sl. No	Details of Stack	Stack 1	Stack 2	Stack 3
a)	Attached to:	Coal fired Boiler	Thermic fluid heater	D. G.S et
b)	Capacity	8.0 TPH & 10.0 TPH	2 No's of 4.0 Lakh K. Cal	2 X 2000 KVA
c)	Name of the Fuel :	Coal	Diesel	Diesel
d)	Stack height above ground (m.)	30 m	----	9.0 m each above roof
e)	Air Pollution Control Equipment:	Cyclone separator followed by Bag filter for each boiler	----	Silencer and Acoustic enclosures

8. A sampling port with removable dummy of not less than 15 cm diameter shall be provided in the stack at a distance of 8 times the diameter of the stack from the nearest constraint such as bends etc. A platform with suitable ladder shall be provided below 1 meter of sampling port to accommodate three persons with instruments. A 15 AMP 250 V plug point shall be provided on the platform.
9. The industry shall provide multi-stage scrubbers to the process vents to control the process emissions. The industry shall provide online pH measuring facility with auto recording system to the scrubbers provided to treat the process emissions.
10. The industry shall provide VOC monitoring system with auto recording facility.
11. The industry shall implement adequate measures to control all fugitive emissions from the plant.

12. The proponent shall ensure compliance of the National Ambient Air quality standards notified by MoEF, GoI vide notification No. GSR. 826 (E), dated. 16.11.2009 during construction and regular operational phase of the project at the periphery.

The generator shall be installed in a closed area with a silencer and suitable noise absorption systems. The ambient noise level shall not exceed 75 dB(A) during day time and 70 dB(A) during night time.

13. The proponent shall not use or generate odour causing substances or Mercaptans and cause odour nuisance in the surroundings.
14. The industry shall send the used / spent solvents to the recyclers (or) process them at their own solvent recovery facility within the premises.
15. The evaporation losses in solvents shall be controlled by taking the following measures:
- Chilled brine circulation shall be carried out to effectively reduce the solvent losses into the atmosphere.
 - Transfer of solvents shall be done by using pumps instead of manual handling.
 - Closed centrifuges shall be used to reduce solvent losses.
 - All the solvent storage tanks shall be connected with vent condensers to prevent solvent vapours.
 - The reactor vents shall be connected with primary & secondary condensers to prevent escaping of solvent vapour emissions into atmosphere.
16. In the present proposal Hydrogen Bromide gases would be generated. The industry shall provide three stage scrubbers for controlling HBr gases. The vent of the scrubber shall be dipped in Caustic Solution for total control of HBr gases generated from the industry.

Solid Waste:

17. The proponent shall comply with the following:

S. No.	Solid / Hazardous waste	Quantity	Mode of final disposal
a)	Used Oil / Waste Lubrication Oil	1000 KL/ annum	To authorized Re-processors / Recyclers / to the Cement industries to use as alternate fuel in the kiln
b)	Containers & Container Liners	300 Nos/ month	To authorized agencies, after complete detoxification for re-use/ recycle.
c)	Glass Bottles / Scrap	50 kg/month	To scrap vendors.
d)	HDPE Bags and Polythene Bags	500 nos/ month	TSDF / Authorized recyclers
e)	Boiler Ash	9400 kg/day	To Brick Manufacturers.
f)	Used Lead Acid Batteries	40 Nos / annum	To dealers on buy back system
g)	Spent Solvents	20.0 TPD	Recovery within the premises / to authorised agency for recovery.
h)	Mixed Spent Solvents	2.0 TPD	To authorized recovery units / Authorized cement plant for co-processing.
i)	Insulation Waste	50kg/Annum	Sent to authorized agencies (or) TSDF, Parawada / Cement Industries
j)	Process Organic Residues and Distillation Bottom Residue	5320 kg/day	To the authorized Cement industries for being used as alternate fuel in the kiln (or) TSDF, Parawada for incineration

k)	Spent Carbon	1180 kg/day	To the authorized Cement industries to used alternate fuel in the kiln (or) TSDF, Parawada for incineration
l)	Inorganic Residue	2540 kg/day	To TSDF, Parawada for secured land filling.
m)	ETP Sludge	2000 kg/day	To cement plant for co-processing/ TSDF for secured landfill.
n)	PPFRP Waste	20 kg/Annum	TSDF / Authorized recyclers

18. The proponent shall place the chemical drums and / or any drums in a shed provided with concrete platform only. The Platform shall be provided with sufficient dyke wall and effluent collection system. The industry shall provide containers detoxification facility. Container & Container liners shall be detoxified at the specified covered platform with dyke walls and the wash wastewater shall be routed to low TDS collection tank.
19. The following rules and regulations notified by the MoE&F, GoI shall be implemented.
- Hazardous waste and other wastes (Management and Transboundary Movement) Rules, 2016.
 - Manufacture, Storage and Import of Hazardous Chemicals Rules, 1989
 - Batteries (Management & Handling) Rules, 2010.
 - E-Waste (Management) Rules, 2016.
 - Construction and Demolition waste Management Rules, 2016.

Other Conditions:

20. The industry shall comply with the following conditions:
- Storm water drains shall be provided and connect to the rainwater runoff collection tank.
 - Rainwater runoff tank for collection of rainwater for first 15 minutes of rain shall be provided.
 - The industry shall install web camera to flow meters along with commissioning of the plant.
 - In the present proposal Hydrogen Bromide gases would be generated. The industry shall provide three stage scrubber for controlling HBr gases. The vent of the scrubber shall be dipped in Caustic Solution for total control of HBr gases generated from the industry.
 - The industry shall collect the effluents into a HDPE tank in masonry tank (i.e., tank in tank) and store the effluents in the above ground effluent storage tanks.
21. Green belt shall be developed all along the boundary & vacant spaces with tall growing trees with good canopy and it shall not be less than 22% of the total area.
22. Concealing the factual data or submission of false information/ fabricated data and failure to comply with any of the conditions mentioned in this order and attract action under the provisions of relevant pollution control Acts.
23. Notwithstanding anything contained in this conditional consent, the Board hereby reserves its right and power under Sec.27(2) of Water (Prevention and Control of Pollution) Act, 1974 and under Sec.21(4) of Air (Prevention and Control of Pollution) Act, 1981 to revoke the order, review any or all the conditions imposed herein and to make such alternation as deemed fit and stipulate any additional conditions or revoke the order in the interest of environment protection.

24. Any person aggrieved with this order may within thirty days from the date on which the order is communicated to him, prefer an appeal as per Andhra Pradesh Water Rules, 1976 and Air Rules, 1982, to the Appellate Authority constituted under Section 28 of Water (Prevention and Control of Pollution) Act, 1974 and Section 31 of the Air (Prevention and Control of Pollution) Act, 1981.

MEMBER SECRETARY

To

M/s. Vasudha Pharma Chem Limited, Unit -- V,
Plot No. 79, JNPC, Parawada,
JN Pharmacy,
Vishakhapatnam District.
raman72000@gmail.com