



ANDHRA PRADESH POLLUTION CONTROL BOARD
D.No.33-26-14D/2, Near Sunrise Hospital, Pushpa Hotel Centre,
Chalamalavaari Street, Kasturibaipet, Vijayawada - 520 010
Phone. No.0866-2436217, Website : www.appcb.ap.nic.in

**RED CATEGORY
 CONSENT & AUTHORIZATION ORDER**

Consent Order No : APPCB/VSP/VSP/304/HO/CFO/2019-

15/02/2019

CONSENT is hereby granted for Operation under section 25/26 of the Water (Prevention & Control of Pollution) Act, 1974 and under section 21 of Air (Prevention & Control of Pollution) Act 1981 and amendments thereof and Authorisation under Rule 6 of the Hazardous & Other Wastes (Management and Transboundary, Movement) Rules, 2016 and the rules and orders made there under (hereinafter referred to as 'the Acts', 'the Rules') to:

**M/s. Vasudha Pharma Chem. Ltd., Unit - II,
 (Change of product mix),
 Plot No.79,JN Pharmacy,
 Parawada, Visakhapatnam
 Email : hrdcorporate@vasudhapharma.com**

(Hereinafter referred to as 'the Applicant') authorizing to operate the industrial plant to discharge the effluents from the outlets and the quantity of emissions per hour from the chimneys as detailed below:

The industry shall handover the original Consent order No. APPCB/VSP/VSP/304/HO/CFO/2016, dated 30.06.2016 having validity upto 31.05.2021 to the RO, Visakhapatnam after receipt of this order and the same stands cancelled from the date of receipt of this order.

i. Outlets for discharge of effluents:

Outlet No.	Outlet Description	Max Daily Discharge (KLD)	Point of Disposal
1.	High TDS effluents	90.20	To MEE of CETP, Pharmacy, Parawada for evaporation and further disposal.
2.	Low TDS effluents	53.30	To CETP, Pharmacy for further treatment and disposal.

ii) Emissions from chimneys:

Chimney No.	Description of Chimney	Quantity of Emissions at peak flow in m3/hr.
1.	Attached to 10 TPH Coal Fired Boiler	32940
2.	Attached to 6 TPH Coal Fired Boiler (Standby)	--
3.	Attached to 1 X 4 Lakhs Kilo Cal/hr Thermic fluid heater	--
4.	Attached to 1 X 0.5 Lakhs Kilo Cal/hr	

	Thermic fluid heater	
5.	Attached to Process Vents	--
6.	Attached to 2 X 1010 KVA & 1 X 725 KVA DG Sets	--

iii) **HAZARDOUS WASTE AUTHORISATION (FORM - II) [See Rule 6 (2)]:**

M/s. Vasudha Pharma Chem. Ltd., JN Pharmacity, Parawada, Visakhapatnam District is hereby granted an authorization to operate a facility for collection, reception, storage, treatment, transport and disposal of Hazardous Wastes namely:

• **HAZARDOUS WASTES WITH DISPOSAL OPTION:**

Sl. No	Name of Hazardous Waste	Stream	Quantity	Method of disposal
1.	Organic Residue	28.1 of Schedule - I	1632.3 Kg/Day	TSDF, Parawada for incineration / Cement Industries for co-processing in cement kiln
2.	Spent carbon	28.3 of Schedule - I	845.6 Kg/Day	
3.	PP & PPE Waste		100 Kg/Month	
4.	Organic residue/ Distillation residue	28.1 of Schedule - I	1632 Kg/Day	
5.	Discarded personal Protective equipment (PPE's)		100 Kgs/month	
6.	Off Specification / Discarded Products	28.4 of Schedule - I	30 Kg/day	
7.	Expired Products	28.4 of Schedule - I	60 Kg/Day	
8.	ETP Sludge	34.3 of Schedule - I	500 Kg/day	To TSDF, Parawada (or) to the Cement industries for incineration.
9.	Inorganic Waste from Process	28.1 of Schedule - I	1694.2 Kg/Day	
10.	Used Insulation Wool	15.1 of Schedule - I	1.0 TPD	
11.	Glass wool / Asbestos / Gypsum Boards	15.1 of Schedule - I	25 Kgs/Annum	

• **HAZARDOUS WASTES WITH RECYCLING OPTION:**

Sl. No	Name of Hazardous Waste	Stream	Quantity	Method of disposal
1.	Spent Solvents	28.6 of Schedule - I	12 KLD	To Solvent Recovery Plant (Vasudha Unit-III) for Recovery (OR) to APPCB Authorized Solvent Recovery Recyclers.
2.	Spent Mixed Solvents	28.6 of Schedule- I	10 KLD	
3.	Used Oils	5.1 of Schedule - I	170 LPM	APPCB Authorized Agencies
4.	Containers & Container Liners	33.1 of Schedule - I	120 No's/Day	After Detoxification sent back to suppliers / APPCB authorized parties

5.	Spent Catalyst	28.2 of Schedule - I	10 Kg/day	To the Supplier for Recovery/Recyclers
----	----------------	-------------------------	-----------	--

This consent order is valid for the following products along with quantities indicated only:

Sl. No.	Products	Quantity (Kg/Day)	No. of Stages	Starting Raw material	Quantity (Kg/Day)
1.	Carvedilol (CDL)	0.33	3	4-Hydroxy Carbazole	0.50
2.	Cyproheptadine (CYP)	166.67	3	4-Chloro-1-methyl piperidine	140.0
3.	Dextromethorphan Hydrobromide (DBR)	100.00	1	3-Methoxy Morphinan	111.0
4.	Diatrizoicacid Dihydrate (DZA)	166.67	3	3,5-Diaminobenzoic acid	74.1
5.	Domperidone (DOM)	500.00	2	1-(3-Chloropropyl)-1,3-dihydro-2H-benzimidazole-2-one (DOM-II), (CPDB)	287.2
6.	Domperidone Maleate (DM)	133.33	1	Domperidone	111.3
7.	Fexofenadine Hydrochloride (FFH)	333.33	3	Methyl 2-(4-(4-chlorobutanoyl) phenyl) methyl propanoate	274.1
8.	Loratadine (LRD)	133.33	2	(8-Chloro-11-(1-methylpiperidin-4-ylidene)-6,11-dihydro-5H-benzo [5, 6] cyclohepta [1,2-b] pyridine) [Methyl Loratadine]	152.5
9.	Losartan Potassium (LTP)	600.00	3	4'-Bromomethyl -2-biphenylcarbonitrile	450.0
10.	Pantoprazole Sesquihydrate (PZL)	566.67	3	2-(Chlormethyl)-3,4-dimethoxy pyridine (100%) (PZL-700)	378.0
11.	Quetiapine fumarate (QPF)	166.67	2	Di benzo [b, f] [1,4] thiazepine-1 1 (10H) one (Keto)	100.0
12.	Telmisartan (TLS)	200.00	3	4'-(Bromomethyl)-biphenyl-2-carbonitrile (Bromo OTBN)	134.7
13.	2-Butyl-1H-imidazole-5-carboxaldehyde (BFI)	166.67	1	2-Butyl-4-chloro-1H-imidazole-5-carboxyldehyde (BCFI-IV)	228.1
14.	2-(Chloromethyl)-3,4-dimethoxypyridine hydrochloride (PZL-700)	166.67	7	Maltol	218.4
15.	4-Amino-5-Chloro-2-Methoxy-N-(3-Methoxypiperidin-4yl) Benzamide (CIS-VI)	4.33	6	Ethyl -4-oxopiperidine-1-carboxylate (NCP)	8.0
16.	5-Bromo-6-Iso thiocyanate	2.33	4	4-Nitrobenzene-1,2-diamine	3.2

	Quinoxaline (BAQ)				
17.	2-Butyl -4-chloro-1H-imidazole -5-carbaldehyde (BCFI)	146.67	1	2-Butyl-4-chloro-1H-imidazole-5-carboxyldehyde (BCFI-IV)	150.5
18.	5-(Difluoromethoxy)-H-benzo [d] imidazole-2-thiol (BZL)	140.00	1	5-(Difluoromethoxy)-1H-Benzo[d] imidazole-2-thiol Crude	145.8
19.	Fexofenadine Base	10.00	3	Methyl 2-(4-(4-chlorobutanoyl) phenyl) methyl propanoate	8.3
20.	Validation Products	100.00	-	-	-
21.	Dabigatran Etexilate	33.33	4	Ethyl 3-((3-amino-4-(methylamino) benzoyl) (pyridin-2-yl) amino) propanoate	66.7
22.	Dimethyl fumarate	16.67	2	Fumaric acid	20.0
23.	Abametapir	16.67	2	2-Bromo-5-methyl-pyridine	41.7
24.	Teneligliptin Hydrobromide	16.67	4	3-((S)-1-tert-butoxycarbonyl-4-oxo-2-pyrrolidinylcarbonyl)-1,3-thiazolidine	20.0
25.	Levetiracetam	50.00	2	4-Chloro butyryl chloride	110.0
26.	Diatrizoate Sodium	16.67	1	Diatrizoicacid dihydrate	18.5
27.	Diatrizoate Meglumine	16.67	1	Diatrizoicacid dihydrate	14.7
28.	Methoxy phenamine hydrochloride	16.67	4	2-Methoxy benzaldehyde	21.7
29.	Dex-Lansoprazole	16.67	2	4-(2, 2, 2-trifluoroethoxy)-2-(Chloromethyl)-3-methylpyridine	33.3
30.	Mirabegron	63.00	4	2-(4-Nitrophenyl) ethylamine hydrochloride	42.1
31.	Cisapride Monohydrate	16.67	2	4-amino-5-chloro-2-methoxy-N-(3-methoxy piperidin-4-yl) benzamide	15.0
32.	Dolutegravir	16.67	3	6-(methoxycarbonyl)-1,4-dihydro-5-methoxy-1-(2,2-dimethoxyethyl)-4-oxopyridine-3-carboxylic acid	41.7
33.	Linagliptin	16.67	3	8-Bromo-7-(2-butynyl)-3,7-dihydro-3-methyl-1H-purine-2,6-dione	27.7
34.	Loperamide	33.33	2	3,3-Diphenyltetrahydrofuran-2-ylidene(dimethyl)ammonium	30.0

				bromide	
35.	Des Loratadine	16.67	2	Ethyl 4-(8-chloro-5,6-dihydro-11H-benzo [5,6] cyclohepta [1,2-b] pyridin-11-ylidene) piperidine-1-carboxylate (Loratadine)	28.0
36.	Rupatadine Fumarate	16.67	2	8-chloro-11-piperidin-4-ylidene-5,6-dihydrobenzo [1,2] cyclohepta [2,4-b] pyridine (Des Loratadine)	13.3
37.	Valsartan	16.67	4	4-Bromomethyl-2 Cyanobiphenyl (Bromo OTBN)	50.0
38.	3,4-Bis(benzyloxy) benzaldehyde (DBB)	16.67	1	3,4-Di-hydroxy benzaldehyde (DHB)	8.4
39.	(R)-N-(2-Benzoyl-4-chloro)-1-Benzylpyrrolidine-2-carboxamide hydrochloride (APR-I)	16.67	1	3-Ethoxy 4-methoxy benzonitrile	14.0
40.	Glycine-Ni-D-2- [N-(N-benzyl prolyl)-2-amino]-5-chlorobenzophenone (CNG)	16.67	3	D-Proline	14.5
41.	2-(Chloromethyl)-3-methyl-4-(2,2,2-trifluoroethoxy) pyridine hydrochloride (LPZ-300)	33.33	1	2-(Chloromethyl)-3-methyl-4-(2,2,2-trifluoroethoxy) pyridine hydrochloride	34.5
42.	1-(2,6-Difluorobenzyl)-1H-1,2,3-Triazole-4-Carboxylic acid (RFN)	16.67	2	2,6-Difluorobenzyl chloride	18.6
	TOTAL	4300.0			

This order is subject to the provisions of 'the Acts' and the Rules' and orders made thereunder and further subject to the terms and conditions incorporated in the schedule A, B & C enclosed to this order.

This combined order of consent & Hazardous Waste Authorization shall be valid for a period ending with the 31st day of January, 2024.

Bandla Siva
Sankar Prasad

Digitally signed by Bandla Siva Sankar Prasad
Date: 2019.02.15 18:26:36 +05'30'

BANDLA SIVA SANKARA PRASAD
CHAIRMAN

To
M/s. Vasudha Pharma Chem. Ltd., Unit - II,
(Change of Product mix),
Plot No.79, JN Pharmacy,
Parawada, Visakhapatnam

Copy to :

1. The JCEE, Zonal Office, **Visakhapatnam** for information and necessary action.
2. The Environmental Engineer, Regional Office, **Visakhapatnam** for information and necessary action.

SCHEDULE-A

1. Any up-set condition in any industrial plant / activity of the industry, which result in, increased effluent / emission discharge and/ or violation of standards stipulated in this order shall be informed to this Board, under intimation to the Collector and District Magistrate and take immediate action to bring down the discharge / emission below the limits.
2. The industry should carryout analysis of waste water discharges or emissions through chimneys for the parameters mentioned in this order on quarterly basis and submit to the Board.
3. All the rules & regulations notified by Ministry of Law and Justice, Government of India regarding Public Liability Insurance Act, 1991 should be followed as applicable.
4. The industry should put up two sign boards (6x4 ft. each) at publicly visible places at the main gate indicating the products, effluent discharge standards, air emission standards, hazardous waste quantities and validity of CFO and exhibit the CFO order at a prominent place in the factory premises.
5. Not withstanding anything contained in this consent order, the Board hereby reserves the right and powers to review / revoke any and/or all the conditions imposed herein above and to make such variations as deemed fit for the purpose of the Acts by the Board.
6. The applicant shall submit Environment statement in Form V before 30th September every year as per Rule No.14 of E(P) Rules, 1986 & amendments thereof.
7. The applicant should make applications through Online for renewal of Consent (under Water and Air Acts) and Authorization under H&OW (M&TM) Rules, 2016 at least 120 days before the date of expiry of this order, along with prescribed fee under Water and Air Acts and detailed compliance of CFO conditions for obtaining Consent & HW Authorization of the Board. The industry should immediately submit the revised application for consent to this Board in the event of any change in the raw material used, processes employed, quantity of trade effluents & quantity of emissions. Any change in the management shall be informed to the Board. The person authorized should not let out the premises / lend / sell / transfer their industrial premises without obtaining prior permission of the State Pollution Control Board.
8. Any person aggrieved by an order made by the State Board under Section 25, Section 26, Section 27 of Water Act, 1974 or Section 21 of Air Act, 1981 may within thirty days from the date on which the order is communicated to him, prefer an appeal as per Andhra Pradesh Water Rules, 1976 and Air Rules 1982, to Appellate authority constituted under Section 28 of the Water(Prevention and Control of Pollution) Act, 1974 and Section 31 of the Air(Prevention and Control of Pollution) Act, 1981.

SCHEDULE-B

1. The industry shall handover the original Consent order No. APPCB/VSP/VSP/304/HO/CFO/2016, dated 30.06.2016 having validity upto 31.05.2021 to the RO, Visakhapatnam after receipt of this order and the same stands cancelled from the date of receipt of this order.

WATER POLLUTION:

2. The source of water is JNPC Supply. The following is the permitted water consumption:

Sl. No.	Description	Quantity (KLD)
1.	Process & Washings	78.3
2.	Boiler Feed	55.0
3.	Cooling Towers Makeup	50.0
4.	Scrubber	10.0
5.	PD & QC	3.0
6.	Raw water RO Plant (Drinking)	12.0
7.	Domestic	20.0
8.	Gardening	7.0
	Total	235.3

3. Digital flow meters with totalizers with necessary pipelines shall be provided so as to assess the water used for different purposes within 1 month and maintain them properly and also maintain the records of the readings.

4. The LTDS effluent discharged shall not contain constituents in excess of the tolerance limits mentioned below, as per their MOU dt.09.05.2007 with Ramky Pharma City and committed vide letter dt.01.10.2007.

Outlet	Parameter	Concentration in mg/l
2	pH	6.50 - 8.50
	Temperature °C	< 45°C
	TDS	12,000 mg/l
	TSS	600 mg/l
	BOD	3,000 mg/l
	COD	8,000 mg/l
	Oil and Grease	20 mg/l
	Chromium Hexavalent (as Cr+6)	2 mg/l
	Chromium (total) (as Cr)	2 mg/l
	Ammonical Nitrogen (as N)	30 mg/l
	Cynide (as CN)	0.20 mg/l
	Lead (as Pb)	1 mg/l
	Nickel (as Ni)	3 mg/l
	Zinc (as Zn)	15 mg/l
	Arsenic (as As)	0.20 mg/l
	Mercury (as Hg)	0.01 g/l

The industry shall segregate the HTDS and LTDS effluent streams and the effluents which are not meeting the above standards shall be treated as HTDS effluents and shall be sent CETP of Pharmacity for evaporation.

5. The industry shall install and maintain Electro Magnetic flow meters with totalisers for effluent quantity measurement for HTDS & LTDS effluent immediately. The industry shall install and maintain web camera for flow meters and connect the same to the CPCB immediately.

6. The LTDS and HTDS effluents shall be stored in above ground level collection tanks separately.

7. Effluents shall not be discharged onland or any water bodies or aquifers or outside under any circumstances. Floor washings shall be admitted into effluent collection system only and shall not be allowed to find their way into storm water drains or open areas.

8. The industry shall maintain rainwater runoff tank for collection and storage of first flush storm water. The industry shall maintain dry condition outside drains in non-rainy season.
9. Container & Container liners shall be detoxified at the specified covered platform with dyke walls and the wash wastewater shall be routed to low TDS collection tank after characterization.
10. The drums containing chemicals / solvents shall be stored under a roof on elevated platform with a provision to collect leakages / spillages in the collection pit.
11. The industry shall comply with CPCB directions dated 05.02.2014 / 02.03.2015 and guidelines issued regarding online monitoring systems issued from time to time. The online monitoring system shall be calibrated periodically as per equipment suppliers manual / CPCB guidelines.
12. The industry shall maintain proper manifest system for effluent transported to CETP. They shall submit monthly reports to the E.E., RO-Visakhapatnam.
13. The industry shall submit the details of quantity of High TDS and Low TDS effluents sent to CETP of Pharmacity every month to the RO, Visakhapatnam.
14. The industry shall maintain dry condition outside drains in un-rainy season.

AIR POLLUTION:

15. The industry shall not operate the 4.0 lakhs kilo calorie thermic fluid heater until installation of suitable air pollution control equipment to meet the emission standards stipulated as committed in the CFO committee meeting held on 08.02.2019.
16. The emissions shall not contain constituents in excess of the prescribed limits mentioned below:

Chimney No.	Parameter	Emission Standards
1, 2, 3 & 4	Particulate matter	100 mg/Nm ³
5	Acid mist	35 mg/Nm ³

17. The industry shall comply with ambient air quality standards of PM₁₀ (Particulate Matter size less than 10 microns) - 100 micro gram/ m³; PM_{2.5} (Particulate Matter size less than 2.5 microns) - 60 micro gram/ m³; SO₂ - 80 micro gram/ m³; NO_x - 80 micro gram/m³, outside the factory premises at the periphery of the industry.

Standards for other parameters as mentioned in the National Ambient Air Quality Standards CPCB Notification No.B-29016/20/90/PCI-I, dated 18.11.2009.

Noise Levels: Day time (6 AM to 10 PM) - 75 dB (A)

Night time (10 PM to 6 AM) - 70 dB (A)

18. The industry shall comply with emission limits for DG sets of capacity upto 800 KW as per the Notification G.S.R.520 (E), dated 01.07.2003 and G.S.R.448(E), dated 12.07.2004 under the Environment (Protection) Act Rules. In case of DG sets of capacity more than 800 KW shall comply with emission limits as per the Notification G.S.R.489 (E), dated 09.07.2002 at

serial no.96, under the Environment (Protection) Act, 1986.

- 19.The industry shall install and operate the two stage scrubber for scrubbing of process emissions at all emission sources.
- 20.The industry shall maintain multi stage scrubber with online pH meters to control gaseous emissions. The scrubbed solutions shall be recycled to the maximum extent. The details of chemicals consumption used in the scrubber shall be recorded and kept accessible for the inspection officials of the Board.
- 21.The industry shall maintain auto recording system to the online pH measuring facility of the scrubber and report compliance to Regional Office, Visakhapatnam. Scrubber solution shall be recycled as far as possible and finally sent to CETP of Pharmacity for further treatment.
- 22.The industry shall maintain online VOC analyzer and the monitoring records shall be submitted to the RO-Visakhapatnam.
- 23.The evaporation losses in solvents shall be controlled by taking suitable measures, which include:
 1. Chilled brine circulation to effectively reduce the solvent losses into the atmosphere.
 2. Transfer of solvents by using pumps and closed conveyance instead of manual handling.
 3. Closed centrifuges be used due to which solvent losses are reduced drastically.
 4. The reactor vents connected with primary & secondary condensers to catch the solvent vapours.
 5. All the solvent storage tanks are connected with vent condensers to prevent solvent vapours.
- 24.The industry shall not use odour causing substances such as Mercaptan or cause odour nuisance in the surroundings.
- 25.The industry shall provide the hood on the top of the effluent storage tank with in 3 months as committed in the CFO committee meeting held on 08.02.2019.
- 26.The industry shall inform the APPCB, Regional Office during maintenance Air pollution control equipments.

GENERAL:

- 27.The industry shall update the information in OCEMS - Industry Information Data Entry Software for Compliance Reporting Protocol in PART-II (Sections F & G) Every Quarter on 1st January, 1st April, 1st July and 1st October through this software system.
- 28.The industry shall submit the information regarding usage of Ozone Depleting Substance once in six months to the Board.
- 29.The industry shall maintain online real time monitoring (web camera) facilities to flow meters as per CPCB guidelines.
- 30.The industry shall not manufacture any product, other than those mentioned in this order.
- 31.The industry shall maintain the following records and the same shall be made available to the inspecting officers of the Board:
 1. Daily production details (ER-1 Central Excise Returns).

2. Quantity of Effluents generated, treated, recycled/reused and disposed to CETP.
3. Log Books for pollution control systems.
4. Characteristics of effluents and emissions.
5. Hazardous/non hazardous solid waste generated and disposed.
6. Inspection book.
7. Manifest copies of effluents / hazardous waste.
32. The industry shall submit AAQ monitoring reports conducted by Authorised Agency every month.
33. The industry shall dispose solid waste (NON HAZARDOUS) as follows:

S. No.	Name of the Solid Waste	Quantity	Disposal
1.	Coal ash	5.0 TPD	Disposed to Brick Manufacturers
2.	Paper, cotton waste & packing materials i.e. wood, carton & ropes etc.,	500 Kgs/month	Sale to outside agencies/recyclers
3.	Metal scrap (MS, SS, GI & Aluminium)	2 TPM	

34. Green belt of adequate width and density shall be maintained along the boundary of the industry with minimum area of 33% of total area within 1 month.

SCHEDULE - C

[See rule 6(2)]

[CONDITIONS OF AUTHORISATION FOR OCCUPIER OR OPERATOR HANDLING HAZARDOUS WASTES]

1. The authorised person shall comply with the provisions of the Environment (Protection) Act, 1986, and the rules made there under.
2. The authorisation shall be produced for inspection at the request of an officer authorised by the State Pollution Control Board.
3. The person authorised shall not rent, lend, sell, transfer or otherwise transport the hazardous and other wastes except what is permitted through this authorisation.
4. Any unauthorised change in personnel, equipment or working conditions as mentioned in the application by the person authorised shall constitute a breach of his authorisation.
5. The person authorised shall implement Emergency Response Procedure (ERP) for which this authorisation is being granted considering all site specific possible scenarios such as spillages, leakages, fire etc. and their possible impacts and also carry out mock drill in this regard at regular interval of time;
6. The person authorised shall comply with the provisions outlined in the Central Pollution Control Board guidelines on "Implementing Liabilities for Environmental Damages due to Handling and Disposal of Hazardous Waste and Penalty".
7. It is the duty of the authorised person to take prior permission of the State Pollution Control Board to close down the facility.
8. An application for the renewal of an authorisation shall be made as laid down under these Rules.
9. Any other conditions for compliance as per the Guidelines issued by the Ministry of Environment, Forest and Climate Change or Central Pollution Control Board from time to time.

Specific Conditions:

10. Annual return shall be filed by June 30th for the period ensuring 31st March of the year.
11. The industry shall enter an agreement with the Cement industries for disposal of incinerable waste or shall dispose to Alternative Fuel Raw material facility (AFRF) OR to TSDF for co-incineration.
12. The industry shall transport the hazardous waste to cement industries through GPS vehicle.
13. The industry shall not store hazardous waste for more than 90 days as per the Hazardous and Other Wastes (Management & Transboundary Movement) Rules, 2016.
14. The industry shall store Used / Waste Oil and Used Lead Acid Batteries in a secured way in their premises till its disposal to the manufacturers / dealers on buyback basis.
15. The industry shall maintain 7 copy manifest system for transportation of waste generated and a copy shall be submitted to concerned Regional Office of APPCB. The driver who transports Hazardous Waste should be well acquainted about the procedure to be followed in case of an emergency during transit. The transporter should carry a Transport Emergency (TREM) Card.
16. The industry shall maintain proper records for Hazardous and Other Wastes stated in Authorisation in Form-3 i.e., quantity of Incinerable waste, land disposal waste, recyclable waste etc., and file annual returns in Form-4 as per Rule 20 (2) of the Hazardous and Other Wastes (Management & Transboundary Movement) Rules, 2016.

Bandla Siva Sankar Prasad
Digitally signed by Bandla Siva Sankar Prasad
Date: 2019.02.15 18:27:15 +05'30'

BANDLA SIVA SANKARA PRASAD
CHAIRMAN

To
M/s. Vasudha Pharma Chem. Ltd., Unit - II,
(Change of product mix),
Plot No.79,JN Pharmacy,
Parawada, Visakhapatnam