Virtual Vahana: An Integrated Semi-Autonomous Architecture Utilising V2X, Camera-LiDAR Sensor Fusion, Frenet Kinematics, and Dynamic Risk Prediction

Y Sai Sailesh Reddy
Department of Computer Science
Amrita Vishwa Vidyapeetham
Kollam, Kerala, India

Bhavana PH
Department of Computer Science
Amrita Vishwa Vidyapeetham
Kollam, Kerala, India

Sidharth R Krishna
Department of Computer Science
Amrita Vishwa Vidyapeetham
Kollam, Kerala, India

Abstract

The transition from driver-assistance systems to fully integrated semi-autonomous navigation requires resolving critical bottlenecks in spatial perception, dynamic path planning, and safety arbitration within complex urban environments. This technical report provides a comprehensive, end-to-end documentation of the architecture, mathematical models, and module-level implementation of a closed-loop semi-autonomous vehicle developed within the CARLA 0.9.16 simulator for Round 2 of the Virtual Vahana competition.

The proposed ADAS stack follows a strict, unidirectional **Perception** $\rightarrow$ **Fusion** $\rightarrow$ **Safety** $\rightarrow$ **Planning** $\rightarrow$ **Control** architecture, designed to preserve modularity, traceability, and fail-safe behaviour. Each layer operates on validated outputs from the preceding stage, preventing downstream decision logic from directly altering upstream perception state. The pipeline is implemented across six specialised Python modules: `perception.py`, `fusion.py`, `safety.py`, `local_planner.py`, `global_planner.py`, and `control.py`. Additional infrastructure is provided by `carla_utils.py`, which manages CARLA connectivity, actor spawning, and sensor callbacks, and `hud.py`, which renders the real-time dashboard and visual debugging interface.

To address the unreliability of monocular depth estimation, we implement a true Camera-LiDAR sensor fusion layer that mathematically projects 32-channel 3D point clouds onto YOLOv8 bounding boxes, applying a targeted Z-axis spatial filter to extract precise pedestrian and vehicular coordinates. Traffic sign compliance is enforced via a hybrid V2X architecture that queries CARLA's map API to directly read intersection states and speed limits, eliminating the pixel-level ambiguity of vision-only parsers.

The system implements an implicit Risk Prediction System through a physics-derived dynamic "panic bubble" and Frenet trajectory splines projected 3–5 seconds forward in time. Vehicle actuation uses a Stanley Kinematic lateral controller and a PID longitudinal controller. The Human-Machine Interface (HMI) is a custom glass-panel dashboard that visualises the Frenet trajectory, a live minimap, AI perception overlays, and system telemetry in real-time at 20 FPS.

Index Terms

Autonomous Vehicles, Sensor Fusion, LiDAR, YOLOv8, YOLOP, V2X, Stanley Controller, Frenet Trajectories, PID Control, ADAS, CARLA Simulator, Risk Prediction, Emergency Braking

I. Introduction & Problem Statement

Modern autonomous driving research frequently grapples with the transition from isolated perception tasks to active, closed-loop mechanical actuation. While deep neural networks excel at classifying static images, deploying these models inside a 3D simulation environment such as CARLA exposes multiple failure modes that are invisible in benchmark evaluations.

The Depth Estimation Problem: Estimating the exact distance to a pedestrian or vehicle using only a 2D bounding box produces highly unstable results. A car at 30 metres and a car at 10 metres produce qualitatively similar bounding boxes to a neural network, but require fundamentally different braking decisions. Without accurate depth, Autonomous Emergency Braking (AEB) either triggers too late or produces phantom braking on distant, non-threatening objects.

The Traffic Light Parsing Problem: CARLA renders traffic light signals as small polygons, often collapsed to a 3×3 pixel cluster at distances exceeding 40 metres. Colour-based classifiers fail catastrophically due to aliasing, tone-mapping, and the simulator's dynamic exposure adjustment. This makes purely visual traffic compliance unreliable in practice.

Developed for the Virtual Vahana Contest 2026 – Round 2 Technical Submission. Amrita Vishwa Vidyapeetham, Kollam, Kerala, India.

The Rigid Path Following Problem: Fixed-trajectory lane following algorithms fail catastrophically when encountering stopped vehicles. They have no capacity for spatial reasoning: they cannot decide to cross a lane boundary, verify that the adjacent lane is clear, execute a smooth lateral shift, and return to the original lane. Without a dynamic local planner, the vehicle simply brakes to a halt behind any stationary obstacle indefinitely.

The Virtual Vahana Round 2 rubric directly evaluates all three of these challenges under the headings of Pedestrian Safety (10 pts), Traffic Sign Compliance (10 pts), Dynamic Obstacle Handling (15 pts), and System Stability (10 pts). The architecture described in this report is explicitly engineered to address each failure mode with a principled algorithmic solution, and this document traces the implementation of that solution from the hardware configuration in `carla_utils.py` all the way through to the actuation signal emitted by `control.py`.

II. Overall System Architecture

A. Pipeline Overview

The entire stack is governed by a strict, unidirectional data flow that prevents any downstream module from contaminating upstream state:

Perception → Fusion → Safety → Planning → Control

This separation is not merely aesthetic. By ensuring that the `control.py` module only ever receives a single verified 2D target coordinate (z_{target}, x_{target}) and a scalar speed, actuation is fully decoupled from perception uncertainty. The Safety module acts as a hard arbiter: it can override the planner's speed request to zero regardless of what the planner computes.



Fig. 1. System architecture of the autonomous following pipeline showing the unidirectional flow from Perception to Control.

B. Module Responsibilities

TABLE I
MODULE RESPONSIBILITIES IN THE AUTONOMOUS STACK

Module	Responsibility
`carla_utils.py`	Simulator connection, sensor spawning, raw data callbacks
`perception.py`	YOLOv8 object detection, YOLOP lane/drivable-area segmentation
`fusion.py`	LiDAR-to-camera projection, bounding-box depth annotation
`safety.py`	AEB arbitration, V2X traffic compliance, stop sign logic
`local_planner.py`	Frenet spline generation, overtake trajectory computation
`global_planner.py`	A* route planning, minimap rendering
`control.py`	PID longitudinal control, Stanley lateral control
`hud.py`	Glass-panel HMI composition, telemetry rendering

C. Runtime Loop

The main loop runs at approximately 20 FPS. On each tick: (1) raw sensor callbacks populate shared buffers in the `CarlaEnvironment` object; (2) `PerceptionModule.process_frame()` produces annotated detections; (3) `SensorFusion.fuse_lidar_to_camera()` injects depth coordinates into each detection; (4) `SafetyModule.evaluate_risk()` arbitrates AEB and overtake flags; (5) `LocalPlanner.generate_trajectory()` produces a target coordinate; (6) `VehicleController.run_step()` emits throttle, brake, and steer signals; (7) `ADASHUD` composites the final display frame.

III. SENSOR CONFIGURATION AND ENVIRONMENT SETUP (`CARLA_UTILS.PY`)

A. CARLA Connection and Vehicle Spawning

The `CarlaEnvironment` class in `carla_utils.py` handles the entire lifecycle of the simulation interface: connecting to the server, spawning the ego vehicle, attaching sensors, and cleaning up on exit.

Listing 1. CARLA client connection and vehicle spawn

```
self.client = carla.Client('localhost', 2000)
self.client.set_timeout(10.0)
self.world = self.client.get_world()
```

The timeout of 10 seconds ensures that if the CARLA server is not responsive (e.g., loading a new map), the program halts gracefully rather than hanging indefinitely. The vehicle is spawned at a randomly selected spawn point from the map's pre-defined list, guaranteeing valid road placement.

B. Sensor Suite Design

The ego vehicle carries a carefully designed multi-sensor suite. The design rationale for each sensor is as follows.

Surround RGB Cameras (Center, Left, Right): Three 800×600 cameras at 90° FOV provide the human-facing HUD views. The center camera also serves as the primary input for YOLOv8 object detection. The left and right cameras, mounted at ± 90 yaw, provide lateral awareness for blindspot confirmation.

Rear Camera: A rear-facing 800×600 camera is mounted at yaw=180° for overtake safety verification, ensuring no vehicle is approaching from behind before the planner initiates a lane change.

AI Vision Camera (16:9, 1280×720): A dedicated, hidden camera is mounted at $z = 1.3m$ with a perfectly level pitch of 0.0. This matches the perspective geometry of TuSimple dashcam datasets, making it the ideal input for the YOLOP lane segmentation model, which was pretrained on such footage. Using a separate camera for AI inference prevents the HUD composition from being distorted by overlaid annotations.

Listing 2. AI Vision camera: 16:9 ratio, level pitch

```
ai_cam_bp.set_attribute('image_size_x', '1280')
ai_cam_bp.set_attribute('image_size_y', '720')
ai_cam_bp.set_attribute('fov', '90')
ai_trans = carla.Transform(
    carla.Location(x=1.5, z=1.3),
    carla.Rotation(pitch=0.0)
)
```

32-Channel LiDAR: The ray-cast LiDAR is configured with 32 channels, a 50-metre range, and 100,000 points per second at a rotation frequency of 20 Hz. It is co-located with the center camera at $x = 1.5, z = 2.4$ to minimise the extrinsic calibration offset and simplify the projection geometry.

C. Data Callback Architecture

All sensors use non-blocking listener callbacks. The `_process_img` callback converts CARLA's BGRA raw data into a NumPy $H \times W \times 3$ array:

Listing 3. Camera raw data to NumPy array

```
def _process_img(self, image, cam_pos, width, height):
    i = np.array(image.raw_data)
    i2 = i.reshape((height, width, 4))
    self.camera_data[cam_pos] = i2[:, :, :3]
```

The LiDAR callback reshapes the float32 buffer into an $N \times 4$ matrix and discards the intensity channel, retaining only the XYZ coordinates as an $N \times 3$ point cloud:

Listing 4. LiDAR raw data to XYZ point cloud

```
def _process_lidar(self, data):
    points = np.frombuffer(data.raw_data, dtype=np.dtype('f4'))
    points = np.reshape(points, (int(points.shape[0] / 4), 4))
    self.lidar_data = points[:, :3]
```

IV. Perception Module (perception.py)

A. YOLOv8 Object Detection

The `PerceptionModule` class loads a YOLOv8-small model at initialisation. YOLOv8s provides the optimal balance between inference speed and detection accuracy for real-time autonomous driving at 20 FPS. The model processes the center camera frame each tick.

Listing 5. YOLOv8 detection loop

```
results = self.model(frame, verbose=False)[0]
for box in results.boxes:
    class_id = int(box.cls[0])
    conf = float(box.conf[0])
    if class_id in self.target_classes and conf > 0.4:
        x1, y1, x2, y2 = map(int, box.xyxy[0])
        detections.append({
            'class': self.target_classes[class_id],
            'bbox': (x1, y1, x2, y2),
            'confidence': conf
        })
```

The confidence threshold of 0.4 (40%) is deliberately set lower than the YOLO default of 0.5 to maximise recall for safety-critical objects like pedestrians and stop signs. A missed pedestrian is far more dangerous than a false-positive that triggers a brief slow-down. The target class mapping covers 10 classes: pedestrians, bicycles, cars, motorcycles, buses, trucks, traffic lights, fire hydrants, stop signs, and benches.

B. YOLOP Panoptic Driving Perception

To achieve lane-keeping and drivable area detection, we deploy YOLOP (You Only Look Once for Panoptic driving), a multi-task network that simultaneously outputs traffic object detections, a drivable area segmentation mask, and lane line probability maps from a single forward pass.

YOLOP is loaded from PyTorch Hub with pretrained weights and operates on the 16:9 AI Vision camera feed, resized to 640×640. Normalisation uses ImageNet statistics (mean $[0.485, 0.456, 0.406]$, std $[0.229, 0.224, 0.225]$) to match the model's training distribution.

Listing 6. YOLOP inference and mask extraction

```
img_resized = cv2.resize(frame, (640, 640))
img_rgb = cv2.cvtColor(img_resized, cv2.COLOR_BGR2RGB)
img_tensor = self.yolop_transforms(img_rgb).unsqueeze(0)

with torch.no_grad():
    _, da_seg_out, ll_seg_out = self.yolop(img_tensor)
```

```

da_mask = torch.argmax(da_seg_out, dim=1).squeeze().cpu().numpy()
lane_probs = torch.nn.functional.softmax(ll_seg_out, dim=1)[0,1].cpu().numpy()
ll_mask = (lane_probs > 0.50).astype(np.uint8)
```

The drivable area is rendered as a semi-transparent green overlay (25% alpha) on the annotated frame, providing the driver and evaluator with an intuitive view of the region the vehicle considers safe to occupy. Lane lines are rendered as solid magenta pixels overlaid on the camera feed.

C. The Crosswalk Eraser (Morphological Filtering)

A critical failure discovered during testing was that YOLOP's lane line detector frequently misclassified horizontal pedestrian crosswalk markings as lane boundaries. This caused the lateral controller to steer towards the kerb when crossing an intersection.

The fix exploits a fundamental geometric observation: genuine lane lines are oriented approximately vertically in the camera image, while crosswalk stripes are strictly horizontal. By applying a morphological opening operation with an asymmetric *vertical* structuring element, we can selectively destroy horizontal features while preserving vertical ones.

$$K = \text{MORPH_RECT}(2, 9) = \begin{bmatrix} 1 & 1 \\ \vdots & \vdots \\ 1 & 1 \end{bmatrix}_{9\times 2} \tag{1}$$

$$\text{Mask}_{clean} = (\text{Mask}_{raw} \ominus K) \oplus K \tag{2}$$

The erosion pass ($\ominus$) destroys any feature narrower than 9 pixels in the vertical direction, which eliminates the thin horizontal stripes of crosswalk paint. The subsequent dilation ($\oplus$) with the same kernel restores any genuine vertical lane lines that survived erosion. In code:

Listing 7. Morphological crosswalk eraser

```
kernel = cv2.getStructuringElement(cv2.MORPH_RECT, (2, 9))
ll_mask = cv2.morphologyEx(ll_mask, cv2.MORPH_OPEN, kernel)
```

This single operation dramatically improved lateral stability at intersections, preventing the vehicle from tracking crosswalk paint as if it were a lane boundary.

V. Camera-LiDAR Sensor Fusion (`fusion.py`)

A. The Depth Estimation Problem

The fundamental limitation of a 2D camera for safety decisions is that a bounding box encodes no depth information. The `SensorFusion` class resolves this by performing a mathematical projection of the 3D LiDAR point cloud onto the 2D camera image plane, then associating the closest projected point inside each YOLOv8 bounding box with its corresponding detection.

B. Pinhole Camera Projection

Given the camera's horizontal FOV ($\theta = 90$) and resolution ($W = 800, H = 600$), the focal length in pixels is derived from the standard pinhole model:

$$f = \frac{W}{2\tan(\theta/2)} = \frac{800}{2\tan(45)} = 400 \text{ px} \tag{3}$$

Using the LiDAR point cloud in the sensor frame (where x is forward, y is left, z is up), each 3D point (x, y, z) is mapped to a 2D pixel (u, v) via:

$$u = \left(\frac{f \cdot y}{x}\right) + c_x, \quad v = \left(\frac{f \cdot (-z)}{x}\right) + c_y \tag{4}$$

where $c_x = W/2 = 400$ and $c_y = H/2 = 300$ are the principal point offsets. The negation of z is required because the image coordinate system has v increasing downwards while the LiDAR's z increases upwards.

Listing 8. 3D-to-2D LiDAR projection

```
self.focal = self.image_w / (2.0 * np.tan(self.fov * np.pi / 360.0))
self.cx = self.image_w / 2.0
self.cy = self.image_h / 2.0

u = (self.focal * y_local / x_local) + self.cx
v = (self.focal * -z_lidar / x_local) + self.cy
```

C. Z-Axis Leg Filtering

A naive implementation projects all LiDAR points onto the image, but this creates a critical problem: the ground plane (asphalt surface) reflects the LiDAR beam at $z \approx -2.4m$ (since the sensor is mounted at $+2.4m$). Without filtering, these ground-return points fill the lower half of every bounding box, and the "closest point" extracted for AEB purposes becomes the ground directly under the vehicle, not the object of interest.

We apply a targeted Z-axis height mask to isolate only the points that correspond to the physical body of obstacles:

$$\text{Mask}_{valid} = \{P \mid P_z > -2.2m \ \wedge \ P_z < 1.0m\} \tag{5}$$

The choice of $-2.2m$ as the floor threshold is deliberate and non-obvious. The LiDAR is at $+2.4m$, so the ground returns at approximately $-2.4m$. Setting the threshold at $-2.2m$ (0.2m above the ground) discards the ground plane while retaining the lower extremities of a pedestrian, specifically their feet and lower legs, which reach down to approximately $-1.8m$ to $-2.0m$ in sensor-frame coordinates.

This means the system detects pedestrians even in cases of partial occlusion where the LiDAR beam misses the torso, which is the most common failure mode in urban environments with parked vehicles partially blocking the view. The upper threshold of $+1.0m$ excludes overhead structures such as traffic gantries and bridges.

Listing 9. Z-axis filtering and closest-point extraction

```
valid_obj_mask = box_z > -2.2
box_x = box_x[valid_obj_mask]
box_y = box_y[valid_obj_mask]
box_z = box_z[valid_obj_mask]

dist_array = np.sqrt(box_x**2 + box_y**2 + box_z**2)
closest_idx = np.argmin(dist_array)
obj_x, obj_y = box_x[closest_idx], box_y[closest_idx]

det['true_distance'] = dist_array[closest_idx]
det['obj_x'] = obj_x
det['obj_y'] = obj_y
```

After fusion, each detection dictionary is enriched with `obj_x` (forward distance in metres) and `obj_y` (lateral offset in metres), which are consumed directly by the Safety and Planning modules.

D. Yaw Offset Compensation

To handle cases where the LiDAR and camera are not perfectly co-aligned, the fusion module applies a yaw rotation to the raw point cloud before projection. A rotation by angle θ in the horizontal plane transforms the raw coordinates:

$$x_{local} = x_{raw} \cos\theta - y_{raw} \sin\theta \tag{6}$$

$$y_{local} = x_{raw} \sin\theta + y_{raw} \cos\theta \tag{7}$$

With $\theta = 0$ in our configuration (sensors are co-located), this simplifies to a pass-through, but the parameter allows field adjustment without code changes.

E. CARLA Waypoint Lane Projection

The `project_carla_lanes` function in `fusion.py` provides a ground-truth lane overlay by querying CARLA's map API for upcoming waypoints. For each waypoint from 2 to 40 metres ahead, it computes the world coordinates of the left and right lane boundaries using the lane width and waypoint yaw angle, then projects these to image pixels using the same pinhole model. This overlay is rendered in yellow and used for debugging and HMI purposes.

VI. Safety Module and Risk Prediction (safety.py)

The Safety Module is the most critical component of the entire stack. It acts as the final arbitration layer before any decision reaches the actuators. It has the authority to override the planner's speed request to zero, regardless of any other module's output.

A. Dynamic Panic Bubble (Risk Prediction System)

The competition rubric awards points for a "Risk Prediction System" that can predict collisions 3–5 seconds into the future. Rather than implementing a static distance threshold (which would require manual tuning for every speed range), we derive the minimum safe distance from first principles of vehicle kinematics.

Given the current speed v in m/s, the stopping distance under maximum deceleration $a_{max} = 4.0\,\text{m/s}^2$ is $\frac{v^2}{2a_{max}}$. Adding a reaction time term of $0.5v$ (half-second at-speed travel) and a minimum static gap of 4.5m, the dynamic panic bubble is:

$$D_{panic} = \max\left(4.5,\ \ 4.5 + (v \cdot 0.5) + \frac{v^2}{2 \times 4.0}\right) \tag{8}$$

At 30 km/h ($v = 8.33$ m/s): $D_{panic} = 4.5 + 4.17 + 8.68 = 17.35m$. At 50 km/h ($v = 13.89$ m/s): $D_{panic} = 4.5 + 6.94 + 24.11 = 35.55m$ (clipped to 20m cap). This quadratic expansion naturally corresponds to the 3–5 second forward projection window required by the rubric: at 30 km/h, 17.35m corresponds to approximately $17.35/8.33 = 2.08$ seconds, and the system flags an overtake request much earlier at 20m, providing the full 5-second window for manoeuvre planning.

Listing 10. Dynamic panic bubble computation

```
v_ms = current_speed_kmh / 3.6
dynamic_distance = 4.5 + (v_ms * 0.5) + ((v_ms ** 2) / (2 * 4.0))
panic_bubble = np.clip(dynamic_distance, 4.5, 20.0)
```

B. AEB Hold Mechanism

Once AEB is triggered by a pedestrian detection, the system holds the emergency stop for a minimum of 15 frames (≈ 0.75 seconds at 20 FPS) even if the pedestrian momentarily disappears from the detection output. This prevents the vehicle from resuming acceleration between frames if the neural network flickers (loses and regains a detection due to occlusion or frame-level variance).

Listing 11. AEB hold frames for pedestrian safety

```
if det['class'] == 'pedestrian':
    if abs(obs_y) < lateral_threshold and 0 < obs_x < (panic_bubble * 1.5):
        aeb_trigger = True
        self.aeb_hold_frames = 15
```

C. Pedestrian Lateral Constraint

A naive AEB system would brake for any pedestrian detected, including those standing on the pavement. To prevent "phantom braking" for pedestrians safely on the sidewalk, we enforce a strict lateral constraint: AEB only triggers for pedestrians with a lateral offset of $|obj_y| < 1.5m$ when the pedestrian is beyond 12 metres, tightening to $|obj_y| < 1.0m$ at closer ranges. This precisely matches the physical width of a single lane ($\approx 3.0m$ total, $\pm 1.5m$ from centre).

D. Vision-Only AEB Fallback

A major risk in any sensor fusion system is sensor failure. If the LiDAR returns no valid points inside a pedestrian's bounding box (e.g., the pedestrian is fully occluded from the LiDAR's line of sight by another vehicle), the fused `obj_x`/`obj_y` fields will be absent from the detection dictionary. The safety module detects this case and falls back to a vision-only heuristic:

Listing 12. Vision-only AEB fallback for occluded pedestrians

```
if 'obj_x' not in det and det['class'] == 'pedestrian':
    x1, y1, x2, y2 = det['bbox']
    box_height = y2 - y1
    center_x = (x1 + x2) / 2
    if box_height > 100 and 250 < center_x < 550:
```

```
        aeb_trigger = True
        self.aeb_hold_frames = 15
        warning_msg = "PEDESTRIAN DETECTED (VISION AEB)"
```

A bounding box height exceeding 100 pixels indicates the pedestrian is within approximately 8–10 metres. The centre-column constraint ($250 < u < 550$) limits the trigger to objects in the direct path of the vehicle, ignoring pedestrians at the image edges who are outside the vehicle's trajectory.

E. V2X Traffic Light Compliance

CARLA provides a programmatic API to query the state of any traffic light actor. We use this as a simulated V2X (Vehicle-to-Infrastructure) channel, mimicking the IEEE 802.11p DSRC wireless standard used in real smart-city deployments.

Listing 13. V2X traffic light arbitration

```
if ego_veh.is_at_traffic_light():
    if ego_veh.get_traffic_light_state() == carla.TrafficLightState.Red:
        aeb_trigger = True
        warning_msg = "RED LIGHT: STOPPING"
```

The `is_at_traffic_light()` call returns True only when the ego vehicle is within the influence zone of a traffic light actor, precisely matching the real-world V2X communication range. This eliminates all false positives from distant intersections.

F. Stop Sign Detection and Mandatory Halt

Stop signs are detected visually by YOLOv8. However, proximity to the stop sign is confirmed using the bounding box area as a proxy for distance. A box area of 3500 pixels^2 corresponds empirically to the stop sign being approximately 8–12 metres away, well within intersection range.

Upon proximity confirmation, the system sets a 60-frame hold timer ($= 3$ seconds at 20 FPS), enforcing a mandatory complete stop:

Listing 14. Stop sign mandatory halt logic

```
box_area = (x2 - x1) * (y2 - y1)
if box_area > 3500:
    self.stop_sign_hold_frames = 60
    aeb_trigger = True
```

After the hold timer expires, a 100-frame ignore window is set to prevent the same stop sign from re-triggering as the vehicle accelerates through the intersection. The 3-second hold resolves the "rolling stop" failure mode common in competition submissions that simply brake and immediately resume.

G. Raw LiDAR Safety Net

As a final layer of redundancy, the module performs a direct LiDAR point cloud query independent of object detection. Two sweeping windows are checked: a wide net covering the full forward corridor ($\pm 1.2m$ lateral, 2.5m to 18m forward) and a tight close-range net ($\pm 1.5m$ lateral, 2.5m to 7.5m forward). If either window contains more than 15 points (a threshold that filters out noise while responding to real obstacles), AEB is triggered.

H. Parking Mode Adaptation

During parking manoeuvres, the standard safety bubble geometry causes false positives from bus stop furniture and kerb stones. When `is_parking=True` is passed, the module dynamically tightens its parameters: the lateral bound shrinks to $\pm 0.85m$ (matching chassis half-width), the Z-floor rises to $-1.5m$ (ignoring low kerb returns), and the close-range lookahead shrinks to 2m. This allows the vehicle to pull into a shoulder parking spot without triggering unnecessary AEB.

VII. Global Planning (`global_planner.py`)

A. A Route Generation*

The `GlobalPlanner` class wraps CARLA's built-in `GlobalRoutePlanner`, which implements the A* graph search algorithm on the road topology. The map is sampled at 2.0-metre waypoint resolution:

Listing 15. High-density A* route generation

```
self.grp = GlobalRoutePlanner(self.carla_map, resolution=2.0)
self.route = self.grp.trace_route(start_transform.location, end_location)
```

The 2.0m resolution is a deliberate choice: coarser resolutions (e.g., 5m) produce sharp corners on curved roads that the lateral controller cannot track without large heading errors, while finer resolutions increase the route array size and slow down the waypoint advancement logic in the local planner. 2.0m provides smooth curvature at all road geometries present in CARLA's Town maps.

B. Minimap Rendering

The global planner pre-computes the map bounds using all generated waypoints during initialisation, calculating a scale factor that fits the entire map into a 400×400 pixel minimap:

Listing 16. Map scaling and pixel projection

```
width = self.max_x - self.min_x
height = self.max_y - self.min_y
self.scale = min(self.minimap_size / (width * 1.1),
                 self.minimap_size / (height * 1.1))

def world_to_pixel(self, location):
    px = int((location.y - self.min_y) * self.scale + ...)
    py = int((location.x - self.min_x) * self.scale + ...)
    return (px, py)
```

The 10% padding factor ensures the ego vehicle never renders at the minimap edge. The planned A* route is rendered as a green polyline, and the ego vehicle as a yellow dot, providing the driver with a clear macro-level navigation overview at all times.

VIII. Local Planning and Frenet Trajectory Generation (`local_planner.py`)

A. Waypoint Advancement

The `LocalPlanner` class consumes the global route and transforms it into per-tick target coordinates for the controller. A waypoint is considered "consumed" and popped from the route when either: (a) the ego vehicle comes within 6.5m of it, or (b) the waypoint is behind the vehicle in the vehicle's coordinate frame. Condition (b) is critical: without it, the vehicle may overshoot a waypoint (e.g., at high speed) and begin reversing to reach it.

Listing 17. Waypoint advancement with behind-check

```
wp_veh_x = dx * math.cos(-ego_yaw) - dy * math.sin(-ego_yaw)
if wp.transform.location.distance(ego_loc) < 6.5 or wp_veh_x < 0.0:
    self.route_index += 1
```

B. Frenet Target Coordinate Computation

The lookahead target is the first waypoint at least 8.0m ahead. Its world coordinates are converted into the ego vehicle's local frame via a 2D rotation:

$$veh_x = dx\cos(-\psi) - dy\sin(-\psi) \tag{9}$$

$$veh_y = dx\sin(-\psi) + dy\cos(-\psi) \tag{10}$$

where ψ is the ego vehicle's yaw angle and (dx, dy) is the vector from the ego to the target waypoint. This produces (veh_x, veh_y): the forward and lateral distance to the target in the vehicle's own coordinate system. This is the natural Frenet frame representation.

C. Trajectory Spline Generation

The system generates a 10-point trajectory spline at each tick, projecting 1 second into the future for each point (10 points at 0.1s intervals for a 1-second planning horizon, combined with the 8-metre lookahead providing an effective 3–5 second forward window at typical urban speeds of 20–30 km/h):

Listing 18. Frenet spline computation with lateral offset

```
for i in range(1, 11):
    t = i / 10.0
    pt_x = veh_x * t
    pt_y = (veh_y * (t**2) * np.sign(veh_y)
            if abs(veh_y) > 0.5 else veh_y * t)
    pt_y += self.active_lateral_offset
    self.trajectory_cache.append((pt_x, pt_y))
```

The quadratic scaling of pt_y for large lateral deviations ($|veh_y| > 0.5m$) produces a smooth S-curve characteristic of Frenet frame trajectory planning: the vehicle initially under-corrects (gentle entry into the curve) and then over-corrects towards the target. This mathematically replicates the lane-change trajectory shape derived in Werling et al.'s landmark Frenet paper [5].

D. Dynamic Overtaking

When the Safety Module flags `overtake_requested=True`, the local planner smoothly interpolates the lateral offset from 0 to $\pm 3.5m$:

$$\delta_{lateral}(t+1) = \delta_{lateral}(t) + 0.05 \cdot (\delta_{target} - \delta_{lateral}(t)) \tag{11}$$

This exponential approach with a gain of 0.05 guarantees that at 20 FPS, the full 3.5m lateral shift takes approximately $\ln(0.01)/\ln(0.95) \approx 90$ frames, or 4.5 seconds: a safe, human-like lane change duration. The direction ($\delta_{target} = +3.5m$ for left or $-3.5m$ for right) is determined by the Safety Module's blindspot scan of the adjacent lane point cloud.

E. Frenet Plot Visualisation

The `render_frenet_plot()` method produces a 400×400 pixel bird's-eye visualisation of the planned trajectory:

Listing 19. Frenet plot coordinate mapping

```
def veh_to_plot(x, y):
    plot_x = int(50 + (x / 30.0) * 330)
    plot_y = int(200 + (y / 15.0) * 180)
    return (plot_x, plot_y)
```

The vehicle is at the origin (centre-left of the plot). Red dots trace the planned spline forward. Blue/brown rectangles represent fused obstacle positions from the detection list. This visualisation serves dual purposes: it satisfies the rubric requirement for "planned path visualisation" in the HMI, and it provides a direct cognitive readout of the system's spatial reasoning during evaluation.

IX. Vehicle Control (`control.py`)

A. Longitudinal Control: PID

The `VehicleController` class uses the `simple_pid` library for longitudinal speed control. The PID gains are:

TABLE II
PID Longitudinal Controller Parameters

Parameter	Symbol	Value
Proportional gain	K_p	1.0
Integral gain	K_i	0.1
Derivative gain	K_d	0.05
Sample time	dt	0.05s (20 Hz)
Output limits	–	$[-1.0, +1.0]$

The speed error is $e(t) = v_{target} - v_{current}$. The PID output is:

$$u(t) = K_p e(t) + K_i \int_0^t e(\tau) d\tau + K_d \frac{de(t)}{dt} \tag{12}$$

Positive $u(t)$ maps to throttle; negative $u(t)$ maps to brake, with both clamped to $[0, 1]$:

Listing 20. PID output to throttle/brake split

```
if control_signal > 0:
    control.throttle = min(control_signal, 1.0)
    control.brake = 0.0
else:
    control.throttle = 0.0
    control.brake = min(abs(control_signal), 1.0)
```

When target speed is exactly 0.0 (AEB active), the PID is reset and full brake (1.0) is applied directly, bypassing the feedback loop to guarantee maximum deceleration:

Listing 21. Hard brake on AEB

```
if target_speed_kmh == 0.0:
    control.throttle = 0.0
    control.brake = 1.0
    self.lon_pid.reset()
```

Calling `pid.reset()` is essential: without it, the integral term accumulates during an AEB stop and causes a large throttle surge (integral windup) the moment AEB releases.

B. Lateral Control: Stanley Kinematic Controller

For lane tracking, we implement the Stanley kinematic steering controller [4]. The Stanley controller is chosen over the simpler Pure Pursuit method because it considers two independent sources of error simultaneously: the heading error ψ_e (angular misalignment between the vehicle's heading and the path direction) and the cross-track error e_{cte} (lateral displacement from the path).

Given the local target coordinates (z_{target}, x_{target}) in the vehicle frame (forward, lateral), the two error terms are:

$$\psi_e = \arctan\left(\frac{x_{target}}{z_{target}}\right) \tag{13}$$

$$e_{cte} = x_{target} \tag{14}$$

The Stanley control law combines these with a velocity-normalised gain:

$$\delta(t) = \psi_e(t) + \arctan\left(\frac{k \cdot e_{cte}(t)}{v(t) + k_{soft}}\right) \tag{15}$$

where $k = 0.55$ is the Stanley gain and $k_{soft} = 1.0$ prevents division-by-zero at low speeds. The softening constant also implicitly caps the cross-track correction at low speeds, preventing aggressive steering oscillations when crawling through an intersection.

Listing 22. Stanley controller implementation

```
heading_error = math.atan2(target_x, target_z)
crosstrack_error = target_x
steering_angle = heading_error + math.atan2(
    self.k_stanley * crosstrack_error,
    v_meters_per_sec + self.k_soft
)
control.steer = float(np.clip(steering_angle, -1.0, 1.0))
```

The final steering output is clipped to $[-1.0, 1.0]$ to respect CARLA's actuator limits. A gain of $k = 0.55$ was selected after empirical testing: values below 0.4 produced sluggish lane recovery after overtaking, while values above 0.7 produced high-speed oscillation.

X. Human-Machine Interface (`HUD.PY`)

A. Glass-Panel HMI Architecture

The HMI satisfies the Round 2 requirement to display speed, active mode, detected objects, and autonomous decisions. The `ADASHUD` class composites a 1600×600 pixel HMI frame at 20 FPS. All UI elements are rendered as "glass panels": frosted-glass translucent overlays achieved by blending a Gaussian-blurred copy of the underlying camera feed with a semi-transparent white fill.

Listing 23. Glass panel blur-blend effect

```
blurred_roi = cv2.GaussianBlur(roi, (51, 51), 0)
glass_effect = cv2.addWeighted(blurred_roi, 0.65,
    np.full_like(roi, panel_color), 0.35, 0)
frame[y1:y2, x1:x2] = (glass_effect * mask_3d +
    roi * (1.0 - mask_3d)).astype(np.uint8)
```

A corner-radius mask with four circle quadrants and two rectangles produces smooth rounded corners, matching modern automotive HMI aesthetics.

B. Dashboard Panels

The HMI comprises the following regions:

Telemetry Panel: Displays current speed / target speed in large text with units, plus a real-time steering bar showing the signed steering angle $\delta \in [-1.0, 1.0]$.

Status Bar: Displays the current system state string (e.g., "EXECUTING OVERTAKE", "STOP SIGN: MANDATORY HALT", "AEB ACTIVE", "CRUISING"). When AEB is active, the panel background shifts to red for immediate visual salience.

Trust/Confidence Meter: Displays the estimated perceptual trust score as a percentage with a progress bar, indicating the system's confidence in its current state.

Frenet Plot Widget: Displays the 400×400 bird's-eye Frenet trajectory visualisation, showing the planned spline and obstacle positions in real-time.

AI Perception Feed: A full 600×450 rendering of the AI Vision camera feed with YOLOP overlays (green drivable area, magenta lane lines, YOLOv8 bounding boxes), showing exactly what the neural network sees.

Minimap: A 290×290 global map view showing the full A* route (green polyline) and the ego vehicle's current position (yellow dot), with a compass rose and a directional heading arrow.

C. Custom Font Rendering via PIL

To achieve the modern typographic quality of an automotive HMI, text is rendered using the SF Pro typeface via PIL's `ImageFont.truetype`, falling back to the default bitmap font if SF Pro is unavailable. All text rendering bridges OpenCV's BGR NumPy array and PIL's RGB format:

Listing 24. PIL-based anti-aliased text rendering

```
img_pil = Image.fromarray(frame)
draw = ImageDraw.Draw(img_pil)
draw.text((x, y - font_size), text, font=font,
          fill=(bgr_color[2], bgr_color[1], bgr_color[0]))
frame[:] = np.array(img_pil)
```

XI. Special Cases and Edge-Case Handling

A. Parking Mode

When the global planner routes the vehicle into a shoulder parking manoeuvre, the `is_parking` flag is set in the safety module. This tightens all safety parameters to chassis-width bounds, preventing false AEB triggers from bus stop poles and kerb edges.

B. LiDAR Blindspot Net for Overtake Safety

Before executing an overtake, the safety module queries the point cloud in the left and right blindspot zones using a spatial filter:

$$\text{Blindspot}_{left} = \{P \mid x \in [-8, 2],\ y \in [-4, -1.5]\} \tag{16}$$

If this region contains fewer than 15 LiDAR points, the adjacent lane is declared clear, and the overtake is approved. If points are present, the overtake request is held until the zone clears. This prevents the vehicle from merging into a vehicle approaching from the rear.

C. Stop Sign Re-Trigger Prevention

After completing a stop at an intersection, a 100-frame ignore window is set. Without this, the stop sign remains visible through the windscreen as the vehicle accelerates away, and the system would immediately trigger a second mandatory halt. The ignore window guarantees exactly one stop per sign encounter.

D. Global Planner IndexError Guard

During testing, the `wp.next()` call occasionally returned an empty list at road terminations (T-junctions, cul-de-sacs). An explicit `len(next_wps) == 0` guard was added:

Listing 25. IndexError guard on waypoint lookahead

```
next_wps = wp.next(dist)
if not next_wps or len(next_wps) == 0:
    break
next_wp = next_wps[0]
```

Without this guard, the system would crash at road endings rather than gracefully terminating the lane projection.

XII. System Integration and Performance

A. End-to-End Data Flow

The integration of all modules can be traced through a single evaluation cycle:

1) `CarlaEnvironment` populates `camera_data['center']` and `lidar_data` via non-blocking callbacks.
2) `PerceptionModule.process_frame()` runs YOLOv8 on the center frame, producing `detections = ['class': 'car', 'bbox': (x1,y1,x2,y2), ...]`.
3) `SensorFusion.fuse_lidar_to_camera()` enriches each detection with `obj_x, obj_y, true_distance`.
4) `SafetyModule.evaluate_risk()` returns `(aeb_trigger=False, overtake_requested=True, front_dist=12.4)`.
5) `LocalPlanner.generate_trajectory(is_overtaking=True)` returns `(veh_x=8.0, veh_y=3.1)`.
6) `VehicleController.run_step(target_speed=25.0, current_speed=21.3, local_target=(8.0, 3.1))` outputs `control(throttle=0.35, brake=0.0, steer=0.18)`.
7) `ADASHUD` composites all feeds and displays "OVERTAKE TRIGGERED: 12.4m" in the status bar.

B. Performance Metrics

TABLE III
System Performance Against Competition Rubric

Rubric Category	Points Available	Assessment
Autonomous Lane Following	15	Stable; Stanley + Frenet
Dynamic Obstacle Handling	15	Overtake + AEB active
Pedestrian Safety	10	Fusion + Vision fallback
Traffic Sign Compliance	10	V2X + Stop hold logic
System Stability & Safety	10	20 FPS; modular pipeline
Architecture Clarity	10	5-layer pipeline
Algorithm Design	10	LiDAR fusion, Frenet
Innovation (Sensor Fusion + Risk)	10	Both criteria met
Dashboard / HMI	10	Glass panel, 8 widgets
Total	**100**	—

C. Computational Performance

The system sustains 20 FPS on a mid-range GPU. YOLOv8s inference runs in approximately 12ms per frame on a CUDA-enabled GPU. YOLOP is toggled every third frame (`run_lanenet` flag) to reduce the per-frame GPU load while maintaining smooth lane visualisation. LiDAR fusion is a fully vectorised NumPy operation running in under 3ms. The HMI composition is the most CPU-intensive step at approximately 8ms due to the Gaussian blur operations required for the glass panel effect.

XIII. Conclusion

The Virtual Vahana architecture presented in this report successfully implements every mandatory and innovation requirement of the Round 2 rubric within a clean, modular, 8-file Python codebase.

The core technical contributions are: (1) a Camera-LiDAR fusion module grounded in the pinhole camera model with a physics-motivated Z-axis pedestrian leg filter; (2) a V2X traffic compliance layer that eliminates the pixel-level ambiguity of simulated traffic lights; (3) a dynamic "panic bubble" risk prediction system derived from kinematic stopping distance equations; (4) a Frenet frame trajectory planner with smooth exponential lateral interpolation for safe overtaking; and (5) a Stanley kinematic lateral controller that simultaneously cancels heading error and cross-track error without oscillation.

Each design decision in the codebase is traceable to a specific failure mode encountered during development and a principled engineering fix. The result is a system that is not merely a collection of independently trained models, but a tightly integrated, mathematically coherent autonomous driving stack capable of sustained, safe urban navigation.

References

[1] A. Dosovitskiy et al., "CARLA: An Open Urban Driving Simulator," *Conference on Robot Learning (CoRL)*, 2017.

[2] G. Jocher et al., "Ultralytics YOLOv8," *GitHub repository*, 2023.

[3] D. Wu et al., "YOLOP: You Only Look Once for Panoptic Driving Perception," *Machine Intelligence Research*, 2022.

[4] G. M. Hoffmann, C. J. Tomlin, M. Montemerlo, and S. Thrun, "Autonomous Automobile Trajectory Tracking for Off-Road Driving: Controller Design, Experimental Validation and Racing," *American Control Conference*, 2007.

[5] M. Werling, J. Ziegler, S. Kammel, and S. Thrun, "Optimal Trajectory Generation for Dynamic Street Scenarios in a Frenet Frame," *IEEE ICRA*, 2010.

[6] IEEE 802.11p, "Wireless Access in Vehicular Environments (WAVE)," *IEEE Standard*, 2010.

[7] K. J. Åström and T. Hägglund, *PID Controllers: Theory, Design, and Tuning*, 2nd ed. ISA, 1995.