

Nepali Sentiment Analysis of Post-COVID Data

Using XLMRoberta for Text Classification

Amulya Bhandari Sailesh Dahal Sarayu Gautam Tohfa Niraula

May 2, 2025

Department of Computer Engineering
Kathmandu University

Outline

Introduction

Problem Statement

Dataset Description

Data Preprocessing

Tokenization and Encoding

Model Architecture

Training Pipeline

Results

Conclusion

Introduction

What is Sentiment Analysis?

- Sentiment analysis classifies text based on emotion or opinion.
- Categories:
 - Positive — praise, approval
 - Neutral — factual
 - Negative — criticism, disapproval
- Applications:
 - Social media monitoring
 - Product reviews
 - Survey analysis

Problem Statement

What Are We Solving?

- Goal: Classify Nepali-language text into sentiment categories.
- Motivation:
 - Nepali is underrepresented in NLP.
 - Lack of labeled Nepali datasets.
- Objectives:
 1. Clean and preprocess post-COVID Nepali data.
 2. Train a multilingual BERT model.
 3. Evaluate performance using real-world test data.

Dataset Description

About the Dataset

- Source: Nepali COVID/post-COVID text samples.
- Total Samples:
 - Training: 33,602 samples
 - Testing: 8,401 samples
- Labels: 0 = Negative, 1 = Positive, 2 = Neutral
- Common issues:
 - Invalid labels ('o', '-', etc.)
 - Missing values and noisy characters

Data Preprocessing

Data Cleaning Steps

Steps we took:

1. Removed missing and malformed data.
2. Filtered invalid labels.
3. Tokenized using XLM-Roberta tokenizer.
4. Truncated inputs to max length of 256 tokens.

Result: Clean, structured datasets ready for training/testing.

Tokenization and Encoding

Tokenizing with XLM-Roberta

- XLM-Roberta tokenizer is multilingual and supports Nepali language.
- Key features of `tokenizer.batch_encode_plus`:
 - Automatically handles padding and truncation for consistent input length.
 - Generates:
 - `input_ids`: Numerical representation of tokens.
 - `attention_mask`: Identifies non-padded tokens for focus.
- Attention masks ensure the model processes only relevant tokens. It tells the model which sentence is real and which is padding.

Understanding Tokenization and Encoding

- Tokenizing is like chopping a sentence into Lego blocks that the model knows.
- Encoding is turning those blocks into numbers so the model can do math with them.
- Why It Matters:
 - The model sees only numbers.
 - Tokenization keeps input size fixed (e.g., max_length=256). Long texts are trimmed, short ones are padded.

Tokenization Example

Step	Output
Input Sentence	सरकारले अस्पतालमा निःशुल्क उपचार उपलब्ध गरायो।
Tokens	['__सरकारले', '__अस्पतालमा', '__नि', 'ः', 'शुल्क', '__उपचार', '__उपलब्ध', '__गरायो', '।']
Token IDs	[25033, 149007, 946, 6, 153794, 26409, 38071, 87995, 4]

- The model doesn't understand text. It only understands numbers.
- Tokenizer breaks the sentence into subwords it knows (like 'नि', 'ः', 'शुल्क' for 'निःशुल्क').
- The tokenizer assigns a unique ID to each known token.
- These token IDs are what get passed to the model as input.

Model Architecture

XLM-Roberta Model Details

Transformers process all words at the same time (not one-by-one like RNN).

Structure:

- XLM-R supports multiple languages, including Nepali, out of the box.
- Fine-tuning was performed to adapt the model's top layers specifically for sentiment classification.
- Produces probabilities for three sentiment classes: Negative, Positive, and Neutral.

Trained on: PyTorch with mixed precision (autocast enabled)

Model Usage Example

"यो उत्पादन उत्कृष्ट छ।"

Tokenized Input:

- Tokens: [CLS] यो उत्पादन उत्कृष्ट छ । [SEP]
- Converted to input_ids: [101, 2345, 5678, 9101, 1123, 102] (Note: These are example token IDs.)

Model Output (Softmax Probabilities):


- Negative: 0.05
- Neutral : 0.10
- Positive: 0.85

Prediction: → Positive sentiment

- [CLS] and [SEP] are special tokens used by BERT-like models (e.g., XLM-Roberta).
- input_ids are the numerical representation of tokens.
- The model outputs a probability score for each class.
- The highest score (0.85 for Positive) becomes the final prediction.

Training Pipeline


Main Workflow Steps



Training Loop




Deployment and Evaluation



Results

Loss and Accuracy Over Epochs




Test Set Evaluation Metrics

Label	Precision	Recall	F1-score
Negative (0)	0.80	0.74	0.77
Positive (1)	0.78	0.83	0.80
Neutral (2)	0.52	0.52	0.52
Overall Accuracy	74.0%		

Key Insights:

- High precision/recall for Positive/Negative.
- Neutral class more ambiguous → lower performance.

Confusion Matrix (Test Set)



Sample Predictions on Unseen Data

Nepali Sentiment Analysis

Discover the emotional tone of Nepali text through our advanced AI analysis tool.




Sentiment Analyzer

Enter your Nepali text below to analyze its emotional tone

मरसाला मरिजको मध्य देखि।


32 characters

Analyze Sentiment




Sentiment:
Negative


Confidence
100%



Fast Analysis
Get results in seconds with our optimized model.



Accurate Results
Trained on diverse Nepali language datasets.



Privacy Focused
Your text is processed securely and never stored.

© 2025 Nepali Sentiment Analysis. All rights reserved.

Conclusion

Conclusion and Future Work

Key Takeaways:

- Trained a sentiment classifier on Nepali-language text using XLM-Roberta.
- Achieved 74% of overall accuracy.
- Strong performance on binary sentiment; neutral remains challenging.

Future Improvements:

1. Larger or augmented datasets.
2. Additional validation set for tuning.
3. Model deployment as an API/web service.

Thank You!

Questions or feedback?

Project Resources:

GitHub: github.com/saileshbro/ai-proj

We appreciate your time and attention!