

[Open in app](#)[Get started](#)

Published in Better Programming

This is your **last** free member-only story this month. [Sign up for Medium and get an extra one](#)



Shinichi Okada

[Follow](#)Feb 10, 2021 · 10 min read ★ · [Listen](#)

Save



27 Simple Bash Scripting Tips for Beginners

Don't be afraid of Bash scripting. It will be easier after reading these tips



[Open in app](#)[Get started](#)

[Updated on 2021-02-18. Codes changed to Gist and added links]

Table of Contents

[Introduction](#)

[1. Clean Structure](#)

[2. Install ShellCheck on Your Editor](#)

[3. Usage Function](#)

[4. Error Messages](#)

[5. Function Comments](#)

[6. How To Concatenate String Variables](#)

[7. How To Set a Debug Mode](#)

[◦ Other useful set options](#)

[8. How To Slice Strings](#)

[9. How To Make Sure Users Use a Correct Bash Version](#)

[10. How To Transform a String Case](#)

[11. Ternary Operator-Like Statement](#)

[12. How To Find the Length of a String and an Array](#)

[13. How To Unset Variables](#)

[14. How To Set a Default Value](#)

[15. How To Determine Your Bash Script Name](#)

[16. How To Make a Variable Constant](#)

[17. How To Find OSs](#)

[18. How To Determine Which HTTP Get Tool the System Has Installed](#)

[19. How To Determine Which Python the System Has Installed](#)

[20. Parameter expansion: How to Find the Script Name and Directory](#)

[21. How To Make Status Messages](#)

[22. How To Set Locale](#)

[23. Type Hinting in Bash?](#)

[24. Store Exit Status in a Variable](#)

[25. Using Trap for Unexpected Termination](#)

[26. Don't Reinvent the Wheel](#)

[27. Subshell and Exit Status](#)

[Conclusion](#)

[Newsletter](#)

[References](#)

Introduction

After learning the [basics of Bash scripting](#), you can use these practices to make your Bash script look more professional. Here are 27 tips for Bash script beginners.

1. Clean Structure



[Open in app](#)[Get started](#)


Declare all of the global variables first and then declare all of the functions after the global variables. Use local variables in functions and write the main body after the functions. Use an explicit exit status code in your functions, the `if` statement, and at the end of the script.

2. Install ShellCheck on Your Editor




[Open in app](#)[Get started](#)


Or you can install it on [VS Code](#).



ShellCheck

Timon Wong |  147,266 installs | ★★★★★ (18) | Free

Integrates ShellCheck into VS Code, a linter for Shell scripts.

[Install](#) [Trouble Installing?](#) 

VSCode ShellCheck extension

If you are interested in checking the ShellCheck error code list, check this [gist](#).

3. Usage Function

If your script is using positional parameters, add a function explaining how and what users can use the parameters.



[Open in app](#)[Get started](#)

`$0` outputs the script name. In the above case, the `usage` function will be called when a user uses `h` or any letters except `f`, `d`, or `t`.



[Open in app](#)[Get started](#)

[Try this online](#)

The above script checks if the number of parameters is two. If it is not, it displays `usage` .

You can use Bash Here doc:



[Open in app](#)[Get started](#)

4. Error Messages

Google's [shell style guide](#) recommends a function to print out messages along with other status information.



[Open in app](#)[Get started](#)

The guide suggests that all error messages should go to `STDERR` because this makes it easier to separate normal status from actual issues.

5. Function Comments

All functions should have comments mentioning description, global variables, arguments, outputs, and returned values, if applicable.



[Open in app](#)[Get started](#)

6. How To Concatenate String Variables



[Open in app](#)[Get started](#)

Photo by [Alina Grubnyak](#) on [Unsplash](#)

In a Bash script, you can concatenate strings in different ways.



[Open in app](#)[Get started](#)

[Try this online](#)

Please note that there is no space before and after an equal sign when you are assigning a value to a variable. The first one uses the `+=` sign to concatenate the second value to the first one. The second one uses a double quote with a space between variables. The last one is using a curly bracket since the variable `foo` is immediately followed by a character.

7. How To Set a Debug Mode



[Open in app](#)[Get started](#)

[Try this online.](#)

The output is a verbose trace of the script's execution.

```
+ foo=Bash
+ '[' Bash == Bash ']'
+ echo Bash
Bash
```



[Open in app](#)[Get started](#)

`set -u` treats unset variables as an error when substituting.

`set -c` disallows existing regular files to be overwritten.

So you can use `set -ceu` at the beginning of your script.

Find more about `set` using `help set`.

8. How To Slice Strings

You can use `cut -cstart-end` to slice a string.



[Open in app](#)[Get started](#)

[Try this online](#)

The first one slices the string from the first letter to the third. The second one slices from the second to the fourth. The last one slices the fifth letter.

A parameter expansion performs substring extraction, `${s:off-set-index:length}` :

```
#!/usr/bin/env bash
```



[Open in app](#)[Get started](#)

```
# abc  
# bcd  
# e
```

The offset is zero-based.

9. How To Make Sure Users Use a Correct Bash Version

The following script ensures the users use Bash version 4.0 or higher.

```
if ((BASH_VERSINFO[0] < 4)); then  
    printf '%s\n' "Error: This requires Bash v4.0 or higher. You have  
version $BASH_VERSION." 1>&2  
    exit 2  
fi
```

10. How To Transform a String Case

When you read user input, the input can be in lowercase or uppercase. For Bash lower than version 4, you can change it to uppercase using the `tr` command with `[:lower:]` and `[:upper:]`.



[Open in app](#)[Get started](#)

[Try this online](#)

Please note that we set the option `-x` for debugging.

Line 4: Read user input.

Line 5: Pipes, `|`, let you use the output of a command as the input of another command.

We `cut` the first letter, then transform it from lowercase to uppercase. You can interchange the position of lowercase and uppercase to transform from uppercase to lowercase.



[Open in app](#)[Get started](#)

[Try this online](#)

Using these case modification operators, you can create functions.



[Open in app](#)[Get started](#)

[Try this online](#)

11. Ternary Operator-Like Statement

Bash doesn't have a ternary operator, but you can do a similar thing for simple variable assignments.

We can write an `if` statement:



[Open in app](#)[Get started](#)

Using `&&` and `||` together, we can create a statement similar to a ternary statement:

```
[ $foo -ge $bar ] && baz="Smile!" || baz="Sleep!"
```



[Open in app](#)[Get started](#)

Photo by [Fleur](#) on [Unsplash](#)

`${#string}` returns the string length and similarly `${#array[@]}` returns the array length.



[Open in app](#)[Get started](#)

[Try this online](#)

13. How To Unset Variables

Unsetting variables ensures you are not using predefined variables.

At the beginning of the script:

```
#!/usr/bin/env bash
```



[Open in app](#)[Get started](#)

14. How To Set a Default Value

`${foo-$DEFAULT}` and `${foo=$DEFAULT}` evaluate as `$DEFAULT` if `foo` is not set.

`${foo:-$DEFAULT}` and `${foo:=$DEFAULT}` evaluates as `$DEFAULT` if the `foo` is not set or is empty.



[Open in app](#)[Get started](#)

[Try this online.](#)

15. How To Determine Your Bash Script Name

By adding all your Bash scripts to the `~/bin` directory and adding its path to your terminal config file, `~/.bashrc` or `~/.zshrc`, you can run them from any directory. But before you



[Open in app](#)[Get started](#)

```
$ type my_script
my_script not found
$ which which
which: shell built-in command
```

There is no script name with `my_script`, but `which` is already taken.

16. How To Make a Variable Constant

`readonly` makes variables and functions read-only.



[Open in app](#)[Get started](#)

[Try this online.](#)

Line 3: Set a read-only variable.

Line 5: Trying to overwrite the read-only variable. But this returns an error, “line 5: MAX: readonly variable”.

Output:





10

[Open in app](#)[Get started](#)

You can output the `readonly` variables:

[Try this online.](#)



[Open in app](#)[Get started](#)

The following example is rather trivial, but it finds the user's OS and applies the correct command.

Output:



[Open in app](#)[Get started](#)

18. How To Determine Which HTTP Get Tool the System Has Installed

Your Bash script may use an HTTP `GET` tool. Different systems use different tools. It can be `curl`, `wget`, `http`, `fetch`, or something else.

`ps /dev/null` redirects both the standard output stream and the standard error stream to



[Open in app](#)[Get started](#)

19. How To Determine Which Python the System Has Installed

Similarly, if your script uses Python, you can find the system Python:

20. Parameter expansion: How to Find the Script Name and Directory



[Open in app](#)[Get started](#)

[Try this online.](#)

This [Tech.io page](#) explains how to use `${parameter%word}` , `${parameter%%word}` ,
`${parameter#word}` , `${parameter##word}` .

You can use `basename "$0"` to get the file name as well.



[Open in app](#)[Get started](#)

```
c=$0
echo "${c%/*}"
```

Outputs:

```
/Users/shinokada/bin
```

21. How To Make Status Messages

You may want to inform users what your script is doing.

If you want to output status messages, you should start it with the program name. Use `$(basename "$0")` to get the program name. The message should be written on the standard error by using `echo ... 1>&2`.

```
#!/usr/bin/env bash

progname=$(basename "$0")
...
echo "$progname: Running this and that" 1>&2
```

22. How To Set Locale

You can find your locale environment:



[Open in app](#)[Get started](#)

Not all programmers use the same locale. Programmers from France may use `fr_CH.UTF-8`; geeks from England may be using `en_GB.UTF-8`. To ensure that the users use the correct locale, you can use `LC_ALL` to set the locale:

```
LC_ALL="en_US.UTF-8"
```



[Open in app](#)[Get started](#)

declare .

You can use + instead of – to turn off the attribute.



[Open in app](#)[Get started](#)

[Try this online.](#)

We declared `var1` as an integer in line 3. If you try to change it to a string, you get an error (line5). But you can change it to another integer (line7).



[Open in app](#)[Get started](#)

[Try this online.](#)

Please note that when you use `declare` in a function, the variable becomes a local variable which you can't access outside of the function.

24. Store Exit Status in a Variable



[Open in app](#)[Get started](#)

Photo by [Artem Beliaikin](#) on [Unsplash](#)

Rather than using `$?` in `if` statements:

```
mkdir /tmp/tmp_dir
if [ $? = 0 ]; then
  # do something
fi
```

Store the exit status in a variable:



[Open in app](#)[Get started](#)

The following stores the exit status for checking if a file exists and is a directory.

```
test -d /tmp/tmp_dir
test_es=$?
if [[ ${test_es} -ne 0 ]]; then
    echo "No dir found. Exiting script!" >&2
    exit 1
fi
```



[Open in app](#)[Get started](#)

modifying a directory or a file, you need to bring it back to the original state. The command `trap` is for this situation.



556



4

When a user uses `ctrl-c`, it generates a signal `SIGINT`. When a user kills a process, it generates a signal `SIGTERM`. You can list all the signals using:

```
# Linux, from terminal
$ trap --list
# macOS, from a script
trap --list
```

Sign up for Coffee Bytes

By Better Programming

You can find the standard signals on man7.org.

A newsletter covering the best programming articles published across Medium [Take a look](#).

The `trap` command has the form of `trap "do something" signal_to_trap`. If your cleanup code is long, you can create a function.

Let's trap the `ctrl-c` signal:

```
tempfile=/tmp/myfile
cleanup(){
    rm -f $tempfile
}
```

`trap cleanup SIGINT`



Read more about the [trap command](#).

26. Don't Reinvent the Wheel

If your goal is learning, then you can reinvent the wheel, but if not, use snippets from [pure-bash-bible](#). The pure-bash-bible is a great learning place as well. There are many functions you can use in your scripts. The scripts include strings, arrays, loops, file handling, file paths, and more.



[Open in app](#)[Get started](#)

pure bash bible

A collection of pure bash alternatives to external processes.

build **passing** license MIT

The goal of this book is to document commonly-known and lesser-known methods of doing various tasks using only built-in `bash` features. Using the snippets from this bible can help remove unneeded dependencies from scripts and in most cases make them faster. I came across these tips and discovered a few while developing [neofetch](#), [pxlrm](#) and other smaller projects.

The snippets below are linted using `shellcheck` and tests have been written where applicable. Want to contribute? Read the [CONTRIBUTING.md](#). It outlines how the unit tests work and what is required when adding snippets to the bible.



Image from [pure bash bible](#)

27 Subshell and Exit Status



[Open in app](#)[Get started](#)

The first one returns:

```
/Users/myname/bin/ex5: line 34: no_func1: command not found  
there is nothing  
1
```



[Open in app](#)[Get started](#)

The difference is the parentheses and braces. Parentheses cause the commands to be run in a subshell, and braces cause the commands to be grouped together but not in a subshell.


Since braces don't create a subshell, `exit` exits the main shell process, so it never reaches the point where it would run `echo $?`.

Conclusion

These are 27 Bash scripting tips you can use in your next Bash script project. Many of them are easy to adopt and they make your Bash script look more professional.

Happy coding!

Get full access to every story on Medium by [becoming a member](#).



<https://blog.codewithshin.com/subscribe>

References

- <https://tldp.org/LDP/abs/html/special-chars.html>



[Open in app](#)[Get started](#)

The Ultimate Programmer's Guide to Bash Scripting

A deep dive into Bash scripts to help you automate tasks

medium.com

13 Fantastic Learning Tools and Resources for Bash Scripting

Alternative Bash scripting tools you will use daily

medium.com

Comparing SH, BASH, KSH, and ZSH Speed

The winner goes to ... Drumroll

towardsdatascience.com

Thanks to Emile Okada and Anupam Chugh

