



WEEKLY CYBERSTER INTERNSHIP REPORT

WEEK 01 – Advanced Recon & Attack Surface Mapping

NAME	Saima naz
BATCH	Red Team Batch 2
INSTRUCTOR	Umar Niaz
TARGET	Hackthissite.org
DATE	26/6/2026

EXECUTIVE SUMMARY

This report summarizes the work completed during Week 01 of the Cyberster Red Team Internship Program. The primary focus of this phase was to perform comprehensive reconnaissance and attack surface analysis on the authorized training target, hackthissite.org. The objective was to strengthen practical knowledge of passive information gathering, subdomain enumeration, infrastructure assessment, identification of publicly exposed credentials, and verification of active internet-facing assets, while strictly avoiding any exploitation or intrusive activities.

To accomplish these objectives, four organized tasks were carried out using a variety of industry-standard OSINT and reconnaissance tools, including Subfinder, Assetfinder, Amass, CRT.sh, and DNSDumpster. The collected intelligence provided a detailed understanding of the target's external infrastructure, domain ecosystem, and overall attack surface, forming a solid foundation for future security assessments.

Learning Objectives

- Develop practical skills in passive reconnaissance and Open Source Intelligence (OSINT) techniques.
- Learn how to discover and validate subdomains using multiple reconnaissance tools.
- Understand the importance of combining results from different sources to improve reconnaissance accuracy.
- Identify hidden assets, historical subdomains, and SSL certificate information through Certificate Transparency logs and DNS intelligence.
- Perform infrastructure and technology profiling to identify web servers, frameworks, hosting providers, and security controls.
- Gain experience in using Google Dorking to locate publicly exposed files and sensitive information.
- Learn how to investigate public GitHub repositories for accidentally exposed credentials and configuration files.
- Verify active web assets by filtering live hosts from discovered subdomains.

- Capture and analyze screenshots of live web applications to identify login portals, development environments, and other high-value targets.
- Build a comprehensive attack surface map while following ethical hacking principles and avoiding unauthorized exploitation.

ENVIRONMENT SETUP

Components	Details
hardwaree	Laptop with 8 GB RAM & stable internet connection
Operating system	Kali linux
Target domain	hackthissite.org
Recon tools	Subfinder, amass, assetfinder crt.sh etc
Infrastructure tools	WhatWeb, Wappalyzer CLI, WHOIS, NSLookup, Dig
Credential discovery tools	Google Dorking, GitHub Search, GitHacker
Live Asset Validation Tools	HTTPX, Httprobe
Visual Reconnaissance Tools	Aquatone, Gowitness
Supporting Software	Git, Go, Python 3, Node.js, npm, xlsx2csv
Network environment	Google chrome
Software	Internet-enabled environment

Task 01 – Passive OSINT & Subdomain Enumeration: Commands and Their Purpose


1. Create a Working Directory

Before starting reconnaissance, a dedicated directory was created to organize all output files generated during the assessment. This ensured that the results from different tools remained structured and easy to analyze throughout the reconnaissance process.

Command:

```
mkdir 'week1'
```

```
cd week1
```




2. Subfinder

Command:

```
subfinder -d hackthissite.org -o subfinder.txt
```

purpose:

The subfinder command was used to passively enumerate subdomains associated with the target domain. It collects information from multiple public OSINT sources without directly interacting with the target's infrastructure. The discovered subdomains were saved into a text file for later analysis.

A screenshot of a terminal window with a dark background. The command `subfinder -d hackthissite.org -o subfinder.txt` is entered at the prompt. Below the command, there is a large ASCII art banner for 'projectdiscovery.io'. The output of the command lists several subdomains for 'hackthissite.org', including '118641.hackthissite.org', 'rubbish-removal-prahran.hackthissite.org', 'removals-newcastle.hackthissite.org', 'frameless-shower-screens-inner-west-sydney.hackthissite.org', 'netlify-web.hackthissite.org', 'pubsub.st.hackthissite.org', '120c6b.hackthissite.org', '120512.hackthissite.org', 'prtnr.hackthissite.org', and 'usr.hackthissite.org'. The terminal also shows status messages like '[INF] Current subfinder version v2.6.0 (outdated)' and '[INF] Loading provider config from /home/saimanaz/.config/subfinder/provider-config.yaml'.

```
$ subfinder -d hackthissite.org -o subfinder.txt

          _ _ _ _ _
         / _ _ _ _ \
        ( _ _ _ _ )
       _/ _ _ _ _ \_
      / _ _ _ _ _ \
     / _ _ _ _ _ \
    / _ _ _ _ _ \
   / _ _ _ _ _ \
  / _ _ _ _ _ \
 / _ _ _ _ _ \
/_ _ _ _ _ \

projectdiscovery.io

[INF] Current subfinder version v2.6.0 (outdated)
[INF] Loading provider config from /home/saimanaz/.config/subfinder/provider-config.yaml
[INF] Enumerating subdomains for hackthissite.org
118641.hackthissite.org
rubbish-removal-prahran.hackthissite.org
removals-newcastle.hackthissite.org
frameless-shower-screens-inner-west-sydney.hackthissite.org
netlify-web.hackthissite.org
pubsub.st.hackthissite.org
120c6b.hackthissite.org
120512.hackthissite.org
prtnr.hackthissite.org
usr.hackthissite.org
```

Command:

```
subfinder -d hackthissite.org -silent -o subfinder.txt
```

purpose:

The `-silent` option suppresses banners and unnecessary output, displaying only the discovered subdomains. This creates cleaner output that is easier to save, process, and merge with results from other reconnaissance tools.

```
$ subfinder -d hackthissite.org -silent -o subfinder.txt
h5ai.hackthissite.org
lille.irc.hackthissite.org
v3dev.hackthissite.org
v3stage-cdn.hackthissite.org
email.hackthissite.org
mta-sts.hackthissite.org
vm-150.outbound.firewall.hackthissite.org
git.hackthissite.org
legal.hackthissite.org
mirror.hackthissite.org
status.hackthissite.org
new-irc.hackthissite.org
psrp.hackthissite.org
qdb.hackthissite.org
stats.hackthissite.org
mail.hackthissite.org
irc-ipv6.hackthissite.org
www.hackthissite.org
ctf.hackthissite.org
vm-050.outbound.firewall.hackthissite.org
vm-200.outbound.firewall.hackthissite.org
```

3. Assetfinder

Command:

```
assetfinder --subs-only hackthissite.org > assetfinder.txt
```

purpose:

The assetfinder tool was used to identify additional subdomains by querying publicly available sources such as Certificate Transparency logs, DNS services, and threat intelligence databases. The --subs-only option ensures that only subdomains belonging to the target are displayed, reducing unrelated results and improving data accuracy.

```
$ assetfinder --subs-only hackthissite.org > assetfinder.txt

$ assetfinder --subs-only hackthissite.com | tee subs.txt
www.hackthissite.com
hackthissite.com
file.abc
40class
cupp
soma.txt

$ cat assetfinder.txt
api.hackthissite.org
ctf.hackthissite.org
vm-005.outbound.firewall.hackthissite.org
vm-050.outbound.firewall.hackthissite.org
vm-099.outbound.firewall.hackthissite.org
vm-150.outbound.firewall.hackthissite.org
vm-200.outbound.firewall.hackthissite.org
forums.hackthissite.org
git.hackthissite.org
h5ai.hackthissite.org
hp.hackthissite.org
irc.hackthissite.org
irc-hub.hackthissite.org
download
saima.txt
lab.txt
demo.exe
```

4. Amass (Passive Enumeration)

Command:

```
amass enum -passive -d hackthissite.org -o amass.txt
```

purpose:

Amass was executed in passive mode to perform comprehensive asset discovery without sending direct requests to the target. It gathers information from numerous OSINT sources, including DNS records, certificate transparency logs, ASN information, and reverse DNS lookups. This helps reveal a broader view of the target's infrastructure, including additional subdomains and externally

exposed assets.

```
$ amass enum -passive -d hackthissite.org -o amass.txt
hackthissite.org (FQDN) mx_record alt1.aspmx.l.google.com (FQDN)
hackthissite.org (FQDN) mx_record alt2.aspmx.l.google.com (FQDN)
hackthissite.org (FQDN) mx_record aspmx3.googlemail.com (FQDN)
hackthissite.org (FQDN) mx_record aspmx4.googlemail.com (FQDN)
hackthissite.org (FQDN) mx_record aspmx.l.google.com (FQDN)
hackthissite.org (FQDN) mx_record aspmx2.googlemail.com (FQDN)
hackthissite.org (FQDN) mx_record aspmx5.googlemail.com (FQDN)
hackthissite.org (FQDN) node irc-www.hackthissite.org (FQDN)
hackthissite.org (FQDN) node forums.hackthissite.org (FQDN)
hackthissite.org (FQDN) node qdb.hackthissite.org (FQDN)
hackthissite.org (FQDN) node v3stage-cdn.hackthissite.org (FQDN)
forums.hackthissite.org (FQDN) cname_record hackthissite.org (FQDN)
qdb.hackthissite.org (FQDN) cname_record irc-www.hackthissite.org (FQDN)
2-v3stage-cdn.hackthissite.org (FQDN) cname_record v3stage-cdn.hackthissite.org (FQDN)
hackthissite.org (FQDN) node h5ai.hackthissite.org (FQDN)
hackthissite.org (FQDN) node v3dev.hackthissite.org (FQDN)
hackthissite.org (FQDN) node irc-hub.hackthissite.org (FQDN)
hackthissite.org (FQDN) node psrp.hackthissite.org (FQDN)
h5ai.hackthissite.org (FQDN) cname_record hackthissite.github.io (FQDN)
```

5. Merge Results

Command:

```
cat subfinder.txt assetfinder.txt amass.txt | sort -u > master_subdomains.txt
```

purpose:

The outputs generated by Subfinder, Assetfinder, and Amass were merged into a single file. The sort -u option sorts the results alphabetically while removing duplicate entries. This produced one consolidated list of unique subdomains representing the target's overall attack surface.


6. Display the Master List

Command:

```
cat master_subdomains.txt
```

purpose:

This command was used to display all discovered unique subdomains stored in the master list. Reviewing the consolidated output helped verify the enumeration results before proceeding with additional reconnaissance activities.



```
$ cat subfinder.txt assetfinder.txt amass.txt | sort -u > master_subdomains.txt

[~/week1]
$ cat master_subdomains.txtvv
cat: master_subdomains.txtvv: No such file or directory

[~/week1]
$ cat master_subdomains.txt
112088.hackthissite.org
113211.hackthissite.org
114003.hackthissite.org
114081.hackthissite.org
118641.hackthissite.org
120512.hackthissite.org
120c6b.hackthissite.org
1256.hackthissite.org
198218.hackthissite.org
314.hackthissite.org
0.0.1.0.7.8.1.0.4.7.0.0.7.3.1.0.8.d.c.c.8.0.0.0.0.d.1.4.1.0.0.2.ip6.arpa (FQDN) ptr_record
0 (ASN) announces 172.83.94.0/24 (Netblock)
0 (ASN) announces 2406:d500:7::/48 (Netblock)
0 (ASN) announces 2602:f685:69::/48 (Netblock)
0 (ASN) announces 5.220.0.0/14 (Netblock)
0 (ASN) managed_by Not routed (RIROrganization)
```

7. Count the Total Number of Assets

Command:

```
wc -l master_subdomains.txt
```

purpose:

The `wc -l` command counts the total number of lines in the file, where each line represents one unique subdomain. This provides an estimate of the target's exposed attack surface and helps measure the effectiveness of the enumeration process.


8. Overlap Verification

Command:

```
sort subfinder.txt assetfinder.txt amass.txt | uniq -c | sort -nr | head
```

purpose:

This command compares the outputs from all reconnaissance tools to determine how frequently each subdomain appears. Subdomains discovered by multiple tools have a higher confidence level and are more likely to represent valid assets. In contrast, subdomains identified by only one source require additional validation before being considered reliable.



```
$ wc -l master_subdomains.txt
513 master_subdomains.txt

$ sort subfinder.txt assetfinder.txt amass.txt | uniq -c | sort -nr | head
 3 www.irc.hackthissite.org
 3 www.hackthissite.org
 3 wolf.irc.hackthissite.org
 3 vm-200.outbound.firewall.hackthissite.org
 3 vm-150.outbound.firewall.hackthissite.org
 3 vm-099.outbound.firewall.hackthissite.org
 3 vm-050.outbound.firewall.hackthissite.org
 3 vm-005.outbound.firewall.hackthissite.org
 3 v3stage.hackthissite.org
 3 v3stage-cdn.hackthissite.org
```

9. Certificate Transparency Search (CRT.sh)

Command:

```
crt_v2.sh -d hackthissite.org > crt_hack.txt
```

purpose:

This command queries Certificate Transparency logs to identify historical and current SSL certificates associated with the target domain. It helps discover forgotten subdomains, staging environments, wildcard certificates, and other assets that may not be visible through conventional search engines.

```
(saimanaz@saimanaz) [~/week1]
$ crt_v2.sh -d hackthissite.org > crt_hack.txt
crt_v2.sh: command not found

(saimanaz@saimanaz) [~/week1]
$ find ~ -name "crt_v2.sh"
/home/saimanaz/crt.sh/crt_v2.sh

(saimanaz@saimanaz) [~/week1]
$ /home/saimanaz/crt.sh/crt_v2.sh -d hackthissite.org > crt_hack.txt
jq: parse error: Invalid numeric literal at line 1, column 7

(saimanaz@saimanaz) [~/week1]
$

(saimanaz@saimanaz) [~/week1]
$ /home/saimanaz/crt.sh/crt_v2.sh -d hackthissite.org | head
```

```
(saimanaz@saimanaz) [~/week1]
$ curl -I "https://crt.sh/?q=%25.hackthissite.org&output=json"
HTTP/2 502
server: nginx
date: Fri, 26 Jun 2026 06:09:11 GMT
content-type: text/html
content-length: 150

(saimanaz@saimanaz) [~/week1]
$ curl "https://crt.sh/?q=%25.hackthissite.org&output=json" | head
% Total    % Received % Xferd  Average Speed   Time    Time     Time  Current
           Dload  Upload   Total     Spent    Left     Speed
100 150 100 150    0     0    9      0  0:00:16  0:00:15  0:00:01  40
<html>
<head><title>502 Bad Gateway</title></head>
<body>
<center><h1>502 Bad Gateway</h1></center>
<hr><center>nginx</center>
</body>
</html>
```

Observations:

The `crt_v2.sh` script was executed to retrieve Certificate Transparency records for the target domain. However, the CRT.sh service returned an **HTTP 502 Bad Gateway** response during execution. Since the server returned an HTML error page instead of JSON data, the `jq` parser failed to process the response, resulting in no valid subdomain information being extracted. This issue was caused by the temporary unavailability of the external CRT.sh service rather than an error in the local environment or command syntax.

10. DNSDumpster Analysis and Findings

DNSDumpster was used to gather additional DNS intelligence and identify publicly accessible assets associated with the target domain **hackthissite.org**. The scan revealed valuable information about the target's infrastructure, including subdomains, hosting providers, network locations, and service banners.


The results identified the subdomain **api.hackthissite.org**, which resolves to the IP address **137.74.187.115**. The IP belongs to **OVH SAS (France)** under **ASN 16276**, indicating that part of the target's infrastructure is hosted on the OVH cloud platform.

The hosting analysis also showed that the target utilizes multiple infrastructure providers, including **OVH**, **Google**, **Fastly**, **Akamai-Linode**, and **TILAA**, suggesting a distributed hosting architecture

supported by Content Delivery Networks (CDNs) and cloud services for improved performance and availability.

The service banner information revealed technologies associated with the target environment, including **GitHub.com**, **HackThisSite**, **HackThisSite IRC**, **HackThisSite Load Balancer v2**, and **Nginx 1.18.0 (Ubuntu)**. These banners provide insight into the web server software and supporting services used by the target.

Overall, DNSDumpster provided valuable intelligence that complemented the results obtained from other reconnaissance tools. The collected information helped expand the attack surface map by identifying active DNS records, infrastructure providers, hosting details, and publicly visible services without performing any intrusive **activities**.



11. DNSDumpster Data Conversion

Command:

purpose:

`sudo apt install xlsx2csv -y`

This command installs the xlsx2csv utility, which converts the Excel report downloaded from DNSDumpster into CSV format. Converting the file enables easier searching, filtering, and extraction of discovered DNS records.

```

-$ sudo apt install xlsx2csv -y
[sudo] password for saimanaz:
xlsx2csv is already the newest version (1:0.8.3-1).
The following packages were automatically installed and are no longer required:
  libcrypt-dev libjs-underscore libmbdtdls14t64 libolecf1t64 python3.12
  libgit2-1.8 libllhttp9.1 libmbdtdx509-1t64 libpython3.12-dev python3.12-dev
Use 'sudo apt autoremove' to remove them.
Summary:
  Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 2086
  
```

Command:

```
xlsx2csv -a Dnsdumpster.xlsx > all_sheets.csv
```

purpose:

This command converts all worksheets from the DNSDumpster Excel report into a single CSV file, making the data suitable for command-line processing.

```

saimanaz@~$ cp ~/Dnsdumpster.xlsx ~/week1/
saimanaz@~$ xlsx2csv -a Dnsdumpster.xlsx > all_sheets.csv
Input file not found!
saimanaz@~$ cp ~/Dnsdumpster.xlsx ~/week1/
saimanaz@~$ xlsx2csv -a Dnsdumpster.xlsx > all_sheets.csv
saimanaz@~$ grep -oE "[a-zA-Z0-9.-]+\.[a-z]{2,6}" all_sheets.csv | sort -u > dnsdumpster.txt
saimanaz@~$ cat master_subdomains.txt dnsdumpster.txt crt_hack.txt | sort -u > attack_surface.txt
```

```

$ cat all_sheets.csv
1- Summary
,Domain Profiler Summary for hackthissite.com,,,,,
,Generated on: 2026-06-25 06:58:33,,,,,
,all_sheets.csv,demo.ex,filtered.txt
,Top 5 Banners,,,,,demo.exe,filtt.txt
,Name,Count,,,,,demo.exemsfvenom,filt.txt
,unknown,1,,,,,xt,Desktop,final_domains.txt
,,,,,find.txt,dnsdump_robinhood.txt,findomain.git
,Top 5 ASN,,,,,dnsdumpster.txt,findomain.git.1
,ASN,ASN Name,Network Range,Count,,,findomain.txt
,44273,"GODADDY-DNS - Host Europe GmbH, DE",97.74.98.0/23,2,,
,16509,"AMAZON-02 - Amazon.com, Inc.",76.223.48.0/20,1,,xt
,,,,,Documents,go
,Top 5 Countries,,,,,Downloads,go1.26.0.linux-amd64.tar.gz
,Name,Count,,,,,main.zip,file123,go1.26.0.linux-amd64.tar.gz.1
,United States,3,,,,,file123.pub,hackasset.txt
,,,,,domains.txt,fileee1,hackns.txt
,,,,,hackthissite_2.txt,fileee2,hash.txt
,,,,,hack.txt,filee.exe,ikram.txt
,,,,,h,file.exe,ikramudddin.txt
,,,,,
,,,,,
,,,,,sainanaz@sainanaz)-[~]
,,,,,

```

12. Extract DNSDumpster Subdomains

Command:

```
grep -oE "[a-zA-Z0-9.-]+\\.hackthissite\.org" all_sheets.csv | sort -u > dnsdumpster.txt
```

purpose:

The grep command extracts all subdomains matching the target domain from the converted CSV file. The sort -u option removes duplicate entries, producing a clean list of unique subdomains discovered through DNSDumpster.

13. Create the Final Attack Surface List

Command:

```
cat master_subdomains.txt dnsdumpster.txt crt_hack.txt | sort -u > attack_surface.txt
```

purpose:

This command combines the results obtained from Subfinder, Assetfinder, Amass, DNSDumpster, and CRT.sh into a single file. Duplicate entries are removed to produce a comprehensive attack surface list that represents all publicly discoverable assets associated with the target domain. This consolidated dataset serves as the foundation for the next stages of infrastructure analysis and security assessment.

```
$ cat attack_surface.txt
archive-key.asc
assetfinder.txt
demo.exe
demo.exemsvvenom
Desktop
hood.txt
112088.hackthissite.org
113211.hackthissite.org
114003.hackthissite.org
114081.hackthissite.org
118641.hackthissite.org
120512.hackthissite.org
120c6b.hackthissite.org
1256.hackthissite.org
198218.hackthissite.org
314.hackthissite.org
0.0.1.0.7.8.1.0.4.7.0.0.7.3:1.0.8.d.c.c.8.0.0.0.d.1.4.1.0.0.2.ip6.arpa (FQDN)
0 (ASN) announces 172.83.94.0/24 (Netblock)
0 (ASN) announces 2406:d500:7::/48 (Netblock)
0 (ASN) announces 2602:f685:69::/48 (Netblock)
0 (ASN) announces 5.220.0.0/14 (Netblock)
demo.txt
flltt.txt
fllt.txt
final_domains.txt
findomain.git
findomain.git.1
findomain.txt
fll.txt
ftp.txt
go
gol.26.0.linux-amd64.tar.gz
gol.26.0.linux-amd64.tar.gz.1
hackasset.txt
hackns.txt
hash.txt
lm.txt
master_sub
Music
newfolder1
OS_Lab
passfile.t
Pictures
Public
result.txt
resume.cfg
saima123
saimanaz.t
shadow
shell1.exe
ptr_recor
sherlock
```

Task 02 – Infrastructure & Technology Profiling

1. WhatWeb

Command:

```
whatweb https://hackthissite.org
```

Purpose:

The **WhatWeb** tool was used to identify the technologies powering the target website. It performs web fingerprinting by analyzing HTTP headers, HTML content, cookies, and scripts. The scan identifies the web server, content management system (CMS), frameworks, programming languages, analytics services, and security-related technologies. This information helps security professionals understand the target's technology stack and identify components that may require further security assessment.

```
-$ whatweb https://hackthissite.org
https://hackthissite.org [200 OK] Content-Language[en], Cookies[HackThisSite], Country[CANADA][CA], HTTPServer[HackThisSite], IP[137.74.187.10], JQuery[1.8.1], Meta-Author[HackThisSite.org Staff], Open-Graph-Protocol[website], PasswordField[password], Script[text/javascript], Strict-Transport-Security[max-age=31536000; includeSubDomains; preload], Title[Hack This Site], UncommonHeaders[upgrade, onion-location, access-control-allow-origin, content-security-policy, referrer-policy, feature-policy, public-key-pins-report-only, report-to, nel], X-XSS-Protection[0]
```


WhatWeb Analysis and Findings

The **WhatWeb** tool was used to fingerprint the technologies deployed on **hackthissite.org**. The scan successfully identified several components of the target's web infrastructure.

The target website responded with an **HTTP 200 OK** status code, confirming that the web application was accessible and functioning normally at the time of the assessment.

The scan identified the server header as **HackThisSite**, while the website resolved to the IP address **137.74.187.104**, indicating the publicly accessible host serving the application. The detected

Content-Language was **English (en)**, confirming that the website primarily serves English-language content.

A session cookie named **HackThisSite** was identified, indicating that the application uses cookies to maintain user sessions and authentication state.

The website was found to use **jQuery version 1.8.1**, which indicates that JavaScript libraries are used to provide interactive functionality within the web application.

The HTML metadata revealed the author as **HackThisSite.org Staff**, while the **Open Graph Protocol** was detected, suggesting that the website supports enhanced previews when its links are shared on social media platforms.

A **password input field** was identified, confirming the presence of user authentication functionality such as a login page.

Several HTTP security headers were also detected. **Strict-Transport-Security (HSTS)** was enabled with a one-year policy, forcing browsers to communicate with the website only over HTTPS. Additional security-related headers, including **Content-Security-Policy**, **Referrer-Policy**, **Feature-Policy**, **Report-To**, **NEL**, and **Onion-Location**, were present, indicating that multiple browser security mechanisms have been implemented to improve protection against common web-based attacks.

Overall, the WhatWeb scan provided valuable insight into the target's technology stack, server configuration, client-side libraries, authentication mechanisms, and implemented security controls. This information contributes to a better understanding of the target's infrastructure and supports further reconnaissance activities.


2. Wappalyzer CLI

Command:

```
wappalyzer --target https://hackthissite.org --disable-ssl --output output.json
```

Purpose:

The Wappalyzer CLI was used to verify the technologies detected on the target website. It identifies frontend frameworks, backend technologies, hosting providers, content delivery networks (CDNs), analytics tools, and security controls. Cross-verifying technology fingerprints with multiple tools increases the accuracy of reconnaissance and reduces false positives.



The screenshot displays the Wappalyzer web interface. At the top is a purple header with the Wappalyzer logo, a toggle switch, a settings gear, and a refresh icon. Below the header are two tabs: 'TECHNOLOGIES' (active) and 'MORE INFO'. An 'Export' button with a download icon is located to the right of the tabs. The main content area is divided into two columns. The left column, titled 'Miscellaneous', contains three items: 'RSS' with an RSS icon, 'PWA' with a PWA icon, and 'Open Graph' with an Open Graph icon. The right column, titled 'JavaScript libraries', contains one item: 'jQuery 1.8.1' with a jQuery icon. Below these columns is a link that says 'Something wrong or missing?'. At the bottom of the interface is a light purple banner with the text 'See website technologies in your CRM' and an upward arrow. Below this text is a description: 'Add website technology data to HubSpot, Salesforce, or Pipedrive so your team can prioritize accounts and personalize outreach faster.' At the bottom of the banner is a dark purple button with the text 'Enrich CRM records' and a right arrow.

Wappalyzer

TECHNOLOGIES MORE INFO [Export](#)

Miscellaneous

- [RSS](#)
- [PWA](#)
- [Open Graph](#)

JavaScript libraries

- [jQuery 1.8.1](#)

[Something wrong or missing?](#)

See website technologies in your CRM

Add website technology data to HubSpot, Salesforce, or Pipedrive so your team can prioritize accounts and personalize outreach faster.

Enrich CRM records →

Miscellaneous	RSS	N/A	Indicates that the website provides an RSS feed for users to subscribe to updates and news.
Miscellaneous	PWA	N/A	Shows that the website supports Progressive Web App features, allowing an app-like experience in supported browsers.
Miscellaneous	Open graph	N/A	The website uses Open Graph metadata, enabling rich previews when links are shared on social media platforms.
Javascript libraray	jquery	1.8.1	The website uses the jQuery JavaScript library to provide dynamic and interactive web functionality.

3. Node.js Wappalyzer (Alternative)

Commands:

```
sudo apt install nodejs npm
```

```
node -v
```

```
npm -v
```

```
npx wappalyzer https://hackthissite.org
```

Purpose:

If the standalone Wappalyzer CLI does not produce accurate results, the Node.js version can be used as an alternative. Installing Node.js and npm allows the latest version of Wappalyzer to run directly from the Node package repository. This often provides improved technology detection and more up-to-date fingerprints.

4. WHOIS

Command:

whois hackthissite.org

Purpose:

The **WHOIS** command retrieves domain registration information, including the registrar, registration dates, name servers, organization details (when publicly available), and abuse contact information. It also provides valuable infrastructure details such as network ownership and Autonomous System Number (ASN), helping analysts understand who manages the target's network resources.

```
└─$ whois hackthissite.org all.exec (/usr/share/nodejs/npm/lib/commands/install.js:15
Domain Name: hackthissite.org (/usr/share/nodejs/npm/lib/npm.js:193:9)
Registry Domain ID: REDACTED (/usr/share/nodejs/npm/lib/cli/entry.js:67:5) {
  Registrar WHOIS Server: http://whois.porkbun.com
  Registrar URL: https://porkbun.com
  Updated Date: 2025-07-15T23:08:30Z
  Creation Date: 2003-08-10T15:01:25Z
  Registry Expiry Date: 2026-08-10T15:01:25Z
  Registrar: Porkbun LLC
  Registrar IANA ID: 1861
  Registrar Abuse Contact Email: abuse@porkbun.com
  Registrar Abuse Contact Phone: +1.8557675286
  Domain Status: clientDeleteProhibited https://icann.org/epp#clientDeleteProhibited
  Domain Status: clientTransferProhibited https://icann.org/epp#clientTransferProhibited
  Name Server: c.ns.buddyns.com
  Name Server: f.ns.buddyns.com
  Name Server: g.ns.buddyns.com
  Name Server: h.ns.buddyns.com
  Name Server: j.ns.buddyns.com
  DNSSEC: unsigned
  URL of the ICANN Whois Inaccuracy Complaint Form: https://icann.org/wicf/
  >>> Last update of WHOIS database: 2026-06-27T06:14:33Z <<<
  For more information on Whois status codes, please visit https://icann.org/epp
```

5. NSLookup

Command:

```
nslookup hackthissite.org
```

Purpose:

The **NSLookup** command resolves the domain name to its IP address and retrieves DNS information. It helps identify the hosting environment, detect shared infrastructure, and understand how the domain is configured within the DNS system.

```
$ nslookup hackthissite.org
Server: or path 192.168.208.2 /lib/node_modules'
Address: 192.168.208.2#53
Non-authoritative answer:as rejected by your operating
Name: hackthissite.org you do not have the permissions
Address: 137.74.187.100
Name: hackthissite.org this might be a permissions i
Address: 137.74.187.101 again as root/Administrator.
Name: hackthissite.org of this run can be found in:
Address: 137.74.187.102
Name: hackthissite.org ~/week1]
Address: 137.74.187.103 wappalyzer
Name: hackthissite.org alizer@7.0.3: Package no longe
Address: 137.74.187.104
added 1 package in 1m
```

6. Query Specific DNS Records

A Record

Command:

```
nslookup -type=A hackthissite.org
```

Purpose:

Retrieves the IPv4 address associated with the target domain, allowing the identification of the web server hosting the website.

```

$ nslookup -type=A hackthissite.org
Server: 192.168.208.2
Address: 192.168.208.2#53
Non-authoritative answer:
Name: hackthissite.org
Address: 137.74.187.100
Name: hackthissite.org
Address: 137.74.187.101
Name: hackthissite.org
Address: 137.74.187.102
Name: hackthissite.org
Address: 137.74.187.103
Name: hackthissite.org
Address: 137.74.187.104

```

MX Record

Command:

`nslookup -type=MX hackthissite.org`

Purpose:

Displays the mail servers responsible for receiving email on behalf of the target domain. This helps map the organization's email infrastructure.

```

$ nslookup -type=MX hackthissite.org
Server: 192.168.208.2
Address: 192.168.208.2#53
Non-authoritative answer:
hackthissite.org mail exchanger = 10 aspmx.l.google.com.
hackthissite.org mail exchanger = 20 alt1.aspmx.l.google.com.
hackthissite.org mail exchanger = 30 aspmx3.googlemail.com.
hackthissite.org mail exchanger = 30 aspmx4.googlemail.com.
hackthissite.org mail exchanger = 30 aspmx2.googlemail.com.
hackthissite.org mail exchanger = 20 alt2.aspmx.l.google.com.
hackthissite.org mail exchanger = 30 aspmx5.googlemail.com.
Authoritative answers can be found from:

```

NS Record

Command:

```
nslookup -type=NS hackthissite.org
```

Purpose:

Lists the authoritative name servers managing the target domain's DNS records. This information is useful for understanding the domain's DNS architecture.

```
└─$ nslookup -type=NS hackthissite.org modules
Server: or )      192.168.208.2
Address: r        192.168.208.2#53
npm error The operation was rejected by your operating system.
Non-authoritative answer: ; do not have the permissions to access this file as the
hackthissite.org      nameserver = j.ns.buddyns.com.
hackthissite.org believe nameserver = g.ns.buddyns.com: issue, please double-check t)
hackthissite.org command nameserver = f.ns.buddyns.com.
hackthissite.org delete log nameserver = h.ns.buddyns.com. /home/saimanaz/.npm/_logs/20
hackthissite.org      nameserver = c.ns.buddyns.com.
--(saimanaz@saimanaz)~:/week1
Authoritative answers can be found from:
f.ns.buddyns.com ed wapp internet address = 5.223.55.119 supported. Contact Support
f.ns.buddyns.com      has AAAA address 2a01:4ff:2f0:3661::3
```

TXT Record

Command:

```
nslookup -type=TXT hackthissite.org
```

Purpose:

Retrieves TXT records, which commonly contain SPF, DKIM, DMARC, and domain verification information used for email authentication and domain ownership verification.

```
saimind@kali:~/Documents$ nslookup -type=TXT hackthissite.org
Server: 192.168.208.2
Address: 192.168.208.2#53
Non-authoritative answer:
hackthissite.org text = "Harica-PM9RrLqWMFZXTJCoEoK"
hackthissite.org text = "v=spf1 a mx ip4:137.74.187.96 ip4:137.74.187.97 ip4:137.74.187.98 a:mail.hackthissite.org include:aspmx.googlemail.com include:spf.hackmail.org -all"
hackthissite.org text = "Harica-9mEHYfxOM4FZwd9l0gG"
hackthissite.org text = "t-verify=e3f12c9c23e2e475563590326df31a12"
Authoritative answers can be found from:
```

7. Dig

Command:

dig hackthissite.org ANY

Purpose:

The **dig** command provides detailed DNS information, including A, MX, NS, TXT, and other available DNS records. It offers more comprehensive DNS analysis than NSLookup and is commonly used for infrastructure mapping and DNS troubleshooting.

```
$ dig hackthissite.org ANY
;; communications error to 192.168.208.2#53: timed out
;; <<>> DiG 9.20.11-4+b1-Debian <<>> hackthissite.org ANY
;; global options: +cmd
;; Got answer:
;; -->HEADER<-- opcode: QUERY, status: NOERROR, id: 34300
;; flags: qr rd ra; QUERY: 1, ANSWER: 30, AUTHORITY: 0, ADDITIONAL: 0
;; OPT PSEUDOSECTION:
;; EDNS: version: 0, flags: 0, udp: 1220
;; COOKIE: 10aaedf531620f45010000006a3f6b80701881254db78dd9 (good)
;; QUESTION SECTION:
;hackthissite.org. IN ANY
;; ANSWER SECTION:
hackthissite.org. 3600 IN SOA c.ns.buddyns.com.
hackthissite.org. 3600 IN TXT "Harica-PM9RrLqWMFZXTJCoEoK"
hackthissite.org. 3600 IN TXT "v=spf1 a mx ip4:137.74.187.96 ip4:137.74.187.97 ip4:137.74.187.98 a:mail.hackthissite.org include:aspmx.googlemail.com include:spf.hackmail.org -all"
hackthissite.org. 3600 IN TXT "Harica-9mEHYfxOM4FZwd9l0gG"
hackthissite.org. 3600 IN TXT "t-verify=e3f12c9c23e2e475563590326df31a12"
hackthissite.org. 3600 IN MX 20 alt2.aspmx.l.google.com.
```


Task 2 part(2)– Google Dorking


1. Search for phpinfo Pages

Google Dork:

site:hackthissite.org inurl:phpinfo.php

Purpose

This Google Dork searches for publicly accessible **PHP information pages**. These pages may reveal details about the server environment, installed PHP modules, operating system, and software versions. Such information helps analysts understand the target's technology stack without directly interacting with the server.



2. Search for Environment Files

Google Dork:

site:hackthissite.org ext:env

Purpose

This query searches for publicly indexed **.env files**, which may contain sensitive configuration data such as database credentials, API keys, and application secrets.

site:hackthissite.org ext:env

AI Mode All Images Videos Forums News Short videos More ▾ Tools ▾

 Hack This Site
<https://www.hackthissite.org/articles/read>

Introduction to SASS/SCSS Pre-processors

23-Jul-2014 — To begin with, think of SASS as a dynamic implementation of CSS. It falls under two categories: a stylesheet language and a scripting one. By ... [Read more](#)

 Hack This Site
<https://www.hackthissite.org/programs/programs>

Useful Stuff

HackThisSite.org is a free, safe and legal training ground for hackers to test and expand their ethical hacking skills with challenges, CTFs, and more.

 Hack This Site
<https://www.hackthissite.org/articles/read>

Java Basics - HackThisSite

HackThisSite.org is a free, safe and legal training ground for hackers to test and expand their ethical hacking skills with challenges, CTFs, and more.

3. Search for Backup Files

Google Dork:

site:hackthissite.org ext:bak OR ext:zip OR ext:sql

Purpose

This dork searches for backup files, compressed archives, and SQL database dumps that may have been accidentally exposed on the web server.

site:hackthissite.org ext:bak

AI Mode All Images Videos News Forums Short videos More ▾ Tools ▾

 hackthissite.org
http://mirror.hackthissite.org › hackthiszine2 PDF ⋮

Call in sick. Skip school. Go do something you always

02-Dec-2004 — This can also happen when backups are made by copying a file as config.inc.php.bak so forth, which might reveal login or mysql information. [Read more](#)

 Hack This Site
https://www.hackthissite.org › articles › read ⋮

Google Hacking Codes

07-Oct-2008 — HackThisSite.org is a free, safe and legal training ground for hackers to test and expand their ethical hacking skills with challenges, ...

 Hack This Site
https://www.hackthissite.org › articles › read ⋮

Realistic 5 - Full Tutorial

28-Jan-2008 — HackThisSite.org is a free, safe and legal training ground for hackers to test and expand their ethical hacking skills with challenges, ...

site:hackthissite.org ext:zip



AI Mode

All

Images

Videos

News

Forums

Short videos

More ▾

Tools ▾



Hack This Site

<https://www.hackthissite.org> › articles › read



Steganography 101

27-Jun-2011 — HackThisSite.org is a free, safe and legal training ground for hackers to test and expand their ethical hacking skills with challenges, ...



hackthissite.org

<http://mirror.hackthissite.org> › hackthiszine2 PDF



Call in sick. Skip school. Go do something you always

02-Dec-2004 — Call in sick. Skip school. Go do something you always wanted to do. Take over an intersection with a bunch. [Read more](#)



Hack This Site

<https://www.hackthissite.org> › programs › programs



Useful Stuff

HackThisSite.org is a free, safe and legal training ground for hackers to test and expand their ethical hacking skills with challenges, CTFs, and more.

site:hackthissite.org ext:sql

AI Mode **All** Images Videos Forums Short videos News More ▾ Tools ▾



Hack This Site

<https://www.hackthissite.org> › articles › read ⋮

LAMP setup

11-Jan-2008 — HackThisSite.org is a free, safe and legal training ground for hackers to test and expand their ethical hacking skills with challenges, ...



Hack This Site

<https://www.hackthissite.org> › articles › read ⋮

Google Hacking Codes

07-Oct-2008 — HackThisSite.org is a free, safe and legal training ground for hackers to test and expand their ethical hacking skills with challenges, ...



Hack This Site

<https://www.hackthissite.org> › articles › read ⋮

XSS

22-Aug-2007 — HackThisSite.org is a free, safe and legal training ground for hackers to test and expand their ethical hacking skills with challenges

4. Search for robots.txt

Google Dork:

site:hackthissite.org robots.txt

Purpose

The robots.txt file provides instructions to search engine crawlers and may reveal hidden directories or administrative paths that website owners prefer not to be indexed.

Observation

Review the file for any directories or files that could provide additional reconnaissance information.

site:hackthissite.org robots.txt

AI Mode **All** Images Videos Forums Short videos News More ▾ Tools ▾



Hack This Site

<https://www.hackthissite.org> › articles › read ⋮

Alternative to Robots.txt

25-Aug-2009 — With robots.txt you spell out all of your files, and without robots.txt search engines will spell out all of your files for you. However, if ... [Read more](#)



Hack This Site

<https://www.hackthissite.org> › articles › read ⋮

What is OSINT and what are the most common techniques?

02-Jun-2021 — A robots.txt file contains instructions for bots that tell them which webpages they can and cannot access. Robots.txt files are most ... [Read more](#)



hackthissite.org

<http://mirror.hackthissite.org> › hackthiszine8_print PDF ⋮

eXploit cODe... NOT PEOPLE!

We need to learn these skills now, before the robot armies takes over. I challenge you this week to learn a technological skill that you always wanted to. What ... [Read more](#)



hackthissite.org

5. Search for Directory Listings

Google Dork:

site:hackthissite.org intitle:"index of"

Purpose

This query searches for open directory listings where files and folders may be publicly browsable.

Observation

If no results are returned, it indicates that directory indexing is not publicly accessible.

site:hackthissite.org intitle:index of

All Mode **All** Images Videos Forums News Short videos More ▾

Your search - **site:hackthissite.org intitle:index of** - did not match any documents.

Suggestions:

- Make sure that all words are spelled correctly.
- Try different keywords.
- Try more general keywords.
- Try fewer keywords.

6. Search for Login Pages

Google Dork:

site:hackthissite.org inurl:login

Purpose

This dork identifies login portals within the target domain. These pages help analysts understand the authentication surface of the application.

Observation

Any identified login pages can be documented as publicly accessible authentication interfaces.

site:hackthissite.org inurl:login

AI Mode **All** Images News Videos Forums Short videos More ▾ Tools ▾



Hack This Site

<https://www.hackthissite.org> › user › login

Login

Secure, fast, and private web browser with a built-in adblocker. Username: Password: Login

Anonymously Forgot Password - Forgot Username - Register [Read more](#)

Missing: inurl:



Hack This Site

<https://www.hackthissite.org>

Hack This Site

HackThisSite.org is a free, safe and legal training ground for hackers to test and expand their ethical hacking skills with challenges, CTFs, and more.



Hack This Site

<https://www.hackthissite.org> › user › view › intitle

View User: intitle

HackThisSite.org is a free, safe and legal training ground for hackers to test and expand their ethical hacking skills with challenges, CTFs, and more.

Images

Task 3 – Public Credential Discovery (GitHub Reconnaissance)

Objective

The objective of this task is to search publicly available GitHub repositories for accidentally exposed credentials, API keys, configuration files, and other sensitive information related to the target domain. This activity relies entirely on publicly accessible information and does not involve interacting with the target's systems.


1. Search GitHub for the Target Domain

Search Query:

hackthissite.org

Purpose

This search identifies public repositories, source code, configuration files, documentation, or scripts that reference the target domain. It helps determine whether developers have publicly disclosed information related to the organization's infrastructure.




2. Search for API Keys

GitHub Search:

hackthissite.org api_key

Purpose

This search attempts to identify publicly exposed API keys or authentication tokens associated with the target.



Your search did not match any repositories

However we found [38 code results](#) and [2 commits](#) that matched your search query. Alternatively try one of the tips below.

Search across an organization

Within an organization:

org:rails

User's code:

user:mona

Note that we don't currently support regular expressions in the repo or org qualifiers. For more information on search syntax, see our [syntax guide](#).

Saved searches

You could try an [advanced search](#).


3. Search for Passwords

GitHub Search:

hackthissite.org password

Purpose

Searches for source code or configuration files that may contain hardcoded passwords or authentication credentials.



4. Search for Environment Files

GitHub Search:

hackthissite.org .env

Purpose

Looks for environment configuration files that may contain database credentials, API secrets, and application configuration values.

hackthissite.org+.env&type=repositories



Your search did not match any repositories

However we found [234 code results](#) and [2 commits](#) that matched your search query. / try one of the tips below.

Search across an organization

Within an organization: [org:rails](#)

User's code: [user:mona](#)

Note that we don't currently support regular expressions in the repo or org qualifiers. For more information on search syntax, see our [syntax guide](#).

Saved searches

You could try an [advanced search](#).


5. Search for Configuration Files

GitHub Search:

hackthissite.org config

Purpose

Searches for publicly available configuration files that may reveal server settings, database connections, or infrastructure details.



```
1 [nickserv]
2 nick = "LectorBeta"
3 registered = FALSE
4 password = ""
5
6 [access]
7 Bren2010[level] = 0
8 Bren2010[hostmask] = "Brendan!Bren2010@bren2010.com"
9
10 ;Thetan[level] = 2
11 ;Thetan[hostmask] = "Thetan!Thetan@HTS-EE848195.dsl.mindspring.com"
12
13 [lecture]
14 lector = "Thetan"
15 intro = "The lecture is about to begin, so the channel will be muted until the speaker periodically unmutes it for questions. Our speaker today is %LECTURER, ar
16 postIntro = "There is currently a lecture proceeding in %CHANNEL. If you don't understand, it's fine; the lecture recording will be posted on the site so you can \
17 rules = "Any flooding, trolling, flaming, or interruption will result in a verbal warning. If it continues, you will be kick banned from the channel. If you fee
18
19 [server]
20 server = "ssl://irc.hackthissite.org"
21 port = 7000
22 channel = "#bren2010"
23 password = ""
24
25 [system]
26 daemon = FALSE
27 output = TRUE
28 rawOutput = FALSE
29 debug = TRUE
```

GitHub Repository Analysis – Findings

- A public GitHub repository named **HTS-Lecture-Bot** was examined to identify any exposed credentials or sensitive configuration data related to the target.
- The repository contained a configuration file named **config.ini**, which was manually inspected.
- The configuration file defined the IRC bot nickname as **LectorBeta**.
- The IRC server was configured as **ssl://irc.hackthissite.org** using **port 7000**.
- The bot was configured to join the IRC channel **#bren2010**.
- User access information, including an IRC hostmask, was present for administrative purposes.
- Two password fields were identified in the configuration file; however, both contained **empty values ("")**, indicating that no hardcoded passwords were stored.
- No API keys, authentication tokens, database credentials, or private keys were found within the configuration file.
- No sensitive information or confidential credentials related to **hackthissite.org** were publicly exposed in the examined repository.

- The repository primarily contained source code and configuration files required for the IRC lecture bot and did not reveal any exploitable secrets.
- The assessment concluded that no publicly exposed credentials associated with the target were identified during the GitHub reconnaissance activity.


6. Search for Private Keys

GitHub Search:

hackthissite.org PRIVATE KEY

Purpose

Attempts to identify accidentally exposed SSH keys, RSA private keys, or TLS certificates that have been committed to public repositories.



Your search did not match any repositories

However we found [738 code results](#) that matched your search query. Alternatively try one of the tips below.

Search across an organization
^

Within an organization:
org:rails

User's code:
user:mona

Note that we don't currently support regular expressions in the repo or org qualifiers. For more information on search syntax, see our [syntax guide](#).

Saved searches
v

You could try an [advanced search](#).

7. search for sql

Github search:

Hackthissite.org "SQL_CONNECNTION"



Your search did not match any repositories

You could try one of the tips below.

Search across an organization

Saved searches

You could try an [advanced search](#).

Task 04 – Live Asset Filtering & Visual Recon

Objective

The objective of this task is to filter inactive subdomains, identify live web assets, and perform visual reconnaissance by capturing screenshots of accessible web applications. This process helps security analysts focus on active attack surfaces instead of wasting time on inactive or parked hosts.

Learning Objectives

- Identify active web assets from the discovered subdomains.
- Filter inactive or unreachable hosts.
- Collect HTTP status codes and webpage titles.
- Detect technologies running on live hosts.
- Capture screenshots of active websites.
- Identify login pages, admin panels, development environments, and other interesting web assets.
- Prioritize high-value targets for further security assessment.

Why This Task is Important

After Task 1, hundreds or even thousands of subdomains may have been discovered. However, many of these assets may no longer exist or may not respond to network requests.

Common scenarios include:

- Dead subdomains
- Parked domains
- Offline servers
- Temporary infrastructure
- Non-responsive hosts

Instead of manually checking every subdomain, automated filtering tools identify only the active assets, making reconnaissance faster and more efficient.

Step 1 – Verify Live Hosts using Httprobe

Command

```
cat subdomains.txt | httprobe --prefer-https > live-urls.txt
```

Purpose

This command reads every subdomain from subdomains.txt and tests whether it responds over HTTP or HTTPS. If HTTPS is available, it is preferred. Only reachable URLs are saved into live-urls.txt, reducing the attack surface to active web assets.

```
└─$ cat subs.txt | httprobe --prefer-https > live-urls.txt

└─$ cat live-urls.txt
https://www.hackthissite.com
https://hackthissite.com

└─$
```



Step 2 – View Live URLs

Command

```
cat live-urls.txt
```

Purpose

Displays all live URLs discovered during the previous step so they can be verified before further analysis.



```
$ cat live-urls.txt
https://www.hackthissite.com
https://hackthissite.com
```

Step 3 – Validate Hosts using Httpx

Command


```
cat subdomains.txt | httpx -status-code -title -tech-detect -o live-httpx.txt
```

Purpose

This command validates all discovered subdomains and records:

- HTTP status code
- Website title
- Detected technologies
- Live URLs

The output is stored in **live-httpx.txt**, which provides detailed information about each responsive host.



```
$ cat subs.txt | $HOME/go/bin/httpx -status-code -title -tech-detect -o live-httpx.txt
[INF] Current httpx version v1.9.0 (latest)
[WRN] UI Dashboard is disabled, Use -dashboard option to enable
https://www.hackthissite.com [200]
https://hackthissite.com [200]
```

Step 4 – Capture Screenshots using Gowitness (Alternative)

Command

```
gowitness scan file -f live-urls.txt -s ~/gowitness_screenshots --write-db
```

Purpose

Gowitness is an alternative to Aquatone that captures screenshots of every live web application and stores them in the specified directory.

```
└─$ gowitness scan file -f live-urls.txt -s ~/gowitness_screenshots --write-db
2026/06/28 03:51:40 INFO result 📡 target=https://www.hackthissite.com:443 status-code=200 title="" have-screenshot=true
2026/06/28 03:51:40 INFO result 📡 target=https://hackthissite.com:443 status-code=200 title="" have-screenshot=true
└─(osintops@osintops) - [~/work3]
```

Step 5 – Start Gowitness Report

Command

```
gowitness report serve
```

Purpose

Starts the built-in web server for Gowitness so that screenshots can be viewed through a browser dashboard.

```
└─$ gowitness report server
2026/06/28 03:52:14 INFO starting web server host=127.0.0.1 port=7171
2026/06/28 03:57:56 "GET http://127.0.0.1:7171/ HTTP/1.1" from 127.0.0.1:38612 - 200 481B in 19.499975ms
2026/06/28 03:57:56 "GET http://127.0.0.1:7171/assets/index-CLzylN3h.css HTTP/1.1" from 127.0.0.1:38628 - 200 42974B in 132.478µs
2026/06/28 03:57:56 "GET http://127.0.0.1:7171/assets/index-Dy9LEUPM.js HTTP/1.1" from 127.0.0.1:38612 - 200 895660B in 125.822823ms
2026/06/28 03:57:57 "GET http://127.0.0.1:7171/favicon.ico HTTP/1.1" from 127.0.0.1:38628 - 200 1150B in 135.866µs
2026/06/28 03:57:58 "GET http://127.0.0.1:7171/api/statistics HTTP/1.1" from 127.0.0.1:38628 - 200 119B in 1.234122ms
2026/06/28 03:58:13 "GET http://127.0.0.1:7171/api/results/gallery?page=1&limit=24&technologies=6&status=6&perception=false&failed=true HTTP/1.1" from 127.0.0.1:38628 - 200 509B in 1.126257ms
2026/06/28 03:58:13 "GET http://127.0.0.1:7171/api/wappalyzer HTTP/1.1" from 127.0.0.1:38612 - 200 654832B in 12.185812ms
2026/06/28 03:58:13 "GET http://127.0.0.1:7171/screenshots/https—hackthissite.com-443.jpeg HTTP/1.1" from 127.0.0.1:38612 - 404 196µs
2026/06/28 03:58:13 "GET http://127.0.0.1:7171/screenshots/https—www.hackthissite.com-443.jpeg HTTP/1.1" from 127.0.0.1:38628 - 404 21.715µs
```

Open the Report

Open your browser and visit:

<http://127.0.0.1:7171>

Purpose

Displays the Gowitness dashboard containing all captured screenshots and metadata for the scanned web assets.

The first screenshot shows the **Dashboard** view of the gowitness v3 interface. It displays summary statistics: Database Size (0.1 MB), Total Results (2), Headers (6), Network Logs (6), and Console Logs (0). The second screenshot shows the **Gallery** view, which displays a grid of scanned website thumbnails. The third screenshot shows the **Overview** view, which provides detailed information for each scanned target in a table format.

Actions	Code	URL	Title	Size	Protocol
View	200	https://www.hackthissite.com:443		0.10 KB	http/1.1
View	200	https://hackthissite.com:443		0.10 KB	http/1.1

observations

- **Gallery:** Displays screenshots of the scanned websites for visual inspection.
- **Overview:** Shows detailed information for each scanned target, including URL, status code, headers, and page title.
- **Search Bar:** Allows searching for a specific scanned target.
- **New Probe:** Can be used to start another scan from the web interface.

