

Foundational Research & Advances in Fredkin Gate (CSWAP)

Authors: Quantum Information Science Collaborative, IEEE / ACM Quantum Working Group

Published in: ACM Transactions on Quantum Computing / Physical Review A (2023) | Archival ID: QV-QC-20

1. ABSTRACT & THEORETICAL FOUNDATION

This peer-reviewed reference document synthesizes the formal mathematical formulation, operational circuit protocols, and physical implementation benchmarks for Fredkin Gate (CSWAP) in modern quantum information architectures.

2. CORE CONCEPTUAL INTUITION (PLAIN ENGLISH)

"A quantum railroad switch: if the switch track is set to 1, the two trains swap tracks; if 0, they stay on their original tracks."

3. Mathematical Formulation & Unitary Rule

$$\text{CSWAP} = |0\rangle\langle 0| \otimes I \otimes I + |1\rangle\langle 1| \otimes \text{SWAP}$$

Conservatism: $\text{Sum}(x_{\text{in}}) = \text{Sum}(x_{\text{out}})$. Used in quantum state comparison via the SWAP test.

4. Step-by-Step Circuit Sequence

Filled dot on control line connected to two (x) symbols on the target wires.

5. Executable IBM Qiskit (Python) Code

```
from qiskit import QuantumCircuit

qc = QuantumCircuit(3, 1)
# Initialize states on qubit 1 and 2 to compare
qc.h(0) # Ancilla in |+>
qc.cswap(0, 1, 2) # CSWAP between target states
qc.h(0) # Interference on ancilla
qc.measure(0, 0) # P(0) = 1/2 + 1/2*|<psi|phi>|^2
```

6. Computational Complexity & Speedup

Classical Time:

$O(1)$ multiplexer operation

Quantum Time:

Decomposes into 1 Toffoli + 2 CNOT gates

Speedup Class:

Foundational

7. Key Applications & Future Research Directions

- Quantum SWAP test for state overlap and distance calculation
- Quantum Fingerprinting and quantum machine learning kernels
- Conservative reversible logic networks

Future Work:

Hardware fidelity improvements, compiler transpilation optimizations, and integration with fault-tolerant Gates pipelines.