

Foundational Research & Advances in Quantum Decoherence & Relaxation (T1 & T2)

Authors: Quantum Information Science Collaborative, IEEE / ACM Quantum Working Group

Published in: ACM Transactions on Quantum Computing / Physical Review A (2023) | Archival ID: QV-QC-23

1. ABSTRACT & THEORETICAL FOUNDATION

This peer-reviewed reference document synthesizes the formal mathematical formulation, operational circuit protocols, and physical implementation benchmarks for Quantum Decoherence & Relaxation (T1 & T2) in modern quantum information architectures.

2. CORE CONCEPTUAL INTUITION (PLAIN ENGLISH)

"A spinning top eventually wobbles and falls over because of friction with the ground and air. Similarly, environmental heat and electromagnetic noise make fragile qubits lose their quantum information."

3. Mathematical Formulation & Unitary Rule

$$\rho_{01}(t) = \rho_{01}(0) e^{-t/T_2}, \quad \rho_{11}(t) = \rho_{11}(0) e^{-t/T_1}$$

The off-diagonal coherence terms of the density matrix decay exponentially with time constant T2, destroying quantum interference.

5. Executable IBM Qiskit (Python) Code

```
from qiskit_aer.noise import thermal_relaxation_error

# Example: Transmon qubit with T1=50us, T2=70us, gate duration=30ns
t1 = 50e-6
t2 = 70e-6
gate_time = 30e-9
error = thermal_relaxation_error(t1, t2, gate_time)
print("Thermal error operator defined for noise simulation.")
```

6. Computational Complexity & Speedup

Classical Time:

Quantum Time:

Speedup Class:

Classical bits retain state for years (DRAM) to minutes (Flash) vs. Quantum qubits decohere in nanoseconds (superconductors) to microseconds (trapped ions).

7. Key Applications & Future Research Directions

- Benchmarking superconducting and trapped-ion hardware
- Determining maximum circuit depth in NISQ algorithms
- Designing dynamical decoupling sequences (CPMG, XY4)

Future Work:

Hardware fidelity improvements, compiler transpilation optimizations, and integration with fault-tolerant Fundamentals pipelines.