



Routing in React

In single-page-application, we need to navigate end-user to the different-different components (views) that we have define in our application.

React-router-dom library allows us to define the navigation in react application.

React-router-dom intercept the browser url and according to browser URL it renders the component.

React-router-dom library comes with several predefine components, by using them we can implement the routing.

1. **BrowserRouter: -**

BrowserRouter component intercepts the value of browser URL in sync manner. and as URL of a browse gets changed it provide updated browser url to its child component. BrowserRouter component allows routing in react application.

2. **Routes: -**

Routes component wraps all the mappings on URLs and their corresponding components as children. And insures at a time only on component get render among of them.

3. **Route: -**

Route component is use for mapping purpose. it defines the mapping of path to desired component.

Route Component has two important props

1. path: - path props get the value of url endpoint mapping
2. element: - get the component which needs to be render



CJC

Complete Java Classes

by Kunal Sir

4. Link: -

Link component is use to change the browser URL. Instead of using `<button>` or `<a>` elements we use Link component.

It has two important props

1. `className`: - get the css class name to style the link
2. `to` :- it accepts the string value on which you want to shift the browser url

Q) How to install `react-router-dom` library?

-> Using npm command:- **npm install react-router-dom**

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
PS D:\B176 React Workspace\react-routing> npm install react-router-dom
```

```
added 3 packages, and audited 1548 packages in 3s
```

Complete Java Classes

❖ Below example will demonstrate the routing in react application.

1. Application folder structure.





CJC

Complete Java Classes

by Kunal Sir

2. Snippet of Index.js

```
JS index.js M X
src > JS index.js > ...
1  import React from 'react';
2  import ReactDOM from 'react-dom/client';
3  import './index.css';
4  import App from './App';
5
6
7  const root = ReactDOM.createRoot(document.getElementById('root'));
8  root.render(
9
10     <App />
11
12 );
13
```

3. Snippet of App.js

```
JS App.js M X
src > JS App.js > App
1
2  import './App.css';
3  import '../node_modules/bootstrap/dist/css/bootstrap.css'
4  import Header from './template/header/Header';
5  import { BrowserRouter } from 'react-router-dom';
6  import Home from './template/home/Home';
7  import About from './template/about/About';
8  import Courses from './includes/courses/Courses';
9  import Enquiry from './includes/enquiry/Enquiry';
10 import SignIn from './includes/sign-in/SignIn';
11 function App() {
12   return (
13     <div>
14       <BrowserRouter>
15         <Header/>
16         <Routes>
17           <Route path="/" element={<Home/>} />
18           <Route path="/home" element={<Home/>} />
19           <Route path="/about" element={<About/>} />
20           <Route path="/courses" element={<Courses/>} />
21           <Route path="/contact-us" element={<Enquiry/>} />
22           <Route path="/login" element={<SignIn/>} />
23         </Routes>
24       </BrowserRouter>
25     </div>
26   );
27 }
28
29 export default App;
```



CJC

Complete Java Classes

by Kunal Sir

4. Snippet of Header.js

```
JS Header.js U X
src > template > header > JS Header.js > [🔍] default
1  import { Link } from "react-router-dom";
2
3  function Header()
4  {
5      return <nav className="d-flex justify-content-around bg-primary">
6          <h1 className="text-white">Welcome To CJC..!</h1>
7          <div className="mt-2">
8
9              <Link className="btn btn-dark fs-5 me-2" to={"/home"}>Home</Link>
10             <Link className="btn btn-dark fs-5 me-2" to={"/about"}>About</Link>
11             <Link className="btn btn-dark fs-5 me-2" to={"/courses"}>Courses</Link>
12             <Link className="btn btn-dark fs-5 me-2" to={"/contact-us"}>Enquiry</Link>
13             <Link className="btn btn-dark fs-5 me-2" to={"/login"}>Sign-In</Link>
14
15         </div>
16     </nav>
17 }
18
19 export default Header;
```

5. Snippet of Home.js

```
JS Home.js U X
src > template > home > JS Home.js > 🏠 Home
1  import React from 'react'
2
3  function Home() {
4      return (
5          <h1 className='text-center'>Home</h1>
6      )
7  }
8
9  export default Home
```



CJC

Complete Java Classes

by Kunal Sir

6. Snippet of About.js

JS About.js U X

src > template > about > JS About.js > About

```
1 import React from 'react'
2
3 function About() {
4   return (
5     <h1 className='text-center'>About</h1>
6   )
7 }
8
9 export default About
```

7. Snippet of Courses.js

JS Courses.js U X

src > includes > courses > JS Courses.js > Courses

```
1 import React from 'react'
2
3 function Courses() {
4   return (
5     <h1 className='text-center text-primary'>.....Featching courses information...!</h1>
6   )
7 }
8
9 export default Courses
```



CJC

Complete Java Classes

by Kunal Sir

8. Snippet of Enquiry.js

```
JS Enquiry.js U X
src > includes > enquiry > JS Enquiry.js > Enquiry
1  import React from 'react'
2
3  function Enquiry() {
4    return (
5      <h1 className='text-center'>Feel free to enquir..!</h1>
6    )
7  }
8
9  export default Enquiry
```

9. Snippet of SignIn.js

```
JS SignIn.js U X
src > includes > sign-in > JS SignIn.js > SignIn
1  import React from 'react'
2
3  function SignIn() {
4    return (
5      <h1 className='text-center'>Sign-In here..!</h1>
6    )
7  }
8
9  export default SignIn
```