



CJC

Complete Java Classes

by **Kunal Sir**

Yes, you can absolutely access the **keys (properties)** of each object inside an **array of objects** using **map()** in React.

React does not change how JavaScript arrays or map work — it works exactly like JavaScript.

✓ Example: Accessing Keys of Array of Objects Using map()

Suppose you have this array:

```
const users = [  
  { id: 1, name: "Sainath", age: 25 },  
  { id: 2, name: "Rahul", age: 22 },  
  { id: 3, name: "Priya", age: 24 }  
];
```

✓ Display specific keys from each object

You can access them directly inside map:

```
users.map((user) => (  
  <div key={user.id}>  
    <h3>{user.name}</h3>  
    <p>{user.age}</p>  
  </div>  
))
```



CJC

Complete Java Classes

by Kunal Sir

✓ Example: If you want to access the KEY NAMES dynamically

Sometimes you want: **id, name, age**

Use `Object.keys()` inside map:

```
users.map((user) => (  
  <div key={user.id}>  
    {Object.keys(user).map((key) => (  
      <p key={key}>  
        {key} : {user[key]}  
      </p>  
    ))}  
  </div>  
))
```

This will output:

```
id : 1  
name : Sainath  
age : 25
```



CJC

Complete Java Classes

by Kunal Sir

✓ Example Component

```
import React from "react";
```

```
const UserList = () => {  
  const users = [  
    { id: 1, name: "Sainath", age: 25 },  
    { id: 2, name: "Rahul", age: 22 },  
    { id: 3, name: "Priya", age: 24 }  
  ];  
  
  return (  
    <div>  
      {users.map((user) => (  
        <div key={user.id} style={{ marginBottom: "10px" }}>  
          {Object.keys(user).map((key) => (  
            <p key={key}>  
              {key}: {user[key]}  
            </p>  
          ))}  
        </div>  
      ))}  
    </div>  
  );  
};
```

```
export default UserList;
```



CJC

Complete Java Classes

by Kunal Sir

✓ Summary

Task	Possible with map()?	How?
Access values	✓ Yes	<code>user.name</code>
Access keys	✓ Yes	<code>Object.keys(user)</code>
Access key + value	✓ Yes	<code>Object.keys(user).map(key => ...)</code>



CJC

Complete Java Classes



CJC

Complete Java Classes

by Kunal Sir

Yes!

You can get the **keys only one time** for the **table headings** when you have an array of objects.

This is a very common requirement in React.

✓ How to Get Table Headings Only Once

If your data looks like:

```
const users = [
  { id: 1, name: "Sainath", age: 25 },
  { id: 2, name: "Rahul", age: 22 },
  { id: 3, name: "Priya", age: 24 }
];
```

✓ Step 1: Get the keys from the first object ONLY

```
const headings = Object.keys(users[0]);
```

✓ Step 2: Render once in <thead>

```
<thead>
  <tr>
    {headings.map((head) => (
      <th key={head}>{head.toUpperCase()}</th>
    ))}
  </tr>
</thead>
```

✓ Step 3: Render the table rows

```
<tbody>
  {users.map((u) => (
    <tr key={u.id}>
      {headings.map((head) => (
        <td key={head}>{u[head]}</td>
      ))}
    </tr>
  ))}
</tbody>
```



CJC

Complete Java Classes

by Kunal Sir

✓ Full Working Example

```
import React from 'react';

const TableExample = () => {
  const users = [
    { id: 1, name: "Sainath", age: 25 },
    { id: 2, name: "Rahul", age: 22 },
    { id: 3, name: "Priya", age: 24 }
  ];

  const headings = Object.keys(users[0]); // ✓ Only one time

  return (
    <table border="1" cellPadding="10">
      <thead>
        <tr>
          {headings.map((head) => (
            <th key={head}>{head.toUpperCase()}</th>
          ))}
        </tr>
      </thead>
      <tbody>
        {users.map((user) => (
          <tr key={user.id}>
            {headings.map((h) => (
              <td key={h}>{user[h]}</td>
            ))}
          </tr>
        ))}
      </tbody>
    </table>
  );
};

export default TableExample;
```



CJC

Complete Java Classes

by Kunal Sir

✓ Why this works

- **Object.keys(users[0])** → gets all the field names
 - You use them once for headings
 - You reuse the same keys for table rows
 - This keeps the table clean and consistent
-



CJC

Complete Java Classes