



CJC

Complete Java Classes

by Kunal Sir

MCQ

1. What are React components?

- a) CSS elements
- b) Reusable UI building blocks
- c) JavaScript libraries
- d) APIs

2. Which of the following is *not* a React component type?

- a) Functional component
- b) Class component
- c) Object component
- d) None

3. Functional components in React are written using:

- a) Java
- b) JavaScript functions
- c) JSX templates only
- d) CSS

4. Which of these must always start with a capital letter in React?

- a) JSX element
- b) Component name
- c) Props
- d) useState

5. What is the purpose of props?

- a) To store local state
- b) To pass data from one component to another
- c) To manage lifecycle
- d) To call APIs

6. What is the correct syntax to use props in React functional components?

- a) props = ()
- b) function Home({props})
- c) function Home(props)
- d) const props()



CJC

Complete Java Classes

by Kunal Sir

7. Which of these is used to manage state in functional components?

- a) this.state
- b) useState()
- c) setProps()
- d) useClass()

8. What does `useState()` return?

- a) Single value
- b) Array of two values
- c) Object
- d) Function only

9. What is the first element in `useState()` return array?

- a) Function
- b) Component name
- c) Current state value
- d) Initial state

10. What is the purpose of the second element in `useState()` return array?

- a) Access current state
- b) Update state
- c) Reset component
- d) None

11. How do you import `useState` in React?

- a) `import { useState } from 'react';`
- b) `import useState from 'react';`
- c) `const useState = require('react');`
- d) None

12. In React, when state changes, what happens automatically?

- a) App restarts
- b) UI re-renders
- c) Data resets
- d) Component unmounts



CJC

Complete Java Classes

by Kunal Sir

13. Which hook cannot be called inside an event handler?

- a) useEffect()
- b) useState()
- c) Both
- d) None

14. What is JSX?

- a) JavaScript XML
- b) Java Syntax Extension
- c) JSON extension
- d) Java XObject

15. Can functional components return multiple elements?

- a) Yes, wrapped inside one parent element
- b) No
- c) Only class components can
- d) None

16. Props are:

- a) Mutable
- b) Immutable
- c) Optional in React
- d) Functions

17. Which function updates the value in useState()?

- a) updateState()
- b) changeState()
- c) setState()
- d) setVariable()

18. React Hooks can only be used in:

- a) Class components
- b) Functional components
- c) Both
- d) None



CJC

Complete Java Classes

by Kunal Sir

19. What is the correct way to render a component in JSX?

- a) `render(Home)`
- b) `<Home />`
- c) `Home()`
- d) `{Home}`

20. What happens when you call `setState()` with a new value?

- a) Re-renders the component with updated data
- b) Restarts the component
- c) Throws error
- d) Nothing

Practical Questions.

1 Welcome Component

Problem:

Design a simple React functional component named `WelcomeMessage` that displays a welcome heading and a short paragraph about React Components. Include a CSS class to style the heading in blue color.

Goal: Understand JSX structure and return statements.

2 Student Information Card

Problem:

Create a functional component `StudentInfo` that accepts props — `name`, `rollNo`, and `course`. Display these details in a card format with proper labels. Render this component multiple times with different students' data to show how props work for reusability.

Goal: Practice props & multiple rendering of components.



CJC

Complete Java Classes

by Kunal Sir

3 Product Display Using Props

Problem:

Develop a `ProductCard` component that takes props such as `productName`, `price`, and `imageUrl`.

Display all three in a visually appealing product box.

Render four product cards using different prop values.

Goal: Use props for data display and card-based UI.

4 Counter with State

Problem:

Build a `Counter` functional component using `useState()`.

Add buttons “Increment”, “Decrement”, and “Reset”.

Display the current count dynamically as the user interacts.

Goal: Practice `useState` and UI re-rendering.

5 Login Toggle Button

Problem:

Create a component `LoginStatus` that maintains a boolean state `isLoggedIn`.

Show “User Logged In” when `isLoggedIn` is true, otherwise “User Logged Out”.

Provide a button to toggle between the two states.

Goal: Manage boolean state and conditional rendering.



CJC

Complete Java Classes

by Kunal Sir

6 Background Color Changer

Problem:

Make a `ColorChanger` component that changes the background color of a div when a button is clicked.

Use a state variable `bgColor` initialized with “white” and update it with random colors using `useState`.

Goal: Learn dynamic styling and state updates.

7 Profile Card with Props

Problem:

Build a `Profile` component that receives `name`, `age`, and `location` via props. Display them in a styled card with an avatar image (can use a placeholder). Ensure reusability by passing different profiles from a parent component.

Goal: Combine props with simple layout design.

8 Shopping Cart Counter

Problem:

Develop a `Cart` component using `useState()` to display the number of items in the cart. Add two buttons: “Add Item” and “Remove Item” that update the item count. Show a message “Cart is empty” when `count = 0`.

Goal: Understand numeric state manipulation and UI conditionals.



CJC

Complete Java Classes

by Kunal Sir

9 Feedback Form

Problem:

Create a `FeedbackForm` component with an input field and a submit button.

When a user types a message and submits it, display “Thank You for Your Feedback!” below the form.

Use `useState()` to handle the text input and submitted state.

Goal: Handle user input and conditional rendering.

10 Image Gallery

Problem:

Design a `Gallery` component that accepts an array of image URLs as props.

Render all images in a grid layout using `.map()` and apply simple hover effects with CSS.

Goal: Learn list rendering and passing arrays via props.