



THROWS KEYWORD TASK: -

List of tasks related to throws keyword–

Q1. What is the purpose of throws keyword?

Q2. Explain difference between try-catch and throws keyword with example.

Q3. Check the code for throws keyword.

```
public class A {  
    public void m1(){  
        m2();  
    }  
    public void m2(){  
        m3();  
    }  
    public void m3() throws FileNotFoundException {  
        FileReader f=new FileReader("abc.txt");  
    }  
    public static void main(String[] args) {  
        A a=new A();  
    }  
}
```



```
        a.m1();  
    }  
}
```

Q4. Complete the code without handling exception and write the output of the program.

```
public class A3 {  
    public void m1() {  
        System.out.println("m1_____A3_____Start");  
        B3 b=new B3();  
        b.m2();  
        System.out.println("m1_____A3_____End");  
    }  
    public static void main(String[] args){  
        System.out.println("main _____start");  
        A3 a=new A3();  
        a.m1();  
        System.out.println("main _____End");  
    }  
}
```



```
public class B3 {  
    public void m2() {  
        System.out.println("B3_____m2 Start");  
        Class.forName("Demmo.java");  
        System.out.println("B3_____m2 End");  
    }  
}
```

Q5. Complete the code with handling exception and write the output of the program

```
public class A3 {  
    public void m1() {  
        System.out.println("m1_____A3_____Start");  
        B3 b=new B3();  
        b.m2();  
        System.out.println("m1_____A3_____End");  
    }  
  
    public static void main(String[] args){  
        System.out.println("main _____start");  
        A3 a=new A3();  
    }  
}
```



CJC
Complete Java Classes

```
//handle Exception here.  
  
    a.m1();  
  
    System.out.println("main _____End");  
  
    }  
  
}  
  
public class B3 {  
    public void m2() {  
        System.out.println("B3_____m2 Start");  
        Class.forName("A");  
        System.out.println("B3_____m2 End");  
    }  
}
```

Q6. Complete the code with and without handling exception, what will be the output of the program?

```
public class A4 {  
    public void m1() {  
        System.out.println("m1_____A4___Start");  
  
        B4 b=new B4();  
  
        b.m2();  
    }  
}
```



CJC
Complete Java Classes

```
        System.out.println("m1_____A4____End");
    }

    public static void main(String[] args){

        System.out.println("main _____start");

        A4 a=new A4();

        //handle exception here

        a.m1();

        System.out.println("main _____End");

    }
}

public class B4 {

    public void m2() {

        System.out.println("B4_____m2____ Start");

        String s=null;

        System.out.println(s.length());

        System.out.println("B4_____m2____ End");

    }

}
```



Q7. Complete the code with handling exception and write the output of the program

```
public class A1 {  
    public void m1(){  
        System.out.println("m1_____A1");  
        B1 b=new B1();  
        //Handle Exception Here  
        b.m2();  
        System.out.println("m1_____A1_____End");  
    }  
    public static void main(String[] args){  
        System.out.println("main _____start");  
        A1 a=new A1();  
        a.m1();  
        System.out.println("main _____End");  
    }  
}  
  
public class B1 {  
    public void m2(){  
        System.out.println("B1_____m2 Start");
```



CJC
Complete Java Classes

```
        int a=10/0;  
  
        System.out.println(a);  
  
        System.out.println("B1_____m2 End");  
  
    }  
  
}
```

Q8. Complete the code with handling exception and write the output of the program .

```
public class A2 {  
    public void m1(){  
        System.out.println("m1_____A1");  
        B2 b=new B2();  
        b.m2();  
        System.out.println("m1_____A1____End");  
    }  
}
```

```
public static void main(String[] args){  
    System.out.println("main _____start");  
    A2 a=new A2();  
    //Handle Exception Here
```



CJC
Complete Java Classes

```
        a.m1();  
  
        System.out.println("main _____End");  
  
    }  
  
}  
  
public class B2 {  
  
    public void m2(){  
  
        System.out.println("B2_____m2 Start");  
  
        int i=10/0;  
  
        System.out.println(i);  
  
        System.out.println("B2_____m2 End");  
  
    }  
  
}
```

Q9. Check the program for method overriding with throws in case of unchecked exception.

```
public class A{  
  
    //First scenario for unchecked  
  
    public void m1()throws ArithmeticException{  
  
    }  
  
  
    //Second scenario for unchecked
```



CJC
Complete Java Classes

```
public void m3(){  
}
```

```
//Third scenario for unchecked
```

```
public void m5()throws ArithmeticException{  
}
```

```
//Fourth scenario for unchecked
```

```
public void m7()throws Exception{  
}
```

```
//fifth scenario for unchecked
```

```
public void m9()throws ArithmeticException{  
}  
}
```

```
public class B extends A{
```

```
    //First scenario for unchecked
```

```
    @Override
```

```
    public void m1(){  
    }
```



CJC
Complete Java Classes

//Second scenario for unchecked

@Override

```
public void m3()throws ArithmeticException{  
}
```

//Third scenario for unchecked

@Override

```
public void m5()throws ArithmeticException{  
}
```

//Fourth scenario for unchecked

@Override

```
public void m7()throws ArithmeticException{  
}
```

//fifth scenario for unchecked

@Override

```
public void m9()throws Exception{  
}  
}
```



Q10. Check the program for method overriding with throws in case of checked exception.

```
public class A{  
    //First Scenario for checked  
    public void m2()throws IOException{  
    }  
  
    //Second Scenario for checked  
    public void m4(){  
    }  
  
    //Third scenario for checked  
    public void m6()throws IOException{  
    }  
  
    //Fourth scenario for checked  
    public void m8()throws Exception{  
    }  
  
    //fifth scenario for checked  
    public void m10()throws IOException{  
    }
```



CJC
Complete Java Classes

```
public class B extends A{  
    //First Scenario for checked  
    @Override  
    public void m2(){  
    }  
  
    //Second scenario for checked  
    @Override  
    public void m4()throws IOException{  
    }  
  
    //Third scenario for checked  
    @Override  
    public void m6()throws IOException{  
    }  
  
    //Fourth scenario for checked  
    @Override  
    public void m8()throws IOException{  
    }  
  
    //fifth scenario for checked
```



CJC
Complete Java Classes

@Override

```
public void m10()throws Exception{
```

```
}
```

```
}
```



THANK YOU

CJC
Complete Java Classes