



CJC

Complete Java Classes

by Kunal Sir

Spread Operator: -

In JavaScript spread operators are use to copy one object property into the other object.

The symbol of spread operator is `...`.

The spread operator is immediately followed by the object reference which supposed to be copied.

Example: - we have u1 and u2 object, and the u1 needs to be copied in u2

```
const u1={
  id:101,
  username:"samrth",
  password:"samrth@123"
}
console.log(u1); //{ id:101,username:"samrth",password:"samrth@123"}

const u2={
  ...u1,// this will copy all properties and their values from u1 to u2
  email:"samrthk123@gmail.com"
}
console.log(u2); // { id:101,username:"samrth",password:"samrth@123",
                  // email:"samrthk123@gmail.com"}
```

Note: - Using spread operator we can copy an array into another array to.



by Kunal Sir

Example: - We have nos1 array and nos2 array, we need to copy the elements of nos1 array into nos2 array.

```
const nos1=[10,20,30,40,50];  
console.log(nos1);           // [10, 20, 30, 40, 50]  
const nos2=[...nos1,60,70,80,90,100];  
  
console.log(nos2);           // [10, 20, 30, 40, 50, 60, 70, 80, 90, 100]
```

Rest Parameter: -

The rest parameter syntax allows a function to accept infinite number of arguments as an array.

```
function add(...params)  
{  
  let result=0;  
  for(let no of params)  
  {  
    result +=no;  
  }  
  console.log(result)  
}  
  
add(10,20,30,40,50,60)
```



De-structuring: -

The de-structuring assignment syntax unpack object/array values into variables.

In case of object de-structuring **sequence of object properties can be avoid.**

In Case object de-structuring **name of object property is considered**

To de-structure the object we **use object literals { }**

```
const student={
  rollno:1,
  firstName:'aaa',
  lastName:'zzzz',
  batchNo:'FDJ-176',
  classroom:'ground class',
  course:'Java Fullday'
}

console.log(student.rollno);
console.log(student.batchNo);

const {rollno,batchNo,classroom}=student

document.write(`<h1>${rollno}</h1>`)
document.write(`<h1>${batchNo}</h1>`)
document.write(`<h1>${classroom}</h1>`)
```

In case of array de-structuring sequence of array index is considered.



CJC

Complete Java Classes

by Kunal Sir

```
// 0    1    2    3    4    5    6
const days=['SUN','MUN','TUE','WED','THU','FRI','SAT'];

// let i=days[0];
// let j=days[1];

const [i,j,,,k]=days

document.write(`<h1>${i}</h1>`);
document.write(`<h1>${j}</h1>`);
document.write(`<h1>${k}</h1>`);
```



CJC

Complete Java Classes