

SKILL Week 11

Task1 : To connect different program modules, validate their interfaces, test end-to-end execution, handle errors, improve reliability, and refactor components.

Aim : To develop a modular C program where separate components communicate through well-defined interfaces, verify the complete execution flow, handle errors properly, and improve code reliability through refactoring.

Step 1: Create the header file

nano calculator.h

```
GNU nano 7.2 calculator.h *
#ifndef CALCULATOR_H
#define CALCULATOR_H

int add(int a, int b);
int subtract(int a, int b);
int multiply(int a, int b);
int divide_numbers(int a, int b);

#endif
```

Step 2: Create the implementation file

nano calculator.c

```
GNU nano 7.2 calculator.c *
#include <stdio.h>
#include "calculator.h"

int add(int a, int b)
{
    return a + b;
}

int subtract(int a, int b)
{
    return a - b;
}

int multiply(int a, int b)
{
    return a * b;
}

int divide_numbers(int a, int b)
{
    if (b == 0)
    {
        printf("Error: Division by zero is not allowed.\n");
        return 0;
    }
    return a / b;
}
```

Step 3: Create the main program

nano main.c

```
GNU nano 7.2 main.c *
#include <stdio.h>
#include "calculator.h"

int main()
{
    int a = 20;
    int b = 5;

    printf("Module Integration Test\n");
    printf("-----\n");

    printf("Addition: %d\n", add(a, b));
    printf("Subtraction: %d\n", subtract(a, b));
    printf("Multiplication: %d\n", multiply(a, b));
    printf("Division: %d\n", divide_numbers(a, b));

    printf("\nTesting error handling...\n");
    divide_numbers(a, 0);

    printf("\nAll modules executed successfully.\n");

    return 0;
}
```

Step 4: Compile and run

```
sainath@LAPTOP-GJ94VPOB:~/OSSP/module_integration$ gcc main.c calculator.c
-o module_test
sainath@LAPTOP-GJ94VPOB:~/OSSP/module_integration$ ./module_test
Module Integration Test
-----
Addition: 25
Subtraction: 15
Multiplication: 100
Division: 4

Testing error handling...
Error: Division by zero is not allowed.

All modules executed successfully.
```

Observation

The modular C program was successfully developed using separate source and header files. The calculator.h file provided well-defined function interfaces, while calculator.c contained their implementations. The main.c module communicated with the calculator module through the header file. All arithmetic operations were tested successfully, and division-by-zero was handled using an error-checking condition. The complete program was compiled and executed successfully, verifying the end-to-end communication between the modules.

Result

The modular C program was successfully integrated and tested. The interfaces between the modules were validated, arithmetic operations executed correctly, division-by-zero errors were handled safely, and the code was organized into reusable components for improved reliability and maintainability.

Task 2 : To detect runtime errors, generate meaningful error messages, log failures, handle invalid syntax, recover gracefully, and test different error scenarios.

Aim : To implement a C program that detects and handles runtime and syntax errors, displays appropriate error messages, records failures in a log file, and continues execution safely after recoverable errors.

Step 1: Create the C program

error_handler.c

```
GNU nano 7.2 error_handler.c *
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <errno.h>
#include <time.h>

void log_error(const char *message)
{
    FILE *log_file;
    time_t current_time;

    log_file = fopen("error.log", "a");

    if (log_file == NULL)
    {
        printf("Error: Unable to open log file.\n");
        return;
    }

    current_time = time(NULL);

    fprintf(log_file, "%s: %s\n",
            ctime(&current_time), message);

    fclose(log_file);
}

int main()
{
    int choice;
    int a, b;
    FILE *file;

    printf("Runtime Error Handling Program\n");
    printf("-----\n");

    printf("\n1. Division\n");
    printf("2. Open File\n");
    printf("3. Invalid Input\n");
    printf("Enter your choice: ");
```

```
GNU nano 7.2 error_handler.c *

if (scanf("%d", &choice) != 1)
{
    printf("Error: Invalid syntax/input.\n");
    log_error("Invalid menu input");
    return 1;
}

if (choice == 1)
{
    printf("Enter two integers: ");
    if (scanf("%d %d", &a, &b) != 2)
    {
        printf("Error: Invalid integer input.\n");
        log_error("Invalid integer input");
        return 1;
    }

    if (b == 0)
    {
        printf("Error: Division by zero is not allowed.\n");
        log_error("Division by zero");
    }
    else
    {
        printf("Result: %d\n", a / b);
    }
}
else if (choice == 2)
{
    file = fopen("missing.txt", "r");

    if (file == NULL)
    {
        printf("Error: File could not be opened.\n");
        printf("Reason: %s\n", strerror(errno));
        log_error("File opening failed");
    }
    else
    {
        printf("File opened successfully.\n");
        fclose(file);
    }
}
else if (choice == 3)
{
    printf("Error: Invalid option selected.\n");
    log_error("Invalid option selected");
}
else
{
    printf("Error: Unknown choice.\n");
    log_error("Unknown menu choice");
}

printf("\nProgram continues safely after error handling.\n");

return 0;
}
```

Step 2: Compile and run the program

```
sainath@LAPTOP-GJ94VP0B :~/OSSP/module_integration$ cd ~/OSSP
sainath@LAPTOP-GJ94VP0B :~/OSSP$ cd error_handling
sainath@LAPTOP-GJ94VP0B :~/OSSP/error_handling$ pwd
/home/sainath/OSSP/error_handling
sainath@LAPTOP-GJ94VP0B :~/OSSP/error_handling$ nano error_handler.c

sainath@LAPTOP-GJ94VP0B :~/OSSP/error_handling$ gcc error_handler.c -o error_handler
sainath@LAPTOP-GJ94VP0B :~/OSSP/error_handling$ ./error_handler

Runtime Error Handling Program
-----

1. Division
2. Open File
3. Invalid Input
Enter your choice: 1
Enter two integers: 10 0
Error: Division by zero is not allowed.

Program continues safely after error handling.
sainath@LAPTOP-GJ94VP0B :~/OSSP/error_handling$ |
```

```
sainath@LAPTOP-GJ94VP0B :~/OSSP/error_handling$ ./error_handler
Runtime Error Handling Program
-----

1. Division
2. Open File
3. Invalid Input
Enter your choice: 2
Error: File could not be opened.
Reason: No such file or directory

Program continues safely after error handling.
sainath@LAPTOP-GJ94VP0B :~/OSSP/error_handling$ |
```

```
sainath@LAPTOP-GJ94VP0B :~/OSSP/error_handling$ ./error_handler
Runtime Error Handling Program
-----

1. Division
2. Open File
3. Invalid Input
Enter your choice: 3
Error: Invalid option selected.

Program continues safely after error handling.
```

```
sainath@LAPTOP-GJ94VP0B :~/OSSP/error_handling$ ./error_handler
Runtime Error Handling Program
-----

1. Division
2. Open File
3. Invalid Input
Enter your choice: 5
Error: Unknown choice.

Program continues safely after error handling.
```

Observation

The C program successfully detected and handled different runtime and input errors. Division by zero was detected before performing the operation, missing file errors were identified using `fopen()` and `errno`, and invalid menu/input values were handled using input validation. Meaningful error messages were displayed to the user, and failures were recorded in the `error.log` file using a dedicated logging function. The program handled recoverable errors safely without causing an unexpected crash.

Result

Runtime and input error handling was successfully implemented and tested. The program generated meaningful error messages, logged failures, handled invalid inputs and missing files, and continued execution safely after recoverable errors.

Task 3: . To run Valgrind, identify memory leaks and memory errors, fix the errors, release allocated resources, verify cleanup, and document the findings.

Aim : To analyze dynamic memory usage in a C program using Valgrind, detect memory leaks and invalid memory operations, correct the errors, and verify that all allocated memory is properly released.

Step 1: Create a C file

nano memory_error.c

```
GNU nano 7.2 memory_error.c *
#include <stdio.h>
#include <stdlib.h>

int main()
{
    int *numbers;

    numbers = malloc(5 * sizeof(int));

    if (numbers == NULL)
    {
        printf("Memory allocation failed.\n");
        return 1;
    }

    for (int i = 0; i < 5; i++)
    {
        numbers[i] = i + 1;
    }

    printf("Numbers:\n");

    for (int i = 0; i < 5; i++)
    {
        printf("%d ", numbers[i]);
    }

    printf("\n");

    free(numbers);

    return 0;
}
```

Step 2: Compile and run the program

```
sainath@LAPTOP-GJ94VP0B :~/OSSP/valgrind_memory$ gcc -g memory_error.c -o memory_error
sainath@LAPTOP-GJ94VP0B :~/OSSP/valgrind_memory$ ./memory_error
Numbers:
1 2 3 4 5
sainath@LAPTOP-GJ94VP0B :~/OSSP/valgrind_memory$ valgrind --leak-check=full --track-origins=yes ./memory_error
==1136== Memcheck, a memory error detector
==1136== Copyright (C) 2002-2022, and GNU GPL'd, by Julian Seward et al.
==1136== Using Valgrind-3.22.0 and LibVEX; rerun with -h for copyright info
==1136== Command: ./memory_error
==1136==
Numbers:
1 2 3 4 5
==1136==
==1136== HEAP SUMMARY:
==1136==    in use at exit: 0 bytes in 0 blocks
==1136==   total heap usage: 2 allocs, 2 frees, 1,044 bytes allocated
==1136==
==1136== All heap blocks were freed -- no leaks are possible
==1136==
==1136== For lists of detected and suppressed errors, rerun with: -s
==1136== ERROR SUMMARY: 0 errors from 0 contexts (suppressed: 0 from 0)
sainath@LAPTOP-GJ94VP0B :~/OSSP/valgrind_memory$ |
```

Observation

Valgrind was successfully used to analyze the dynamic memory usage of the C program. Initially, it detected an invalid memory read and a memory leak. The invalid access was corrected by limiting the array index to the valid range, and the memory leak was corrected by releasing the dynamically allocated memory using `free()`.

Result

The C program was successfully tested using Valgrind. The memory errors and leak were identified and corrected, and the allocated resources were properly released. The corrected program was verified to have 0 memory errors and 0 memory leaks.

Task-4 : To design test cases, create test scripts, automate their execution, verify outputs, compare expected and actual results, and generate test reports.

Aim : To implement an automated testing system for a C program that executes multiple test cases, checks the program output against expected results, and generates a test report.

Step 1: Create a C file

nano calculator.c

```
GNU nano 7.2 calculator.c
#include <stdio.h>

int main()
{
    int a, b;
    char op;

    printf("Enter expression: ");
    scanf("%d %c %d", &a, &op, &b);

    if (op == '+')
    {
        printf("Result: %d\n", a + b);
    }
    else if (op == '-')
    {
        printf("Result: %d\n", a - b);
    }
    else if (op == '*')
    {
        printf("Result: %d\n", a * b);
    }
    else if (op == '/')
    {
        if (b == 0)
        {
            printf("Error: Division by zero\n");
        }
        else
        {
            printf("Result: %d\n", a / b);
        }
    }
    else
    {
        printf("Error: Invalid operator\n");
    }

    return 0;
}
```

Step 2: Compile and run the program

```
sainath@LAPTOP-GJ94VP0B:~/OSSP/valgrind_memory$ cd ~/OSSP
sainath@LAPTOP-GJ94VP0B:~/OSSP$ mkdir automated_testing
sainath@LAPTOP-GJ94VP0B:~/OSSP$ cd automated_testing
sainath@LAPTOP-GJ94VP0B:~/OSSP/automated_testing$ pwd
/home/sainath/OSSP/automated_testing
sainath@LAPTOP-GJ94VP0B:~/OSSP/automated_testing$ nano calculator.c
sainath@LAPTOP-GJ94VP0B:~/OSSP/automated_testing$ gcc calculator.c -o calculator
sainath@LAPTOP-GJ94VP0B:~/OSSP/automated_testing$ echo "10 + 5" | ./calculator
Enter expression: Result: 15
sainath@LAPTOP-GJ94VP0B:~/OSSP/automated_testing$ echo "10 + 5" | ./calculator
Enter expression: Result: 15
sainath@LAPTOP-GJ94VP0B:~/OSSP/automated_testing$ echo "10 - 5" | ./calculator
Enter expression: Result: 5
sainath@LAPTOP-GJ94VP0B:~/OSSP/automated_testing$ echo "10 * 5" | ./calculator
Enter expression: Result: 50
sainath@LAPTOP-GJ94VP0B:~/OSSP/automated_testing$ echo "10 / 5" | ./calculator
Enter expression: Result: 2
sainath@LAPTOP-GJ94VP0B:~/OSSP/automated_testing$ echo "10 / 0" | ./calculator
Enter expression: Error: Division by zero
```

Step 3: Create the Automated Test Script

nano test_script.sh

```
GNU nano 7.2 test_script.sh *
#!/bin/bash

echo "Automated Testing Started"
echo "===== "

passed=0
failed=0

run_test()
{
    test_name="$1"
    input="$2"
    expected="$3"

    actual=$(echo "$input" | ./calculator)

    if [ "$actual" = "$expected" ]
    then
        echo "$test_name : PASS"
        passed=$((passed + 1))
    else
        echo "$test_name : FAIL"
        echo "Expected: $expected"
        echo "Actual: $actual"
        failed=$((failed + 1))
    fi
}
```

```

run_test "Test 1 - Addition" \
"10 + 5" \
"Enter expression: Result: 15"

run_test "Test 2 - Subtraction" \
"10 - 5" \
"Enter expression: Result: 5"

run_test "Test 3 - Multiplication" \
"10 * 5" \
"Enter expression: Result: 50"

run_test "Test 4 - Division" \
"10 / 5" \
"Enter expression: Result: 2"

run_test "Test 5 - Division by Zero" \
"10 / 0" \
"Enter expression: Error: Division by zero"

echo
echo "=====
echo "Test Summary"
echo "=====
echo "Passed: $passed"
echo "Failed: $failed"
echo "Total : $((passed + failed))"

if [ $failed -eq 0 ]
then
    echo "All test cases passed."
else
    echo "Some test cases failed."
fi

```

Step 4: Run the Automated Test Script

```

sainath@LAPTOP-GJ94VPOB:~/OSSP/automated_testing$ nano calculator.c
sainath@LAPTOP-GJ94VPOB:~/OSSP/automated_testing$ nano test_script.sh
sainath@LAPTOP-GJ94VPOB:~/OSSP/automated_testing$ chmod +x test_script.sh
sainath@LAPTOP-GJ94VPOB:~/OSSP/automated_testing$ ./test_script.sh
Automated Testing Started
=====
Test 1 - Addition : PASS
Test 2 - Subtraction : PASS
Test 3 - Multiplication : PASS
Test 4 - Division : PASS
Test 5 - Division by Zero : PASS

=====
Test Summary
=====
Passed: 5
Failed: 0
Total : 5
All test cases passed.

```

Step 5: Generate a Test Report

```
GNU nano 7.2 test_script.sh *
#!/bin/bash

REPORT="test_report.txt"

echo "Automated Testing Report" > $REPORT
echo "===== " >> $REPORT
echo "Date: $(date)" >> $REPORT
echo >> $REPORT

passed=0
failed=0

run_test()
{
    test_name="$1"
    input="$2"
    expected="$3"

    actual=$(echo "$input" | ./calculator)

    if [ "$actual" = "$expected" ]
    then
        echo "$test_name : PASS"
        echo "$test_name : PASS" >> $REPORT
        passed=$((passed + 1))
    else
        echo "$test_name : FAIL"
        echo "$test_name : FAIL" >> $REPORT
        echo "Expected: $expected" >> $REPORT
        echo "Actual: $actual" >> $REPORT
        failed=$((failed + 1))
    fi
}
```

```

run_test "Test 1 - Addition" \
"10 + 5" \
"Enter expression: Result: 15"

run_test "Test 2 - Subtraction" \
"10 - 5" \
"Enter expression: Result: 5"

run_test "Test 3 - Multiplication" \
"10 * 5" \
"Enter expression: Result: 50"

run_test "Test 4 - Division" \
"10 / 5" \
"Enter expression: Result: 2"

run_test "Test 5 - Division by Zero" \
"10 / 0" \
"Enter expression: Error: Division by zero"

echo >> $REPORT
echo "===== >> $REPORT
echo "Test Summary" >> $REPORT
echo "===== >> $REPORT
echo "Passed: $passed" >> $REPORT
echo "Failed: $failed" >> $REPORT
echo "Total : $((passed + failed))" >> $REPORT

echo
echo "=====
echo "Test Summary"
echo "=====
echo "Passed: $passed"
echo "Failed: $failed"
echo "Total : $((passed + failed))"

if [ $failed -eq 0 ]
then
    echo "All test cases passed."
    echo "Result: All test cases passed." >> $REPORT
else
    echo "Some test cases failed."
    echo "Result: Some test cases failed." >> $REPORT
fi

echo
echo "Test report saved to: $REPORT"

```

Step 6: Run the Test and View the Report

```

sainath@LAPTOP-GJ94VPOB:~/OSSP/automated_testing$ nano test_script.sh
sainath@LAPTOP-GJ94VPOB:~/OSSP/automated_testing$ chmod +x test_script.sh
sainath@LAPTOP-GJ94VPOB:~/OSSP/automated_testing$ ./test_script.sh
Test 1 - Addition : PASS
Test 2 - Subtraction : PASS
Test 3 - Multiplication : PASS
Test 4 - Division : PASS
Test 5 - Division by Zero : PASS

=====
Test Summary
=====
Passed: 5
Failed: 0
Total : 5
All test cases passed.

Test report saved to: test_report.txt

```

Observation

An automated testing system was implemented using a C calculator program and a Bash test script. Multiple test cases were executed automatically. The script captured the actual output of the program and compared it with the expected output. Each test case was marked as PASS or FAIL, and the number of passed and failed tests was calculated. A test report was also generated automatically in test_report.txt.

Result

The automated testing system was successfully implemented and tested. All five test cases were executed successfully, with the expected and actual outputs matching. The final report showed:

Passed: 5

Failed: 0

Total: 5

Thus, automated test execution, output verification, comparison of expected and actual results, and test report generation were successfully demonstrated.