

COLOURS



MUSTANG BROWN



NEELONG WHITE



SELA BLACK

SPECIFICATIONS

ENGINE

Type	Single cylinder, 4-stroke, SOHC, air-cooled, fuel injection
Bore x Stroke (in mm)	81mm x 86mm
Displacement	443cc
Compression Ratio	9.5:1
Maximum Power	25.4 BHP (18.7 kW) @ 6250 RPM
Maximum Torque	34.0 Nm @ 4000 RPM
Idle RPM	1300 RPM
Starting System	Electric Start
Lubrication	Wet Sump
Engine Oil Grade	Semi-synthetic, SAE 15W-50, API SL, Grade JASO MA2
Clutch	Wet multi-plate
Gearbox	6-speed
Fuel Injection	Electronic Fuel Injection

CHASSIS & SUSPENSION

Type	Half-Duplex, Split-Cradle Frame
Front Suspension	Telescopic, 41mm forks
Front Wheel Travel	200mm travel
Rear Suspension	Monoshock with linkage
Rear Wheel Travel	180mm wheel travel

DIMENSIONS & WEIGHTS

Wheelbase	1460mm
Ground Clearance	220mm
Length	2190mm
Width	840mm
Height	1370mm (flyscreen top)
Seat Height	800mm
Kerb Weight (90% Fuel + Oil)	199 Kg
Payload with Standard Equipment	176 Kg
Fuel Capacity	15 l

BRAKES & TYRES

Wheel Type	Spoke
Tyre Type	Tube
Front Tyre	90/90-21", Spoked, Tube-type
Rear Tyre	120/90-17", Spoked, Tube-type
Front Brake	300mm hydraulic disc, 2-piston floating caliper
Rear Brake	240mm hydraulic disc, single-piston floating caliper
ABS	Dual-channel, switchable ABS at rear

ELECTRICALS

Electrical System	12V
Battery	12V, 8Ah, Maintenance-free
Head Lamp	14/12W LED
Tail Lamp	LED
Turn Signal Lamp	12V, 10W
Other Equipment	Type-C USB charger
Instrument Cluster	Digital-Analogue cluster
Navigation	Tripper Pod
